



YUTA NAVY SUPER

Art. cod.: 03991



PRODUCT SPECIFICATION SHEET

www.novartiplastitalia.it



Article	YUTA NAVY SUPER
Primary use	Outdoor, Hospitality, Contract, Residential Upholstery, Marine, Bags.
Origin	Italy
Custom tariff	59031090
Roll length	25 LM
Useful width (± 3cm)	140 cm
Compliant with	MED 3.20 2014/90/EU mod. B 0497/1378 – mod. D 0497/1388 (IMO part 8) EU: REACH / US: PROP 65 – Law AB2998
Environmental concern	Phthalates free - Heavy metal free - Azo free. Produced on site partially powered by solar panels.

Technical properties	Standard	Unit	Values
Total weight ± 5%	UNI EN ISO 2286-P.2°	gr/m2	750
Backing's weight ± 5%	UNI EN ISO 2286-P.2°	gr/m2	80
Thickness ± 0,1	UNI EN ISO 2286-P.3°	mm	0,95
Density	-----	gr/m3	0,78
Coating composition	100% VINYL (Phthalates free)		
Backing composition	65% PES / 35% CO		
Full composition	90% VINYL / 6% PES / 4% CO		
Tensile resistance / warp side	UNI EN ISO 1421	N/5cm	300
Tensile resistance / weft side	UNI EN ISO 1421	N/5cm	150
Ultimate elongation / warp	UNI EN ISO 1421	%	30
Ultimate elongation / weft	UNI EN ISO 1421	%	150
Tear resistance / warp	UNI EN ISO 4674-1 meth.B	N	20
Tear resistance / weft	UNI EN ISO 4674-1 meth.B	N	15
Peel adhesion / warp	UNI EN ISO 2411	N/5cm	25
Peel adhesion / weft	UNI EN ISO 2411	N/5cm	25
Bally at + 23° C	UNI 4818 - P.13	cycles	150.000
Bally at - 10° C	UNI 4818 - P.13	cycles	30.000
Xeno test	UNI EN ISO 4892-2 B1	Grey scale	4
Colour fastness to rubbing with alcohol	UNI EN ISO 105-X12	Grey scale	4
Martindale *	UNI EN ISO 12947-2	cycles	≥ 80.000
Molds resistance	UNI EN ISO 846 B	Growth ratio	No Growth
Flame retardant	IT: Classe 1 I M - UNI 9175 US: TB 117 : 2013 - FMVSS 302 EU: UNI EN 1021 part 1 & part 2 : 2014 UK: BS 5852 : 2006 source 0 & source 1		
Cleaning	Surface washable with water and neutral soap. For disinfection, sanitization and cleaning suggestions refer to the appropriate annex via our web site.		

* Slight variations of the printed colour surface may occur.

The surface of this article is treated with an anti-ink finish. Dab with alcohol to remove most difficult stains.

These are statistic average results. We reserve the right to make changes without notice insofar as the product remains suitable for the intended use.