

Smart **Mono** Laser Series for Convenient Printing

Target Group: SMB, Enterprises, Government



- High-speed printing at 33 ppm for everyday tasks
- 3.5-inch intuitive touchscreen for flagship models
- Powerful ADF accelerates printing jobs
- Economical choice with reduced overall printing cost

Stunning **Color** Laser Series, Superb Experience **Coming**

Target Group: SMB, Enterprises



- Print speed of up to 20 ppm to achieve precise results
- Compact, fresh design to maximize workspace
- One-step driver installation, effortless printing
- Reliable, outstanding color performance on every print



Print Easier,
Smarter, Faster



Easy
Installation



Built to
Last Longer



Compact in Size,
Simple to Use



Metal Frame Inside

GP3300 Series Key Specifications

Model	GP3300DN	GP3300DW
Specifications		
Print Speed	33 ppm(A4) 35 ppm(Letter)	
First Print Out Time	Less than 8.5s	
Monthly Duty Cycle	60,000 pages	
Recommended Monthly Page Volume	750 to 3,500 pages	
Print Resolution	Max.1200x600 dpi	
Printer Language	PCL5e, PCL6, PS3, PDF	
Processor Speed	350 MHz	
Memory	256 MB	
Control Panel	2 Line LCD	
Duplex Model	Automatic	
Paper Handling		
Paper Input Tray	250 pages	
Multipurpose Tray	1 page	
Paper Output Tray	120 pages	
Media Types	Plain, Thick, Transparency, Cardstock, Label	
Media Sizes	A4, A5, JIS B5, ISO B5, A6, Letter, Legal, Executive, Folio, Oficio, Statement, Japanese Postcard, ZL, Big 16K, Big 32K, 16K, 32K, B6, Yougata4, Postcard, Younaga3, Nagagata3, Yougata2	
Media Weight	Input tray: 60-105 g / , Multipurpose tray: 60-200 g/	
Other		
Dimensions (w*d*h)	354x334x232 mm	
Wight (Without Toner Cartridge)	6.8 kg	
Operating Temperature Range	10 ~ 32 C	
Operating Humidity Range	20% ~ 80% RH	
Input Voltage	AC100-127 V, 50/60 Hz (±2 Hz), 9 A AC220-240 V, 50/60 Hz, 4.5 A	
Noise	Printing: ≤ 52 dBA / Standby: ≤ 30 dBA	
Power Consumption	Print: Average 550 W / Standby: 45 W / Sleep: Less than 2.8 W	
Operating System	Microsoft Windows Server2003/Server2008/Server2012/XP/Vista/Win7/Win8/Win8.1/Win10/Win11(32/64 Bit); / Mac OS 10.10-14.3; / Linux: Ubuntu 16.04/18.04/20.04/22.04 (32/64 Bit)	
Compatibility	IOS 11.0-16.0 / Android 6.0-12.0	
Interface	High-speed USB 2.0 Ethernet: IEEE 802.3 10/100Base-Tx	High-speed USB 2.0 Ethernet: IEEE 802.3 10/100Base-Tx WiFi: IEEE 802.11b/g/n
Supplies		
Cartridge Type	Toner Cartridge & Drum Unit	
Starter Toner Capacity (1)	GT321A (1,500 pages)	
Starter Drum Unit Lifetime (2)	GD320 (12,000 pages)	
Standard Toner Capacity (1)	GT321A (1,500 pages) GT321H (3,000 pages) GT321X (6,000 pages)	
Standard Drum Unit Lifetime (2)	GD320 (12,000 pages)	

Note: (1) Toner capacity is based on ISO 19752.
(2) Drum unit lifetime is based on 3 average letter/A4-size pages per print job and 5% coverage. Actual lifetime is determined by different printing habits and printing environments.

GM3300 / 3310 Series Key Specifications

Models	GM3300DN / DW		GM33100DN / DW
Type	3in1ADF		3in1ADF
Print			
Print Speed (Letter, Black)	33 ppm (A4) / 35 ppm (Letter)		
First Print Out Time	Less than 8.5s		
Maximum Monthly Duty Cycle	60,000 pages		
Recommended Monthly Page Volume	750 to 3,500 pages		
Print Resolution (maximum dpi)	Max 1200x600 dpi		
Print Languages	PCL5e, PCL6, PS, PDF		
Processor Speed	525 MHz		800 MHz
Memory, Standard	256 MB	256MB / 512 MB	512 MB
Duplex Printing	Automatic		
Network	Yes		
Wi-Fi	DN: No / DW: Yes		
Copy			
Copy Speed (Letter, Black)	33 cpm (A4) / 35 cpm (Letter)		
First Copy Out Time	flatbed: less than 10s / ADF: less than 11s		
Copy Resolution (max.dpi)	Max600x600 dpi		
Maximum Copy Pages	99 pages		
Copy Reduce / Enlarge Settings	25% ~ 400%		
Copy Special Features	ID copy, Receipt copy, N-up copy, Clone copy, Poster copy, Manual Duplex Copy, Collated copy		
Scan			
Scanner Type	Flatbed & ADF		Flatbed & DADF
ADF Capacity	50 pages		
Scan Speed (maximum)	24 ppm (A4) / 25 ppm (Letter)		
Scan Size (maximum)	Flatbed: 216x297 mm / ADF: 216 x 356 mm		
Scan Resolution	Flatbed: Max 1200x1200 dpi / ADF: Max 600x600 dpi		
Color Scanning	Yes		
Scan Destinations	Scan to PC, E-mail, FTP, thumb drive		
Paper Handling			
Paper Input Capacity	250 pages		
Multipurpose Tray	1 page		
Paper Output Capacity	120 pages		
Media Types	Plain, Thick, Thin, Transparency, Cardstock, Label		
Media Sizes	A4, A5, JIS B5, ISO B5, A6, Letter, Legal, Executive, Folio, Oficio, Statement, Japanese Postcard, ZL, Big 16K, Big 32K, 16K, 32K, B6, Yougata4, Postcard, Younaga3, Nagagata3, Yougata2		
Media Weights	Standard tray: 60-105 g/ / Multipurpose tray: 60-200 g/		
General			
Dimensions (WxDxH)	415x360x352 mm		
Weight (Without Cartridge)	10.46 kg		10.54 kg
Operating Environment	Recommended temperature: 10 ~ 32 °C		
Power Consumption	Printing: 550 W / Ready: less than 50 W / Sleep: less than 2 W		
Noise Level	Print: 52 dB(A) / Copy: 54 dB(A) / Scan: 52 dB(A) / Standby: 30 dB(A)		
Operating System Compatibility	Microsoft Windows Server2003/Server2008/Server2012/X-P/Vista/Win7/Win8/Win8.1/Win10/Win11(32/64 Bit); / Mac OS 10.10-14.3; / Linux: Ubuntu 16.04/18.04/20.04/22.04 (32/64 Bit) IOS 11.0-16.0 / Android 6.0-12.0		
Standard Ports	Hi-Speed USB 2.0; Net: IEEE 802.3 10/100 Base-Tx WiFi: IEEE 802.11b/g/n (for 3300DW & 3310DW)		
Consumable *			
Consumable Type	Toner Cartridge & Drum Unit		
Starter Cartridge (1)	GT321A (1,500 pages)		
Starter Drum (2)	GD320 (12,000 pages)		
Cartridge Model and Yield (1)	GT321A (1,500 pages) / GT321H (3,000 pages) / GT321X (6,000 pages)		
Standard Drum (2)	GD320 (12,000 pages)		
Note: (1) Toner capacity is based on ISO 19752. (2) Drum unit lifetime is based on 3 average letter/A4-size pages per print job and 5% coverage. Actual lifetime is determined by different printing habits and printing environments.			

GP2000 Series Key Specifications

Model	GP2000CDN	GP2000CDW
Print		
Function	Print	
Print Speed (A4/LTR)	20 ppm / 21 ppm	
Print Speed (Duplex) (A4/LTR)	6 ppm	
First Print Out Time	Black: 10s	
Black/Color	Color: 12s	
Print Resolution	600x600 dpi (Optical)	
Recommended Monthly Page Volume	150-1,500 pages	
Maximum Monthly Duty Cycle	30,000 pages	
Print Languages	GDI	
Processor Speed	500 MHz	
Memory	DDR3L 512 MB	
Operation Panel	2Line LCD	
Direct USB	No	
Standard Ports	USB2.0 10/100 Base-Tx	USB2.0 / WiFi (2.4G) 10/100 Base-Tx
Wireless Network	/	Yes
Mobile Printing	G&G APP	
WiFi Funtion	Router mode: support mobile devices and PC devices WiFi direct: supports mobile devices	
Paper Handling		
Paper Input Capacity	250 pages	
Multipurpose Tray	1 page	
Paper Output Capacity	100 pages	
Optional Paper Tray	No	
Media Types	Plain Paper/Colored Paper/Card Stock/Labels/Letterhead/Preprinted/Bond/Glossy/Light Paper/Heavy Paper/Rough&Cotton/Recycled/Envelope	
Med Ia Sizes	Paper & Envelope size: A4, A5, JIS B5, IS0 B5, A6, Letter, Legal, Executive, Folio, Oficio, Statement, Japanese Postcard, ZL, Big 16K, Big 32K, 16K, 32K, B6, Yougata4, Postcard, Younaga3, Nagagata3, Yougata2, No.10 Env, Monarch Env, DL Env, C5 Env, C6 Env Custom: Min 96x148 mm~Max 216x356 mm	
Media Weights	Standard tray: 60-105 g/± / Multipurpose tray : 60-200 g/± / Duplex : 70-105 g/±	
Supplies		
Starter Cartridge Capacity (K/CMY) (1)	1,500 pages / 1,000 page	
Standard Cartridge Capacity (K/CMY) (1)	GT201K/C/M/Y: 1.5K/1K/1K/1K GT201XK/XC/XM/XY: 3K/2.5K/2.5K/2.5K	
Waste Toner Bottle Capacity	GWT-201: 15K	
General		
Power	110 V Model: AC100-127 V (±10%), 50/60 Hz (±3 Hz) 8 A 220V Model: AC220-240V(10%), 50/60Hz(±3Hz) 4A	
Power Consumption	Print: ≤380W / Ready: 5W / Sleep: 2W / Hibernate: 0.5W	
Noise Level	Sleep/Hibernate/Ready/Idle: ≤30dBA Print: ≤54dBA / Mute mode printing: ≤50dBA	
Operating Environment	Temperature: 10-32 °C / Humidity: 20%-80% / Altitude: 0-3000 Meters	
Operating System Compatibility	Microsoft Windows Server2003/Server2008/Server2012/XP/Vista/Win7/Win8/Win8.1/Win10/Win11(32/64 Bit); Mac OS 10.10-14.3; / Linux: Ubuntu 16.04/18.04/20.04/22.04 (32/64 Bit) IOS 11.0-16.0 / Android 6.0-12.0	
Product Dimensions (L*W*H)	401*400*225 mm	
Product Weight	15.3 kg	
Package Size (L*W*H)	566*512*339 mm	
Package Weight	18.1 kg	

GM2000 / 2010 Series Key Specifications

Model	GM2000CDN	GM2010CDW
Print		
Function	Print/Copy/Scan	
Print speed (A4/LTR)	20 ppm/21 ppm	
First Print Out Time (black/color)	Black: 10s	Color: 12s
Print Resolution	600x600 dpi (Optical)	
Recommended Monthly Page Volume	150-1,500 pages	
Maximum Monthly Duty Cycle	30,000 pages	
Processor Speed	833 MHz	
Memory	DDR4 512 MB	
Operation Panel	2 Line LCD	3.5-inch touch screen
Direct USB	No	
Standard Ports	USB2.0 / 10/100 Base-Tx	USB2.0 / WiFi (2.4G) / 10/100 Base-Tx
Mobile Printing	G&G APP	
WiFi Funtion	/	Router mode: support mobile devices and PC devices WiFi direct: supports mobile devices
Copy		
Copy Speed (A4/LTR)	/	20 ppm
First Copy Out Time (Black/Color)	Flatbed: 17s	Flatbed: 17s / ADF: 18s
Copy Resolution	600x600 dpi	FB/ADF: Max. 600x600 dpi
Copy Reduce/Enlarge Settings	25% - 400%	
Maximum Copy Pages	99 pages	
Copy Special Features	ID copy, Receipt copy, N-up copy, Clone copy	
Scan		
ADF Type	/	SADF (Simplex scan)
ADF Capacity	/	50 pages (80 g/±)
Scan Resolution (Black/Color)	Max. 1200 x 1200 dpi (FB)	Max. 600x600 dpi (ADF) Max. 1200x1200 dpi (FB)
Maximum Media Size	Max. 216 mm x297 mm (FB)	Max. 216 mm x 297 mm (FB) Max. 216 mm x 356 mm (ADF)
ADF Scanning Speed (Black/Color)	/	A4/LTR: 20 ipm (300x300 dpi grey mode)
Scan To	Email / FTP / PC	USB / Email / FTP / PC
Paper Handling		
Paper Input Capacity	250 pages	
Multipurpose Tray	1 page	
Paper Output Capacity	100 pages	
Media Types	Plain Paper/Colored Paper/Card Stock/Labels/Letterhead/Preprinted/Bond/Glossy/Light Paper/Heavy Paper/Rough&Cotton/Recycled/Envelope	
Media Sizes	Paper & Envelope size: A4, A5, JIS B5, IS0 B5, A6, Letter, Legal, Executive, Folio, Oficio, Statement, Japanese Postcard, ZL, Big 16K, Big 32K, 16K, 32K, B6, Yougata4, Postcard, Younaga3, Nagagata3, Yougata2, No.10 Env, Monarch Env, DL Env, C5 Env, C6 Env Custom: Min 96x148 mm~Max 216x356 mm	
Media Weights	Standard tray: 60-105 g/± / Multipurpose tray : 60-200 g/± / Duplex : 70-105 g/±	
Supplies		
Starter Cartridge Capacity (K/CMY)(1)	1,500 pages / 1,000 page	
Standard Cartridge Capacity (K/CMY)(1)	GT201K/C/M/Y: 1.5K/1K/1K/1K	GT201XK/XC/XM/XY: 3K/2.5K/2.5K/2.5K
Waste Toner Bottle Capacity	GWT-201: 15K	
General		
Power	110 V Model: AC100-127 V (±10%), 50/60 Hz (±3 Hz), 8 A 220 V Model: AC220-240 V (±10%), 50/60 Hz (±3 Hz), 4 A	
Power Consumption	Print: ≤380W / Ready: <5W / Sleep: <2W / Hibernate: <0.5W	
Noise Level	Sleep/Hibernate/Ready/Idle: ≤30dBA / Print: ≤54dBA / Mute mode printing: ≤50dBA	
Operating Environment	Temperature: 10-32 °C / Humidity: 20%-80% / Altitude: 0-3000 Meters	
Operating System compatibility	Microsoft Windows Server2003/Server2008/Server2012/XP/Vista/Win7/Win8/Win8.1/Win10/Win11 (32/64 Bit); Mac OS 10.10-14.3; / Linux: Ubuntu 16.04/18.04/20.04/22.04 (32/64 Bit) / IOS 11.0-16.0 / Android 6.0-12.0	
Product Dimensions (L*W*H)	415*403*303 mm	
Product Weight	18.2 kg	