

Product Overview

PROTEUS™ BRUTUS / FS	PROTEUS™ MAXIMUS	PROTEUS™ LUCIUS	PROTEUS™ ODEON
SOURCE 1200W 6,500K Bright White LED Engine 30,000 Hour Average LED Life*	SOURCE 950W 6,500K Bright White Peak Field LED Engine 30,000 Hour Average LED Life*	SOURCE 580W 6,500K Bright White Peak Field LED Engine 30,000 Hour Average LED Life*	SOURCE - High Efficiency 850W 6,500K Variable CRI White LED Engine 30,000 Hour Average LED Life*
PHOTOMETRIC DATA 75000+ Total Lumen Output (BRUTUS) 16000lx (1470fc) @ 20m (BRUTUS FS) - CRI 70+ (82+ / 90+ HCRI Filter)	PHOTOMETRIC DATA 50000+ total lumen output - CRI 70+ (82+ HCRI Filter)	PHOTOMETRIC DATA 33500+ Total Lumen Output - CRI 71+ (85+ with HCRI Filter)	PHOTOMETRIC DATA 32000 Total Lumen Fixture Output @ CRI 80 - TruTone variable CRI up to CRI 93
EFFECTS 4.5° - 45° Motorized Zoom (BRUTUS) 3.5° - 35° Motorized Zoom (BRUTUS FS) (220mm / 8.7 in Front Aperture) - Full 360° Bi-Directional Animation Wheel (BRUTUS) - Ultra Long Throw Beam Mode (BRUTUS FS) - Variable Frost Filter / Iris	EFFECTS 5.5° - 55° Motorized Zoom (Large 180mm Front Aperture) 4 Rotating Full Blackout Framing, +/-50° Index - Animation Wheel 4-facet and Linear Rotating Prisms - Light and Wash Frost Filters	EFFECTS 5.5 - 50° Motorized Zoom 4 Rotating Full Blackout Framing, +/-50° Index - Animation Wheel 4-facet and Linear Rotating Prisms	EFFECTS 5.5° - 50 Motorized Zoom 4 Rotating Full Blackout Framing Blades +/-45° Framing Indexing - Full 360° Bi-Directional Animation Wheel
COLOR - CMY Color Mixing - Linear CTO Color Correction 6 Colors (BRUTUS) / High CRI Filter	COLOR - Full CMY + CTO Color Mixing 6 Dichroic Colors incl. High CRI Filter and UV	COLOR - Full CMY + CTO Color Mixing 5 Dichroic Colors incl. High CRI Filter	COLOR - CMY Color Mixing - Linear CTO Color Correction 5 Dichroic Colors including UV Filter
GOBOS 5 Rotating / Indexing Beam Shaping + FX Gobos 1 Rot. Multi Color Glass Gobo (BRUTUS) - Framing Module (BRUTUS)	GOBOS 2 Gobo Wheels 6 Rotating / Indexing Interchangeable Glass Gobos 7 Static Glass Gobos	GOBOS 3 Gobo Wheels 6 Rotating Gobo (Wheel #1) 7 Rotating Gobos (Wheel #2) 7 Static Gobos (Wheel #3)	GOBOS 3 Gobo Wheels 6 Rotating Gobos (Wheel #1) 7 Rotating Gobos (Wheel #2) 7 Static Gobos (Wheel #3)
CONTROL / CONNECTIONS 4 / 2 DMX Channel Modes - DMX, RDM, Art-NET, sACN - Locking IP65 Spin XLR + Ethernet In/Out, Power In - BRUTUS FS Camera Connections: NDI, POE++ Output, HD-SDI, AUX Control, 12V Camera Power	CONTROL / CONNECTIONS 2 DMX Modes (37 / 61) - DMX, RDM, Art-NET, sACN - Locking IP65 Spin XLR + Ethernet In/Out - Locking IP65 Power In	CONTROL / CONNECTIONS 2 DMX Modes - DMX, RDM, Art-NET, sACN - Locking IP65 Spin XLR + Ethernet In/Out - Locking IP65 Power In	CONTROL / CONNECTIONS 4 DMX Modes - DMX, RDM, Art-NET, sACN - Locking IP65 Spin XLR + Ethernet In/Out - IP66 5pin DMX In/Out - IP66 RJ45 Ethernet In/Out - IP66 Locking Power Cable In
SIZE / WEIGHT - LxWxH: 467 x 370 x 825 mm (BRUTUS) 464 x 643.6 x 829 mm (BRUTUS FS) - Weight: 54 kg / 53.4 kg	SIZE / WEIGHT - LxWxH: 458 x 591 x 825 mm (18" x 23.3" x 32.5") - Weight: 53 kg (117 lbs.)	SIZE / WEIGHT - LxWxH: 468 x 370 x 682 mm (18.4" x 14.6" x 26.8") - Weight: 40.8 kg (89.9 lbs.)	SIZE / WEIGHT - LxWxH: 467.6 x 370 x 692 mm (18.41" x 14.57" x 27.2") - Weight: 43.4 kg (97.7 lbs.)
PROTEUS™ RADIUS	PROTEUS™ ATLAS	PROTEUS™ EXCALIBUR	PROTEUS™ HYBRID MAX
SOURCE 100W Laser Illuminated Lighting Instrument (LILI) Light Engine / 6,000K, CRI 70 10,000 Hour Average LED Life*	SOURCE 500W Laser Illuminated Lighting Instrument (LILI) Light Engine / 9,000K, CRI 70 10,000 Hour Average LED Life*	SOURCE - Philips MSD Platinum 500 Flex 550W Lamp - Up to 4,000h Lamp Life*	SOURCE - Philips MSD Platinum 500 Flex 550W Lamp - Up to 4,000 Hour Lamp Life*
PHOTOMETRIC DATA 2700 Lumen Total Fixture Output - Beam Angle 0.9°	PHOTOMETRIC DATA Beam Angle 0.6° - 8.5°	PHOTOMETRIC DATA 20000+ Total Lumen Output - CRI 77+	PHOTOMETRIC DATA 22000+ Lumen Total Fixture Output
EFFECTS 4 Prisms on Dual Planes - CMY Color, Gobo, Prism Macros - Motorized Focus - Digital Shutter and Strobe - Dual Frost	EFFECTS - Dual Frost (Hot- Spot Beam, Wash FX) - Ultra- Fast Zoom - Focus 2x 3 Prisms on Dual Planes - Digital Shutter and Strobe	EFFECTS 0.8° Beam Angle, Variable Focus 1.6° Field Angle 3.5° Beam Expander 8-Facet , 4 Facet Linear Prism 2 Light and Wash Frost Filters	EFFECTS - Beam, Spot, Wash Modes 1.8° - 45° Motorized Zoom - Dual Frost Filter for Light Frost/ Full Wash 4 Prisms on Dual Planes - High Speed Shutter and Strobe
COLOR - Full CMY Color Mixing System 25 Position Color Wheel	COLOR - Full CMY Color Mixing System 25 Position Color Wheel	COLOR - CMY Color Mixing 14 Dichroic Colors incl. CTO and UV	COLOR - Full CMY Color Mixing - Variable CTO 16 Position Color Wheel
GOBOS 2 Gobo Wheels 13 Interchangeable-Rotating / Indexing Metal Gobos 24 Static-Stamped Metal Gobos	GOBOS 2 Gobo Wheels 13 Interchangeable-Rotating / Indexing Metal Gobos 26 Static-Stamped Metal Gobos	GOBOS 2 Gobo Wheels 8 Rotating / Indexing Interchangeable Glass Gobos 17 Position Static Gobo Wheel	GOBOS 2 Gobo Wheels 8 Interchangeable-Rotating / Indexing Glass Gobosk 16 Static-Stamped Metal Gobos plus Animation Track
CONTROL / CONNECTIONS 2 DMX Channel Modes - DMX, RDM, Art-NET, sACN - Locking IP65 Spin XLR + Ethernet In/Out - Locking IP65 Power In	CONTROL / CONNECTIONS 2 DMX Channel Modes - DMX, RDM, Art-Net,sACN (6) Button Touch Panel - Full Color 180° Reversible LCD Menu Display	CONTROL / CONNECTIONS 2 DMX Channel Modes - DMX, RDM, Art-Net,sACN - Locking IP65 Spin DMX + Ethernet In/Out - Locking IP65 Power In	CONTROL / CONNECTIONS 2 DMX Channel Modes - DMX, RDM, Art-NET, sACN - IP66 5pin DMX In/Out - IP66 RJ45 Ethernet In/Out - IP66 Locking Power Cable In
SIZE / WEIGHT - LxWxH: 270 x 395 x 516 mm (10.6" x 15.5" x 20.3") - Weight: 20.4 kg (45 lbs.)	SIZE / WEIGHT - LxWxH: 370 x 508 x 800 mm (14.5" x 20" x 31.5") - Weight: 53 kg (117 lbs.)	SIZE / WEIGHT 493 x 383 x 697 mm (19.4" x 15.1" x 27.4") - Weight: 49 kg (108 lbs.)	SIZE / WEIGHT 287.5 x 476.8 x 677 mm (11.3" x 18.8" x 26.7") - Weight: 35.5 kg (78.3 lbs.)



Elation Professional Europe
Junostraat 2 • 6468 EW Kerkrade • The Netherlands
www.elationlighting.eu

*Lamp/ LED Life may vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control, and Dimming. Gobos & Colors. The information in this catalog has been carefully compiled, but errors or changes may still occur. Technical data, images, and specifications are provided for general information purposes only and may change without prior notice. We assume no liability for printing errors, inaccuracies, or subsequent updates to the specifications.



PROTEUS™

THE **ULTIMATE POWERHOUSE PACKAGE**
FOR MAXIMUM IMPACT **INDOORS** OR **OUT!**



EXPERIENCE
TOMORROW



ELATION.GLOBAL



THE WASH BEAM FX

PROTEUS BRUTUS™
75000 lumens of cutting power!



THE FOLLOW

PROTEUS BRUTUS FS™
The ultimate IP66 multi-system followspot with power!



THE PROFILE

PROTEUS MAXIMUS™
Market-proven all-purpose power luminaire!



THE BEAUTY

PROTEUS RAYZOR™
Beam, Wash, Sparkle.
More than just a pretty face!



THE CREATIVE

PROTEUS RAYZOR BLADE™
The market's most versatile FX bar!



THE COMPACT

PROTEUS LUCIUS™
Little but lethal - the Maximus mini-me!



THE VARIABLE

PROTEUS ODEON™
Industry's first completely variable CRI LED engine!



THE SOLID BEAM

PROTEUS RADIUS™
Compact, high-intensity Beam FX!



THE REMARKABLE

PROTEUS ATLAS™
Laser Illuminated Lighting Instrument (LILI)
Beam FX Fixture!



THE BEAM

PROTEUS EXCALIBUR™
Brightest IP65 full-featured beam fixture ever!



THE HYBRID

PROTEUS HYBRID MAX™
Outperforms all other hybrids on the market!

Product Overview

PROTEUS™ RAYZOR 760

- SOURCE**
- 7x 60W Osram RGBW LEDs, 28x 2W White SparkLED™
 - 50,000 Hour Average LED Life*

- PHOTOMETRIC DATA**
- 7200+ Total Lumen Output

- EFFECTS**
- 5° - 77° Beam to Wash Zoom Angle
 - Linear Color Temperature presets (2,700 - 8000K)
 - RGBW Color Mixing and Pixel Control
 - White SparkLED™ Lens Effect
 - 360° Cont. Pan/Tilt Movement

- COLOR**
- 7x RGBW LEDs
 - 28x White SparkLED™

- CONTROL / CONNECTIONS**
- 3 DMX Channel Modes
 - DMX, RDM, Art-NET, sACN
 - Locking IP65 5pin XLR + Ethernet In/Out
 - Locking IP65 Power In

- SIZE / WEIGHT**
- LxWxH: 363.4 x 260 x 493.4 mm (14.31" x 10.24" x 19.43")
 - Weight: 18.6 kg (41.0 lbs.)

PROTEUS™ RAYZOR 1960

- SOURCE**
- 19x 60W Osram RGBW LEDs, 76x 2W White SparkLED™
 - 50,000 Hour Average LED Life*

- PHOTOMETRIC DATA**
- 18100+ Total Lumen Output

- EFFECTS**
- 5° - 55° Motorized Zoom
 - Linear Color Temperature Presets (2,700 - 8000K)
 - RGBW Color Mixing and Pixel Control
 - White SparkLED™ Lens Effect
 - 360° Cont. Pan/Tilt Movement

- COLOR**
- 19x RGBW LEDs
 - 76x White SparkLED™

- CONTROL / CONNECTIONS**
- 3 DMX Channel Modes
 - DMX, RDM, Art-NET, sACN
 - Locking IP65 5pin XLR + Ethernet In/Out
 - Locking IP65 Power In

- SIZE / WEIGHT**
- LxWxH: 370 x 468 x 582 mm (14.6" x 18.4" x 22.9")
 - Weight: 32.6 kg (72.0 lbs.)

PROTEUS™ RAYZOR BLADE S

- SOURCE**
- 6x 60W Osram RGBW LEDs
 - 24x 2W White SparkLED™
 - 128x 1W Strobe LED
 - 50,000 Hour Average LED Life*

- PHOTOMETRIC DATA**
- 6000+ Total Lumen Output

- EFFECTS**
- 6° - 45° Motorized Zoom
 - Linear Color Temperature presets (2,700 - 8,000K)
 - RGBW Color Mixing and Pixel Control
 - White SparkLED™ Lens Effect
 - Dual White Strobe Lines
 - 192° Tilt Angle

- COLOR**
- 6x RGBW LEDs / 12x RGBW LEDs
 - 24x 2W White SparkLED™
 - 256x 1W Strobe LED

- CONTROL / CONNECTIONS**
- DMX, RDM, Art-NET, sACN
 - Locking IP65 5pin XLR + Ethernet In/Out
 - Locking IP65 Power In

- SIZE / WEIGHT**
- LxWxH: 504 x 194 x 336 mm (19.8" x 7.6" x 13.2")
 - Weight: 17.9 kg (39.4 lbs.)

PROTEUS™ RAYZOR BLADE L

- SOURCE**
- 12x 60W Osram RGBW LEDs
 - 48x 2W White SparkLED™
 - 256x 1W Strobe LED
 - 50,000 Hour Average LED Life*

- PHOTOMETRIC DATA**
- 11000+ Total Lumen Output

- EFFECTS**
- 6° - 45° Motorized Zoom
 - Linear Color Temperature presets (2,700 - 8,000K)
 - RGBW Color Mixing and Pixel Control
 - White SparkLED™ Lens Effect
 - Dual White Strobe Lines
 - 192° Tilt Angle

- COLOR**
- 6x RGBW LEDs / 12x RGBW LEDs
 - 24x 2W White SparkLED™
 - 256x 1W Strobe LED

- CONTROL / CONNECTIONS**
- DMX, RDM, Art-NET, sACN
 - Locking IP65 5pin XLR + Ethernet In/Out
 - Locking IP65 Power In

- SIZE / WEIGHT**
- LxWxH: 1004 x 194 x 336 mm (39.5" x 7.6" x 13.2")
 - Weight: 33 kg (72.7 lbs.)