

GX80

NO MORE OBSTACLE, HEAR AND BEING HEARD CLEARLY

Equipped with versatile audio availability, incl. music player MP5, combo mic/line input, 3.5mm audio input and Bluetooth, GX 80 system works perfectly in any gym class or aerobic tutorial. GX 80 system supports three channels with individual volume controls, 2-band EQ, master volume and sound effect (echo). Providing the option of wireless audio connection via additional AudioLink transmitter/receivers, multiple systems can be installed in same place for fluent audio streaming. GX 80 system also allows 70+ wireless range which extends the application, ex. larger gym space. Embedded USB-A charging ports are useful when charging is needed for wireless microphones, smartphones or other audio devices. GX 80 system is an all-in-one portable sound system and can accommodate any need indoors or outdoors. No more obstacle exists and people can always hear / be heard clearly.







-  2" tweeter
-  8" full range speaker
-  60W Max output power
-  108 dB SPL
-  6+ hours run time
-  Lead-Acid battery

To extend the range of wireless audio reproduction, optional AudioLink transmitter/receiver is available for enhance onsite hearing experience.

ACCESSORIES & PARTS

			
Active speaker PA 55	Active speaker PA 80	Active speaker PA 81	Extension speaker PA 81E

				
DECT duo receiver GX 7RM2	DECT quad receiver GX 7RM4	AudioLink transmitter TX-701-80	AudioLink receiver DR-501A-80	SD/USB music player MP 5

				
Handheld mic GX 7H	Bodypack/Pendant mic GX 7T	15M speakON® cable SC-15K	30M speakON® cable SC-30K	Tripod stand ST-750

			
Alkaline battery, AA PD-2900A	Lead-Acid battery BAT-5000	LiFePO4 battery LBT-6000	Li-ion polymer battery LBT-1000

				
Lapel mic LM-96A	Earworn mic HEM-101A	Headset mic HM-35A	Headset mic HM-55A	Headset mic HM-65A

MODELS & SPECIFICATIONS

Models	Powered Speaker	DECT Duo Receiver	DECT Quad Receiver	Music Player	AudioLink Transmitter	AudioLink Receiver
PA 55	v			v		
PA 55R	v			v		v
GX 552	v	v		v		
GX 552T	v	v		v	v	
GX 554	v		v	v		
PA 80	v			v		
PA 80R	v			v		v
GX 802	v	v		v		
GX 802T	v	v		v	v	
GX 804	v		v	v		
PA 81	v			v		
PA 81R	v			v		v
GX 812	v	v		v		
GX 812T	v	v		v	v	
GX 814	v		v	v		
PA 81E	Extension Speaker					

Specifications	GX 55	GX 80	GX 81
Output power	RMS 60W MAX 80W	RMS 50W MAX 60W	RMS 60W MAX 80W
Speaker	1.5" tweeter 5" full range	2" tweeter 8" full range	2" tweeter 8" full range
Amplifier	Class D		
SPL	108 dB @ 1 meter		109 dB @ 1 meter
Frequency	1.9 GHz (DECT)		
RF power	10/20 mW, upon region & local law		
Frequency response	70 ~ 15,000 Hz		
Operation range	50 (low power) ~ 70 (high power) meters, line of sight		
Bluetooth®	Bluetooth 5.0, TWS supported		
Inputs	1 x combo, 1 x 6.3 mm, 1 x 3.5 mm		
Outputs	1 x 3.5 mm, 2 x USB-A		
Speaker output	-	-	4-pole speakON®
Run time ^[1]	6 hours	6 hours	8 hours
Power supply	100 ~ 240 VAC, 20 VDC		
Battery	Lead-Acid, 12 V / 5 Ah	Lead-Acid, 12 V / 5 Ah	LiFePO4, 12.8 V / 6 Ah
Weight (with battery)	6.9 kg	8.1 kg	6.9 kg
Dimensions (WHD)	292 x 473 x 230 mm		

copyright ©
The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and the speakON® word mark and logos are registered trademarks owned by Neutrik AG. Any use of those marks by OKAYO is under license.
[1] Master volume set at 12 o'clock with 1 mic in use for speech.

Specifications	GX 7H	GX 7T
Product Type	Handheld microphone	Bodypack/Pendant microphone
Frequency	1.9 GHz (DECT)	
RF power	10/20 mW, upon region & local law	
Microphone type	Dynamic capsule	Electret condenser
T.H.D.	< 1%	
S/N ratio	> 90 dB	
Dynamic range	> 80 dB	
Latency	< 17 ms	
Frequency response	70 ~ 15,000 Hz	
Operation range	50 (low power) ~ 70 (high power) meters, line of sight	
Battery	2 AA 1.5V Alkaline	Li-ion polymer
Battery life	> 19 hours	> 12 hours
Dimensions	48.6 x 261.7 mm (Φ x L)	25 x 35 x 98 mm (D x W x H)
Weight (with battery)	250 ± 5 g	90 ± 5 g