

airstar

EVENT LIGHTING



#WeAreAirstar

Since 1994, Airstar has been revolutionising event lighting as the inventor and world leader in lighting balloons.

Our products, which combine aesthetics with performance, deliver a unique light that surpasses the capacity of traditional lighting systems.

Designed to adapt to all types of events, our balloons are versatile and fully customisable. Whether for decoration, signage, or brand promotion, they guarantee an outstanding visual presence.

Airstar guarantees reliable innovation, and is ready to illuminate your events and create unforgettable moments.



Our Markets



Social Events Cocktails, parties, diners



Fashion Fashion shows, photo shoots



Festivals Concerts, arts, culture



Branding Showroom,



Sports Championships, tournaments, races






Seminars, trade shows product launches




Backstage, catering areas, parking lots, emergency zones




Tailor-made
















MO





Innovation Airstar LED Matrix

> Airstar LED Matrix

A Unique Solution • Patented Innovation • 100% Airstar Technology

Our innovation is based on the development of a unique device called Matrix: a matrix light structure composed of **various independent LED modules and on-board information systems**. This technological cornerstone is the internal light source of our balloons.

Entirely designed by Airstar, every element - be it hardware, software, or firmware - is a testament to our expertise.

Advantages of the Airstar LED Matrix:

> Power: benefit from high-performance lighting, thanks to the combined power of the LED modules, for long-range illumination.

> Durability: a structure that is mechanically robust, due to the way the modules are assembled, and a longevity that is ensured by the quality of its components.

> Energy Efficiency: optimize your energy consumption with exceptional luminous efficiency.

> Lightness: the unique matrix design makes the product both light and powerful.

> **Reliability**: guaranteed lighting continuity, with each module operating independently to prevent any blackouts.

> **Scalability**: a platform that is designed to evolve and incorporate future functionalities, responding to new market uses.

> Control all your ballons

The Airstar Light mobile app offers unprecedented control over your lighting installations, enabling smooth communication between your balloons through an innovative Mesh network.


Centralized management: control and animate up to 250 balloons remotely, creating personalized, memorable lighting atmospheres for your events.

Complete control: precisely adjust the brightness of each balloon and modify their noise level to make them perfectly suitable for your use, whether indoors or outdoors.

Animation management: with up to 10 pre-programmed animations available directly in the app, you can easily create and customize all your lighting effects.

Atmosphere personalization: select the ideal colour temperature for your event (dynamic white range from 3000/6500 K) or choose vibrant colours (depending on balloon compatibility) to create the perfect atmosphere for every occasion.

Ease of use: The app offers an intuitive solution that works with DMX systems. It simplifies the grouping of different models of balloon, allowing for seamless synchronisation of your Airstar lighting in your staging.



Innovation Application Airstar Light

Available on

App Store

NEW

PowerSwitch: choose your power source

PowerSwitch adds unmatched flexibility to the Crystal Pixel balloon range in lighting management.

This innovative module allows you to easily adapt the energy source of your balloons, offering the choice between mains or battery power, depending on your needs.

Safety and peace of mind: our priorities


With PowerSwitch, you can benefit from a reliable power solution that anticipates necessary redundancy in the event of electrical failure.

Automatic switching to battery in the absence of power keeps lighting running, which is crucial for everyone's safety.

Whether you want to evacuate the public or protect event staff, Power-Switch is your best ally in the face of the unexpected.

Switch to PowerSwitch, illuminate with confidence


Innovation PowerSwitch



New ranges of connected balloons

The advanced Airstar LED Matrix technology is now at the heart of our brand new balloon ranges: Crystal Pixel, Neo Pixel and Sirocco.

This innovation offers an unprecedented connected lighting experience for all your events.




Innovation

Connected balloons



Crystal Pixel Color Dynamic White

Illumination



Technical data

| Lighted area | 1,700 m² / 18,300 ft² | | | | |
|--|--|-------------------------------------|-----------------|-----------------|--|
| Light under the balloon | | 110 lux (4 | m - 13 ft high) | | |
| Flicker | | 20 kHz | | | |
| LED Lifetime | 50,000 hrs | | | | |
| | Dynamic White | | Colors | Full | |
| | wW | cW | RGBA | Whites + Colors | |
| Color temperature | 3000 K | 6500 K | / | 4300 K | |
| CRI | 80 | 80 | / | 90 | |
| Luminous flux | 25,000 lm | 15,000 lm | 9,000 lm | 42,000 lm | |
| Power consumption | 204 W | 132 W | 120 W | 420 W | |
| Power Supply | 100~240 VAC 50-60 Hz Recommanded generator 1 kVA | | | | |
| Battery input - 52V / Backup power | PowerSwitch (included) Provides flexibility in use and installation, while ensuring safety (continuity in case of power failure) and the serenity of your events. | | | | |
| Envelope diameter | 90 cm (3ft), 130 cm (4 ft), 160 cm (5 ft), 200 cm (6.5 ft) | | | | |
| Wind resistance | Up to 80 km/h (49 mph) | | | | |
| Set-up time | 5 minutes | | | | |
| Inflation | Fast and self- | Fast and self-regulated inflation | | | |
| Noise level | 3 modes: silent, standard, high wind | | | | |
| Net weight of the balloon with envelope | From 11 kg (24 lb) to 12 kg (27 lb) | | | | |
| Certifications | CE, IP 54 | | | | |
| Light source | Airstar LED Ma | atrix : 12 macro | -pixels | | |
| Mesh network balloons | 100 m (109 yd | 100 m (109 yd) between each balloon | | | |
| Light controls | > via the control panel on the product > Remotely via the Airstar Light app > DMX • DMX profils available for major control surfaces | | | | |

- DMX profils available for major control surfaces
- 5-pin DMX connectors & CRMX
- Macro mode: 4 to 40 channels
- Pixel mode: 12 pixels/6 colors for 74 channels



Airstar Light App

Control your balloons easily and remotely!



Control up to

250 balloons

7+ light animations available

App Store

Google P

Customisation

RGBA

3000 K

6500 K

Vinyl graphics, Coloured slipcovers, Digitally printed envelopes

Accessories

Packaging


Various stands Stand cover, black or white Sandbags Suspension kit, Guying kit

Shock-proof wheeled case Dimensions : 81 x 47 x 35 cm 31 x 18 x 13 in Total weight: less than 23 kg (50 lb)



Crystal Pixel Dynamic White

Illumination



Airstar Light App

Control your balloons easily and remotely!



Control up to 250 balloons

0

7+ light animations available



Technical data

| Lighted area | 2,000 m |
|---------------------------------------|-------------------------------------|
| Color temperature | Dynamic |
| CRI | 80 |
| Flicker | 3.1 kHz |
| Luminous flux | 2 x 33,00 |
| LED lifetime | 50,000 ł |
| Power consumption | 500 W |
| Power supply | 100-240 |
| Battery input - 52V / Backup power | to (inc |
| | Provides while ens power fail |

| Envelope d | liameter |
|------------|----------|
|------------|----------|

Wind resistance Set-up time

Inflation

Noise level

Net weight of the balloon

with envelope

Certifications

Light source

Mesh network balloons

Light controls

n² / 22,000 ft² ic white: from 3,000 to 6,500 K 00 lm h

0 VAC 50-60 Hz

| 4 | PowerSwitch | Ne |
|----|-------------|----|
| 50 | (included) | |

flexibility in use and installation, suring safety (continuity in case of power failure) and the serenity of your events.

130 cm (4 ft), 160 cm (5 ft), 200 cm (6.5 ft)

Up to 80 km/h (49 mph)

5 minutes

Fast and self-regulated inflation

3 modes: silent, standard, high wind

From 11 kg (24 lb) to 12 kg (27 lb)

CE, IP 54

Airstar LED Matrix : 12 macro-pixels

100 m (109 yd) between each balloon

> via the control panel on the product

> Remotely via the Airstar Light app

- > DMX
 - DMX profils available for major control surfaces
 - 5-pin DMX connectors & CRMX
 - Macro mode: 4 to 16 channels
 - Pixel mode: 6 pixels/2 colors for 14 channels

Customisation

Vinul graphics Coloured slipcovers Digitally printed envelopes

3000K

6500K

Packaging

Shock-proof wheeled case Dimensions : 81 x 47 x 35 cm 31 x 18 x 13 in Total weight: less than 23 kg (50 lb)



Accessories


Various stands Stand cover, black or white Sandbags Suspension kit Guying kit





Crystal Pixel White

Illumination



Airstar Light App

Control your balloons easily and remotely!



Control up to 250 balloons

7+ light animations available



Technical data

Light source Mesh network balloons

Light controls

| Lighted area | 2,000 m² / 22,000 ft² | | |
|---|---|--|--|
| Color temperature | Neutral white : 4,000 K | | |
| CRI | 70 | | |
| Flicker | 3.1 kHz | | |
| Luminous flux | 66,000 lm | | |
| LED lifetime | 50,000 h | | |
| Power consumption | 500 W | | |
| Power supply | 100-240 VAC 50-60 Hz | | |
| Battery input - 52V / Backup power | PowerSwitch New! (included) Provides flexibility in use and installation while ensuring safety (continuity in case power failure) and the serenity of your even | | |
| Envelope diameter | 90 cm (3 ft), 130 cm (4 ft), 160 cm (5 ft), 200 cm (6.5 ft) | | |
| Wind resistance | Up to 80 km/h (49 mph) | | |
| Set-up time | 5 minutes | | |
| Inflation | Fast and self-regulated inflation | | |
| Noise level | 3 modes: silent, standard, high wind | | |
| Net weight of the balloon with envelope | From 10 kg (22 lb) to 12 kg (27 lb) | | |
| | | | |

Airstar LED Matrix : 12 macro-pixels

100 m (109 yd) between each balloon

> via the control panel on the product

- > Remotely via the Airstar Light app
- > DMX
 - DMX profils available for major control surfaces
 - 5-pin DMX connectors & CRMX
 - Macro mode: 4 to 10 channels
 - Pixel mode: 12 white pixels for 14 channels



Customisation

4000 K

Vinyl graphics Coloured slipcovers Digitally printed envelopes

Packaging


Shock-proof wheeled case Dimensions : 81 x 47 x 35 cm 31 x 18 x 13 in Total weight: less than 23 kg (50 lb)



Accessories

Various stands Stand cover, black or white Sandbags Suspension kit Guying kit





Technical data

| | Neo Pixel RGBW - 2.5m | Neo Pixel RGBW - 5m | |
|----------------------------|---|---------------------|--|
| Height | 2.5 m (8.2 ft) | 5 m (16.4 ft) | |
| Diameter | ø 20 cm (7.8 in) | ø 20 cm (7.8 in) | |
| Net weight of the balloon | 840 g (1.85 lb) | 1.6 kg (3.52 lb) | |
| Number of LEDs | 150 | 300 | |
| Light source | RGBW LED | RGBW LED | |
| Power consumption | 32 W | 64 W | |
| Mesh network balloons | 100 m (109 yd) between each balloon | | |
| Power supply | 100-240 VAC 50-60 Hz | | |
| Certifications | CE, IP 54 | | |
| Set-up time | 3 min for each balloon | | |
| Inflation | Air-inflated, airtsealed and without ventilation. Pressure : 350 mlb / 5 psi | | |
| Rallonge | 5 m $/$ 16.4 ft wire (between the controller and the power supply) | | |
| Contrôles de la lumière | > 10 color schemes x 10 animations: let your creativity run wild! > Individual light control using the controller's user interface > Individual or grouped control of the balloons with Airstar Light app > DMX • DMX profils available for major control surfaces • 5-pin DMX connectors • Wireless DMX (optional) • Macro mode: 4 to 28 channels • Pixel mode: • Neo 2.5 m: 75 pixels for 302 channels | | |

• Neo 5 m: 100 pixels for 402 channels

Airstar Light App

Control your balloons easily and remotely!





Control up to 250 balloons



10+ light animations available



Packaging



Transport bag: store up to 3 balloons ! Dimensions : $50 \times 30 \times 40$ cm $19.6 \times 11.8 \times 15.7$ in Total weight: less than 6 kg (12 lb)

Accessories



Optional: Floor stand Stand cover, black or white



Waterproof controller (included)





Sirocco Range



Sirocco 300 ProPack All-in-one product / Up to 12 hours autonomy



Sirocco 700 Over 3,000 m2 illuminated



Sirocco 1000 99,000 lm in less than 2 minutes

Our Sirocco range is perfectly suited to technical lighting requirements: emergency stations, parking lots, work zones, backstage areas, etc.









airstar



www.airstar-light.com