

Technical data

	VARIO 6	VARIO 8
Procedure	vaporizing fog machine with water	
Total requirement	3,4 kW	4,8 kW
Power of heater	2,2 kW	2,2 kW
Voltage	220 V - 245 V (208V – 245V) / 50 Hz (60Hz)	
Phase	1	2
Warm up time	10 min.	10 min.
Fluid consumption at 100% output	200 ml/min.	200 ml/min.
at 30% output	60 ml/min.	60 ml/min.
Fog volume	175 m3/min. 6500 CFM	225 m3/min. 8400 CFM
Water consumption L/hr.	1 – 24	1 – 48
Tube diameter	150mm	150mm
Tube lenght: horizontal use	max. 40m	
vertical use	up to 20m (67 feet)	
Fluid tank capacity	5 liter	
Water tank capacity	5L (optional 25L)	10L (optional 25L)
Fog output adjustable	0-100%	
Continous fogging	at <60%	at <60%
Coverage / minute up to	300m2	400m2
Control	DMX 512 / RDM	
Temperature control	Microprocessor	
Overheating protection	Heater block / thermostat Pump / Thermal switch	
Weight	62kg	80kg
Dimensions (L x W x H cm)	91x55x55	93x74x55



MT-ELECTRONIC GmbH

Am See 56

2443 Deutsch-Brodersdorf
Austria, Europe

Tel.: +43 699 12334455

email: office@mt-electronic.com

web: www.mt-electronic.com