3 Way Valves of Siral





3VT and 3VL

3VT and 3VL: 3-Way brass ball valves. Rugged construction with 2-piece-body Version with <u>2 seals</u> in PTFE

3VL: "L" shaped ball holes 3VT: "T" shaped ball holes Wide range of applications: Water, Air, Vacuum, Oils, non-corrosive-liquids in general

Handle with lable indicating the ball hole position

Range: 1/4" - 2" 1/2 Pressure Rating: PN16 Temp. Rating: -20° / +150°C



Dependable and Durable Valve Solutions



3VNT and 3VNL: 3-Way brass ball valves. Version with 4 seals in PTFE 3VNL: "L" shaped ball holes 3VNT: "T" shaped ball holes Wide range of applications: Water, Air, Vacuum, Oils, non-corrosiveliquids in general Handle with label indicating the ball hole position

Gamma: da 1/4" a 2" Pressione: PN16 Temperatura: -20° / +150°C

Unless otherwise requested, these valves (3VNL/3VNT) are delivered with non-assembled handle with 4 teeth to be cut in function of the desired flow pattern.





T Port 90°, 180°, or 270° rotation levers provides full flexibility for flow control. Please specify flow paths required A, B, C, D.

annahanna	minhimin	minitian	unnolunun	
The start	Tang gan	Tang gas		
A	в	C	D	



Maximum Flexibility in determining the flow patterns



