

## Siral Gas Valves, Always Dependable.

#### V3000 - DVGW EN331



The V3000 is a robust brass ball valve for Gas.

Heavy weight valve of rugged construction.

DVGW EN331 approval

Full bore for minimum pressure drop.

Double stem O-rings for total sealing integrity.

Lockable handle version is available

Size range: 1/4" - 2"

Pressure rating: MOP 5
Temperature rating: -20°C / +60°C

### V3000 Oxygen



Heavy weight valve of rugged construction. Degreased version, especially suitable for use with oxygen and medical gases. Lockable handel version is available. Individually packed. Available on request.

# When Safety is Paramount

### VN3000 HTB (EN331)



The VN3000 HTB is a high temperature resistant gas safety ball valve. It has a unique design charactristic that allows the valve to seal when seats deform or melt due to extreme high temperature caused by fires. This valve can be offered with lockable handle. Allowed thermal charge: +650°C (1202°F) at 1 bar (14.5 psi) working pressure

Size range: 1/2" - 2"

### **Gasline 309**





The Gasline 309 is a gas ball valve with a unique built -in pressure port downstream of the ball that allows for pressure tests with the ball only in the closed position.

The positioning of the pressure port is a deliberate safety feature. The handle must be in hte full closed position to access the pressure port.

www.siral.com Support: +39 0308251211 sales4siral.com