

Underfloor Heating System

Available all the components and accessories for the installation of underfloor heating and refreshing systems. Pipe, thermoformed boards, manifolds, regulation...



Plastic Pipes

We manufacture and sell worldwide a wide variety of high quality plastic pipes.

- 👉 PE-Xa Monolayer
- 👉 PE-Xa EVOH (3 and 5 Layers)
- 👉 PE-Xa Black Protection / PIP
- 👉 PE-Xa EVOH 3 Black Protection
- 👉 PERT EVOH (3 and 5 Layers)
- 👉 Multilayer (PERT/AL/PERT)
- 👉 Multilayer (PEX/AL/PE)



MLC Press Fittings

Made of CW617N brass. Our barb design is a sawtooth profile that ensures a perfect union and tightness. O-ring assembled with 70% peroxide EPDM and sleeve made of stainless steel with inspection windows to ensure that the pipe is fully home.



PEX Press Fittings

Suitable for cross-linked polyethylene pipes. 6-barbed fitting for better water tightness. Stainless steel sleeve with inspection windows to ensure that the pipe is fully home.



Expansion Ring Fittings

Made of CW617N brass and PPSU, compatible with PEXa pipes with diameters 16, 20, 25 and 32 mm (with $\varnothing 16 \times 1.5$; $\varnothing 16 \times 1.8$; $\varnothing 16 \times 2.0$; $\varnothing 16 \times 2.2$; $\varnothing 20 \times 1.9$; $\varnothing 20 \times 2.0$; $\varnothing 20 \times 2.3$; $\varnothing 20 \times 2.8$; $\varnothing 25 \times 2.3$; $\varnothing 25 \times 2.8$; $\varnothing 25 \times 3.5$; $\varnothing 32 \times 2.9$; $\varnothing 32 \times 3.6$; $\varnothing 32 \times 4.4$). Injected ring with a stop to guarantee the secure expansion and contraction. Assembly compatible with all commercially available tools.



Expansion
Ring Fittings

Axial PEX Fittings

Fittings compatible with cross-linked polyethylene pipes (with $\varnothing 16 \times 1.8$; $\varnothing 16 \times 2.0$; $\varnothing 20 \times 1.9$; $\varnothing 20 \times 2.0$; $\varnothing 25 \times 2.3$; $\varnothing 32 \times 2.9$). Designed with barb that allows a turn of the fitting once installed, maintaining all its characteristics without losing the water tightness.



MLC Compression Fittings

Made of chrome plated CW617N brass. With 2 O-rings that reinforce the water tightness, a tightening nut and an anti-electrolysis gasket.



PEX Compression Fittings

Made of CW617N brass. With a tightening nut.



Tools and accessories

Get to know all our tools and spare parts necessary for the assembly of all our flexible plumbing, heating and air conditioning systems.





Passion

As well known, the *passion* moves the world.



Innovation

We adapt to advances of the sector.



Circular Economy

We promote the *sustainable development*.



Commitment

We focus on surpassing *your needs*.



Guarantee

We protect you and we *fulfill* with what has been agreed.



Quality

We provide you with *the best products*.

 **Fittingsestandar**

 **Fittings**
estandar



**WE CONNECT
WITH WATER.**

We connect with you.

www.fittingsestandar.com



Telf. 967 667 690 - clientes@fittingsestandar.com

Pol. Ind. Romica · C/ Estocolmo N° 5

02007 Albacete, España

Connecting with you since

2000

*Flexible Plumbing,
Heating and
Air conditioning systems*