


# womix

Comfort Controls

NEWS  
2024/2025



[www.womix.pl](http://www.womix.pl)

## Buffer tanks with hydraulic sets




Complete boiler room installation systems with a heat buffer were created to enable compact installation of boiler rooms using a heat pump. They are available in three capacities, i.e. 500L, 800L and 1000L. The dedicated mounting bracket and connections, with which the buffers are equipped, allow for the installation of WS40 domestic hot water preparation stations, D pump group sets and the Vertigo VRD solar group in the case of using solar energy. The buffers have a built-in coil for cooperation with various heat sources and the possibility of installing an additional 1 1/2" electric heater, used to support water heating.


### Technical data:

Material:	
tank:	steel
coil:	stainless steel
Maximum pressure:	tank 3 bar
coil:	6 bar
Max. temperature:	tank: 95°C
coil:	110°C
Capacity:	500, 800, 1000 l

Type	Volume [l]	Catalog number
Buffer tank 500L, with mounting a handle and complete set of connections for hydraulic sets	500	606911
Buffer tank 800L, with mounting a handle and complete set of connections for hydraulic sets	800	606921
Buffer tank 1000L, with mounting a handle and complete set of connections for hydraulic sets	1000	606931
Domestic hot water preparation station WS 40		see catalog
Set D		see catalog
Solar group VERTIGO VRD 90 - DN 20 with rotameter 2-12 l/min,		see catalog




## Example of application with heat pump and solar collectors




The diagrams show the application in the case of using all pump groups dedicated to the buffer system. The tank can also be used in the case of selecting only some of them.

Example of application with heat pump and solar collectors together with hybrid use of gas or oil boiler




The diagrams show the application in the case of using all pump groups dedicated to the buffer system. The tank can also be used in the case of selecting only some of them.

## Example of application with heat pump and solar collectors together with hybrid use of a solid fuel boiler



The diagrams show the application in the case of using all pump groups dedicated to the buffer system. The tank can also be used in the case of selecting only some of them.





### Cascade collector, for heating and cooling CH2 100 - DN 50




Cascade collector, for heating and cooling C 2 100 - DN 50 was created to connect heat pumps in a cascade. It is factory-equipped with tightly fitted EPP insulation and wall brackets. The collector can be used for heating and cooling.

**Technical data:**


Material: steel  
 Maximum pressure: 6 bar  
 Maximum temperature: 110°C  
 Axle spacing: 125 mm  
 Insulation: EPP black  
 Connection: heat pump side: 1 1/4" M  
 installation side: 2" F

Type	Power at DT 5°C	Power at DT 10°C	Power at DT 20°C	Flow [m³/h]	Catalog number
Cascade collector, for heating and cooling <b>CH2 100 2F - DN 50</b> , 2 heat pumps	<b>76,00</b>	<b>150,00</b>	<b>300,00</b>	13,00	607141 
Cascade collector, for heating and cooling <b>CH2 100 3F - DN 50</b> , 3 heat pumps	<b>76,00</b>	<b>150,00</b>	<b>300,00</b>	13,00	607142 
Cascade collector, for heating and cooling <b>CH2 100 4F - DN 50</b> , 4 heat pumps	<b>76,00</b>	<b>150,00</b>	<b>300,00</b>	13,00	607143 
Cascade collector, for heating and cooling <b>CH2 100 5F - DN 50</b> , 5 heat pumps	<b>76,00</b>	<b>150,00</b>	<b>300,00</b>	13,00	607144 

thanks to tight insulation it is possible to use a collector for the distribution of heat and cold



## Example of using the CH2 100 - DN 50 cascade collector



Magnetic separators SM

New price!

SM 20



Angle mounting

ball valve included

SM 25,  
SM 32



Magnetic separator SM is used to remove impurities in closed central heating systems. Contaminants in the circulation can accelerate the wear of pumps, valves and other components of the heating system. Contaminants can also limit the flow of the system, thus reducing the efficiency of the entire system. The separator can be installed on vertical or horizontal pipelines, and its unique design allows for excellent filtration and deposition of impurities in the filter tank. Removal of impurities can occur during normal operation of the installation.

Magnetic separator SM 20

Technical data:

Body: Polyamide PA66 reinforced with glass fiber  
 Magnet: Neodymium 9000 G  
 Medium: water/glycol(30%)  
 Temperature range: max. 90°C  
 Max. pressure: 3 bar  
 Flow: kvs 5.8 (recommended 1.7)  
 Seal: EPDM  
 Connection: 3/4" GW  
 Filtration: system of two stainless steel meshes 400/1500 µm

Magnetic separator SM 25, SM 32

Technical data:

Body: Polyamide PA66 reinforced with glass fiber  
 Magnet: Neodymium 9000 G  
 Medium: water/glycol(30%)  
 Temperature range: max. 90°C  
 Max. pressure: 3 bar  
 Flow: SM 25 - kvs 7.1  
 SM 32 - kvs 7.7  
 Seal: EPDM  
 Connection: 1" F or 1 1/4" F  
 Filtration: double mesh stainless steel system 800/1500 µm

Type	Flow [m³/h]	Catalog number
Magnetic separator SM 20 - DN 20	5,8	500035
Magnetic separator SM 25 - DN 25	7,1	500036
Magnetic separator SM 25 - DN 32	7,7	500037

Possibilities of connecting a magnetic separator SM



Installing the separator on a vertical pipeline



Installing the separator on a horizontal pipeline



Installing the separator on a sloped pipeline

## Magnetic separator D-SM



Ball  
valves  
included

High flow  
perfect for heat pumps

1 1/4"  
kvs 33,5

1 1/2"  
kvs 36,2

The D-SM magnetic separator is used to remove impurities in closed central heating systems. Dedicated to heat pump installations. Contaminants in the circulation can accelerate the wear of pumps, valves and other components of the heating system. Contaminants can also limit the flow of the system, thus reducing the efficiency of the entire system. The separator can be installed on vertical or horizontal pipelines, and its unique design allows for excellent filtration and deposition of impurities in the filter tank. Removal of impurities can occur during normal operation of the installation.


### Magnetic separator D-SM 32, D-SM40

#### Technical data:

Body:	Polyamide PA66 reinforced with glass fiber
Magnet:	Neodymium 12000 G
Medium:	water/glycol (30%)
Temperature range:	max. 90°C
Max. pressure:	3 bar
Flow:	D-SM 32 - kvs 33.5 D-SM 40 - kvs 36.2
Seal:	EPDM
Connection:	1 1/4" F or 1 1/2" F
Filtration:	two-mesh system made of stainless steel 1500 µm


Type	Flow [m <sup>3</sup> /h]	Catalog number
Magnetic separator D-SM 32 - DN 32	33,5	500043
Magnetic separator D-SM 40 - DN 40	36,2	500044

### Possibilities of connecting the D-SM magnetic separator




Installing the separator on a vertical pipeline

Possibility of mounting ball valves in any position.




Installing the separator on a horizontal pipeline



Installing the separator on a sloped pipeline

## Domestic hot water preparation station WS 40




The domestic hot water (DHW) preparation station WS40 is a device used for efficient and fast heating of domestic water in residential and commercial buildings. It operates on the principle of flow water heating, thanks to which the water is heated directly at the moment of its use, which eliminates the need to store large amounts of hot water and reduces energy losses. The station is equipped with a heat exchanger, which allows for the efficient use of heat from various sources, such as gas boilers, heat pumps or solar installations. Thanks to advanced automation, DHW preparation stations can adjust their operation to the current demand for hot water, which allows for energy savings and increased user comfort. The system includes a steel closing cabinet.

**Technical data:**


Material:	copper, brass, stainless steel
Maximum operating pressure:	F1-F2 primary side 10 bar F3-F4 secondary side 16 bar
Flow capacity:	40 l/min
Number of exchanger plates:	40
Medium temperature:	max.: +95 °C min.: +2 °C

Nazwa asortymentu	Nr katalogowy
Domestic hot water preparation station WS 40, with pump Grundfos UPM4S 15-60	606711


New



## Connection diagram of the domestic hot water preparation station WS 40



Domestic hot water preparation station, with circulation WS 40C




The domestic hot water (DHW) preparation station is a device used for efficient and fast heating of domestic water in residential and commercial buildings. It operates on the principle of flow water heating, thanks to which the water is heated directly at the moment of its use, which eliminates the need to store large amounts of hot water and reduces energy losses. The station is equipped with a heat exchanger, which allows for the efficient use of heat from various sources, such as gas boilers, heat pumps or solar installations. Thanks to advanced automation, DHW preparation stations can adjust their operation to the current demand for hot water, which allows for energy savings and increased user comfort. The system includes a steel closing cabinet.


**Technical data:**

Material: copper, brass, stainless steel  
 Maximum operating pressure: F1-F2 primary side 10 bar  
 F3-F4 secondary side 16 bar  
 Flow capacity: 40 l/min  
 Number of exchanger plates: 40  
 Medium temperature: max.: +95 °C  
 min.: +2 °C  
 Circulation pump: Womix eco Pro 15-1/65

Type	Catalog number
Domestic hot water preparation station WS 40C, with circulation, with pump Grundfos UPM4S 15-60	606721



Connection diagram of the domestic hot water preparation station WS40C



## Single-circuit hydraulic separator XPN MINI - DN 25

The XPN MINI - DN 25 hydraulic separator is made of steel. It is factory-equipped with insulation, two connections for a temperature sensor and a drain valve (1/2" sleeve). The set includes a plunger sleeve for connecting a 1/2" temperature sensor and a wall bracket.

Possibility of installation horizontally




**Technical data:**

Material: steel  
 Maximum pressure: 6 bar  
 Maximum flow: 1.5 m<sup>3</sup>/h  
 Maximum temperature: 110°C  
 Insulation: EPP black  
 Connection: 1" GZ


Type	Flow [m <sup>3</sup> /h]	Volume [l]	Catalog number
Single-circuit hydraulic separator XPN MINI - DN 25	1,5	0,7	611055



**Mounting bracket included**



**Connection diagram**




magnetic separator SM 25


Set H1

*Simplified schematic diagram of the installation - standard installation elements as well as the boiler room protection diagram were not marked.*

**underfloor heating circuit**



## Set H1 - single-circuit set without mixing valve




Type	Catalog number
Set H1 with pump <b>Wilo Yonos Para 25/6</b>	656051
Set H1 with pump <b>Grundfos UPM3S Auto 25-60</b>	656059
Set H1 with pump <b>DAB Evosta2 65/180</b>	656053

The set includes:

1. Single-circuit hydraulic separator XPN MINI - DN 25 with a bracket,
2. Group SA 125 - DN 25 with a pump (see table).

## Set H2 - single-circuit set with rotary mixing valve and electric actuator



Type	Catalog number
Set H2 with pump <b>Wilo Yonos Para 25/6</b>	656081
Set H2 with pump <b>Grundfos UPM3S Auto 25-60</b>	656082
Set H2 with pump <b>DAB Evosta2 65/180</b>	656083

The set includes:

1. Single-circuit hydraulic separator XPN MINI - DN 25 with a bracket,
2. Group SMT 125 - DN 25 with a pump (see table),
3. Actuator SL 10 - 230 / 120 with adapter no. A 101.

## Set H3 - single-circuit set with thermostatic mixing valve with regulation 20-45 °C




Type	Catalog number
Set H3 with pump <b>Wilo Yonos Para 25/6</b>	656071
Set H3 with pump <b>Grundfos UPM3S Auto 25-60</b>	656072
Set H3 with pump <b>DAB Evosta2 65/180</b>	656073

The set includes:

1. Single-circuit hydraulic separator XPN MINI - DN 25 with a bracket,
2. Group SMT C1 125 - DN 25 with a pump (see table).

## Set H4 - single-circuit set with thermostatic mixing valve with regulation 35-60 °C




Nazwa asortymentu	Nr katalogowy
Set H4 with pump <b>Wilo Yonos Para 25/6</b>	656091
Set H4 with pump <b>Grundfos UPM3S Auto 25-60</b>	656092
Set H4 with pump <b>DAB Evosta2 65/180</b>	656093

The set includes:

1. Single-circuit hydraulic separator XPN MINI - DN 25 with a bracket,
2. Group SMT C1 125 - DN 25 with a pump (see table).

## Flanged air separator SPK



The SPK air separator is used to remove air bubbles from central heating systems. The presence of air in closed systems can lead to corrosion, reduced heat exchange efficiency, noise and mechanical damage. The use of an insert containing Białecki rings (1.) allows the bubbles to rise and accumulate in the upper part of the separator, from where they are then removed. The separator helps maintain high efficiency and reliability of hydraulic systems, thanks to which they operate more efficiently, which translates into energy savings and extended component life.

### Technical data:

Material:	steel
Maximum pressure:	6 bar
Maximum operating temperature:	110°C
Flange pressure standard:	PN 16
Insulation:	EPP black

Type	Flow [m <sup>3</sup> /h]	Catalog number	
Flanged air separator <b>SPK+ 150 - DN 50</b> with additional equipment, with insulation, painted	8,50	609261	New
Flanged air separator <b>SPK+ 150 - DN 65</b> with additional equipment, with insulation, painted	14,00	609162	New
Flanged air separator <b>SPK+ 250 - DN 80</b> with additional equipment, with insulation, painted	21,00	609163	New
Flanged air separator <b>SPK+ 250 - DN 100</b> with additional equipment, with insulation, painted	33,00	609164	New
Flanged air separator <b>SPK+ 300 - DN 125</b> with additional equipment, with insulation, painted	54,00	609165	New
Flanged air separator <b>SPK+ 300 - DN 150</b> with additional equipment, with insulation, painted	79,00	609166	New

## Straight distance connector for FMK basket strainer and SPK air separators



The spacer connector helps in mounting the basket strainer and air separator unit in pump group systems.

Type	Catalog number	
Straight distance connector DN 50 (L-350mm) for <b>FMK 150 - DN 50</b> and <b>SPK 250 - DN 50</b> with screws and gasket EPDM DN 50, with insulation	699061	
Straight distance connector DN 65 (L-350mm) for <b>FMK 150 - DN 65</b> and <b>SPK 250 - DN 65</b> with screws and gasket EPDM DN 65, with insulation	699062	
Straight distance connector DN 80 (L-510mm) for <b>FMK 250 - DN 80</b> and <b>SPK 250 - DN 80</b> with screws and gasket EPDM DN 80, with insulation	699063	
Straight distance connector DN 100 (L-510mm) for <b>FMK 300 - DN 100</b> and <b>SPK 300 - DN 100</b> with screws and gasket EPDM DN 100, with insulation	699064	
Straight distance connector DN 125 (L-510mm) for <b>FMK 300 - DN 125</b> and <b>SPK 300 - DN 125</b> with screws and gasket EPDM DN 125, with insulation	699065	
Straight distance connector DN 150 (L-510mm) for <b>FMK 350 - DN 150</b> and <b>SPK 300 - DN 150</b> with screws and gasket EPDM DN 150, with insulation	699066	New

## Hydraulic separator CPN 300 - DN 150



Hydraulic separator **CPN 300 - DN 150** is made of steel. It is factory-equipped with EPP insulation and two connections for a temperature sensor (1" sleeve) and a vent (1 1/4" sleeve) on the upper side, and a drain (1" sleeve) on the lower side. Separator contains a system of built-in grids (1.) and partitions (2.) that help to precipitate air bubbles and sediments, thus increasing its functionality and efficiency. The set includes mounting feet.

### Technical data:

Material:	steel
Maximum pressure:	6 bar
Maximum temperature:	110°C
Insulation:	EPP black
Flange pressure standard:	PN 16

Type	Power [kW] at DT 20°C	Flow [m³/h]	Volume [l]	Catalog number
Hydraulic separator CPN 300 - DN 150 with insulation	1200,00	50,00	120	609105

## Central heating zone manifold C2 150



Zone manifold **C2 150** was created to facilitate the assembly of DN 25, 32, 40, 50 pump groups. It is factory-equipped with EPP insulation and has a DN 50 flange connection on the installation side. Manifold contains 2 seals with a diameter adapted to the diameter of the distributor connection and a set of 8 assembly screws for connecting to another zone manifold or hydraulic separator. On request, we can make them with a different connection.

### Technical data:

Material:	steel
Maximum pressure:	6 bar
Maximum temperature:	110°C
Insulation:	EPP black

Type	Power [kW] at DT 20°C	Flow [m³/h]	Catalog number
Central heating zone manifold C 2 150 2 F - DN 150 with insulation	1200,00	50,00	609129
Central heating zone manifold C 2 150 3 F - DN 150 with insulation	1200,00	50,00	609130

Type	Catalog number
Brackets for mounting the distributor on the ground (1 set = 2 pieces)	607040

## Reduction flange DN 50




The DN 50 reduction flange was created to facilitate the transition from a flanged connection to a threaded one in C2 125, C2 150 central heating manifolds. The flange includes a set of 4 mounting screws and a DN 50 gasket for connection to the manifold.


### Technical data:

Material:	steel
Maximum pressure:	6 bar
Maximum temperature:	110°C
Norma ciśnieniowa kołnierzy:	PN 16

Type	Catalog number
Reduction flange DN50(flange) – DN25(M), with 4 mounting screws and gasket EPDM DN 50	699081
Reduction flange DN50(flange) – DN32(M), with 4 mounting screws and gasket EPDM DN 50	699082
Reduction flange DN50(flange) – DN40(M), with 4 mounting screws and gasket EPDM DN 50	699083
Reduction flange DN50(flange) – DN50(M), with 4 mounting screws and gasket EPDM DN 50	699084



## Hydraulic separator CPN 300 - DN 150



The CPN 300 - DN 150 hydraulic separator is made of steel. It is factory-equipped with EPP insulation and two connections for a temperature sensor (1" sleeve) and a vent (1 1/4" sleeve) on the upper side, and a drain (1" sleeve) on the lower side. The set includes mounting feet.

### Technical data:

Material:	steel
Maximum pressure:	6 bar
Maximum temperature:	110°C
Maximum flow:	50 m <sup>3</sup> /h
Insulation:	EPP black 40 g/l
Heating power:	1200 kW
Flange pressure standard:	PN 16

Type	Power [kW] at DT 20°C	Flow [m <sup>3</sup> /h]	Volume [l]	Catalog number
Hydraulic separator CPN 300 - DN 150 with insulation	1200,00	50,00	120	609105 <span style="float: right;">New</span>


## Set of connectors for connecting the hydraulic separator to the zone manifold



The connectors are made of steel. They are designed to connect the CPN 300 DN 150 clutch with the DN 150 distributor. The set includes two connectors and a set of 8 mounting screws with gaskets.

Type	Catalog number
Set of connections DN150 for connecting hydraulic separator CPN 300 – DN 150 with manifold DN150, without insulation	699009 <span style="float: right;">New</span>

## Central heating zone manifold C2XL 150 - DN 150



The C2XL 150, 2 or 3 circuit, two-chamber steel distributor was created to facilitate the assembly of DN 50, 65, 80 pump groups. It is factory-equipped with EPP insulation and has a DN 80 flange connection on the installation side. The distributor contains 2 DN 150 seals, a set of 8 assembly screws for connecting to another distributor or hydraulic clutch. On request, we can make distributors with a different connection.

### Technical data:

Material:	steel
Maximum pressure:	6 bar
Maximum temperature:	110°C
Heating power:	1200 kW at ΔT 20°C
Insulation:	EPP black 40 g/l
Flange pressure standard:	PN 16

Type	Power [kW] at DT 20°C	Flow [m <sup>3</sup> /h]	Catalog number
Zone manifold C2XL 150 2 F - DN 150 with insulation	1200,00	50,00	609191 <span style="float: right;">New</span>
Zone manifold C2XL 150 3 F - DN 150 with insulation	1200,00	50,00	609192 <span style="float: right;">New</span>

Type	Catalog number
Brackets for mounting the distributor on the ground (1 set = 2 pieces)	607040

Pump group DXL-SA 300 - DN 50, DN 65, DN 80



Pump group DXL-SA 300 - DN 50, 65, 80 is equipped with a set of steel connectors, an inclined filter, two thermometers, a check valve and additional 1/2" GW outlets on the supply and return.

**Technical data:**


Maximum pressure:	6 bar
Maximum temperature:	110°C
Axle spacing:	300 mm
Seals:	VITON or EPDM
Connection:	DN 50, PN 16 flange for DN 50 groups DN 65, PN 16 flange for DN 65 groups DN 80, PN 16 flange for DN 80 groups

**NOTE!** The pump group is not equipped with shut-off valves. We recommend installing standard products available on the market, i.e. ball valves or butterfly valves with the diameter of the pump group on the boiler and installation side.

Type	Catalog number
Pump group DXL – SA 300 – DN 50 (2") without insulation, without pump, pump installation length 280 mm	629111
Pump group DXL – SA 300 – DN 50/40 (2") without insulation, without pump, with flange pump connection DN40 (250mm)	629112
Pump group DXL – SA 300 – DN 50/32 (2") without insulation, without pump, with flange pump connection DN32 (220mm)	629113
Pump group DXL – SA 300 – DN 65 (2 1/2") without insulation, without pump, pump installation length 340 mm	629121
Pump group DXL – SA 300 – DN 65/50 (2 1/2") without insulation, without pump, with flange pump connection DN50 (280 mm)	629122
Pump group DXL – SA 300 – DN 65/40 (2 1/2") without insulation, without pump, with flange pump connection DN40 (250 mm)	629123
Pump group DXL – SA 300 – DN 80 (3") without insulation, without pump, pump installation length 360 mm	629131
Pump group DXL – SA 300 – DN 80/65 (3") without insulation, without pump, with flange pump connection DN65 (340 mm)	629132
Pump group DXL – SA 300 – DN 80/50 (3") without insulation, without pump, with flange pump connection DN50 (280 mm)	629133

Type	Catalog number
Set of RG 50 280 mm / 240 mm spacer extensions for mounting DN 50 pumps with an installation length of 240 mm	629091
Set of RG 65 340mm / 280mm spacer extensions for mounting DN 65 pumps with an installation length of 280mm	629092
Connector DN80 x DN50 for mounting DXL – DN 50 pump groups on the C2XL 150 – DN150 manifold	699006
Connector DN80 x DN65 for mounting DXL – DN 65 pump groups on the C2XL 150 – DN150 manifold	699007



### Pump group DXL-SMT 300 - DN 50, DN 65, DN 80



Pump group **DXL-SMT 300 - DN 50, 65, 80** is equipped with a set of steel connectors, a check valve, an inclined filter, a flanged mixing valve, two thermometers and additional 1/2" F outlets on the supply and return. Additionally, to ensure automatic operation of the mixing valve, the group should be equipped with an **SL 10 - 10Nm** or **MP 15 - 15 Nm** actuator (depending on the diameter of the mixing valve).

**Technical data:**


Maximum pressure:	6 bar
Maximum temperature:	110°C
Axle spacing:	300 mm
Seals:	VITON or EPDM
Connection:	DN 50, PN 16 flange for DN 50 groups DN 65, PN 16 flange for DN 65 groups DN 80, PN 16 flange for DN 80 groups

**ATTENTION!** The pump group is not equipped with shut-off valves. We recommend installing standard products available on the market, i.e. ball valves or butterfly valves with the diameter of the pump group on the boiler and installation side.

Type	Catalog number	
Pump group <b>DXL - SMT 300 - DN 50 (2")</b> without insulation, without pump, pump installation length 280 mm	629161	New
Pump group <b>DXL - SMT 300 - DN 50/40 (2")</b> without insulation, without pump, with flange pump connection DN40 (250mm)	629162	New
Pump group <b>DXL - SMT 300 - DN 50/32 (2")</b> without insulation, without pump, with flange pump connection DN32 (220mm)	629163	New
Pump group <b>DXL - SMT 300 - DN 65 (2 1/2")</b> without insulation, without pump, pump installation length 340 mm	629171	New
Pump group <b>DXL - SMT 300 - DN 65/50 (2 1/2")</b> without insulation, without pump, with flange pump connection DN50 (280 mm)	629172	New
Pump group <b>DXL - SMT 300 - DN 65/40 (2 1/2")</b> without insulation, without pump, with flange pump connection DN40 (250 mm)	629173	New
Pump group <b>DXL - SMT 300 - DN 80 (3")</b> without insulation, without pump, pump installation length 360 mm	629181	New
Pump group <b>DXL - SMT 300 - DN 80/65 (3")</b> without insulation, without pump, with flange pump connection DN65 (340 mm)	629182	New
Pump group <b>DXL - SMT 300 - DN 80/50 (3")</b> without insulation, without pump, with flange pump connection DN50 (280 mm)	629183	New

Type	Catalog number	
Set of RG 50 280 mm / 240 mm spacer extensions for mounting DN 50 pumps with an installation length of 240 mm	629091	
Set of RG 65 340mm / 280mm spacer extensions for mounting DN 65 pumps with an installation length of 280mm	629092	New
Connector DN80 x DN50 for mounting DXL - DN 50 pump groups on the C2XL 150 - DN150 manifold	699006	New
Connector DN80 x DN65 for mounting DXL - DN 65 pump groups on the C2XL 150 - DN150 manifold	699007	New



## Additional equipment for the system 1200 kW

Basket strainer filter FMK 350  
without insulation



Air separator SPK



Spacer connector



Angle connector 90°  
DN 150



Magnetic insert



Brackets



Actuator



Blanking flanges



Butterfly valves



Type	Catalog number
Basket strainer filter FMK 350 - DN 150 with additional equipment, without insulation, painted	609146
Basket strainer filter <b>FMKo 350</b> - DN 150 with additional equipment, without insulation, galvanized	609156
Flanged air separator <b>SPK+</b> 300 - DN 150 with additional equipment, with insulation, painted	609166
Straight spacer connector DN 150 (L-510mm) for <b>FMK 350 - DN 150</b> and <b>SPK 300 - DN 150</b> with screws and EPDM seal DN 150, with insulation	699066
Angle connector 90° - DN 150 with 4 mounting screws and EPDM seal DN 150	699015
Magnetic strainer filters <b>FMK 250 - DN 80, 300 - DN 100, DN 125, FMK 350 - DN 150</b>	607262
Brackets for mounting the distributor on the ground (1 set = 2 pieces)	607040
Actuator <b>MP 10</b> (for mixing valve diameters up to DN 50)	401011
Actuator <b>MP 15</b> (for mixing valve diameters DN 65, DN 80)	401031
Actuator <b>SL 10</b>	415001
Blanking flange DN 150 with 4 mounting screws and EPDM gasket DN 150	699025
Blanking flange with muff DN 150 with 4 mounting screws and EPDM gasket DN 150	699035
Butterfly valves	see catalog

## Steel flanges for welding



Steel flanges are key elements used in various industries, such as petrochemical, oil, gas, chemical and water. They are used to connect pipes, valves, pumps and other mechanical devices, ensuring tightness and durability of connections. Made of steel, they can withstand high pressures and temperatures, and are also resistant to corrosion. Thanks to their strength and versatility, they are an irreplaceable element of industrial infrastructure.

### Technical data:

Pressure standard: PN 16, EN1092-1  
 Diameter: from DN 50 to DN 125  
 Material: S235JR

Type	Catalog number	
Steel flat flange DN 50, PN16, EN1092-1, S235JR, for welding	698103	New
Steel flat flange DN 65, PN16, EN1092-1, S235JR, for welding	698104	New
Steel flat flange DN 85, PN16, EN1092-1, S235JR, for welding	698105	New
Steel flat flange DN 100, PN16, EN1092-1, S235JR, for welding	698106	New
Steel flat flange DN 125, PN16, EN1092-1, S235JR, for welding	698107	New
Steel flat flange DN 150, PN16, EN1092-1, S235JR, for welding	698108	New

## Automatic air vent **Compact**



Compact automatic air vents are installed to remove air accumulating in heating and air conditioning systems. Thanks to their operation, without the need for manual operation, they allow to avoid harmful phenomena that may threaten the life and efficiency of hydraulic systems. In particular, they limit the negative effect of galvanic corrosion (caused by the presence of oxygen inside the pipeline) and cavitation. Moreover, these valves allow to optimize the heating and cooling power of each system, because they prevent the formation of air pockets inside radiators and fan coils.

### Technical data:

Body: brass  
 Connection diameter: 1/2"  
 Float: polyethylene  
 Max. temperature: 110 °C  
 Max. working pressure: 6 bar

Type	Catalog number
Automatic air vent <b>Compact</b> , with stop valve 1/2"	100100

Manometers



Temperature sensor cover




Safety valve



Immersion sleeve 1/2"



Brass plugs



Brass connector with nuts 1" x 1"



Brass nipples with check valve



Brass quick connector 3/4"




Type

Catalog number

Manometer 0-6 bar	015041	New
Manometer 0-10 bar	015042	New
Safety valve 3 bar	015051	New
Safety valve 6 bar	015052	New
Cover for temperature sensor 1/2" L-70mm, sensor fi 9mm, with o-ring	607215	New
Cover for temperature sensor 1/2" L-150mm, sensor fi 9mm, with o-ring	607216	New
Cover for temperature sensor 3/4" L-200mm, sensor fi 13mm, with o-ring	607217	New
Nipple 1" x 1" with built-in check valve	200188	New
Brass connector with nuts 1" x 1"	200189	New
Brass quick connector 3/4" for expansion tank	607220	
Immersion sleeve 1/2" for L-50 temperature sensor, 6 mm sensor, with O-ring	607228	
Brass reducing plug with gasket DN 25/ DN 15	607231	
Brass reducing plug with gasket DN 32/ DN 15	607232	
Brass reducing plug with gasket DN 40/ DN 15	607233	
Brass reducing plug with gasket DN 50/ DN 15	607234	

## Stainless steel manifold CS-Rot





CS-Rot manifolds are made of SS304 stainless steel and are used to connect a specific number of heating or cooling circuits with individual flow regulation/cut-off. In addition, they enable the connection of a mixing and pump group in order to obtain the design temperature for underfloor heating and maintain appropriate operating parameters of the installation by independently powering each heating circuit. They are available with Taconova rotameters 0-5 l/min or 0-2.5 l/min. They are equipped with chrome-plated handles with adjustable spacing and a vent and drain group with an additional mounting nut.

### Technical data:

Material:	SS304 non-magnetic stainless steel
Medium:	water or a solution of water and glycol up to 30%
Max. temperature:	70 °C
Max. working pressure:	6 bar
Connections:	boiler side 1" F, installation side 3/4" M
Insert connection:	M30x1.5

## Taconova rotameter




**Manifold CS-Rot02 --> rotameter 0 - 2.5 l/min**  
**Manifold CS-Rot05 --> rotameter 0 - 5 l/min**

- Accurate and fast flow regulation, without graphs, tables or measuring devices,
- Flow measured directly in l/min,
- The last set setting can be easily recreated thanks to the locking screw,
- The regulating cap can be sealed,
- Regulating valve with the option of cutting off the flow,
- Removable sight glass,
- Vertical or horizontal installation allowed,

Type	Quantity section	L [mm]	CS-Rot05 Rotameter 0-5 l/min	CS-Rot02 Rotameter 0-2,5 l/min
Stainless steel manifold for underfloor heating CS-Rot 2F	2	130	205002	225002
Stainless steel manifold for underfloor heating CS-Rot 3F	3	180	205003	225003
Stainless steel manifold for underfloor heating CS-Rot 4F	4	230	205004	225004
Stainless steel manifold for underfloor heating CS-Rot 5F	5	280	205005	225005
Stainless steel manifold for underfloor heating CS-Rot 6F	6	330	205006	225006
Stainless steel manifold for underfloor heating CS-Rot 7F	7	380	205007	225007
Stainless steel manifold for underfloor heating CS-Rot 8F	8	430	205008	225008
Stainless steel manifold for underfloor heating CS-Rot 9F	9	480	205009	225009
Stainless steel manifold for underfloor heating CS-Rot 10F	10	530	205010	225010
Stainless steel manifold for underfloor heating CS-Rot 11F	11	580	205011	225011
Stainless steel manifold for underfloor heating CS-Rot 12F	12	630	205012	225012
Stainless steel manifold for underfloor heating CS-Rot 13F	13	680	205013	225013
Stainless steel manifold for underfloor heating CS-Rot 14F	14	730	205014	225014



## Thermoelectric actuator MP VM200



The MP VM200 thermoelectric actuator is a drive for opening and closing valves on underfloor heating manifolds. The set includes an adapter that allows the device to be mounted on thermostatic valves in CS-Rot manifolds. The adapter allows for quick installation of the actuator only by pressing it and subsequent disassembly of the actuator only by using the disassembly button. The actuator is in the normally closed position, after applying voltage it opens the valve flow.

### Technical data:

Actuator version:	normally closed
Voltage:	230 V AC, +10%...-10%, 50/60 Hz
Working power:	2W
Valve opening time:	3 minutes
Actuator stroke:	4mm
Actuator power:	200N

Type	Catalog number
Thermoelectric actuator MP VM200 with adapter for CS-Rot manifolds	401080

## Set of straight ball valves with thermometers



The set includes 2 straight ball valves in blue and red with thermometers, 1" gasket connection

### Technical data:

Thermometers:	scale 0-80 °C
Connections:	1"

Type	Catalog number
Set of 2 straight ball valves with a thermometer and a gasket for connection with CS manifolds	210035

## Set of straight ball valves with thermometers



SL series actuators are compact and solid design. Under the plastic housing are located: transmission with a maximum torque of 10 Nm actuator SL 10, a synchronous motor, two limit switches. The SL actuator factory is equipped with a 1.5 meter cable 3 x 0.75.

### Technical data:

Voltage	230V AC 50-60HZ,
Consumer Power Max	5W
Running time	60sec, 120sec (depending on the model)
Torque	10Nm
Control signal	3 point SPDT,

Type	Voltage	Rotation time	Catalog number
Actuator SL 10 - 230/60s	230 V AC	60 s	415000
Actuator SL 10 - 230/120s	230 V AC	120 s	415001

## Anti-freeze valve WFV



The anti-freeze valve installed in the heat pump installation allows for slow release of the medium when the medium temperature drops below 3 °C. This prevents ice from forming in the installation, protecting its components from damage. It is recommended to install 2 anti-freeze valves in the installation.


### Technical data:

Material:	brass
Max. static pressure:	10 bar (PN 10)
Max. medium temperature:	90°C
Ambient temperature range:	-30°C to + 50°C
Temp. medium starting opening:	+3°C
Temp. closing medium:	+4°C
Accuracy:	+/-1°C
Connections:	1" M for 601561 1 1/4" M for 601562

Possibility to control the anti-vacuum valve.

Possibility to check the cleaning cartridge and replace the sensor.

### Dimensional diagram



P[bar]	Outside and fluid temperature [°C]	Q[L/min]
1	0,5	6
0,2	0,5	2,7
0,05	0,5	1,3

A	B	C	D	E
G1"	26	26	31	76
G 1 1/4"	29,5	29,5	33	78

Type	Kvs	Catalog number
Anti-freeze valve WFV-25M, PN 10, kvs 68	68	200611
Anti-freeze valve WFV-32M, PN 10, kvs 90	90	200612




## Zone 3-way valves WZP3




3-way zone valves of the WZP3 series are intended for heating and cooling systems. They are used in installations where it is required to use an element that switches the flow directions of the medium. The actuator is mounted on the valve with a clip, which facilitates assembly and does not require any additional tools. The actuator is equipped with an anti-blocking function. If the motor is blocked, it reverses its direction of operation. Thanks to this, the actuator is protected against damage, which significantly increases its service life. The valve scale shows the current position of the valve, and the compact dimensions allow it to be used even in small rooms.

Assembly diagram



Possible mounting positions



### Technical data:

Connections:	WZP3-20M - 3/4" M WZP3-25M - 1" M. WZP3-32M - 1 1/4" M.
Kvs:	8 m <sup>3</sup> /h WZP3-25M 13 m <sup>3</sup> /h WZP3-32M
Voltage/Power:	230V AC, 50 Hz, 7VA
Control signal:	2-point SPST
Protection class:	II, IP44
Position indicator:	on top of cover
Maximum Torque:	5 Nm
Cable :	3 x 0,75 mm <sup>2</sup> , 1m
Rotation time and angle:	8s/60°
Ambient temperature:	0°C..+55°C
Certificate:	CE, ROHS
Nominal pressure:	PN10
Medium:	water, glycol < 50%, min. +5°C, max. +80°C
Media temperature:	min. +5°C, max. +80°C
Leakage (Δ p=1 bar):	0,1% kvs
Max. diff. pressure:	1 bar
Materials:	brass, PPS, PTFE
Sealing ring:	PA 66+ rubber

Type	Kvs	Voltage	Rotation time	Catalog number
Zone 3-way valve WZP3-20M	8	230	8 s	601071
Zone 3-way valve WZP3-25M	8	230	8 s	601072

## DHW safety group 6 bar




DHW safety group is an important element of the hot water installation, whose main task is to protect the installation against the increase in pressure caused by the increase in water temperature in the system. It is intended for installation in home heating systems. The beam is equipped with a 6 bar safety valve, a pressure gauge and a set of mounting pins. Additionally, in the lower part of the beam there are connections for the expansion vessel and the safety beam supply.

### Technical data:

Material:	brass
Maximum operating temperature:	95°C
Max. working pressure:	8 bar
Safety valve opening pressure:	6 bar
Vessel connection:	3/4" GW
Installation connection:	3/4"
Medium:	water/glycol

Type	Catalog number
DHW safety group 6 bar, with equipment	200611
DHW safety group 6 bar, with equipment, with automatic 3/4" quick coupling	200612



## Safety group INOX C.H. 3 bar




Central heating safety group is an important element of the central heating system, whose main task is to protect the installation against pressure increases caused by the increase in water temperature in the system. It is intended for installation in home heating systems. The beam is equipped with an automatic air vent with a stop valve, a 3 bar safety valve, a pressure gauge and a set of mounting pins. Additionally, in the lower part of the beam there are connections for the expansion vessel and the boiler power supply.



### Technical data:

Material:	stainless steel
Maximum operating temperature:	95°C
Max. working pressure:	6 bar
Safety valve opening pressure:	3 bar
Vessel connection:	¾" F / ¾" F quick connector
Installation connection:	¾"
Medium:	water/glycol

Type	Catalog number
Safety group INOX for central heating 3 bar, with equipment	200621
Safety group INOX for central heating 3 bar, with equipment, with automatic quick coupler ¾"	200622



## Safety group INOX for domestic hot water 6 bar




Safety group DHW is an important element of the hot water installation, whose main task is to protect the installation against the increase in pressure caused by the increase in water temperature in the system. It is intended for installation in home heating systems. The beam is equipped with a 6 bar safety valve, a pressure gauge and a set of mounting pins. Additionally, in the lower part of the beam there are connections for the expansion vessel and the power supply from the safety beam.

### Technical data:

Material:	stainless steel
Maximum operating temperature:	95°C
Max. working pressure:	8 bar
Safety valve opening pressure:	6 bar
Vessel connection:	3/4" GW
Installation connection:	3/4"
Medium:	water/glycol

Type	Catalog number
Safety group INOX for domestic hot water, 6 bar, with equipment	200625
Safety group INOX for domestic hot water, 6 bar, with equipment, with automatic quick coupler 3/4"	200626



## Safety group 3 bar




Central heating safety group is an important element of the central heating system, whose main task is to protect the system against pressure increase caused by the increase in water temperature in the system. It is designed for installation in home heating systems. The beam is equipped with an automatic air vent with a foot valve, a 3 bar safety valve, a pressure gauge and a set of mounting pins. In addition, in the lower part of the beam, there are connections to the expansion vessel and the power supply from the boiler.

### Technical data:

Material:	steel
Maximum operating temperature:	95°C
working pressure:	6 bar
Safety valve opening pressure:	3 bar
Vessel connection:	3/4" internal thread / quick coupling 3/4" internal thread
Installation connection:	3/4"
Medium:	water/glycol

Type	Catalog number
Safety group 3 bar, equipment	200601
Safety group 3 bar, equipment, with automatic quick coupler 3/4"	200602



## Basket strainer FMK



The FMK basket strainer is a device designed to capture solid pollution transmitted by water in central heating installations, heating networks and heat nodes. Their use allows the proper operation of heat exchangers, pumps, boilers and other system devices, preventing the deposition of impurities that remain in the filter basket and are easy to remove. Cleansing the medium stream is a process of mechanical separation of solid bodies (e.g. gravel, particles from corrosion of pipes) in a filter element, which is a removable basket. The basket is made of perforated stainless steel and 500 µm filter mesh. The body is made depending on the model of powder -painted or galvanized steel. In addition, the device occurs in variants with or without insulation. The basket strainer is equipped with a manual vent and a drain valve. In addition, to ensure the catching of ferromagnetic impurities, the device can be equipped with a magnetic insert.

### Technical data:

Material:	Painted/galvanized steel (depending on the model)
Maximum pressure:	6 bar
Maximum operating temperature:	110 ° C
Filter insert:	500 µm
Pressure norm of collars:	PN 16
Flow:	6-30 m <sup>3</sup> /h (depending on the model)
Isulation:	EPP black/none (depending on the model)

Type	Catalog number
Basket strainer <b>FMK 150 - DN 50</b> with additional equipment, without insulation, painted	609141
Basket strainer <b>FMK 150 - DN 65</b> with additional equipment, without insulation, painted	609142
Basket strainer <b>FMK 250 - DN 80</b> with additional equipment, without insulation, painted	609143
Basket strainer <b>FMK 300 - DN 100</b> with additional equipment, without insulation, painted	609144
Basket strainer <b>FMK 300 - DN 125</b> with additional equipment, without insulation, painted	609145
Type	Catalog number
Basket strainer <b>FMKo 150 - DN 50</b> with additional equipment, without insulation, galvanized	609151
Basket strainer <b>FMKo 150 - DN 65</b> with additional equipment, without insulation, galvanized	609152
Basket strainer <b>FMKo 250 - DN 80</b> with additional equipment, without insulation, galvanized	609153
Basket strainer <b>FMKo 300 - DN 100</b> with additional equipment, without insulation, galvanized	609154
Basket strainer <b>FMKo 300 - DN 125</b> with additional equipment, without insulation, galvanized	609155
Type	Catalog number
Basket strainer <b>FMK+ 150 - DN 50</b> with additional equipment, with insulation, painted	609241
Basket strainer <b>FMK+ 150 - DN 65</b> with additional equipment, with insulation, painted	609242
Basket strainer <b>FMK+ 250 - DN 80</b> with additional equipment, with insulation, painted	609243
Basket strainer <b>FMK+ 300 - DN 100</b> with additional equipment, with insulation, painted	609244
Basket strainer <b>FMK+ 300 - DN 125</b> with additional equipment, with insulation, painted	609245
Type	Catalog number
Basket strainer <b>FMKo+ 150 - DN 50</b> with additional equipment, with insulation, galvanized	609251
Basket strainer <b>FMKo+ 150 - DN 65</b> with additional equipment, with insulation, galvanized	609252
Basket strainer <b>FMKo+ 250 - DN 80</b> with additional equipment, with insulation, galvanized	609253
Basket strainer <b>FMKo+ 300 - DN 100</b> with additional equipment, with insulation, galvanized	609254
Basket strainer <b>FMKo+ 300 - DN 125</b> with additional equipment, with insulation, galvanized	609255



## Connector distance for FMK



The distance connector helps in mounting the basket strainers in pump groups.

Type	Catalog number
Connector distance DN 50 (L-350mm) for <b>FMK 150 - DN 50</b> with 4 mounting screws and a gasket EPDM DN 65	699061
Connector distance DN 65 (L-350mm) for <b>FMK 150 - DN 65</b> with 4 mounting screws and a gasket EPDM DN 65	699062
Connector distance DN 80 (L-510mm) for <b>FMK 250 - DN 80</b> with 4 mounting screws and a gasket EPDM DN 80	699063
Connector distance DN 100 (L-510mm) for <b>FMK 300 - DN 100</b> with 4 mounting screws and a gasket EPDM DN 100	699064
Connector distance DN 125 (L-510mm) for <b>FMK 300 - DN 125</b> with 4 mounting screws and a gasket EPDM DN 125	699065


## Magnetic insert for FMK



The magnetic insert is used to capture metal particles, preventing impurities in the installation.

Type	Catalog number
Magnetic insert 1/2" for basket strainer <b>FMK 150 - DN 50, DN 65</b>	607260
Magnetic insert 3/4" for basket strainer <b>FMK 250 - DN 80</b>	607261
Magnetic insert 1" for basket strainer <b>FMK 300 - DN 100, DN 125</b>	607262

### Example of application



In order to facilitate the periodic cleaning of the installation, it is recommended to mount the shut-off valves before and for basket strainer.



## Butterfly valves WX and WXS



Butterfly valve WX are designed for shutting off and regulating the flow of cold and hot water. They are used in heating systems, sewage systems and tap water systems (with a stainless steel disc). Short construction, low pressure losses and simple assembly allow for use wherever it is impossible to install a ball valve. The dampers are available in diameters DN50 - DN 300 with a cast iron disc or a stainless steel disc.



#### Technical data:

Body:	gray cast iron GG25 (for diameters DN250 and DN300 ductile iron)
Disc:	GGG40 ductile iron or AISI 316 stainless steel
Maximum pressure:	16 bar
Temperature range:	-20 °C to 120 °C

Type	DN	Catalog number
Butterfly valve with handle <b>WX50</b> , with a cast iron disc	50	005061
Butterfly valve with handle <b>WX65</b> , with a cast iron disc	65	005062
Butterfly valve with handle <b>WX80</b> , with a cast iron disc	80	005063
Butterfly valve with handle <b>WX100</b> , with a cast iron disc	100	005064
Butterfly valve with handle <b>WX125</b> , with a cast iron disc	125	005065
Butterfly valve with handle <b>WX150</b> , with a cast iron disc	150	005066
Butterfly valve with handle <b>WX200</b> , with a cast iron disc	200	005067
Butterfly valve with gearbox <b>WX250</b> , with a cast iron disc	250	005068
Butterfly valve with gearbox <b>WX300</b> , with a cast iron disc	300	005069
Type	DN	Catalog number
Butterfly valve with handle <b>WX50S</b> , with a stainless steel disc	50	005081
Butterfly valve with handle <b>WX65S</b> , with a stainless steel disc	65	005082
Butterfly valve with handle <b>WX80S</b> , with a stainless steel disc	80	005083
Butterfly valve with handle <b>WX100S</b> , with a stainless steel disc	100	005084
Butterfly valve with handle <b>WX125S</b> , with a stainless steel disc	125	005085
Butterfly valve with handle <b>WX150S</b> , with a stainless steel disc	150	005086
Butterfly valve with handle <b>WX200S</b> , with a stainless steel disc	200	005087



## Magnetic filter with strainer FM



The **FM** magnetic filter is a device designed to trap solid pollutants carried by water in central heating installations, heating networks, heat centers, boiler rooms, as well as in glycol installations in air-conditioning systems. Their use allows for the proper operation of heat exchangers, pumps, boilers and other system devices, preventing the deposition of impurities that remain in the desilter and are easy to remove. Contrary to systems without a filter separator, the sedimentation of sludge and limescale effectively reduces the efficiency of devices operating in such conditions. This is especially important for heat exchangers.

Advantages of using a magnetic filter with strainer:


- securing and significantly reducing the risk of damage to the installation and its components,
- silencing the operation of the installation,
- exceptional simple removal of the separator contamination, removal of contamination without the need to shut down the installation.

Type	Catalog number
Magnetic filter with strainer <b>FM 65 - DN 25</b> with insulation, with equipment	611091
Magnetic filter with strainer <b>FM 80 - DN 32</b> with insulation, with equipment	611092
Magnetic filter with strainer <b>FM 100 - DN 40</b> with insulation, with equipment	611093
Magnetic filter with strainer <b>FM 150 - DN 50</b> with insulation, with equipment	611094

	FM 65 - DN 25	FM 80 - DN 32	FM 100 - DN 40	FM 150 - DN 50
<b>A</b>	160	160	195	260
<b>Ø</b>	155	155	190	250
<b>L</b>	260	290	350	400
<b>DN</b>	65	80	100	150
<b>G</b>	1" F	1 1/4" F	1 1/2" F	2" F
<b>Power</b>	50 kW	80 kW	120 kW	180 kW



## Heat pump or air conditioner WM stand / bracket



The stands (supports) WM II and WM III intended for heat pumps or air conditioners are made of steel. The stability of the stand has been increased by the use of adjustment fasteners on both sides. The design of the stand guarantees that it can be used with any heat pump or air conditioner. The brackets are equipped with vibration isolators to catch vibrations of the device and feet, together with a handle that allows the stand to be anchored. The bracket with the device should be placed on a permanently leveled base that can carry five times the weight of the device. Possible unevenness can be eliminated by a foot with an adjusting screw

Set contains:

- Steel elements of the stand
- Vibro-isolators with nuts
- Adjustable feet with the possibility of anchoring to the ground
- Mounting screws


Maximum load on the rack:

for WM II - 320kg  
for WM III - 360 kg



Type	Catalog number
Stand / bracket for the heat pump or air conditioner WM II 42/92	610951
Stand / bracket for the heat pump or air conditioner WM II 52/92	610955
Stand / bracket for the heat pump or air conditioner WM II 52/135	610956
Stand / bracket for the heat pump or air conditioner WM III 42/135	610962
Stand / bracket for the heat pump or air conditioner WM III 52/135	610964

### Dimensions:

WM II



WM III



the height of the stands is min 350 mm - max 370 mm

If in doubt, the match of the WM stand to the device used please contact us by e-mail at [export@womix.pl](mailto:export@womix.pl)

Type	cod.	mounting width „B”	mounting width „C”	mounting length „L”	„A”
WM II 42/92	610951	min. 100 - max. 420 mm	600 mm	min. 500 - max. 920 mm	
WM II 52/92	610955	min. 140 - max. 520 mm	700 mm	min. 500 - max. 920 mm	
WM II 52/135	610956	min. 140 - max. 520 mm	700 mm	min. 830 - max. 1350 mm	
WM III 42/135	610962	min. 100 - max. 420 mm	600 mm	min. 830 - max. 1350 mm	min. 100 - max. 710mm
WM III 52/135	610964	min. 140 - max. 520 mm	700 mm	min. 830 - max. 1350 mm	min. 100 - max. 710mm



# NEWS

# 03.2023

**womix**  
Comfort Controls



## ENERGY-SAVING CENTRAL HEATING EQUIPMENT



mixing valves



hydraulic separators



boiler room building systems

[www.womix.pl](http://www.womix.pl)


Womix Sportowa 31 89-200 Szubin  
phone: +48 52 382 44 50  
mobile: 570 108 498

## Zone 3-way valves WZP3




3-way zone valves of the WZP3 series are intended for heating and cooling systems. They are used in installations where it is required to use an element that switches the flow directions of the medium. The actuator is mounted on the valve with a clip, which facilitates assembly and does not require any additional tools. The actuator is equipped with an anti-blocking function. If the motor is blocked, it reverses its direction of operation. Thanks to this, the actuator is protected against damage, which significantly increases its service life. The valve scale shows the current position of the valve, and the compact dimensions allow it to be used even in small rooms.

Assembly diagram



Possible mounting positions



### Technical data:

Connections:	WZP3-20M - 3/4" M WZP3-25M - 1" M
Kvs:	8 m <sup>3</sup> /h
Voltage/Power:	230V AC, 50 Hz, 7VA
Control signal:	2-point SPST
Protection class:	II, IP44
Position indicator:	on top of cover
Maximum Torque:	5 Nm
Cable :	3 x 0,75 mm <sup>2</sup> , 1m
Rotation time and angle:	8s/60°
Ambient temperature:	0°C..+55°C
Certificate:	CE, ROHS
Nominal pressure:	PN10
Medium:	water, glycol < 50%,
Media temperature:	min. +5°C, max. +80°C
Leakage (Δ p=1 bar):	0,1% kvs
Max. diff. pressure:	1 bar
Materials:	brass, PPS, PTFE
Sealing ring:	PA 66+ rubber

Type	Kvs	Voltage	Rotation time	Catalog number
Zone 3-way valve WZP3-20M	8	230	8 s	601071
Zone 3-way valve WZP3-25M	8	230	8 s	601072



## Safety group 3 bar




Central heating safety group is an important element of the central heating system, whose main task is to protect the system against pressure increase caused by the increase in water temperature in the system. It is designed for installation in home heating systems. The beam is equipped with an automatic air vent with a foot valve, a 3 bar safety valve, a pressure gauge and a set of mounting pins. In addition, in the lower part of the beam, there are connections to the expansion vessel and the power supply from the boiler.

### Technical data:

Material:	steel
Maximum operating temperature:	95°C
working pressure:	6 bar
Safety valve opening pressure:	3 bar
Vessel connection:	3/4" internal thread / quick coupling 3/4" internal thread
Installation connection:	3/4"
Medium:	water/glycol

Type	Catalog number
Safety group 3 bar, equipment	200601
Safety group 3 bar, equipment, with automatic quick coupler 3/4"	200602



## Basket strainer FMK



The FMK basket strainer is a device designed to capture solid pollution transmitted by water in central heating installations, heating networks and heat nodes. Their use allows the proper operation of heat exchangers, pumps, boilers and other system devices, preventing the deposition of impurities that remain in the filter basket and are easy to remove. Cleansing the medium stream is a process of mechanical separation of solid bodies (e.g. gravel, particles from corrosion of pipes) in a filter element, which is a removable basket. The basket is made of perforated stainless steel and 500 µm filter mesh. The body is made depending on the model of powder -painted or galvanized steel. In addition, the device occurs in variants with or without insulation. The basket strainer is equipped with a manual vent and a drain valve. In addition, to ensure the catching of ferromagnetic impurities, the device can be equipped with a magnetic insert.

### Technical data:

Material:	Painted/galvanized steel (depending on the model)
Maximum pressure:	6 bar
Maximum operating temperature:	110 ° C
Filter insert:	500 µm
Pressure norm of collars:	PN 16
Flow:	6-30 m <sup>3</sup> /h (depending on the model)
Insulation:	EPP black/none (depending on the model)

Type	Catalog number
Basket strainer <b>FMK 150 - DN 50</b> with additional equipment, without insulation, painted	609141
Basket strainer <b>FMK 150 - DN 65</b> with additional equipment, without insulation, painted	609142
Basket strainer <b>FMK 250 - DN 80</b> with additional equipment, without insulation, painted	609143
Basket strainer <b>FMK 300 - DN 100</b> with additional equipment, without insulation, painted	609144
Basket strainer <b>FMK 300 - DN 125</b> with additional equipment, without insulation, painted	609145
Type	Catalog number
Basket strainer <b>FMKo 150 - DN 50</b> with additional equipment, without insulation, galvanized	609151
Basket strainer <b>FMKo 150 - DN 65</b> with additional equipment, without insulation, galvanized	609152
Basket strainer <b>FMKo 250 - DN 80</b> with additional equipment, without insulation, galvanized	609153
Basket strainer <b>FMKo 300 - DN 100</b> with additional equipment, without insulation, galvanized	609154
Basket strainer <b>FMKo 300 - DN 125</b> with additional equipment, without insulation, galvanized	609155
Type	Catalog number
Basket strainer <b>FMK+ 150 - DN 50</b> with additional equipment, with insulation, painted	609241
Basket strainer <b>FMK+ 150 - DN 65</b> with additional equipment, with insulation, painted	609242
Basket strainer <b>FMK+ 250 - DN 80</b> with additional equipment, with insulation, painted	609243
Basket strainer <b>FMK+ 300 - DN 100</b> with additional equipment, with insulation, painted	609244
Basket strainer <b>FMK+ 300 - DN 125</b> with additional equipment, with insulation, painted	609245
Type	Catalog number
Basket strainer <b>FMKo+ 150 - DN 50</b> with additional equipment, with insulation, galvanized	609251
Basket strainer <b>FMKo+ 150 - DN 65</b> with additional equipment, with insulation, galvanized	609252
Basket strainer <b>FMKo+ 250 - DN 80</b> with additional equipment, with insulation, galvanized	609253
Basket strainer <b>FMKo+ 300 - DN 100</b> with additional equipment, with insulation, galvanized	609254
Basket strainer <b>FMKo+ 300 - DN 125</b> with additional equipment, with insulation, galvanized	609255



## Connector distance for FMK



The distance connector helps in mounting the basket strainers in pump groups.

Type	Catalog number
Connector distance DN 50 (L-350mm) for <b>FMK 150 - DN 50</b> with 4 mounting screws and a gasket EPDM DN 65	699061
Connector distance DN 65 (L-350mm) for <b>FMK 150 - DN 65</b> with 4 mounting screws and a gasket EPDM DN 65	699062
Connector distance DN 80 (L-510mm) for <b>FMK 250 - DN 80</b> with 4 mounting screws and a gasket EPDM DN 80	699063
Connector distance DN 100 (L-510mm) for <b>FMK 300 - DN 100</b> with 4 mounting screws and a gasket EPDM DN 100	699064
Connector distance DN 125 (L-510mm) for <b>FMK 300 - DN 125</b> with 4 mounting screws and a gasket EPDM DN 125	699065


## Magnetic insert for FMK



The magnetic insert is used to capture metal particles, preventing impurities in the installation.

Type	Catalog number
Magnetic insert 1/2" for basket strainer <b>FMK 150 - DN 50, DN 65</b>	607260
Magnetic insert 3/4" for basket strainer <b>FMK 250 - DN 80</b>	607261
Magnetic insert 1" for basket strainer <b>FMK 300 - DN 100, DN 125</b>	607262

### Example of application



In order to facilitate the periodic cleaning of the installation, it is recommended to mount the shut-off valves before and for basket strainer.



## Butterfly valves WX and WXS



Butterfly valve WX are designed for shutting off and regulating the flow of cold and hot water. They are used in heating systems, sewage systems and tap water systems (with a stainless steel disc). Short construction, low pressure losses and simple assembly allow for use wherever it is impossible to install a ball valve. The dampers are available in diameters DN50 - DN 300 with a cast iron disc or a stainless steel disc.



### Technical data:

Body:	gray cast iron GG25 (for diameters DN250 and DN300 ductile iron)
Disc:	GGG40 ductile iron or AISI 316 stainless steel
Maximum pressure:	16 bar
Temperature range:	-20 °C to 120 °C

Type	DN	Catalog number
Butterfly valve with handle <b>WX50</b> , with a cast iron disc	50	005061
Butterfly valve with handle <b>WX65</b> , with a cast iron disc	65	005062
Butterfly valve with handle <b>WX80</b> , with a cast iron disc	80	005063
Butterfly valve with handle <b>WX100</b> , with a cast iron disc	100	005064
Butterfly valve with handle <b>WX125</b> , with a cast iron disc	125	005065
Butterfly valve with handle <b>WX150</b> , with a cast iron disc	150	005066
Butterfly valve with handle <b>WX200</b> , with a cast iron disc	200	005067
Butterfly valve with gearbox <b>WX250</b> , with a cast iron disc	250	005068
Butterfly valve with gearbox <b>WX300</b> , with a cast iron disc	300	005069
Type	DN	Catalog number
Butterfly valve with handle <b>WX50S</b> , with a stainless steel disc	50	005081
Butterfly valve with handle <b>WX65S</b> , with a stainless steel disc	65	005082
Butterfly valve with handle <b>WX80S</b> , with a stainless steel disc	80	005083
Butterfly valve with handle <b>WX100S</b> , with a stainless steel disc	100	005084
Butterfly valve with handle <b>WX125S</b> , with a stainless steel disc	125	005085
Butterfly valve with handle <b>WX150S</b> , with a stainless steel disc	150	005086
Butterfly valve with handle <b>WX200S</b> , with a stainless steel disc	200	005087



## Magnetic filter with strainer FM



The **FM** magnetic filter is a device designed to trap solid pollutants carried by water in central heating installations, heating networks, heat centers, boiler rooms, as well as in glycol installations in air-conditioning systems. Their use allows for the proper operation of heat exchangers, pumps, boilers and other system devices, preventing the deposition of impurities that remain in the desilter and are easy to remove. Contrary to systems without a filter separator, the sedimentation of sludge and limescale effectively reduces the efficiency of devices operating in such conditions. This is especially important for heat exchangers.

Advantages of using a magnetic filter with strainer:

- securing and significantly reducing the risk of damage to the installation and its components,
- silencing the operation of the installation,
- exceptional simple removal of the separator contamination, removal of contamination without the need to shut down the installation.

Type	Catalog number
Magnetic filter with strainer <b>FM 65 - DN 25</b> with insulation, with equipment	611091
Magnetic filter with strainer <b>FM 80 - DN 32</b> with insulation, with equipment	611092
Magnetic filter with strainer <b>FM 100 - DN 40</b> with insulation, with equipment	611093
Magnetic filter with strainer <b>FM 150 - DN 50</b> with insulation, with equipment	611094

	FM 65 - DN 25	FM 80 - DN 32	FM 100 - DN 40	FM 150 - DN 50
<b>A</b>	160	160	195	260
<b>Ø</b>	155	155	190	250
<b>L</b>	260	290	350	400
<b>DN</b>	65	80	100	150
<b>G</b>	1" F	1 1/4" F	1 1/2" F	2" F
<b>Power</b>	50 kW	80 kW	120 kW	180 kW



## Heat pump or air conditioner WM stand / bracket



The stands (supports) WM II and WM III intended for heat pumps or air conditioners are made of steel. The stability of the stand has been increased by the use of adjustment fasteners on both sides. The design of the stand guarantees that it can be used with any heat pump or air conditioner. The brackets are equipped with vibration isolators to catch vibrations of the device and feet, together with a handle that allows the stand to be anchored. The bracket with the device should be placed on a permanently leveled base that can carry five times the weight of the device. Possible unevenness can be eliminated by a foot with an adjusting screw

Set contains:

- Steel elements of the stand
- Vibro-isolators with nuts
- Adjustable feet with the possibility of anchoring to the ground
- Mounting screws


Maximum load on the rack:

for WM II - 320kg  
for WM III - 360 kg



Type	Catalog number
Stand / bracket for the heat pump or air conditioner WM II 42/92	610951
Stand / bracket for the heat pump or air conditioner WM II 52/92	610955
Stand / bracket for the heat pump or air conditioner WM II 52/135	610956
Stand / bracket for the heat pump or air conditioner WM III 42/135	610962
Stand / bracket for the heat pump or air conditioner WM III 52/135	610964

### Dimensions:

WM II



WM III



the height of the stands is min 350 mm - max 370 mm




If in doubt, the match of the WM stand to the device used please contact us by e-mail at [export@womix.pl](mailto:export@womix.pl)

Type	cod.	mounting width „B”	mounting width „C”	mounting length „L”	„A”
WM II 42/92	610951	min. 100 - max. 420 mm	600 mm	min. 500 - max. 920 mm	
WM II 52/92	610955	min. 140 - max. 520 mm	700 mm	min. 500 - max. 920 mm	
WM II 52/135	610956	min. 140 - max. 520 mm	700 mm	min. 830 - max. 1350 mm	
WM III 42/135	610962	min. 100 - max. 420 mm	600 mm	min. 830 - max. 1350 mm	min. 100 - max. 710mm
WM III 52/135	610964	min. 140 - max. 520 mm	700 mm	min. 830 - max. 1350 mm	min. 100 - max. 710mm



## Two-zone accumulation hydraulic separator **DUO-ZONER**

**Equipments:**




The two-zone accumulation hydraulic separator **DUO-ZONER** is made of steel. It works as a tank, hydraulic separator and zone manifold for two heating circuits. Its task is to facilitate the operation of the heat pump in order to meet the heat demand with optimal modulation and to cover the peak loads with the support of an auxiliary heat source. Appropriate placement of connections and a partition ensures proper liquid stratification and maintaining an appropriate difference between the two temperature levels. The diameter and spacing of the connections allow for direct connection of DN 25 pump groups in any configuration, giving the possibility to operate up to 2 heating circuits. They are available in two versions, a capacity of 45 L and 70 L, and each of them has the option of connecting 2 heat sources. An additional sleeve allows the use of a magnetic insert MI 150 - DN 15. The product includes insulation, automatic air vent, immersion sleeve for the temperature sensor, drain valve and mounting feet.


**Technical data:**

Total capacity:	45L or 70L (depending on the model)
Insulation:	EPP black 60 g/l
Pressure:	6 bar
Maximum temperature:	95 °C
Connection diameter:	
heat source side:	1" M
heating circuits side:	1 1/2" nut
Spacing of connections:	
side of heating circuits:	125mm


Type	Capacity [l]	Catalog number
Two-zone accumulation hydraulic separator <b>DUO-ZONER 45</b>	45	606790
Two-zone accumulation hydraulic separator <b>DUO-ZONER 70</b>	70	606791
Wall brackets for mounting on the wall		606799
Magnetic cartridge <b>MS 150 - DN 15</b>		607250



Possibility to connect groups pumps on either side by turning by 180°



The system is designed to enable assembly pump groups on the wall




## DUO-ZONER sets for two heating circuits with left and right connection

Set **DUO-ZONER L** (left sided)



DUO-ZONER 45 - 45 L  
DUO-ZONER 70 - 70 L



Set **DUO-ZONER P** (right sided)



Pump groups mounted on the left side of the two-zone accumulation hydraulic separator. Power supply to the pump groups on the right.

Connection of heat sources on the right side of the two-zone accumulation hydraulic separator.

Pump groups mounted on the right side of the two-zone accumulation hydraulic separator. Supply of the pump groups on the left side.


Connection of heat sources on the left side of the two-zone accumulation hydraulic separator. When ordering this type of set, the pump groups will be factory-delivered with the flow on the left side.

DUO-ZONER 1 set - a set of 2 heating circuits, including one with a rotary mixing valve and an electric actuator

**DUO-ZONER 1L**



**DUO-ZONER 1P**



Set 1P requires changing the supply side of the pump group to the left side




Set contains:

1. Two-zone accumulation hydraulic separator **DUO-ZONER 45** (Cod.:606890) or **DUO-ZONER 70** (Cod.:606891),
2. Pump group **SA 125 - DN 25**:
  - without pump (Cod.:606051),
  - with pump **Wilco Yonos Para 25/6** (Cod.:616054)
  - with pump **Grundfos UPM3S AUTO 25-60** (Cod.:616056)
  - with pump **DAB Evosta2** (Cod.:616057)
3. Pump group **SMT 125 - DN 25**:
  - without pump (Cod.:606081),
  - with pump **Wilco Yonos Para 25/6** (Cod.:616084)
  - with pump **Grundfos UPM3S AUTO 25-60** (Cod.:616086)
  - with pump **DAB Evosta2** (Cod.:616087)
4. Check valve (Cod.:606031),
5. Actuator **MP 10 - 230 / 140** with adapter nr **A 101**(Cod.:401011).



DUO-ZONER 2 set - a set of 2 heating circuits, including one with a thermostatic mixing valve




Set 2P requires changing the supply side of the pump group to the left side



Set contains:

- Two-zone accumulation hydraulic separator **DUO-ZONER 45** (Cod.:606890) or **DUO-ZONER 70** (Cod.:606891),
- Pump group **SA 125 - DN 25**:
  - without pump (Cod.:606051),
  - with pump **Wilo Yonos Para 25/6** (Cod.:616054)
  - with pump **Grundfos UPM3S AUTO 25-60** (Cod.:616056)
  - with pump **DAB Evosta2** (Cod.:616057)
- Pump group **SMT C1 125 - DN 25**:
  - without pump (Cod.:606071),
  - with pump **Wilo Yonos Para 25/6** (Cod.:616074)
  - with pump **Grundfos UPM3S AUTO 25-60** (Cod.:616076)
  - with pump **DAB Evosta2** (Cod.:616077)
- Check valve (Cod.:606031),

DUO-ZONER 3 set - set of 2 heating circuits with rotary mixing valves and electric actuators



Set 3P requires changing the supply side of the pump group to the left side




Set contains:


- Two-zone accumulation hydraulic separator **DUO-ZONER 45** (Cod.:606890) or **DUO-ZONER 70** (Cod.:606891),
- Two pump group **SMT 125 - DN 25**:
  - without pump (Cod.:606081),
  - with pump **Wilo Yonos Para 25/6** (Cod.:616084)
  - with pump **Grundfos UPM3S AUTO 25-60** (Cod.:616086)
  - with pump **DAB Evosta2** (Cod.:616087)
- Two check valves (Cod.:606031),
- Two actuators **MP 10 - 230 / 140** with adapter nr **A 101**(Cod.:401011).



## DUO-ZONER 4 set - set of 2 heating circuits without mixing valves




Set 4P requires changing the supply side of the pump group to the left side



Set contains:

1. Two-zone accumulation hydraulic separator **DUO-ZONER 45** (Cod.:606890) or **DUO-ZONER 70** (Cod.:606891),
2. Two pump group **SA 125 - DN 25**:
  - without pump (Cod.:606051),
  - with pump **Wilo Yonos Para 25/6** (Cod.:616054)
  - with pump **Grundfos UPM3S AUTO 25-60** (Cod.:616056)
  - with pump **DAB Evosta2** (Cod.:616057)

## DUO-ZONER 5 set - set of 2 heating circuits with thermostatic mixing valves



Set 5P requires changing the supply side of the pump group to the left side






Set contains:

1. Two-zone accumulation hydraulic separator **DUO-ZONER 45** (Cod.:606890) or **DUO-ZONER 70** (Cod.:606891),
2. Two pump group **SMTc1 125 - DN 25**:
  - without pump (Cod.:606071),
  - with pump **Wilo Yonos Para 25/6** (Cod.:616074)
  - with pump **Grundfos UPM3S AUTO 25-60** (Cod.:616076)
  - with pump **DAB Evosta2** (Cod.:616077)
3. Two check valves (Cod.:606031).



### Multi-zone accumulation hydraulic separator MULTI-ZONER

**Equipment:**






The multi-zone accumulation hydraulic separator MULTI-ZONER is made of steel. It work as a tank and a hydraulic separator with an output to the central heating system. Its task is to facilitate the operation of the heat pump in order to meet the heat demand with optimal modulation and to cover the peak loads with the support of an auxiliary heat source. Appropriate placement of connections and a partition ensures proper liquid stratification and maintaining an appropriate difference between the two temperature levels. The diameter and spacing of the connections allow direct connection of DN 25 pump groups in any configuration, making it possible to operate multiple heating circuits after using a C 60 or C 70 pump group zone manifold and connection of 2 heat sources. An additional sleeve allows the use of a magnetic insert MI 150 - DN 15. The product includes insulation, automatic air vent, immersion sleeve for the temperature sensor, drain valve and mounting feet.

**Technical data:**

Total capacity:	45 L or 70 L (depending on the model)
Insulation:	EPP black 60 g/l
Maximum pressure:	6 bar
Maximum temperature:	95 °C
Connection diameter:	
heat source side:	1" M
heating circuits side:	1" M
Spacing of connections:	
heat source side:	350 mm
heating circuits side:	125 mm


Type	Capacity [l]	Catalog number
Multi-zone accumulation hydraulic separator <b>MULTI-ZONER 45</b>	45	606795
Multi-zone accumulation hydraulic separator <b>MULTI-ZONER 70</b>	70	606796
Wall brackets for mounting on the wall		606799
Magnetic cartridge <b>MS 150 - DN 15</b>		607250

The system is designed to enable assembly pump groups on the wall




## Connection diagram of the DUO-ZONER

*Simplified schematic diagram of the installation - the standard ones were not marked installation elements as well as the boiler room security scheme.*




## Connection diagram of the MULTI-ZONER

*Simplified schematic diagram of the installation - the standard ones were not marked installation elements as well as the boiler room security scheme.*



## Buffer tanks

Equipment:



The hanging buffer tank has been designed to work with various heating devices, such as central heating boilers, or heat pumps to collect heat. It is equipped with brackets for mounting the device on the wall, an automatic air vent and an immersion sleeve for connecting a temperature sensor.


Technical data:

Total capacity:	45 L or 70 L (depending on the model)
Insulation:	EPP black
Maximum pressure:	6 bar
Maximum temperature:	95 °C
Connection diameter:	
heat source side:	1 1/4" M
heating circuit side:	1 1/4" M

Two tank capacities of 45 L and 70 L

Wall brackets included


Connections 1 1/4" M



A simplified diagram of the internal structure

Tank description:

1. 1 1/4" M connections
2. Automatic air vent
3. 1/2" plunger sleeve for temperature sensor connection
4. Socket 1/2" for connection magnetic cartridge MI 150
5. EPP insulation
6. Incomplete septum
7. Socket 1 1/2" for connecting the heater



Possibility  
usage  
magnetic  
cartridge  
MI 150



Wall brackets  
for mounting the  
device on the  
wall (included)

Type	Volume [l]	Catalog number
Hanging buffer tank 45L, with insulation, without coil	45	606781
Hanging buffer tank 70L, with insulation, without coil	70	606782
Magnetic cartridge MI 150 - DN 15		607255



## Under-boiler magnetic filter PFM20

### PFM20 - DN 20



### PFM20 - DN 20 (with a connector and a ball valve)





The PFM 20 under-boiler magnetic filter is made of brass. It is equipped with a magnetic cartridge 12,000 G, a 500 µm mesh filter and a brass plug. The mesh filter inside eliminates solid impurities in the system, and a strong neodymium magnet collects and catches ferromagnetic impurities.

Thanks to its compact design, the PFM20 filter fits all types of boilers on the market with 3/4" M connections, and the brass body design guarantees long-term reliability of the product.

#### Technical data:

Material:	CW 617N brass
Maximum operating pressure:	6 bar
Maximum working temperature:	110 °C
Magnet:	12,000 G neodymium
Filter cartridge:	500 µm
The diameter of the connections:	3 x M 3/4" (for 100171)
	2 x external thread 3/4" , 1 x external thread 3/4" (for 100172)

#### Possible mounting positions



Type	Catalog number
Under-boiler magnetic filter PFM20 - DN 20	100171
Under-boiler magnetic filter PFM20 - DN 20 with connector and ball valve	100172



## Pump group for hot utility water circulation HW20



The HW20 pump group is intended for the implementation of a hot utility water circulation system in installations with a domestic hot water tank. Its design allows you to avoid incorrect installation of the domestic hot water circulation system. The HW20 group is equipped with a thermostatic mixing valve MIX THERM (35 ÷ 60 ° C), with a kvs flow of 3.4, a ball valve with a thermometer, a circulation pump with a check valve and a return water thermometer. The group can be used for containers equipped with a circulation pipe as well as for containers not equipped with it.

Type	Catalog number
Pump group for hot utility water circulation HW20	606750

1. Circulation pump WOMIX eco Pro.
2. MIX THERM 35-60 ° C thermostatic mixing valve
3. Ball valve with thermometer
4. Drain / vent valve
5. Check valve
6. Bimetallic thermometer




### Technical data:

Connection:	3x 3/4" F, 1x 1/2" F
Maximum static pressure:	10 bar
Maximum differential pressure:	5 bar
Min pressure:	0.2 bar
Flow rate:	70 l / min
Recommended working pressure:	1 - 5 bar
recommendation: for higher pressures it is recommended to install a pressure reducer	
Max. hot water temperature:	90 ° C
Adjustable temperature range:	35 - 60 ° C (+/- 2K)
Kvs:	3.4
Pump power:	8W
Pump supply voltage:	single-phase 200-240V 50/60 Hz



## Hydraulic separator XP 80 - DN 32 ELEC




Hydraulic separator **XP 80 - DN 32 ELEC** for heating systems is made of steel. The factory is equipped with an automatic air vent, an immersion sleeve for connecting a temperature sensor, drain valve and EPP insulation. The hydraulic clutch **XP 80 ELEC** will prove itself in systems powered by a heat pump or a fireplace as an additional source of heat. Additionally, anti-freezing agent can be used in the installation of summer houses or buildings used occasionally.

**Attention! The product does not contain a heater.**

**Attention! To prevent damage to the heating element during operation, a constant flow of medium through the device must be ensured.**

Type	Catalog number
Hydraulic separator <b>XP 80 - DN 32 ELEC</b> with insulation, with equipment	609305
Hydraulic separator <b>XP 100 - DN 40 ELEC</b> with insulation, with equipment	609306

## Flow heating tube HP 100 - DN 40



Flow heating tube **HP 100 - DN 40** for heating systems is made of steel. The factory is equipped with EPP insulation and a thermometer. The flow heating tube **HP 100 - DN 40** will work in systems powered by a heat pump or a fireplace as an additional source of heat. It can be used as a protection against freezing of the medium in the installations of summer houses or buildings used occasionally.

### Technical data:

Material:	steel
Max pressure:	6 bar
Max temp.:	110°C
Insulation:	EPP black 60 g/l
Connections:	1 1/2" F
Electric heater thread required:	1 1/2" M

**Attention! The product does not contain a heater. The maximum power of the heater is 6 kW.**

**Attention! To prevent damage to the heating element during operation, a constant flow of medium through the device must be ensured.**

Type	Catalog number
Flow heating tube <b>HP 100 - DN 40</b> with insulation,	609310



## Steel profile manifold bar



Block (cage) manifolds are used in multi-family buildings, where on each floor it is necessary to separate the medium into several heating circuits. They are made of steel painted black and have 1/2" threaded connections for heating circuits and a threaded supply connection corresponding to the diameter of the manifold. On request, it is possible to make additional connections or manifolds in other diameters according to customer needs.

### Technical data:

Material: steel

maximum working temperature: 95°C

working pressure: 6 bar

Installation side connection spacing: 100mm

Installation side connection diameter: GW 1/2"

Supply connection diameter:

for DN 20 - GW 3/4"

for DN 25 - 1" internal thread

for DN 32 - internal thread 1 1/4"

for DN 40 - internal thread 1 1/2"

Type	Catalog number
Steel profile manifold bar – DN 20/100mm – 2 circuits	621112
Steel profile manifold bar – DN 20/100mm – 3 circuits	621113
Steel profile manifold bar – DN 20/100mm – 4 circuits	621114
Steel profile manifold bar – DN 20/100mm – 5 circuits	621115
Steel profile manifold bar – DN 20/100mm – 6 circuits	621116
Type	Catalogo number
Steel profile manifold bar – DN 25/100mm – 2 circuits	621122
Steel profile manifold bar – DN 25/100mm – 3 circuits	621123
Steel profile manifold bar – DN 25/100mm – 4 circuits	621124
Steel profile manifold bar – DN 25/100mm – 5 circuits	621125
Steel profile manifold bar – DN 25/100mm – 6 circuits	621126
Type	Catalog number
Steel profile manifold bar – DN 32/100mm – 2 circuits	621132
Steel profile manifold bar – DN 32/100mm – 3 circuits	621133
Steel profile manifold bar – DN 32/100mm – 4 circuits	621134
Steel profile manifold bar – DN 32/100mm – 5 circuits	621135
Steel profile manifold bar – DN 32/100mm – 6 circuits	621136
Type	Catalog number
Steel profile manifold bar – DN 40/100mm – 2 circuits	621142
Steel profile manifold bar – DN 40/100mm – 3 circuits	621143
Steel profile manifold bar – DN 40/100mm – 4 circuits	621144
Steel profile manifold bar – DN 40/100mm – 5 circuits	621145
Steel profile manifold bar – DN 40/100mm – 6 circuits	621146



## Magnetic separators SM 20, SM 25



SM 20

Valves  
ball  
complete



SM 25

The SM magnetic separator is used to remove impurities in closed central heating systems. Contaminants in the circuit may accelerate the wear of pumps, valves and other components of the heating system. Contaminants can also restrict the flow of the system, thereby reducing the efficiency of the entire system. The separator can be installed in vertical or horizontal pipelines, and its unique design allows excellent filtration and deposition of impurities in the filter tank. Removal of impurities can take place during normal operation of the installation.

Technical data:

Maximum pressure: 4 bar

Maximum flow: 1.5 m<sup>3</sup>/h for SM 20

3.0 m<sup>3</sup>/h for SM 25

Type	Catalog number
Magnetic separator SM 20 - DN 20	500035
Magnetic separator SM 25 - DN 25	500036

## Ball valve P 25

Ball valve  
P 25



Group PG 25



Technical data:

Body: brass

Shaft seal: EPDM

Ball seal: Teflon

Maximum pressure: 6 bar

Maximum working temperature: 110°C

Installation connection: 1" F

Pump connection: 1 1/2" nut

Type	Catalog number
Ball valve P 25 with brass nut G 1 1/2" with gasket EPDM	700540
Group PG 25 - DN 25 (1"), with pump DAB Evosta2 65/180	700544



**womix**  
Comfort Controls

# CATALOG 2022

## ENERGY-SAVING CENTRAL HEATING EQUIPMENT



mixing valves



hydraulic separators



boiler room building systems

[www.womix.pl](http://www.womix.pl)

Womix Sportowa 31 89-200 Szubin  
phone: +48 52 382 44 50  
mobile: 570 108 498



**From design to productions**

**Qualified staff**

**A wide range of innovative products**

**Over 50 people employed in production**

**Express order fulfillment**

**High inventory**

**Automated production lines**

**Full production identification**

**Modern machinery park**

**Thousands of manufactured systems**

**Polish product**

**Quality certificate ISO 9001:2015**




## OEM solutions

*If there is a demand for non-standard products that are not included in our catalog our construction department is ready to prepare products that meet your technical and quality requirements.*

### PRODUCTS ADAPTED TO THE CUSTOMER'S NEEDS



MIXING  
VALVES




BRASS MANIFOLD  
WITH AUTOMATIC AIR VENTS




PRODUCTS WITH  
CUSTOMIZED CONNECTIONS



### PRODUCTS ADAPTED TO THE CUSTOMER'S BRAND




PUMP GROUPS



MIX-BOX SYSTEM




ACTUATORS



BRASS MANIFOLDS

### CASCADE SYSTEMS ADAPTED TO THE REQUIREMENTS OF CUSTOMERS AND BOILER MANUFACTURERS



## Table of Contents

<b>Circulation pump Womix eco PRO 15-1/65</b>	<b>5</b>
<b>Pump groups M-SMTC - DN 20, M-SMT - DN 20</b>	<b>5</b>
<b>Brass zone manifolds CM</b>	<b>6-7</b>
<b>Actuators</b>	<b>8</b>
<b>Mixing and thermostatic valves</b>	<b>9-11</b>
<b>Hot water circulation, magnetic separators</b>	<b>12-13</b>
<b>Pressure reducing valves, filters</b>	<b>14-15</b>
<b>Ready-made pump group systems</b>	<b>16-28</b>
<b>Boiler room building system DN 20 - up to 35 kW</b>	<b>30-31</b>
<b>Pump groups DN 20</b>	<b>32</b>
<b>Boiler room building system DN 25 - from 40 kW to 110 kW</b>	<b>33-38</b>
<b>Pump groups DN 25</b>	<b>39</b>
<b>Boiler room building system DN 32 - from 120 kW to 220 kW</b>	<b>40-43</b>
<b>Pump groups DN 32</b>	<b>44</b>
<b>Boiler room building system DN 50 - up to 350 kW</b>	<b>45</b>
<b>Boiler room building system up to 700 kW</b>	<b>46-53</b>
<b>Heat pump or air conditioner stand/bracket, mounting frame for boiler</b>	<b>54</b>
<b>Elements for heating the central heating installation</b>	<b>55</b>
<b>Hydraulic separators</b>	<b>56-57</b>
<b>Other products</b>	<b>58</b>

## Circulation pump **WOMIX eco PRO**




### Application:

Domestic hot water circulation installations.  
Water circulation in heating systems.  
Modernization and construction of new installations.  
For single- and multi-family housing.

Type	Catalog number
Circulation pump <b>WOMIX eco PRO 15-1/65</b>	100151


## Pump group **M-SMTC - DN 20** with thermostatic mixing valve



The mixing group **M-SMTC DN 20** with thermostatic valve is designed for floor heating manifolds. Its task is to limit the temperature of the medium introduced into the manifold. The set consists of a 3-way thermostatic mixing valve (DN 20, temperature range 20-45 °C, kv 3,4), thermometer for supply and return water, brass connection fitting and Wilo, DAB or Grundfos pumps.

Type	Catalog number
Pump group <b>M-SMTC - DN 20</b> without pump	200499
Pump group <b>M-SMTC - DN 20</b> with pump <b>Wilo Yonos Para 15/6</b>	200491
Pump group <b>M-SMTC - DN 20</b> with pump <b>Grundfos UPM3S AUTO 15-60</b>	200490
Pump group <b>M-SMTC - DN 20</b> with pump <b>DAB Evosta2 65/130</b>	200492
Set two brass <b>nipples G 1"</b> with o-ring for connection pump with brass manifold	210020

## Pump group **M-SMT - DN 20** with rotary mixing valve




Mixing group **M-SMT - DN 20** with a rotary valve is designed for floor heating manifolds. Its task is to limit the temperature of the medium introduced into the manifold. The group can be connected using a nipple (see table below) with all types of brass manifolds. The set consists of a rotary mixing valve with a flow of kvs 6,3 with the possibility of connecting the actuator MP 10, thermometer for supply water, brass connection fitting and Wilo, DAB or Grundfos pumps.

Type	Catalog number
Pump group <b>M-SMT - DN 20</b> without pump	200489
Pump group <b>M-SMT - DN 20</b> with pump <b>Wilo Yonos Para 15/6 130</b>	200481
Pump group <b>M-SMT - DN 20</b> with pump <b>Grundfos UPM3S AUTO 15-60</b>	200480
Pump group <b>M-SMT - DN 20</b> with pump <b>DAB Evosta2 65/130</b>	200482
Set two brass <b>nipples G 1"</b> with o-ring for connection group with brass manifold	210020
Actuator <b>MP 10</b>	401011

# Brass manifold for radiator heating and underfloor heating


## Brass manifold for radiator heating **CM**



Brass manifold **CM** is responsible for distribution and regulation of the heating medium. The manifold allows connecting different circuits and installation zones, increasing the efficiency of the heating system. It contains two C-profile beams connected with two steel holders, connections for air vents and connections for supply and return of the system.

Name	Nr of sections	A (mm)	Catalog number
<b>CM 2F</b>	2	100	200102
<b>CM 3F</b>	3	150	200103
<b>CM 4F</b>	4	200	200104
<b>CM 5F</b>	5	250	200105
<b>CM 6F</b>	6	300	200106
<b>CM 7F</b>	7	350	200107
<b>CM 8F</b>	8	400	200108
<b>CM 9F</b>	9	450	200109
<b>CM 10F</b>	10	500	200110
<b>CM 11F</b>	11	550	200111
<b>CM 12F</b>	12	600	200112


## Brass manifold for radiator heating **CM-N**



Brass manifold **CM-N** is responsible for distribution and regulation of the heating medium. The manifold allows connecting different circuits and installation zones, increasing the efficiency of the heating system. It contains two C-profile beams connected with two steel holders, connections for air vents, connections for supply and return of the system and nipples with an o-ring.

Name	Nr of sections	A (mm)	Catalog number
<b>CM-N 2F</b>	2	100	200202
<b>CM-N 3F</b>	3	150	200203
<b>CM-N 4F</b>	4	200	200204
<b>CM-N 5F</b>	5	250	200205
<b>CM-N 6F</b>	6	300	200206
<b>CM-N 7F</b>	7	350	200207
<b>CM-N 8F</b>	8	400	200208
<b>CM-N 9F</b>	9	450	200209
<b>CM-N 10F</b>	10	500	200210
<b>CM-N 11F</b>	11	550	200211
<b>CM-N 12F</b>	12	600	200212

## Brass manifold for radiator and underfloor heating **CM-NR**




Brass manifold **CM-NR** is responsible for distribution and regulation of the heating medium. The manifold allows connecting different circuits and installation zones, increasing the efficiency of the heating system. It contains two C-profile beams connected with two steel holders, connections for supply and return of the system, nipples with an o-ring, manual shut-off valves and two brass tees with o-ring, manual air vent and angle drain valve.

Name	Nr of sections	A (mm)	Catalog number
<b>CM-NR 2F</b>	2	100	200302
<b>CM-NR 3F</b>	3	150	200303
<b>CM-NR 4F</b>	4	200	200304
<b>CM-NR 5F</b>	5	250	200305
<b>CM-NR 6F</b>	6	300	200306
<b>CM-NR 7F</b>	7	350	200307
<b>CM-NR 8F</b>	8	400	200308
<b>CM-NR 9F</b>	9	450	200309
<b>CM-NR 10F</b>	10	500	200310
<b>CM-NR 11F</b>	11	550	200311
<b>CM-NR 12F</b>	12	600	200312

# Brass manifold for radiator heating and underfloor heating


## Brass manifold for underfloor heating **CM-NRT**



Brass manifolds **CM-NRT** are used to separate individual loops of floor heating and their proper regulation, ensuring comfort of use and even distribution of heat. It contains two C-profile beams connected with two steel holders, connections for supply and return of the system, nipples with an o-ring, manual shut-off valves, regulating valves for actuators with M30x1,5 thread, two brass tees with o-ring, manual air vent and angle drain valve.

Name	Nr of sections	A (mm)	Catalog number
<b>CM-NRT 2F</b>	2	100	200402
<b>CM-NRT 3F</b>	3	150	200403
<b>CM-NRT 4F</b>	4	200	200404
<b>CM-NRT 5F</b>	5	250	200405
<b>CM-NRT 6F</b>	6	300	200406
<b>CM-NRT 7F</b>	7	350	200407
<b>CM-NRT 8F</b>	8	400	200408
<b>CM-NRT 9F</b>	9	450	200409
<b>CM-NRT 10F</b>	10	500	200410
<b>CM-NRT 11F</b>	11	550	200411
<b>CM-NRT 12F</b>	12	600	200412

## Brass manifold for underfloor heating **CM-NTRot (0,5-5l/min)** and **CM-NTRot026 (0-2,6l/min)**



Brass manifolds **CM-NTRot** and **CM-NTRot026** are used to separate individual loops of floor heating and their proper regulation, ensuring comfort of use and even distribution of heat. Thanks to the rotameters placed on the supply beam, it is possible to precisely set the amount of medium flowing through each loop. The manifold contains two C-profile beams connected with two steel holders, connections for supply and return of the system, nipples with an o-ring, rotameters with a scale of 0,5 - 5 l/min or 0-2,6 l/min (depends on the type), regulating valves for actuators with M30x1,5 thread, two brass tees with o-ring, manual air vent and angle drain valve.

Nr of sections	A (mm)	Cod. CM-NTRot	Cod. CM-NTRot026
2	100	200502	200562
3	150	200503	200563
4	200	200504	200564
5	250	200505	200565
6	300	200506	200566
7	350	200507	200567
8	400	200508	200568
9	450	200509	200569
10	500	200510	200570
11	550	200511	200571
12	600	200512	200572

## Equipment for brass manifolds

Type	Catalog number
Steel holder, L-220 mm	210001
Brass G 1" plug with O-ring seal	210002
Manual shut-off valve (red)	210004
Manual shut-off valve (blue)	210005
Regulating valves for the actuator with 30x1,5 thread	210006
Flow meter (rotameter) 0.5 - 5 l/min	210007
Flow meter (rotameter) 0 - 2,6 l/min	210017
Tee with air-vent and angle drain valve	210008
Manual air vent 1/2"	210009
Angle drain valve 1/2"	210010
Reducer nipple 1/2"x3/4" with seal O-ring with connection eurokonus - for manifold CM-N	210003
Reducer nipple 1/2"x3/4" with seal O-ring with connection eurokonus - for manual shut-of valve	210011
Reducer nipple 1/2"x3/4" with seal O-ring with connection eurokonus - for regulating valves	210012
Reducer nipple 1/2"x3/4" with seal O-ring with connection eurokonus - for flow meter	210013

## Thermoelectric actuator **MP VM100**



The **MP VM100** thermoelectric actuator is a drive for opening and closing valves on manifolds of underfloor heating circuits. The set includes an adapter that allows the device to be mounted on thermostatic valves in the CM-NR, CM-NTRot and CM-NTRot026 manifolds. The adapter allows quick assembly of the actuator only by pressing and subsequent disassembly of the actuator only by using the disassembly button. The actuator is in the normally closed position, after energizing it opens the valve flow.

Type	Catalog number
Thermoelectric actuator MP VM100 with adapter for regulating valves Womix	401075

## Actuator **MP 10, MP 15**




switch to work: manual / automatic.

**MP** actuators consists of a synchronous motor with capacitor, two limit switches, two cams positioned on the 90 degrees, the knob, the color scale for visualizing the position of the heart of the valve, a switch for manually changing the position of the heart of the valve. The factory is equipped with a 2 meter cable 3 x 0.75 mm<sup>2</sup> and an adapter for mounting the actuator on the mixing valve **MIX M** from WOMIX - **A 101**.

Using an adapter connecting actuators, **MP** can be mounted on the mixing valve manufacturing of other companies (see the numbers of adapters).

## Actuator **MP 05 CR**



The actuators **MP 05 CR NEW** with integrated constant thermal regulator are used in central heating systems with mixing valve. The actuator maintains a constant temperature of the medium heating circuit. Through a built-in DIP switch (located under the cover of the actuator), we can choose additional functions such as:

- the direction of rotation of the actuator,
- the minimum temperature limit - a choice: +60...85°C,
- the maximum limit temperature - +25...45°C,
- change of response factor

Type	Torque	Open time	Voltage	Catalog number
Actuator <b>MP 10 - 230 / 70</b> with adapter <b>A 101</b> for valve by WOMIX	10 Nm	70 s./90°	230 V~50Hz	401010
Actuator <b>MP 10 - 230 / 140</b> with adapter <b>A 101</b> for valve by WOMIX	10 Nm	140 s./90°	230 V~50Hz	401011
Actuator <b>MP 10 - 24 / 140</b> with adapter <b>A 101</b> for valve by WOMIX	10 Nm	140 s./90°	24 V~50Hz	401012
Actuator <b>MP 10 - 24 / 140 (0-10V)</b> with adapter <b>A 101</b> for valve by WOMIX	10 Nm	140 s./90°	24 V~50Hz	401041
Actuator <b>MP 15 - 230 / 140</b> with adapter <b>A 101</b> for valve by WOMIX	15 Nm	140 s./90°	230 V~50Hz	401031
Actuator <b>MP 05 CR</b> with built-in constant temperature control	5 Nm	140 s./90°	230 V, +/- 15V, 50/60 Hz	401050
Equipment				Catalog number
Adapter <b>A 101</b> for <b>MP 10</b> for valve by WOMIX (basic equipment)				401101
Adapter <b>A 062</b> for valve by WITA Minimix and type H				401062
Adapter <b>A 063</b> for valve by Meibes V7, Afris (old generation)				401063
Adapter <b>A 064</b> for valve by ESBE, Danfoss (old generation)				401064
Adapter <b>A 065</b> for valve by ESBE VRG / VRB				401065
Adapter <b>A 066</b> for valve by WOMIX (old generation)				401066
Adapter <b>A 151</b> for valve by WOMIX (for actuators MP 15)				401151

## Mixing valves MIX M

MIX M 3



MIX M 4



Type	Kvs	Size	Catalog number
Mixing valve <b>MIX M 3-15</b>	4	1/2"	601000
Mixing valve <b>MIX M 3-20</b>	8	3/4"	601003
Mixing valve <b>MIX M 3-25</b>	12	1"	601005
Mixing valve <b>MIX M 3-32</b>	18	1 1/4"	601007
Mixing valve <b>MIX M 3-40</b>	28	1 1/2"	601008
Mixing valve <b>MIX M 3-50</b>	44	2"	601009

Type	Kvs	Size	Catalog number
Mixing valve <b>MIX M 4-20</b>	8	3/4"	602003
Mixing valve <b>MIX M 4-25</b>	12	1"	602005
Mixing valve <b>MIX M 4-32</b>	18	1 1/4"	602007
Mixing valve <b>MIX M 4-40</b>	28	1 1/2"	602008
Mixing valve <b>MIX M 4-50</b>	44	2"	602009

## Mixing valve MIX M with actuator MP 10




Type	Catalog number
Mixing valve <b>MIX M 3-20 kv 8 with actuator MP 10-230/140</b>	601253
Mixing valve <b>MIX M 3-25 kv 12 with actuator MP 10-230/140</b>	601255
Mixing valve <b>MIX M 3-32 kv 18 with actuator MP 10-230/140</b>	601257
Mixing valve <b>MIX M 4-20 kv 8 with actuator MP 10-230/140</b>	602253
Mixing valve <b>MIX M 4-25 kv 12 with actuator MP 10-230/140</b>	602255
Mixing valve <b>MIX M 4-32 kv 18 with actuator MP 10-230/140</b>	602257

## Mixing valve MIX M 3-20M - 1" M



Kvs 6,3



**MIX M 3 - 20M** is a valve with an external threads. It has three 1" threaded connections, and thanks to its compact dimensions, it can be used in many home boilers. The valve is also a part of the MIX-BOX systems.

Type	Kvs	Size	Catalog number
Mixing valve <b>MIX M 3-20 M - 1" M</b>	6,3	1"	601010

## Mixing valve MIX MT 25, 32 for units SMT DN 25, 32



Kvs 8,3

3-way mixing valve **MIX MT 25, 32** for straight-through flow, applies to small and medium-sized central heating system. It can be adjusted manually or automatically by the actuator **MP 10**.

Type	Kvs	Catalog number
Mixing valve <b>MIX MT 25 - DN 25 with brass nut 1 1/2"</b>	8,3	001021
Mixing valve <b>MIX MT 32 - DN 32 with brass nut 2"</b>	17	001022

## Flanged mixing valves 3F, 4F

**3 F**



**4 F**



Type	Kvs	Size	Catalog number
Flanged mixing valve <b>3F - DN 32</b>	28	32	601123
Flanged mixing valve <b>3F - DN 40</b>	44	40	601124
Flanged mixing valve <b>3F - DN 50</b>	60	50	601125
Flanged mixing valve <b>3F - DN 65</b>	90	65	601126
Flanged mixing valve <b>3F - DN 80</b>	150	80	601127
Flanged mixing valve <b>3F - DN 100</b>	225	100	601128
Flanged mixing valve <b>3F - DN 125</b>	280	125	601129
Flanged mixing valve <b>3F - DN 150</b>	400	150	601030


Type	Kvs	Size	Catalog number
Flanged mixing valve <b>4F - DN 40</b>	44	40	602124
Flanged mixing valve <b>4F - DN 50</b>	60	50	602125
Flanged mixing valve <b>4F - DN 65</b>	90	65	602126
Flanged mixing valve <b>4F - DN 80</b>	150	80	602127
Flanged mixing valve <b>4F - DN 100</b>	225	100	602128

## Additional equipment for mixing valves **MIX M**

Connector for a flat seal to connect the mixing valve DN 25 with pump



Pump ball valve MF TERM 1 " with brass nut G 1 1/2", gasket



Type	Catalog number
Connector for a flat seal to connect the mixing valve DN 25 with pump, with brass nut	607222
Pump ball valve MF TERM 1 " with brass nut G 1 1/2", EPDM gasket	700540



Set o-rings for mixing valve

Type	Catalog number
Set o-rings for mixing valve <b>MIX M DN 15, DN 20M</b>	601090
Set o-rings for mixing valve <b>MIX M DN 20, DN 25, DN 32</b>	601091
Set o-rings for mixing valve <b>MIX M DN 40, DN 50</b>	601092

## Thermostatic mixing valve **MIX THERM**



Thermostatic mixing valves **MIX THERM** series are designed to regulate the power factor of the installation of central heating radiators and floor heating.

Type	Catalog number
Thermostatic mixing valve <b>MIX THERM 20-45 °C</b>	601212
Thermostatic mixing valve <b>MIX THERM 35-60 °C</b>	601213


## Thermostatic mixing valve **MIX THERM - R**



Thermostatic mixing valves **MIX THERM-R** series are designed to regulate the power factor of the installation of central heating radiators and floor. **MIX THERM-R** valve is equipped with a brass female nut 1 1/2" and 1" EPDM gasket.

Type	Catalog number
Thermostatic mixing valve <b>MIX THERM-R 20-45 °C</b> , with brass nut 1 1/2" F	601217
Thermostatic mixing valve <b>MIX THERM-R 35-60 °C</b> , with brass nut 1 1/2" F	601218


## Thermostatic mixing valve **TMT**




Thermostatic mixing valves **TMT** series are designed to regulate domestic hot water. Protect the system against too high temperature hot water which in turn protects the user from burns. Do not install these valves in solar installations.

Type	Kvs	Catalog number
Thermostatic mixing valve <b>TMT 12 F - 1/2" F</b>	1,6	601101
Thermostatic mixing valve <b>TMT 34 F - 3/4" F</b>	1,8	601102
Thermostatic mixing valve <b>TMT 34 M - 3/4" M</b>	1,8	601103
Thermostatic mixing valve <b>TMT 100 F - 1" F</b>	3,2	601104
Thermostatic mixing valve <b>TMT 100 M - 1" M</b>	3,2	601105
Thermostatic mixing valve <b>TMT 114 M - 1 1/4" M</b>	7,4	601106
Thermostatic mixing valve <b>TMT 112 M - 1 1/2" M</b>	7,6	601107

## Pump group for hot utility water circulation HW20



*Simplified schematic diagram of the installation - the standard installation elements as well as the boiler room protection scheme have not been marked.*



The **HW20** pump group is intended for the implementation of a hot utility water circulation system in installations with a domestic hot water tank. Its design allows to avoid incorrect installation of the domestic hot water circulation system. The HW20 group is equipped with a thermostatic mixing valve MIX THERM (35 - 60 °C), with a kvs flow of 3,4, a ball valve with a thermometer, a circulation pump with a check valve, drain/vent valve and a return water thermometer. The group can be used for containers equipped with a circulation pipe as well as for containers not equipped with it.

Type	Catalog number
Pump group for hot utility water circulation HW20	606750

## Magnetic separators SM 20, SM 25



SM 20

Ball  
valves  
included




SM 25

The separator is used to remove water contaminants in closed central heating systems, especially sand and rust particles. Contaminants in the circuit can accelerate the wear of the water pump, valves and other components of the heating system. Dirt can also block the heat exchanger, the ends of the radiators or pipes, reducing the efficiency of the entire system. Due to its special design, the separator can be installed vertically or horizontally on vertical or horizontal pipelines. It enables excellent filtration and the deposition of impurities in the filter tank. Removal of contamination can occur during normal operation of the installation.

Type	Catalog number
Magnetic separators SM 20 - DN 20	500035
Magnetic separators SM 25 - DN 25	500036

## Under-boiler magnetic filter PFM20



The PFM 20 under-boiler magnetic filter is made of brass. It is equipped with a 12000 G magnetic cartridge and brass plug. The magnetic filter eliminates impurities contained in the system thanks to the mesh filter inside. A strong neodymium magnet collects and catches all iron impurities, and solves all problems related to the protection of the boiler and heating installation thanks to its compact design.

Contamination in the installation can lead to:

- blockages and jamming of pumps caused by impurities that circulate in the pumps and can accumulate in them,
- lower efficiency of the heat exchangers due to the deposition of dirt, which can significantly reduce both the flow rate of the media and the heat exchange surface.

Thanks to the compact design of the dirt filter, it fits all types of boilers on the market.

Technical data:

Material:	brass CW 6N7N
Maximum working pressure	6 bar
Maximum working Temperature:	110°C
Magnet:	neodymium 12000 G

Type	Catalog number
Under-boiler magnetic filter PFM20 - DN 20	100171
Magnetic filter connection kit PFM20 (ball valve + connector)	100180

## Automatic air vent Compact



Automatic air vents are installed to remove air that accumulates in heating and air conditioning systems. Thanks to their operation, without the need for manual operation, they allow to avoid harmful phenomena that may threaten the life and efficiency of hydraulic systems. In particular, they reduce the negative effect of galvanic corrosion (caused by the presence of oxygen inside the pipeline) and cavitation. Moreover, these valves optimize the heating and cooling capacity of any system as they prevent the formation of air pockets inside the radiators and fan coils.


Type	Catalog number
Automatic vertical air vent Compact, with a 1/2" check valve	100100

## Compression fitting for multilayer and synthetic pipes with Euroconus connection



Type	Catalog number
Compression fitting for multilayer and synthetic pipes with Euroconus connection 3/4" x 16 x 2,0	210014

## Pressure reducing valves PRF and PRM




Pressure reducing valves are specially designed to reduce and stabilize the pressure of water flowing into the water supply network. Normally the pressure - from tap water - is too high and unstable to be used effectively in a domestic plumbing system. One of the most important features of pressure reducers is that they are able to provide a stable pressure downstream of the valve despite changing pressure upstream of the valve.

Type	Catalog number
Pressure reducing valve PRF 12F - F 1/2"	601600
Pressure reducing valve PRF 34F - F 3/4"	601601
Pressure reducing valve PRF 100F - F 1"	601602
Pressure reducing valve PRF 114F - F 1 1/4"	601603
Pressure reducing valve PRF 112F - F 1 1/2"	601604
Pressure reducing valve PRF 200F - F 2"	601605
Pressure reducing valve PRF 212F - F 2 1/2"	601606
Pressure reducing valve PRF 300F - F 3"	601607

Type	Catalog number
Pressure reducing valve PRM 12M - M 1/2"	601610
Pressure reducing valve PRM 34M - M 3/4"	601611
Pressure reducing valve PRM 100M - M 1"	601612
Pressure reducing valve PRM 114M - M 1 1/4"	601613
Pressure reducing valve PRM 112M - M 1 1/2"	601614
Pressure reducing valve PRM 200M - M 2"	601615
0-10 bar pressure gauge with radial connection for PRF and PRM pressure reducers	601619

## Self-cleaning filter FSV



The self-cleaning filter is suitable for all plants, both civil and industrial ones, where the constant impurities in water could damage or block the present appliances. The water, we usually use, comes from waterworks or wells, contains a great number of particles which, according to their sizes, interact negatively with the installed accessories and compromise, therefore, their correct functioning.

The joints for the connection to the hydraulic plant are internal threaded in compliance with the ISO 228/1 standard. On the body of the self-cleaning filter there are two 1/4"G threads for the connection of two pressure gauges. The self-cleaning filter is equipped with 400 micron filtering cartridge.

Type	Catalog number
Self-cleaning filter FSV 12F - F 1/2"	601650
Self-cleaning filter FSV 34F - F 3/4"	601651
Self-cleaning filter FSV 100F - F 1"	601652
Self-cleaning filter FSV 114F - F 1 1/4"	601653
Self-cleaning filter FSV 112F - F 1 1/2"	601654
Self-cleaning filter FSV 200F - F 2"	601655
0-16 bar pressure gauge with axial connection for FSV self-cleaning filters	601659

## EASYFLUX ball valves with built-in filter




Easyflux ball valves are equipped with a sediment filter for water, which is located directly in the valve ball. Thanks to this solution, the length of the valve's installation is much shorter and the revolutionary way of installing the filter enables its maintenance and cleaning without removing the valve from the installation. The use of the filter in installations results in a significant improvement in water quality and protects the installation against solid contamination, thus extending its operation time. The version with a built-in magnetic cartridge also allows for the retention of metal particles in the installation and their removal when cleaning the filter.

Type	Catalog number
Ball valve with built-in filter <b>Easyflux</b> 1/2"	100101
Ball valve with built-in filter <b>Easyflux</b> 3/4"	100102
Ball valve with built-in filter <b>Easyflux</b> 1"	100103
Ball valve with built-in filter <b>Easyflux</b> 1 1/4"	100104
Ball valve with built-in filter <b>Easyflux</b> 1 1/2"	100105
Ball valve with built-in filter <b>Easyflux</b> 2"	100106

Type	Catalog number
Ball valve with built-in 3/4 " <b>Easyflux</b> filter, with magnetic insert	100162
Ball valve with built-in 1 " <b>Easyflux</b> filter, with magnetic insert	100163
Ball valve with built-in 1 1/4 " <b>Easyflux</b> filter, with magnetic insert	100164
Ball valve with built-in 1 1/2 " <b>Easyflux</b> filter, with magnetic insert	100165
Ball valve with built-in 2 " <b>Easyflux</b> filter, with magnetic insert	100166

## Pump ball valves

Valve **S/C TERM**



Valve **S TERM**



**Valve S TERM** - Thermometer ball valve. (Mounted on the supply)

**Valve S/C TERM** - Thermometer ball valve with check valve. (Mounted on the return)

**Valve S** - Ball valve

Type	Catalog number
Pump ball valve <b>S</b> 1" with cast iron nut G 1 1/2" seal EPDM	700511
Pump ball valve <b>S TERM</b> 1" with cast iron nut G 1 1/2" seal EPDM	700521
Pump ball valve <b>S/C TERM</b> 1" with cast iron nut G 1 1/2" seal EPDM	700522
Type	Catalog number
Pump group <b>G TERM</b> - DN 25 (1"), without pump	700000
Pump group <b>G TERM</b> - DN 25 (1"), with pump <b>Wilо Yonos Para 25/6</b>	700008
Pump group <b>G TERM</b> - DN 25 (1"), with pump <b>Wilо Yonos Para 25/8</b>	700009
Pump group <b>G TERM</b> - DN 25 (1"), with pump <b>Grundfos UPM3S AUTO 25-60</b>	700003
Pump group <b>G TERM</b> - DN 25 (1"), with pump <b>DAB Evosta2 65/180</b>	700004
Type	Catalog number
Pump ball valve <b>S</b> 1 1/4" with cast iron nut G 2" seal EPDM	700611
Pump ball valve <b>S TERM</b> 1 1/4" with cast iron nut G 2" seal EPDM	700621
Pump ball valve <b>S/C TERM</b> 1 1/4" with cast iron nut G 2" seal EPDM	700622
Type	Catalog number
Pump group <b>G TERM</b> - DN 32 (1 1/4"), without pump	700010
Pump group <b>G TERM</b> - DN 32 (1 1/4"), with pump <b>Wilо Yonos Para 30/6</b>	700011
Pump group <b>G TERM</b> - DN 32 (1 1/4"), with pump <b>Wilо Yonos Para 30/8</b>	700012

# SYSTEM MIX-BOX

for 2 or 3 heating circuits


Perfect products for wall-hanging boilers



Built-in hydraulic separator



Available with pumps:



Wilo Yonos Para DAB Evosta2 Grundfos UPM3

The **MIX-BOX SYSTEM** is a complete distribution system of heating circuits in the installation with wall-hanging boiler, both standard and condensing. It can handle up to three heating circuits. The heating circuits may be pumping or mixing with rotary or thermostatic mixing valve. Pump group are equipped with pump **Wilo - type Yonos Para 15/6**, **DAB - type Evosta2 65** or **Grundfos - type UPM3S AUTO 15 - 60**. The housing for **MIX-BOX** system is made in the wall version.

#### Technical data:

Zone manifold material:	steel, insulation black40 g/l
Pump groups material:	brass CW617N, copper
Max temp.:	95°C
Max. work pressure:	6 bar
Supply voltage pumps:	230 VAC, 50 Hz
Thermostatic mixing valve working temperature range:	20 - 45°C.
Length of pump:	130 mm
Connection of the pump:	1" M



Mixing valve  
Kvs 6,3



Thermostatic mixing valve  
Kvs 3,4

### Ready versions of MIX-BOX systems for two heating circuits

#### MIX-BOX 1 System of 2 heating circuits including one with a mixing valve and a rotary electric actuator



Type	Catalog number
System <b>MIX-BOX 1</b> with groups SA/SMT 83, with pumps Wilo Yonos Para 15/6	604102
System <b>MIX-BOX 1</b> with groups SA/SMT 83, with pumps Grundfos UPM3S AUTO 15 - 60	604121
System <b>MIX-BOX 1</b> with groups SA/SMT 83, with pumps DAB Evosta2 65/130	604142

The system contains:

1. Wall cabinet **P2** (catalog no: 604003),
2. Zone manifold **CX 2F** (catalog no: 604012),
3. Group **SA 83 MIX-BOX 20** with pump,
4. Group **SMT 83 MIX-BOX 20** with pump,



#### MIX-BOX 2 System of 2 heating circuits including one with thermostatic mixing valve



Type	Catalog number
System <b>MIX-BOX 2</b> with groups SA/SMTC 83, with pumps Wilo Yonos Para 15/6	604104
System <b>MIX-BOX 2</b> with groups SA/SMTC 83, with pumps Grundfos UPM3S AUTO 15 - 60	604123
System <b>MIX-BOX 2</b> with groups SA/SMTC 83, with pumps DAB Evosta2 65/130	604144

The system contains:

1. Wall cabinet **P2** (catalog no: 604003),
2. Zone manifold **CX 2F** (catalog no: 604012),
3. Group **SA 83 MIX-BOX 20** with pump,
4. Group **SMTC 83 MIX-BOX 20** with pump,



#### MIX-BOX 3 System of 2 heating circuits with a mixing valves and a rotary electric actuators



Type	Catalog number
System <b>MIX-BOX 3</b> with groups SMT/SMT 83, with pumps Wilo Yonos Para 15/6	604106
System <b>MIX-BOX 3</b> with groups SMT/SMT 83, with pumps Grundfos UPM3S AUTO 15 - 60	604125
System <b>MIX-BOX 3</b> with groups SMT/SMT 83, with pumps DAB Evosta2 65/130	604146

The system contains:

1. Wall cabinet **P2** (catalog no: 604003),
2. Zone manifold **CX 2F** (catalog no: 604012),
3. Group **SMT 83 MIX-BOX 20** with pump,
4. Group **SMT 83 MIX-BOX 20** with pump,



## Ready versions of MIX-BOX systems for two heating circuits

### MIX-BOX 4 System of 2 direct heating circuits without a mixing valves



Type	Catalog number
System <b>MIX-BOX 4</b> with groups SA/SA 83, with pumps Wilo Yonos Para 15/6	604108
System <b>MIX-BOX 4</b> with groups SA/SA 83, with pumps Grundfos UPM3S AUTO 15 - 60	604127
System <b>MIX-BOX 4</b> with groups SA/SA 83, with pumps DAB Evosta2 65/130	604148

The system contains:

1. Wall cabinet **P2** (catalog no: 604003),
2. Zone manifold **CX 2F** (catalog no: 604012),
3. Group **SA 83 MIX-BOX 20** with pump,
4. Group **SA 83 MIX-BOX 20** with pump,



### MIX-BOX 5 System of 2 heating circuits with thermostatic mixing valves



Type	Catalog number
System <b>MIX-BOX 5</b> with groups SMTc/SMTc 83, with pumps Wilo Yonos Para 15/6	604110
System <b>MIX-BOX 5</b> with groups SMTc/SMTc 83, with pumps Grundfos UPM3S AUTO 15 - 60	604129
System <b>MIX-BOX 5</b> with groups SMTc/SMTc 83, with pumps DAB Evosta2 65/130	604150

The system contains:

1. Wall cabinet **P2** (catalog no: 604003),
2. Zone manifold **CX 2F** (catalog no: 604012),
3. Group **SMTc 83 MIX-BOX 20** with pump,
4. Group **SMTc 83 MIX-BOX 20** with pump,



### MIX-BOX 6 System of 2 heating circuits including one with a mixing valve and a actuator with built-in constant temperature control



Type	Catalog number
System <b>MIX-BOX 6</b> with groups SA/SMT CR 83, with pumps Wilo Yonos Para 15/6	604112
System <b>MIX-BOX 6</b> with groups SA/SMT CR 83, with pumps Grundfos UPM3S AUTO 15 - 60	604131
System <b>MIX-BOX 6</b> with groups SA/SMT CR 83, with pumps DAB Evosta2 65/130	604152

The system contains:

1. Wall cabinet **P2** (catalog no: 604003),
2. Zone manifold **CX 2F** (catalog no: 604012),
3. Group **SA 83 MIX-BOX 20** with pump,
4. Group **SMT CR 83 MIX-BOX 20** with pump,



### MIX-BOX 111 - System of 3 direct heating circuits without a mixing valves



Type	Catalog number
System <b>MIX-BOX 111</b> with groups SA/SA/SA 83, with pumps Wilo Yonos Para 15/6	604201
System <b>MIX-BOX 111</b> with groups SA/SA/SA 83, with pumps Grundfos UPM3S AUTO 15 - 60	604202
System <b>MIX-BOX 111</b> with groups SA/SA/SA 83, with pumps DAB Evosta2 65/130	604203

Set contains:

1. P3 wall cabinet (catalog no. : 604002)
2. Manifold CX 3F (catalog no. : 604011)
3. Pump group SA 83 MIX BOX 20 with pump
4. Pump group SA 83 MIX BOX 20 with pump
5. Pump group SA 83 MIX BOX 20 with pump



### Zestaw MIX-BOX 112 - System of 3 heating circuits - two without mixing valves and one with a mixing valve rotary and electric actuator



Type	Catalog number
System <b>MIX-BOX 112</b> with groups SA/SA/SMT 83, with pumps Wilo Yonos Para 15/6	604205
System <b>MIX-BOX 112</b> with groups SA/SA/SMT 83, with pumps Grundfos UPM3S AUTO 15 - 60	604206
System <b>MIX-BOX 112</b> with groups SA/SA/SMT 83, with pumps DAB Evosta2 65/130	604207

Set contains:

1. P3 wall cabinet (catalog no. : 604002)
2. Manifold CX 3F (catalog no. : 604011)
3. Pump group SA 83 MIX BOX 20 with pump
4. Pump group SA 83 MIX BOX 20 with pump
5. Pump group SMT 83 MIX BOX 20 with pump



### MIX-BOX 113 - set of 3 heating circuits - two without mixing valves and one with thermostatic mixing valve



Type	Catalog number
System <b>MIX-BOX 113</b> with groups SA/SA/SMTC 83, with pumps Wilo Yonos Para 15/6	604301
System <b>MIX-BOX 113</b> with groups SA/SA/SMTC 83, with pumps Grundfos UPM3S AUTO 15 - 60	604302
System <b>MIX-BOX 113</b> with groups SA/SA/SMTC 83, with pumps DAB Evosta2 65/130	604303

Set contains:

1. P3 wall cabinet (catalog no. : 604002)
2. Manifold CX 3F (catalog no. : 604011)
3. Pump group SA 83 MIX BOX 20 with pump
4. Pump group SA 83 MIX BOX 20 with pump
5. Pump group SMTC 83 MIX BOX 20 with pump



### MIX-BOX 122 - a set of 3 heating circuits - one without a mixing valve and two with mixing valves rotary and electric actuators



Type	Catalog number
System <b>MIX-BOX 122</b> with groups SA/SMT/SMT 83, with pumps Wilo Yonos Para 15/6	604305
System <b>MIX-BOX 122</b> with groups SA/SMT/SMT 83, with pumps Grundfos UPM3S AUTO 15 - 60	604306
System <b>MIX-BOX 122</b> with groups SA/SMT/SMT 83, with pumps DAB Evosta2 65/130	604307

Set contains:

1. P3 wall cabinet (catalog no. : 604002)
2. Manifold CX 3F (catalog no. : 604011)
3. Pump group SA 83 MIX BOX 20 with pump
4. Pump group SMT 83 MIX BOX 20 with pump
5. Pump group SMT 83 MIX BOX 20 with pump



**MIX-BOX 132** - a set of 3 heating circuits - one without a mixing valve, one with a thermostatic valve mixing valve and one with mixing rotary valve and electric actuator



Type	Catalog number
System <b>MIX-BOX 132</b> with groups SA/SMT/SMTC 83, with pumps Wilo Yonos Para 15/6	604401
System <b>MIX-BOX 132</b> with groups SA/SMT/SMTC 83, with pumps Grundfos UPM3S AUTO 15 - 60	604402
System <b>MIX-BOX 132</b> with groups SA/SMT/SMTC 83, with pumps DAB Evosta2 65/130	604403

Set contains:

1. P3 wall cabinet (catalog no. : 604002)
2. Manifold CX 3F (catalog no. : 604011)
3. Pump group SA 83 MIX BOX 20 with pump
4. Pump group SMTC 83 MIX BOX 20 with pump
5. Pump group SMT 83 MIX BOX 20 with pump



**MIX-BOX 133** - a set of 3 heating circuits - one without a mixing valve and two with thermostatic ones mixing valves



Type	Catalog number
System <b>MIX-BOX 133</b> with groups SA/SMTC/SMTC 83, with pumps Wilo Yonos Para 15/6	604405
System <b>MIX-BOX 133</b> with groups SA/SMTC/SMTC 83, with pumps Grundfos UPM3S AUTO 15 - 60	604406
System <b>MIX-BOX 133</b> with groups SA/SMTC/SMTC 83, with pumps DAB Evosta2 65/130	604407

Set contains:

1. P3 wall cabinet (catalog no. : 604002)
2. Manifold CX 3F (catalog no. : 604011)
3. Pump group SA 83 MIX BOX 20 with pump
4. Pump group SMTC 83 MIX BOX 20 with pump
4. Pump group SMTC 83 MIX BOX 20 with pump



**MIX-BOX 222** - set of 3 heating circuits - with rotary mixing valves and electric actuators



Type	Catalog number
System <b>MIX-BOX 222</b> with groups SMT/SMT/SMT 83, with pumps Wilo Yonos Para 15/6	604501
System <b>MIX-BOX 222</b> with groups SMT/SMT/SMT 83, with pumps Grundfos UPM3S AUTO 15 - 60	604502
System <b>MIX-BOX 222</b> with groups SMT/SMT/SMT 83, with pumps DAB Evosta2 65/130	604503

Set contains:

1. P3 wall cabinet (catalog no. : 604002)
2. Manifold CX 3F (catalog no. : 604011)
3. Pump group SMT 83 MIX BOX 20 with pump
4. Pump group SMT 83 MIX BOX 20 with pump
5. Pump group SMT 83 MIX BOX 20 with pump



**MIX-BOX 223** - set of 3 heating circuits - two with mixing rotary valves and electric actuators and one with a thermostatic mixing valve



Type	Catalog number
System <b>MIX-BOX 223</b> with groups SMT/SMT/SMTC 83, with pumps Wilo Yonos Para 15/6	604505
System <b>MIX-BOX 223</b> with groups SMT/SMT/SMTC 83, with pumps Grundfos UPM3S AUTO 15 - 60	604506
System <b>MIX-BOX 223</b> with groups SMT/SMT/SMTC 83, with pumps DAB Evosta2 65/130	604507

Set contains:

1. P3 wall cabinet (catalog no. : 604002)
2. Manifold CX 3F (catalog no. : 604011)
3. Pump group SMT 83 MIX BOX 20 with pump
4. Pump group SMT 83 MIX BOX 20 with pump
5. Pump group SMTC 83 MIX BOX 20 with pump



## MIX-BOX 233 - set of 3 heating circuits - one with a rotary mixing valve and electric actuator and two with thermostatic mixing valve



Type	Catalog number
System <b>MIX-BOX 233</b> with groups <b>SMT/SMTC/SMTC 83</b> , with pumps <b>Wilо Yonos Para 15/6</b>	604601
System <b>MIX-BOX 233</b> with groups <b>SMT/SMTC/SMTC 83</b> , with pumps <b>Grundfos UPM3S AUTO 15 - 60</b>	604602
System <b>MIX-BOX 233</b> with groups <b>SMT/SMTC/SMTC 83</b> , with pumps <b>DAB Evosta2 65/130</b>	604603

Set contains:

1. **P3** wall cabinet (catalog no. : 604002)
2. Manifold **CX 3F** (catalog no. : 604011)
3. Pump group **SMT 83 MIX BOX 20** with pump
4. Pump group **SMTC 83 MIX BOX 20** with pump
5. Pump group **SMTC 83 MIX BOX 20** with pump



## MIX-BOX 333 - set of 3 heating circuits - with thermostatic mixing valves



Type	Catalog number
System <b>MIX-BOX 333</b> with groups <b>SMTC/SMTC/SMTC 83</b> , with pumps <b>Wilо Yonos Para 15/6</b>	604605
System <b>MIX-BOX 333</b> with groups <b>SMTC/SMTC/SMTC 83</b> , with pumps <b>Grundfos UPM3S AUTO 15 - 60</b>	604606
System <b>MIX-BOX 333</b> with groups <b>SMTC/SMTC/SMTC 83</b> , with pumps <b>DAB Evosta2 65/130</b>	604607

Set contains:

1. **P3** wall cabinet (catalog no. : 604002)
2. Manifold **CX 3F** (catalog no. : 604011)
3. Pump group **SMTC 83 MIX BOX 20** with pump
4. Pump group **SMTC 83 MIX BOX 20** with pump
5. Pump group **SMTC 83 MIX BOX 20** with pump



## Cabinet mounting for the system **MIX-BOX** - wall-mounted version **P**






Galvanized plate material. Closing cabinet powder painted - white.

The dimensions of the cabinet **P2** for 2 heating circuits: 590x350x190 (height / width / depth).

The dimensions of the cabinet **P3** for 3 heating circuits: 590x510x190 (height / width / depth).

Type	Catalog number
Wall-mounted cabinet <b>P2</b> for 2 heating circuits	604003
Wall-mounted cabinet <b>P3</b> for 3 heating circuits	604002

## Zone manifold for **CX 2-** or **3-**circuits




The **MINI** hydraulic separator  
The flow diagram between supply and return.

Zone manifold **CX** is made of black painted steel and insulated. It is equipped with mini-hydraulic separator, which by end cap can be opened (see picture).

Type	Catalog number
Zone manifold <b>CX 2F</b> for 2 heating circuits	604012
Zone manifold <b>CX 3F</b> for 3 heating circuits	604011


**Attention! Normally, the mini hydraulic separator in the CX zone manifold is closed.**

### Pump group SA 83 MIX-BOX 20



Pump group SA 83 MIX-BOX 20 without mixing valve is equipped with a check valve, a set of insulated connecting pipes. Pump groups are available without pumps or with Wilo, Grundfos or DAB.


### Pump group SMT 83 MIX-BOX 20



Pump group SMT 83 MIX-BOX 20 is equipped with a 3-way rotary mixing valve MIX M 3-20M (kv 6.3), check valve, a set of insulated connecting pipes, mixing valve actuator MP 10-230 / 140. Pump groups are available without pumps or with Wilo, Grundfos or DAB.


Type	Catalog number	Type	Catalog number
Pump group SA 83 MIX-BOX 20 without pump	604061	Pump group SMT 83 MIX-BOX 20 without pump	604081
Pump group SA 83 MIX-BOX 20 with Wilo Yonos Para 15/6	604062	Pump group SMT 83 MIX-BOX 20 with Wilo Yonos Para 15/6	604082
Pump group SA 83 MIX-BOX 20 with Grundfos UPM3S AUTO 15 - 60	604065	Pump group SMT 83 MIX-BOX 20 with Grundfos UPM3S AUTO 15 - 60	604085
Pump group SA 83 MIX-BOX 20 with DAB Evosta2 65/130	604068	Pump group SMT 83 MIX-BOX 20 with DAB Evosta2 65/130	604087

### Pump group SMTC 83 MIX-BOX 20



Pump group SMTC 83 MIX-BOX 20 is equipped with a 3-way thermostatic mixing valve (DN 20, the range 20-45 C, kv 3,4), check valve, a set of insulated connecting pipes. Pump groups are available without pumps or with Wilo, Grundfos or DAB.

### Pump group SMT CR 83 MIX-BOX 20



The mixing and pump group SMT CR 83 MIX-BOX 20 is equipped with a 3-way mixing valve MIX M 3-20M - GZ 1" - Kvs 6.3, a check valve, pipe insulation. Moreover, the group is equipped with a Wilo, Grundfos or DAB pump and in the MP 05 CR mixing valve actuator with a built-in constant temperature regulator.

Type	Catalog number	Type	Catalog number
Pump group SMTC 83 MIX-BOX 20 without pump	604071	Pump group SMT CR 83 MIX-BOX 20 without pump	604080
Pump group SMTC 83 MIX-BOX 20 with Wilo Yonos Para 15/6	604072	Pump group SMT CR 83 MIX-BOX 20 with Wilo Yonos Para 15/6	604086
Pump group SMTC 83 MIX-BOX 20 with Grundfos UPM3S AUTO 15-60	604075	Pump group SMT CR 83 MIX-BOX 20 with Grundfos UPM3S AUTO 15-60	604088
Pump group SMTC 83 MIX-BOX 20 with DAB Evosta2 65/130	604078	Pump group SMT CR 83 MIX-BOX 20 with DAB Evosta2 65/130	604098

### Hydraulic separator CPN MIX- BOX




The hydraulic separator CPN MIX-BOX is made of steel. The factory is equipped with insulation, immersion sleeve for temperature sensor and the automatic air vent with check valve.

Hydraulic separator CPN MIX-BOX has been produced to ensure the full adjustment of the MIX-BOX system.

Type	Catalog number
Hydraulic separator CPN MIX-BOX 2 with insulation (for system 2 circuits MIX-BOX)	604015
Hydraulic separator CPN MIX-BOX 3 with insulation (for system 3 circuits MIX-BOX)	604016

## Set INSUL-BOX



The INSUL-BOX set is a system used to support two heating circuits in installations up to 35 kW. Set contains:

- pump group SA 90 - DN 20 with ball valves,
- mixing pump group SMT 90 - DN 20 with mixing valve and MP 10 actuator,
- manifold C 60 2F - DN 20 with insulation,
- DELTA wall brackets,
- check valve

### Optional

Hydraulic separator  
CPN 60 - DN 20


Insulated  
tubing kit TBN 60

### Available with pumps:



Wilo Yonos Para DAB Evosta2 Grundfos UPM3

### Connection options for the hydraulic separator CPN 60 - DN 20 with manifold C 60 - DN 20




through the connector TBN 60

directly with a zone manifold

Type	Catalog number
Set INSUL-BOX DN 20 with pump Wilo Yonos Para 15/6	646001
Set INSUL-BOX DN 20 with pump Grundfos UPM3S AUTO 15 - 60	646011
Set INSUL-BOX DN 20 with pump DAB Evosta2 65/130	646021

## Set MIX P



The MIX P set is a system with a hydraulic separator for operating two heating circuits in installations up to 40 kW. It comes in 3 ready variants applicable in various types of heating (see table). Each set is equipped with a hydraulic separator, pump groups with non-insulated ball valves, automatic air vent, drain valve and a built-in pipe for mounting the temperature sensor. Separator can be connected to two heat sources.

### Equipment:



### Available with pumps:



Wilo Yonos Para

DAB Evosta2

Grundfos UPM3

### System **MIX P1** System of 2 heating circuits including one with a mixing valve and a rotary electric actuator



Type	Catalog number
System <b>MIX P1</b> with groups SA 125 and SMT 125 - DN25 without pumps	605100
System <b>MIX P1</b> with groups SA 125 and SMT 125 - DN25 with pumps Wilo Yonos Para 25/6	605103
System <b>MIX P1</b> with groups SA 125 and SMT 125 - DN25 with pumps Grundfos UPM3S AUTO 25 - 60	605104
System <b>MIX P1</b> with groups SA 125 and SMT 125 - DN25 with pumps DAB Evosta2 65/180	605105

The system contains:

1. Hydraulic separator CPN 70 2F - DN 25 with equipment,
2. Group SA 125 - DN 25 with pump (see table),
3. Group SMT 125 DN 25 with pump (see table),
4. Check valve,
5. Actuator MP 10 - 230 / 140 with adapter A 101.

### System **MIX P2** System of 2 heating circuits including one with thermostatic mixing valve



Type	Catalog number
System <b>MIX P2</b> with groups SA 125 and SMT1 125 - DN25 without pumps	605200
System <b>MIX P2</b> with groups SA 125 and SMT1 125 - DN25 with pumps Wilo Yonos Para 25/6	605203
System <b>MIX P2</b> with groups SA 125 i SMT1 125 - DN25 with pumps Grundfos UPM3S AUTO 25 - 60	605204
System <b>MIX P2</b> with groups SA 125 i SMT1 125 - DN25 with pumps DAB Evosta2 65/180	605205

The system contains:

1. Hydraulic separator CPN 70 2F - DN 25 with equipment,
2. Group SA 125 - DN 25 with pump (see table),
3. Group SMT1 125 DN 25 with pump (see table),
4. Check valve,

### System **MIX P4** System of 2 direct heating circuits without a mixing valves



Type	Catalog number
System <b>MIX P4</b> with 2 groups SA 125 - DN25 without pumps	605400
System <b>MIX P4</b> with 2 groups SA 125 - DN25 with pumps Wilo Yonos Para 25/6	605403
System <b>MIX P4</b> with 2 grupami SA 125 - DN25 with pumps Grundfos UPM3S AUTO 25 - 60	605404
System <b>MIX P4</b> with 2 grupami SA 125 - DN25 with pumps DAB Evosta2 65/180	605405


The system contains:

1. Hydraulic separator CPN 70 2F - DN 25 with equipment,
2. Two group SA 125 - DN 25 with pump (see table).




Type	Catalog number
Hydraulic separator CPN 70 2F - DN 25 with insulation, with equipment	606001


**Set D - system of 2 heating circuits zone manifold**



Set D is a system used to operate two heating circuits in installations up to 45 kW. The set is available in 5 pump group configurations. The system can be equipped with a hydraulic separator CPN 70 - DN 25.



**Set DX - system of 2 heating circuits zone manifold with built-in hydraulic separator**



Set DX is a system used to operate two heating circuits in installations up to 55 kW. The set is available in 5 pump group configurations. Manifold with built-in hydraulic separator, equipped with a vent and an immersion sleeve for connecting a temperature sensor.

Available with pumps:



### System D1 System of 2 heating circuits including one with a mixing valve and a rotary electric actuator



Type	Catalog number
Set D1 with groups SA 125 and SMT 125 - DN25 with pumps Wilo Yonos Para 25/6	656007
Set D1 with groups SA 125 and SMT 125 - DN25 with pumps Grundfos UPM3S AUTO 25 - 60	656001
Set D1 with groups SA 125 and SMT 125 - DN25 with pumps DAB Evosta2 65/180	656008

The system contains:

1. Zone manifold C 60 2 F - DN 25,
2. Group SA 125 - DN 25 with pump (see table),
3. Group SMT 125 DN 25 with pump (see table),
4. Wall bracket kit DELTA for manifold,
5. Check valve to manifold C 60 - DN 25,
6. Actuator MP 10 - 230 / 140 with adapter A 101.

### System D2 System of 2 heating circuits including one with thermostatic mixing valve



Type	Catalog number
Set D2 with groups SA 125 and SMT 125 - DN25 with pumps Wilo Yonos Para 25/6	656017
Set D2 with groups SA 125 and SMT 125 - DN25 with pumps Grundfos UPM3S AUTO 25 - 60	656011
Set D2 with groups SA 125 and SMT 125 - DN25 with pumps DAB Evosta2 65/180	656018

The system contains:

1. Zone manifold C 60 2 F - DN 25,
2. Group SA 125 - DN 25 with pump(see table),
3. Group SMT1 125 - DN 25 with pump(see table),
4. Wall bracket kit DELTA for manifold,
5. Check valve to manifold C 60 - DN 25,

### System D3 System of 2 heating circuits with a mixing valves and a rotary electric actuators



Type	Catalog number
Set D3 with 2 groups SMT 125 - DN25 with pumps Wilo Yonos Para 25/6	656027
Set D3 with 2 groups SMT 125 - DN25 with pumps Grundfos UPM3S AUTO 25 - 60	656021
Set D3 with 2 groups SMT 125 - DN25 with pumps DAB Evosta2 65/180	656028

The system contains:

1. Zone manifold C 60 2 F - DN 25,
2. Two group SMT 125 DN 25 with pumps (see table),
3. Wall bracket kit DELTA for manifold,
4. Two check valves to manifold C 60 - DN 25,
5. Two actuators MP 10 - 230 / 140 with adapters A 101.

### System D4 System of 2 direct heating circuits without a mixing valves



Type	Catalog number
Set D4 with 2 groups SA 125 - DN25 with pumps Wilo Yonos Para 25/6	656037
Set D4 with 2 groups SA 125 - DN25 with pumps Grundfos UPM3S AUTO 25 - 60	656031
Set D4 with 2 groups SA 125 - DN25 with pumps DAB Evosta2 65/180	656038

The system contains:

1. Zone manifold C 60 2 F - DN 25,
2. Two groups SA 125 - DN 25 with pumps (see table),
3. Wall bracket kit DELTA for manifold.

### System D5 - System of 2 direct heating circuits with thermostatic mixing vavles




Type	Catalog number
Set D5 with 2 groups SMT1 125 - DN 25, with pumps Wilo Yonos Para 25/6	656047
Set D5 with 2 groups SMT1 125 - DN 25, with pumps Grundfos UPM3S AUTO 25 - 60	656041
Set D5 with 2 groups SMT1 125 - DN 25, with pumps DAB Evosta2 65/180	656048

The system contains:

1. Zone manifold C 60 2 F - DN 25,
2. Two groups SMT1 125 - DN 25 with pump(see table),
3. Wall bracket kit DELTA for manifold,
4. Check valve to manifold C 60 - DN 25.

System **DX1** System of 2 heating circuits including one with a mixing valve and a rotary electric actuator




Type	Catalog number
Set <b>DX1</b> with groups <b>SA 125</b> and <b>SMT 125 - DN25</b> with pumps <b>Wilco Yonos Para 25/6</b>	656107
Set <b>DX1</b> with groups <b>SA 125</b> and <b>SMT 125 - DN25</b> with pumps <b>Grundfos UPM3S AUTO 25 - 60</b>	656101
Set <b>DX1</b> with groups <b>SA 125</b> and <b>SMT 125 - DN25</b> with pumps <b>DAB Evosta2 65/180</b>	656108

The system contains:

1. Zone manifold **CX 100 2 F - DN 25**,
2. Group **SA 125 - DN 25** with pump (see table),
3. Group **SMT 125 DN 25** with pump (see table),
4. Wall bracket kit **DELTA** for manifold,
5. Check valve to manifold **CX 100 - DN 25**,
6. Actuator **MP 10 - 230 / 140** with adapter **A 101**.

System **DX2** System of 2 heating circuits including one with thermostatic mixing valve




Type	Catalog number
Set <b>DX2</b> with groups <b>SA 125</b> and <b>SMTC 125 - DN25</b> with pumps <b>Wilco Yonos Para 25/6</b>	656117
Set <b>DX2</b> with groups <b>SA 125</b> and <b>SMTC 125 - DN25</b> with pumps <b>Grundfos UPM3S AUTO 25 - 60</b>	656111
Set <b>DX2</b> with groups <b>SA 125</b> and <b>SMTC 125 - DN25</b> with pumps <b>DAB Evosta2 65/180</b>	656118

The system contains:

1. Zone manifold **CX 100 2 F - DN 25**,
2. Group **SA 125 - DN 25** with pump(see table),
3. Group **SMTC1 125 - DN 25** with pump(see table),
4. Wall bracket kit **DELTA** for manifold,
5. Check valve to manifold **CX 100 - DN 25**,

System **DX3** System of 2 heating circuits with a mixing valves and a rotary electric actuators




Type	Catalog number
Set <b>DX3</b> with 2 groups <b>SMT 125 - DN25</b> with pumps <b>Wilco Yonos Para 25/6</b>	656127
Set <b>DX3</b> with 2 groups <b>SMT 125 - DN25</b> with pumps <b>Grundfos UPM3S AUTO 25 - 60</b>	656121
Set <b>DX3</b> with 2 groups <b>SMT 125 - DN25</b> with pumps <b>DAB Evosta2 65/180</b>	656128

The system contains:

1. Zone manifold **CX 100 2 F - DN 25**,
2. Two group **SMT 125 DN 25** with pumps (see table),
3. Wall bracket kit **DELTA** for manifold,
4. Two check valves to manifold **CX 100 - DN 25**,
5. Two actuators **MP 10 - 230 / 140** with adapters **A 101**.

System **DX4** System of 2 direct heating circuits without a mixing valves




Type	Catalog number
Set <b>DX4</b> with 2 groups <b>SA 125 - DN25</b> with pumps <b>Wilco Yonos Para 25/6</b>	656137
Set <b>DX4</b> with 2 groups <b>SA 125 - DN25</b> with pumps <b>Grundfos UPM3S AUTO 25 - 60</b>	656131
Set <b>DX4</b> with 2 groups <b>SA 125 - DN25</b> with pumps <b>DAB Evosta2 65/180</b>	656138

The system contains:

1. Zone manifold **CX 100 2 F - DN 25**,
2. Two groups **SA 125 - DN 25** with pumps (see table),
3. Wall bracket kit **DELTA** for manifold.

System **DX5** - System of 2 direct heating circuits with thermostatic mixing vavles



Type	Catalog number
Set <b>DX5</b> with 2 groups <b>SMTC1 125 - DN 25</b> , with pumps <b>Wilco Yonos Para 25/6</b>	656147
Set <b>DX5</b> with 2 groups <b>SMTC1 125 - DN 25</b> , with pumps <b>Grundfos UPM3S AUTO 25 - 60</b>	656141
Set <b>DX5</b> with 2 groups <b>SMTC1 125 - DN 25</b> , with pumps <b>DAB Evosta2 65/180</b>	656148

The system contains:

1. Zone manifold **CX 100 2 F - DN 25**,
2. Two groups **SMTC1 125 - DN 25** with pump(see table),
3. Wall bracket kit **DELTA** for manifold,
4. Check valve to manifold **CX 100 - DN 25**.


## Manifold with built-in hydraulic separator for 2 or 3 heating circuits **CX 100**



Manifold with built-in hydraulic separator, equipped with a air vent and a immersion sleeve for connecting a temperature sensor.

Type	Catalog number
Zone manifold with built-in hydraulic separator <b>CX 100 2F - DN 25</b>	636011
Zone manifold with built-in hydraulic separator <b>CX 100 3F - DN 25</b>	636012

## Set W



The W set is a complete system for separating heating circuits in an installation with a solid fuel boiler. It can handle two heating circuits. The heating circuits can be pump or pump-mixing with a rotary mixing valve. The pump groups are equipped with a **Wilco**, **DAB** or **Grundfos** pump. The entire system is insulated.

Available with pumps:



Wilo Yonos Para




DAB Evosta2



Grundfos UPM3

Type	Catalog number
Set W without pumps	656050
Set W with pumps <b>Wilo Yonos Para 25/6</b>	656054
Set W with pumps <b>Grundfos UPM3S AUTO 25-60</b>	656052
Set W with pumps <b>DAB Evosta2 65/180</b>	656056

## Pump group **SMR4 125 - DN 25 (1")**




Compact mixing group - **SMR4 125 - DN 25** is equipped with a 4 way mixing valve **MIX M 4-25 (kv12)**, two brass ball valves with thermometers flow and return (with built-in check valve) connector steel and insulation. On request, the group can be equipped with a pump company **Wilo**, **DAB** or **Grundfos**. In addition, to ensure automatic operation of the mixing valve should be equipped with an actuator **MP 10 - 10Nm**.


**WARNING!** Group is supplied with the supply to the left side. Sides can be switched.

Type	Catalog number
Group <b>SMR4 125 - DN 25 (1")</b> with 4-way mixing valve, without pump	606401
Group <b>SMR4 125 - DN 25 (1")</b> with 4-way mixing valve, with pump <b>Wilo Yonos Para 25/6</b>	616404
Group <b>SMR4 125 - DN 25 (1")</b> with 4-way mixing valve, with pump <b>Wilo Yonos Para 25/8</b>	616405
Group <b>SMR4 125 - DN 25 (1")</b> with 4-way mixing valve, with pump <b>Grundfos UPM3S AUTO 25-60</b>	616401
Group <b>SMR4 125 - DN 25 (1")</b> with 4-way mixing valve, with pump <b>DAB Evosta2 65/180</b>	616403

## Boiler room building system up to 35 kW




## Hydraulic separator CPN 60 - DN 20 (3/4")



Hydraulic separator **CPN 60 - DN 20** is made of steel. The factory is equipped with insulation, the upper side with two connections for the temperature sensor and a vent and the lower side of the drain connection. In the set they are automatic air vent with check valve, immersion sleeve for temperature sensor and drain valve.

Type	Catalog number
Hydraulic separator <b>CPN 60</b> with equipment	605002
Insulated tubing kit <b>TBN 60/2</b> for connection <b>CPN 60 - DN 20</b> with <b>C 60 - DN 20</b>	605005
Insulated tubing kit <b>TBN 60/3</b> for connection <b>CPN 60 - DN 20</b> with <b>C 60 - DN 20</b>	605006
Insulated tubing kit <b>TBN 60/4</b> for connection <b>CPN 60 - DN 20</b> with <b>C 60 - DN 20</b>	605007


## Central heating zone manifold C 60 - DN 20



Two-chamber steel manifold **C 60, 2, 3 or 4 zones DN 20** was created to facilitate the assembly of mixing groups. The factory manifold is equipped with EPP insulation. In addition has a **DN 25** output on the supply side for connecting the safety group. On request, the manifold can be equipped with a set of mounting brackets on the wall **DELTA** (see bushings M8).

Type	Catalog number
Central heating zone manifold <b>C 60 2 F - DN 20</b> with insulation	605011
Central heating zone manifold <b>C 60 3 F - DN 20</b> with insulation	605012
Central heating zone manifold <b>C 60 4 F - DN 20</b> with insulation	605013
Wall bracket kit <b>DELTA</b> for zone manifolds	606015

## Additional equipment for groups DN 20




Type	Catalog number
Wall bracket kit <b>Delta</b> for zone manifolds	606015
Actuator <b>MP 10</b>	401011
Safety group 1" <b>UNI X - MINI</b> with safety valve 3 bar (1/2"x3/4"), automatic vent, manometer 0 - 4 bar with insulation	606021
Connect tube <b>L 90 MINI</b> for connection safety group <b>UNI X MINI (73,6 kW)</b> with manifold <b>C 60, C 70, CN 70, CN 100</b>	606025
Check valve for manifold <b>Womix DN 20</b> - recommended when using each group with mixing valve.	606030

### Pump group SA 90 - DN 20 (3/4")



Compact pump group SA 90 - DN 20 is equipped with three brass ball valves, two of them with supply and return water thermometers, connector with non-return valve and insulation. On request, the group can be equipped with a Wilo, Grundfos or DAB pump.

### Pump group SMT 90 - DN 20 (3/4")



The compact mixing and pump group SMT 90 - DN 20 is equipped with a brass three-way mixing valve, two brass ball valves with supply and return water thermometers, a connector with non-return valve and insulation. On request, the group can be equipped with a Wilo, Grundfos or DAB pump. Additionally, to ensure automatic operation of the mixing valve, the group should be equipped with an MP 10 - 10 Nm actuator.

### Pump group SMTC 90 - DN 20 (3/4")



Compact mixing and pump group SMTC 90 - DN 20 is equipped with thermostatic brass three-way mixing valve with temperature range 20 °C-45 °C, two brass ball valves with supply and return water thermometers, connector with non-return valve and insulation. On request, the group can be equipped with a Wilo, Grundfos or DAB pump.


Type	Catalog number
Pump group SA 90 - DN 20 (3/4") with insulation, without pump	605051
Pump group SA 90 - DN 20 (3/4") with insulation, with pump Wilo Yonos Para 15/6	605056
Pump group SA 90 - DN 20 (3/4") with insulation, with pump Grundfos UPM3S AUTO 15 - 60	605057
Pump group SA 90 - DN 20 (3/4") with insulation, with pump DAB Evosta2 65/130	605058

Type	Catalog number
Pump group SMT 90 - DN 20 (3/4") with insulation, without pump	605081
Pump group SMT 90 - DN 20 (3/4") with insulation, with pump Wilo Yonos Para 15/6	605086
Pump group SMT 90 - DN 20 (3/4") with insulation, with pump Grundfos UPM3S AUTO 15 - 60	605087
Pump group SMT 90 - DN 20 (3/4") with insulation, with pump DAB Evosta2 65/130	605088

Type	Catalog number
Pump group SMTC 90 - DN 20 (3/4") with insulation, without pump	605071
Pump group SMTC 90 - DN 20 (3/4") with insulation, with pump Wilo Yonos Para 15/6	605076
Pump group SMTC 90 - DN 20 (3/4") with insulation, with pump Grundfos UPM3S AUTO 15 - 60	605077
Pump group SMTC 90 - DN 20 (3/4") with insulation, with pump DAB Evosta2 65/130	605078

# Boiler room building system up to 40 kW

Pump groups DN 25  
equipped with pumps  
Wilo, DAB or Grundfos



## Hydraulic separator CPN MINI - DN 25 (1")

### Equipment:



40 kW

2,5 m³/h

Hydraulic separator **CPN MINI - DN 25** is made of steel. The factory is equipped with insulation and connection for a temperature sensor. In the set is a immersion sleeve for temperature sensor.

Type	Catalog number
Hydraulic separator <b>CPN MINI - DN 25</b> with insulation	606211

## Central heating zone manifold CN 70 - DN 25



Two-chamber zone manifold **CN 70 - DN 25** was created to facilitate the assembly of pump groups. The factory manifold is equipped with EPP insulation. In addition, the manifold has a DN 25 output on the supply side for connecting the safety group. On request, the zone manifold can be equipped with a set of mounting brackets on the wall L.

**WARNING! Pump groups directed downwards must have a supply side on the left (unlike the standard).**

Type	Catalog number
Central heating zone manifold <b>CN 70 2/3 F - DN 25</b> with insulation	606221
Central heating zone manifold <b>CN 70 3/5 F - DN 25</b> with insulation	606222
Wall bracket kit <b>L</b> for zone manifolds <b>CN 70</b>	605015
Check valve for pump group with mixing valve for manifolds <b>C 60, C70, CN 70, C 100, CN 100 - DN 25</b>	606031




## **Boiler room building system up to 45 kW or 55 kW**

**Pump groups DN 25  
equipped with pumps  
Wilo, DAB or Grundfos**

**Zone manifold  
C 60 - DN 25 - up to 45 kW  
or  
C 70 - DN 25 - up to 55 kW**

**Safety group  
UNI X MINI 3 bar**



**Connect L 90 MINI  
for safety group**


**Wall bracket kit  
DELTA**

**Insulated tubing kit TBN 70  
for connection C 60 / C 70 - DN 25  
with hydraulic separator CPN 70**

**Hydraulic separator  
CPN 70 - DN 25**

## Hydraulic separator CPN 70 - DN 25

### Equipment:



55 kW

2,5 m³/h

TBN 70  
(optional)



Hydraulic separator **CPN 70** is made of steel. The factory is equipped with insulation, the upper side with two connections for the temperature sensor and a vent, and the lower side of the drain connection. In the set they are automatic air vent with check valve, immersion sleeve for temperature sensor, drain valve, four cast-iron fittings 1" and wall brackets.

Type	Catalog number
Hydraulic separator <b>CPN 70 - DN 25</b> with equipment	606002
Insulated tubing kit <b>TBN 70/2 - DN 25</b> for connection <b>C 60/70 2F - DN 25</b> with <b>CPN 70 - DN 25</b>	606005
Insulated tubing kit <b>TBN 70/3 - DN 25</b> for connection <b>C 60/70 3F - DN 25</b> with <b>CPN 70 - DN 25</b>	606006
Insulated tubing kit <b>TBN 70/4 - DN 25</b> for connection <b>C 60/70 4F - DN 25</b> with <b>CPN 70 - DN 25</b>	606007

Hydraulic separator **CPN 70 - DN 25** is dedicated to pump group systems. For use outside the system, we recommend the **XP** and **XPN** series of separators

see p. 56,57

## Central heating zone manifold C 60 - DN 25



45 kW

Two-chamber steel manifold **C 60 DN 25** - 2, 3 or 4 heating circuits was created to simplify installation of pump groups. The factory manifold is equipped with EPP insulation. In addition, the manifold has an output DN 20 on the return side for connecting pressure vessel and the output DN 25 on the power supply for connecting the safety group. On request, the manifold can be equipped with a set of mounting brackets on the wall **DELTA** (see bushings M8).

Type	Catalog number
Central heating zone manifold <b>C 60 2F - DN 25</b> with insulation	616011
Central heating zone manifold <b>C 60 3F - DN 25</b> with insulation	616012
Central heating zone manifold <b>C 60 4F - DN 25</b> with insulation	616013
Wall bracket kit <b>DELTA</b> for zone manifolds	606015
Check valve for pump group with mixing valve for manifolds <b>C 60, C 70, CN 70, C 100, CN 100 - DN 25</b>	606031

## Central heating zone manifold C70 - DN 25




55 kW

Two-chamber steel manifold **C 70 DN 25** - 2, 3, 4 or 5 heating circuits was created to simplify installation of pump groups. The factory manifold is equipped with EPP insulation. In addition, the manifold has an output DN 20 on the return side for connecting pressure vessel and the output DN 25 on the power supply for connecting the safety group. On request, the manifold can be equipped with a set of mounting brackets on the wall **DELTA** (see bushings M8).


Type	Catalog number
Central heating zone manifold <b>C 70 2F - DN 25</b> with insulation	606011
Central heating zone manifold <b>C 70 3F - DN 25</b> with insulation	606012
Central heating zone manifold <b>C 70 4F - DN 25</b> with insulation	606013
Central heating zone manifold <b>C 70 5F - DN 25</b> with insulation	606014
Wall bracket kit <b>DELTA</b> for zone manifolds	606015
Check valve for pump group with mixing valve for manifolds <b>C 60, C 70, CN 70, C 100, CN 100 - DN 25</b>	606031

# Boiler room building system up to 73 kW

Pump groups DN 25  
equipped with pumps  
Wilo, DAB or Grundfos



## Hydraulic separator CPN 100 - DN 32



Hydraulic separator CPN 100 DN 32 is made of steel. The factory is equipped with insulation, and the upper side with two connections for the temperature sensor and a vent, and the lower side of the drain connection. In the set they are automatic air vent with check valve, immersion sleeve for temperature sensor, four cast-iron fittings 1 1/4" and wall brackets.

Type	Catalog number
Hydraulic separator CPN 100 - DN 32 with equipment	607001
Connect tube TBCN 100 - DN 32 with insulation for connection CPN 100 - DN 32 with CN 100 - DN	617004


## Central heating zone manifold CN 100 - DN 25




Two-chamber zone manifold CN 100 - DN25 was created to simplify installation of pump groups. The factory manifold is equipped with EPP insulation. In addition, the manifold has a DN 25 output on the supply side for connecting the safety group. On request, the manifold can be equipped with a set of mounting brackets on the DELTA wall.

Type	Catalog number
Hydraulic zone manifold CN 100 2/3 F - DN 25 with insulation	626111
Hydraulic zone manifold CN 100 3/5 F - DN 25 with insulation	626112
Hydraulic zone manifold CN 100 4/7 F - DN 25 with insulation	626113
Wall bracket kit DELTA for zone manifolds	606015
Check valve for pump group with mixing valve for manifolds C 60, C 70, CN 70, C 100, CN 100 - DN 25	606031

## Boiler room building system up to 80 kW




## Boiler room building system up to 110 kW



**WARNING!** Brackets are used instead of DELTA brackets for the C 100 6F manifold (cod.607030)

## Hydraulic separator CPN 100 - DN 32 (1 1/4")



80 kW

4,5 m³/h


**TBN 101**  
(optional)



Hydraulic separator **CPN 100 DN 32** is made of steel. The factory is equipped with insulation, and the upper side with two connections for the temperature sensor and a vent, and the lower side of the drain connection. In the set they are automatic air vent with check valve, immersion sleeve for temperature sensor, four cast-iron fittings 1 1/4" and wall brackets.

Type	Catalog number
Hydraulic separator <b>CPN 100 - DN 32</b> with equipment	607001
Insulated tubing kit <b>TBN 101 / 2</b> for connection <b>CPN 100 - DN 32</b> with <b>C 100 2F - DN 25</b>	617005
Insulated tubing kit <b>TBN 101 / 3</b> for connection <b>CPN 100 - DN 32</b> with <b>C 100 3F - DN 25</b>	617006
Insulated tubing kit <b>TBN 101 / 4</b> for connection <b>CPN 100 - DN 32</b> with <b>C 100 4F - DN 25</b>	617007
Insulated tubing kit <b>TBN 101 / 5</b> for connection <b>CPN 100 - DN 32</b> with <b>C 100 5F - DN 25</b>	617008
Insulated tubing kit <b>TBN 101 / 6</b> for connection <b>CPN 100 - DN 32</b> with <b>C 100 6F - DN 25</b>	617009

## Hydraulic separator CPN 100 - DN 40 (1 1/2")



120 kW

6,5 m³/h

**TBN 100**  
(optional)



Hydraulic separator **CPN 100 DN 40** is made of steel. The factory is equipped with insulation, and the upper side with two connections for the temperature sensor and a vent, and the lower side of the drain connection. In the set they are automatic air vent with check valve, immersion sleeve for temperature sensor, four cast-iron fittings 1 1/2" and mounting feet.

Type	Catalog number
Hydraulic separator <b>CPN 100 - DN 40</b> with equipment	607002
Insulated tubing kit <b>TBN 100/2 - DN 32</b> for connection <b>CPN 100 - DN 40</b> with <b>C 100 2F - DN 25</b>	607005
Insulated tubing kit <b>TBN 100/3 - DN 32</b> for connection <b>CPN 100 - DN 40</b> with <b>C 100 3F - DN 25</b>	607006
Insulated tubing kit <b>TBN 100/4 - DN 32</b> for connection <b>CPN 100 - DN 40</b> with <b>C 100 4F - DN 25</b>	607007
Insulated tubing kit <b>TBN 100/5 - DN 32</b> for connection <b>CPN 100 - DN 40</b> with <b>C 100 5F - DN 25</b>	607008
Insulated tubing kit <b>TBN 100/6 - DN 32</b> for connection <b>CPN 100 - DN 40</b> with <b>C 100 6F - DN 25</b>	607009

## Central heating zone manifold C 100 - DN 25 (1")



Two-chamber steel manifold **C 100 DN 25 - 2, 3, 4, 5** or **6** heating circuits was created to simplify installation of pump groups. The factory manifold is equipped with EPP insulation. In addition, the manifold has an output DN 20 on the return side for connecting pressure vessel and the output DN 25 on the power supply for connecting the safety group. On request, the manifold can be equipped with a set of mounting brackets on the wall **DELTA** (see bushings M8).

**Warning!** The exception is the manifold **C 100 6F**. The above-mentioned manifold can be equipped with a set of mounting brackets on the floor (cod.607030).

Type	Catalog number
Central heating zone manifold <b>C 100 2F - DN 25</b> with insulation	626011
Central heating zone manifold <b>C 100 3F - DN 25</b> with insulation	626012
Central heating zone manifold <b>C 100 4F - DN 25</b> with insulation	626013
Central heating zone manifold <b>C 100 5F - DN 25</b> with insulation	626014
Central heating zone manifold <b>C 100 6F - DN 25</b> with insulation	626015
Brackets for mounting manifold <b>C 100 6F - DN 25/DN 32</b> on the floor (1set. = 2 pcs)	607030
Wall bracket kit <b>DELTA</b> for zone manifolds	606015
Check valve for pump group with mixing valve for manifolds <b>C 60, C 70, CN 70, C 100, CN 100 - DN 25</b>	606031

**Pump group  
SA 125 - DN 25 (1")  
- without mixing valve**



Compact pump group SA 125 - DN 25 is equipped with three brass ball valves including two with thermometers on supply and return (with built-in check valve) steel connector and insulation. On request, the group can be equipped with a pump **Wilo, DAB** or **Grundfos**.

**WARNING!** Group comes from the supply side to the right. Sides can be switched.

**Pump group  
SMT 125 - DN 25 (1")  
- with rotary mixing valve**



Compact mixing group SMT 125 - DN 25 is equipped with a brass three-way mixing valve **MIX MT 25**, two brass ball valves with thermometers supply and return (with built-in check valve) steel connector and insulation. On requests group can be equipped with a pump **Wilo, DAB** or **Grundfos**. Additionally to ensure automatic operation of the mixing valve must be equipped with an actuator **MP 10 - 10 Nm**.

**WARNING!** Group comes from the supply side to the right. Sides can be switched.

**Pump group  
SMTC 125 - DN 25 (1")  
- with thermostatic mixing valve**



Compact thermostatic mixing group SMTC 125 - DN 25 is equipped with a thermostatic mixing valve brass three-way **MIX THERM** (kv 3,4) for regulating the temperature of 20 - 45 °C or 35-60°C (depending on the model of the group), two thermometers supply and return (with built-in check valve) steel connector and insulation. On request, the group can be equipped with a pump **Wilo, DAB** or **Grundfos**.


**WARNING!** Group comes from the supply side to the right. Sides can be switched.

Type	Catalog number
Pump group SA 125 - DN 25 with insulation, without pump	606051
Pump group SA 125 - DN 25 with insulation, with pump <b>Wilo Yonos Para 25/6</b>	616054
Pump group SA 125 - DN 25 with insulation, with pump <b>Wilo Yonos Para 25/8</b>	616055
Pump group SA 125 - DN 25 with insulation, with pump <b>Grundfos UPM3S AUTO 25-60</b>	616056
Pump group SA 125 - DN 25 with insulation, with pump <b>DAB Evosta2 65/180</b>	616057


Type	Catalog number
Pump group SMT 125 - DN 25 with insulation, without pump	606081
Pump group SMT 125 - DN 25 with insulation, with pump <b>Wilo Yonos Para 25/6</b>	616084
Pump group SMT 125 - DN 25 with insulation, with pump <b>Wilo Yonos Para 25/8</b>	616085
Pump group SMT 125 - DN 25 with insulation, with pump <b>Grundfos UPM3S AUTO 25-60</b>	616086
Pump group SMT 125 - DN 25 with insulation, with pump <b>DAB Evosta2 65/180</b>	616087

Type	Catalog number SMTC1 20-45°C	Catalog number SMTC2 35-60°C
Pump group SMTC 125 - DN 25 with insulation, without pump	606071	606091
Pump group SMTC 125 - DN 25 with insulation, with pump <b>Wilo Yonos Para 25/6</b>	616074	616094
Pump group SMTC 125 - DN 25 with insulation, with pump <b>Wilo Yonos Para 25/8</b>	616075	616095
Pump group SMTC 125 - DN 25 with insulation, with pump <b>Grundfos UPM3S AUTO 25-60</b>	616076	616096
Pump group SMTC 125 - DN 25 with insulation, with pump <b>DAB Evosta2 65/180</b>	616077	616097

## Boiler room building system up to 80 kW




## Boiler room building system up to 120 kW



WARNING! Brackets are used instead of DELTA brackets for the C 100 6F manifold (cod. 607030)


## Hydraulic separator CPN 100 - DN 32 (1 1/4")



Hydraulic separator CPN 100 DN 32 is made of steel. The factory is equipped with insulation, and the upper side with two connections for the temperature sensor and a vent, and the lower side of the drain connection. In the set they are automatic air vent with check valve, immersion sleeve for temperature sensor, four cast-iron fittings 1 1/4" and wall brackets.

Type	Catalog number
Hydraulic separator CPN 100 - DN 32 with equipment	607001
Insulated tubing kit TBN 101 / 2 for connection CPN 100 - DN 32 with C 100 2F - DN 32	617005
Insulated tubing kit TBN 101 / 3 for connection CPN 100 - DN 32 with C 100 3F - DN 32	617006
Insulated tubing kit TBN 101 / 4 for connection CPN 100 - DN 32 with C 100 4F - DN 32	617007
Insulated tubing kit TBN 101 / 5 for connection CPN 100 - DN 32 with C 100 5F - DN 32	617008
Insulated tubing kit TBN 101 / 6 for connection CPN 100 - DN 32 with C 100 6F - DN 32	617009

## Hydraulic separator CPN 100 - DN 40 (1 1/2")



Hydraulic separator CPN 100 DN 40 is made of steel. The factory is equipped with insulation, and the upper side with two connections for the temperature sensor and a vent, and the lower side of the drain connection. In the set they are automatic air vent with check valve, immersion sleeve for temperature sensor, four cast-iron fittings 1 1/2" and mounting feet.

Type	Catalog number
Hydraulic separator CPN 100 - DN 40 with equipment	607002
Insulated tubing kit TBN 100/2 - DN 32 for connection CPN 100 - DN 40 with C 100 2F - DN 32	607005
Insulated tubing kit TBN 100/3 - DN 32 for connection CPN 100 - DN 40 with C 100 3F - DN 32	607006
Insulated tubing kit TBN 100/4 - DN 32 for connection CPN 100 - DN 40 with C 100 4F - DN 32	607007
Insulated tubing kit TBN 100/5 - DN 32 for connection CPN 100 - DN 40 with C 100 5F - DN 32	607008
Insulated tubing kit TBN 100/6 - DN 32 for connection CPN 100 - DN 40 with C 100 6F - DN 32	607009

## Central heating zone manifold C 100 - DN 32




Two-chamber steel manifold C 100 DN 32 - 2, 3, 4, 5 or 6 heating circuits was created to simplify installation of pump groups DN 32. The factory manifold is equipped with EPP insulation. In addition, the manifold has an output DN 20 on the boiler side for connecting pressure vessel and the output DN 25 on the installation side for connecting the safety group. On request, the manifold can be equipped with a set of mounting brackets on the wall DELTA (see bushings M8).

**Warning!** In order to connect the DN 32 group to the manifold it is necessary to buy additional connections DN 1 1/4" x 2" or connections with integrated ball valve (see below).

**Warning!** The exception is the manifold C 100 6F. The above-mentioned manifold can be equipped with a set of mounting brackets on the floor (cod.607030).

Type	Catalog number
Central heating zone manifold C 100 2F - DN 32 with insulation	607011
Central heating zone manifold C 100 3F - DN 32 with insulation	607012
Central heating zone manifold C 100 4F - DN 32 with insulation	607013
Central heating zone manifold C 100 5F - DN 32 with insulation	607014
Central heating zone manifold C 100 6F - DN 32 with insulation	607015
Brackets for mounting manifold C 100 6F - DN 25/DN 32 on the floor (1 set. = 2 pcs)	607030
Wall bracket kit DELTA for zone manifolds	606015
Reduction for mounting groups DN 25 on manifold C 100 DN 32, C2 100 - DN 32 - set = 2 pcs.	607023
Connection DN 1 1/4" x 2" with brass nut - 1 pc	607016
Connection DN 1 1/4" x 2" with built-in ball valve, with brass nut - 1 pc	607017
Connection DN 1 1/4" x 2" with brass nut, with check valve for groups SMT, SMTC - 1 pc	607018

# Boiler room building system up to 220 kW



## Central heating zone manifold C 2 100 - DN 32




Two-chamber steel manifold **C2 100 DN 32** - 2, 3, 4, 5 or 6 heating circuits was created to simplify installation of pump groups. The factory manifold is equipped with EPP insulation. Additional manifold is equipped with two thermometers and two the socket 1/2" F drain.

**Warning!** In order to connect the DN 32 group to the manifold it is necessary to buy additional connections DN 1 1/4" x 2" or connections with integrated ball valve (see below).

Type	Catalog number
Central heating zone manifold <b>C2 100 2F - DN 32</b> with insulation	607041
Central heating zone manifold <b>C2 100 3F - DN 32</b> with insulation	607042
Central heating zone manifold <b>C2 100 4F - DN 32</b> with insulation	607043
Central heating zone manifold <b>C2 100 5F - DN 32</b> with insulation	607044
Central heating zone manifold <b>C2 100 6F - DN 32</b> with insulation	607045
Brackets for mounting manifold on the floor (1 set = 2 pcs )	607040
Reduction mounting groups <b>DN 25</b> on manifold <b>C 100 DN 32, C2 100 - DN 32</b> - set - 2 pcs.	607023
Connection <b>DN 1 1/4" x 2"</b> with brass nut	607016
Connection with built-in ball valve <b>DN 1 1/4" x 2"</b> with brass nut	607017
Connection <b>DN 1 1/4" x 2"</b> with brass nut , with check valve for groups <b>SMT</b>	607018

## Hydraulic separator CPN 120 - DN 50 (2")

### Equipment:



220 kW

9,5 m³/h

**TBN 120 - DN 50**  
(optional)



Hydraulic separator **CPN 120** is made of steel. The factory is equipped with insulation, and the upper side with two connections for the temperature sensor and a vent, and the lower side of the drain connection. In the set they are automatic air vent with check valve, immersion sleeve for temperature sensor, four cast-iron fittings 2" and mounting feet.

Type	Catalog number
Hydraulic separator <b>CPN 120 - DN 50</b> with equipment	609001
Connect tube <b>TBN 120 - DN 50</b> for connection <b>C2 100 - DN 32</b> with <b>CPN 120 - DN 50</b>	609005

## Additional equipment for pump groups systems DN 25/DN 32

Wall bracket kit  
**Delta**



Check valve for  
zone manifold **DN 25**



Reduction mounting  
groups **DN 25**  
on manifold **C 100 DN 32** or  
**C2 100 - DN 32**



Connect tube  
**L 90 MINI/MAGNUM**



Actuator **MP**



Safety group  
**UNI X - MINI (73,6 kW)**



Safety group  
**UNI X - MAGNUM (200 kW)**



Brackets for mounting manifold  
**C 100 6F - DN 25** on the floor



Connect tube **S**



Type	Catalog number
Wall bracket kit <b>DELTA</b> for zone manifolds	606015
Actuator <b>MP 10</b>	401011
Safety group 1" <b>UNI X - MINI (73,6 kW)</b> with safety valve. 3 bar (1/2"x3/4"), automatic vent, manometer 0 - 4 bar, with insulation EPP.	606021
Safety group 1" <b>UNI X - MAGNUM (200 kW)</b> with safety valve. 3 bar (1"x1 1/4"), automatic vent, manometer 0 - 4 bar, with insulation EPP.	606022
Connect tube <b>L90</b> for connection group <b>UNI X - MINI (73,6 kW)</b> with manifold <b>C 60, C 70, CN 70, CN 100 - DN 25</b>	606025
Connect tube <b>L90</b> for connection group <b>UNI X - MAGNUM (200 kW)</b> with manifold <b>C 100, C2 100</b>	606027
Connect tube <b>S</b> for connection vessel with manifold <b>C 60, 70 - DN - 25</b>	606026
Check valve for pump group with mixing valve for manifolds <b>C 60, C 70, CN 70, C 100, CN 100 - DN 25</b>	606031
Brackets for mounting manifold <b>C 100 6F - DN 25/DN 32</b> on the floor (1set. = 2 pcs)	607030
Brackets for mounting manifold <b>C 2 100 - DN 32</b> and <b>C 100 6F 32</b> on the floor (1set. = 2 pcs)	607040
Reduction mounting groups <b>DN 25</b> on manifold <b>C 100 DN 32, C2 100 - DN 32 - set - 2 pcs.</b>	607023
Connection <b>DN 1 1/4" x 2"</b> with brass nut	607016
Connection <b>DN 1 1/4" x 2"</b> with built-in ball valve, with brass nut.	607017
Connection <b>DN 1 1/4" x 2"</b> with brass nut, with check valve for mixing group <b>SMT</b>	607018


**Pump group  
SA 125 - DN 32 (1 1/4")  
- without mixing valve**



Compact pump group **SA 125 - DN 32** is equipped with three brass ball valves including two with thermometers supply and return (with built-in check valve) steel connector and insulation. On request, the group can be equipped with a pump **Grundfos** or **Wilo**.

**WARNING!** Group comes from the supply side to the right. Sides can be switched.

**Pump group  
SMT 125 - DN 32 (1 1/4")  
- with rotary mixing valve**



Compact mixing group **SMT 125 - DN 32** is equipped with a brass three-way mixing valve **MIX MT 32**, two brass ball valves with thermometers supply and return (with built-in check valve) steel connector and insulation. On requests group can be equipped with a pump **Grundfos** or **Wilo**. Additionally to ensure automatic operation of the mixing valve must be equipped with an actuator **MP 10 - 10 Nm**.


**WARNING!** Group comes from the supply side to the right. Sides can be switched.

Type	Catalog number
Pump group <b>SA 125 - DN 32 (1 1/4")</b> with insulation, without pump	607051
Pump group <b>SA 125 - DN 32 (1 1/4")</b> with insulation, with pump <b>Wilo Yonos Para 30/6</b>	607158
Pump group <b>SA 125 - DN 32 (1 1/4")</b> with insulation, with pump <b>Wilo Yonos Para 30/8</b>	607159
Pump group <b>SA 125 - DN 32 (1 1/4")</b> with insulation, with pump <b>Grundfos Alpha 1 L 32-60</b>	607055

Type	Catalog number
Pump group <b>SMT 125 - DN 32 (1 1/4")</b> with insulation, without pump	607061
Pump group <b>SMT 125 - DN 32 (1 1/4")</b> with insulation, with pump <b>Wilo Yonos Para 30/6</b>	607066
Pump group <b>SMT 125 - DN 32 (1 1/4")</b> with insulation, with pump <b>Wilo Yonos Para 30/8</b>	607067
Pump group <b>SMT 125 - DN 32 (1 1/4")</b> with insulation, with pump <b>Grundfos Alpha 1 L 32-60</b>	607065

## Hydraulic separator CPN 120 - DN 65 (2 1/2")

### Equipment:



350 kW

18 m<sup>3</sup>/h

TBN 120 - DN 65  
(optional)




Hydraulic separator **CPN 120 – DN 65** is made of steel. The factory is equipped with insulation, the upper side have two connections for the temperature sensor and a vent, and the lower side of the drain connection. In the set they are automatic air vent with check valve, immersion sleeve for temperature sensor, four cast-iron fittings 2 1/2" and mounting feet.

### Technical data:

Max pressure:	8 bar
Flow rate:	18 m <sup>3</sup> /h
Max temp.:	110°C
Insulation material:	EPP black 40 g/l
Connections:	2 1/2"

Type	Catalog number
Hydraulic separator <b>CPN 120 - DN 65</b> with equipment	609002
Connect tube <b>TBN 120 - DN 65</b> for connection <b>CPN 120 - DN 65</b> with <b>C 2 120 - DN 50</b>	609006

## Central heating zone manifold C 2 120 - DN 50



Two-chamber steel manifold **C2 120 DN 50** – 2 or 3 heating circuits was created to simplify installation of pump groups DN 25, DN 32, DN 40, DN 50. The factory manifold is equipped with EPP insulation. Additional manifold is equipped with two thermometers and two the socket 1/2" F drain.

### Technical data:



Max pressure:	6 bar
Max temp.:	110°C
Max. power:	350 kW ( $\Delta T 20^{\circ}C$ )
Axle spacing:	Installation side: 250 mm
Connections:	Installation side: 2" M
	Boiler side: 2 1/2"
Insulation material:	EPP black 40 g/l

Type	Catalog number
Central heating zone manifold <b>C 2 120 2 F - DN 50</b> with insulation	609011
Central heating zone manifold <b>C 2 120 3 F - DN 50</b> with insulation	609012
Brackets for mounting manifold on the floor (1 set = 2 pcs)	607040




Send us a boiler room project or development guidelines, and we will prepare for you quote with visualization.

Connector spacer application proposal (page 53) in the case of using a Y-strainer



Can be mounted directly hydraulic separator with a zone manifold

Frame assembly RK



### Boiler connections DN 32, DN 40



Schematic drawing of the boiler connection to the cascade distributor

Boiler connections DN 32, DN 40 have been designed to facilitate the connection of the boiler with a Womix cascade manifold. They have 1 1/4" or 1 1/2" male thread outputs (depending on the model) and a cast iron nut on the boiler side. Additionally, one of the connections has a 1/2" socket for connecting the drain valve (included).

Type	Catalog number
<b>MK-T</b> under-boiler assembly kit - DN 32 (price per set)	610830
<b>MK-T</b> under-boiler assembly kit - DN 40 (price per set)	610840

### Cascade manifold MK 65, MK 80, MK 100, MK 125



Two-chamber steel cascade manifolds MK 65, MK 80, MK 100, MK 125 are designed to connect two or more heat sources. They are factory-equipped with EPP insulation. After sending the request, the manifold is adjusted to the designed boiler (any size of the spacing and connections from the boiler side is possible)

Type	Power at $\Delta T 20^{\circ}\text{C}$	Flow [m <sup>3</sup> /h]	Catalog number
Cascade manifold <b>MK 65 2 F - DN 50</b> two-circuit module with insulation	120,00	6,00	610102
Cascade manifold <b>MK 65 3 F - DN 50</b> three-circuit module with insulation	120,00	6,00	610103
Cascade manifold <b>MK 65 2 F - DN 65</b> two-circuit module with insulation	210,00	9,00	610202
Cascade manifold <b>MK 65 3 F - DN 65</b> three-circuit module with insulation	210,00	9,00	610203
Cascade manifold <b>MK 80 2 F - DN 80</b> two-circuit module with insulation	280,00	12,00	610302
Cascade manifold <b>MK 80 3 F - DN 80</b> three-circuit module with insulation	280,00	12,00	610303
Cascade manifold <b>MK 100 2 F - DN 100</b> two-circuit module with insulation	470,00	20,00	610402
Cascade manifold <b>MK 100 3 F - DN 100</b> three-circuit module with insulation	470,00	20,00	610403
Cascade manifold <b>MK 125 2 F - DN 125</b> two-circuit module with insulation	700,00	30,00	610502
Cascade manifold <b>MK 125 3 F - DN 125</b> three-circuit module with insulation	700,00	30,00	610503
Brackets for mounting manifold on the floor (1set. = 2 pcs)			607040
Brackets for mounting cascade manifold on the floor (1set. = 2 pcs) - low assembly			607050

## S connector for connecting a cascade zone manifolds with hydraulic separator



The connectors are made of steel. They are designed to reduce the installation height of the cascade manifold. The set includes one connector and a set of 4 assembly screws with a gasket.

Type	Catalog number
Connector S - DN 50 for connecting a cascade manifold with hydraulic separator CPN 150 - DN 50	699040
Connector S - DN 65 for connecting a cascade manifold with hydraulic separator CPN 250 - DN 65	699041
Connector S - DN 80 for connecting a cascade manifold with hydraulic separator CPN 250 - DN 80	699042
Connector S - DN 100 for connecting a cascade manifold with hydraulic separator CPN 300 - DN 100	699043
Connector S - DN 125 for connecting a cascade manifold with hydraulic separator CPN 300 - DN 125	699044

## Hydraulic separator CPN 150, CPN 250, CPN 300



Mounting feet included

The CPN 250, CPN 300 hydraulic separator is made of steel. The factory is equipped in EPP insulation and from the upper side with two connections for a temperature sensor (socket 1") and a vent (socket 1 1/4"), and from the bottom with a drain (socket 1 1/4"). Hydraulic separator contains a system of built-in meshes (1.) and baffles (2.) to help precipitate air bubbles and sediments, thus increasing its functionality and efficiency. It is included in the set mounting foot.

### Technical data:

Maximum pressure:	6 bar
Maximum temperature:	110 C
Maximum flow:	6-30 m <sup>3</sup> / h (depending on the model)
Insulation:	EPP black 40 g/l
Heating power:	120-700 kW (depending on the model)
Flange pressure standard:	PN 16

Type	Power at $\Delta T$ 20°C	Flow [m <sup>3</sup> /h]	Volume [l]	Catalog number
Hydraulic separator CPN 150 - DN 50 with insulation	120,00	6,00	9	609100
Hydraulic separator CPN 250 - DN 65 with insulation	210,00	9,00	26	609101
Hydraulic separator CPN 250 - DN 80 with insulation	280,00	12,00	26	609102
Hydraulic separator CPN 300 - DN 100 with insulation	470,00	20,00	61	609103
Hydraulic separator CPN 300 - DN 125 with insulation	700,00	30,00	62	609104

## Central heating zone manifold C2 100 - DN 50



Two-chamber steel manifold C 2 100 - DN 50 2 or 3-circuit DN 50 was created to facilitate the installation of pump groups DN 25, 32. The factory is equipped with EPP insulation, 2 gaskets with a diameter adapted to the diameter of the manifold connection and a set of 8 assembly screws for connecting with another manifold or hydraulic clutch.

C2 100 - DN 50 manifolds are adapted to the assembly of DN 25, DN 32 groups with a spacing of 125 mm.

**The manifold can be combined with the C2 125 - DN 50 manifold, making it possible to use pump groups with spacings of 125 mm and 250 mm in one boiler room.**

Type	Power at $\Delta T$ 20°C	Flow [m <sup>3</sup> /h]	Catalog number
Zone manifold C2 100 2 F - DN 50 with insulation,	120,00	6,00	609112
Zone manifold C2 100 3 F - DN 50 with insulation,	120,00	6,00	609113
Reduction mounting groups DN 25 on manifold C 100 DN 32, C2 100 - DN 32 - set - 2 pcs.			607023
Connection DN 1 1/4" x 2" with brass nut			607016
Connection DN 1 1/4" x 2" with built-in ball valve, with brass nut.			607017
Connection DN 1 1/4" x 2" with brass nut, with check valve for mixing group SMT			607018
Brackets for mounting manifold on the floor (1 set = 2 pcs )			607040
Pump groups DN 25, DN 32			Page 39 and 44

## Central heating zone manifold C2 125, C2 150



The two-chamber steel manifold C 2 125, C 2 150, 2 or 3 circuit was created to facilitate the assembly of pump groups DN 25, 32, 40, 50. The factory is equipped with EPP insulation and has a DN 50 flange connection on the installation side. The manifold contains 2 gaskets with a diameter adapted to the diameter of the manifold connection and a set of 8 mounting screws to connect with another manifold or hydraulic separator. We can make manifolds on request with a different connection.

Technical data:

Raw material:

Max pressure: 6 bar


Max temp.: 110 °C

Power: 120-700 kW at  $\Delta T$  20 °C


Insulation material: EPP black 40 g/l

Type	Power at $\Delta T$ 20°C	Flow [m <sup>3</sup> /h]	Catalog number
Central heating zone manifold C 2 125 2 F - DN 50 with insulation	120,00	6,00	609119
Central heating zone manifold C 2 125 3 F - DN 50 with insulation	120,00	6,00	609120
Central heating zone manifold C 2 125 2 F - DN 65 with insulation	210,00	9,00	609121
Central heating zone manifold C 2 125 3 F - DN 65 with insulation	210,00	9,00	609122
Central heating zone manifold C 2 125 2 F - DN 80 with insulation	280,00	12,00	609123
Central heating zone manifold C 2 125 3 F - DN 80 with insulation	280,00	12,00	609124
Central heating zone manifold C 2 150 2 F - DN 100 with insulation	470,00	20,00	609125
Central heating zone manifold C 2 150 3 F - DN 100 with insulation	470,00	20,00	609126
Central heating zone manifold C 2 150 2 F - DN 125 with insulation	700,00	30,00	609127
Central heating zone manifold C 2 150 3 F - DN 125 with insulation	700,00	30,00	609128
Type			Catalog number
Brackets for mounting manifold on the floor (1 set = 2 pcs )			607040

Pump group **D-SA 250 - DN 25, DN 32**  
- without mixing valve



Pump group **D-SMT 250 - DN 25, DN 32**  
- with rotary mixing valve



Compact pump group **D-SA 250 - DN 25, 32** is equipped with three ball valves, including two with thermometers, one with non-return valve, oblique filter, steel connectors and insulation. On request, the group can be equipped with a Wilo, DAB or Grundfos pump. To connect the group with the **C 2 125, C 2 150** manifold, two connections DN 50 should be purchased - see accessories.

Compact pump group **D-SMT 250 - DN 25, 32** equipped with two ball valves with thermometers, including one with non-return valve, **MIX-MT** rotary mixing valve, oblique filter, steel connectors and insulation. On request, the group can be equipped with a Wilo, DAB or Grundfos pump. To connect the group with the **C 2 125, C 2 150** manifold, two connections DN 50 should be purchased - see accessories. Additionally, to ensure automatic operation of the mixing valve, the group should be equipped with an **MP 10 - 10Nm** actuator.

Type	Catalog number
Pump group <b>D-SA 250 - DN 25 (1")</b> with insulation, without pump	609051
Pump group <b>D-SA 250 - DN 25 (1")</b> with insulation, with pump <b>Wilo Yonos Para 25/6</b>	609054
Pump group <b>D-SA 250 - DN 25 (1")</b> with insulation, with pump <b>Wilo Yonos Para 25/8</b>	609055
Pump group <b>D-SA 250 - DN 25 (1")</b> with insulation, with pump <b>Grundfos UPM3S AUTO 25-60</b>	609053
Pump group <b>D-SA 250 - DN 25 (1")</b> with insulation, with pump <b>DAB Evosta2 65/180</b>	609058

Type	Catalog number
Pump group <b>D-SA 250 - DN 32 (1 1/4")</b> with insulation, without pump	619051
Pump group <b>D-SA 250 - DN 32/25 (1 1/4")</b> with insulation, without pump, with connection for a threaded pump DN 25 (180 mm)	619058
Pump group <b>D-SA 250 - DN 32 (1 1/4")</b> with insulation, with pump <b>Wilo Yonos Para 30/6</b>	619054
Pump group <b>D-SA 250 - DN 32 (1 1/4")</b> with insulation, with pump <b>Wilo Yonos Para 30/8</b>	619055
Pump group <b>D-SA 250 - DN 32 (1 1/4")</b> with insulation, with pump <b>Grundfos Alpha 1L 32 - 60</b>	619053

Type	Catalog number
Pump group <b>D-SMT 250 - DN 25 (1")</b> with insulation, without pump	649051
Pump group <b>D-SMT 250 - DN 25 (1")</b> with insulation, with pump <b>Wilo Yonos Para 25/6</b>	649054
Pump group <b>D-SMT 250 - DN 25 (1")</b> with insulation, with pump <b>Wilo Yonos Para 25/8</b>	649055
Pump group <b>D-SMT 250 - DN 25 (1")</b> with insulation, with pump <b>Grundfos UPM3S AUTO 25-60</b>	649053
Pump group <b>D-SMT 250 - DN 25 (1")</b> with insulation, with pump <b>DAB Evosta2 65/180</b>	649058

Type	Catalog number
Pump group <b>D-SMT 250 - DN 32 (1 1/4")</b> with insulation, without pump	659051
Pump group <b>D-SMT 250 - DN 32/25 (1 1/4")</b> with insulation, without pump, without pump, with connection for a threaded pump DN 25 (180 mm)	659058
Pump group <b>D-SMT 250 - DN 32 (1 1/4")</b> with insulation, with pump <b>Wilo Yonos Para 30/6</b>	659054
Pump group <b>D-SMT 250 - DN 32 (1 1/4")</b> with insulation, with pump <b>Wilo Yonos Para 30/8</b>	659055
Pump group <b>D-SMT 250 - DN 32 (1 1/4")</b> with insulation, with pump <b>Grundfos Alpha 1L 32 - 60</b>	659053

Type	Catalog number
Connection <b>DN 50 (Flange) x 1" (Nut G 1 1/2")</b> - to connect groups DN 25 with zone manifolds	699001
Connection <b>DN 50 (Flange) x 1" (Nut G 1 1/2")</b> with check valve - to connect groups DN 25 with zone manifolds	699002
Connection <b>DN 50 (Flange) x 1 1/4" (Nut G 2")</b> - to connect groups DN 32 with zone manifolds	699003
Connection <b>DN 50 (Flange) x 1 1/4" (Nut G 2")</b> with check valve - to connect groups DN 32 with zone manifolds	699004

## Pump group D-SA 250 - DN 40, DN 50




Compact pump group **D-SA 250 - DN 40, 50** is equipped with a set of steel connectors, oblique filter, two thermometers and additional outputs 1/2 "GW on the power supply and return and isolation.

Technical data:

Maximum pressure:	6 bar
Maximum temperature:	110 °C
Wheelbase:	250 mm
Seals:	VITON or EPDM
Connection: boiler side:	flange DN 50, PN 16
installation side:	M 1 1/2 "for D-SA 250 - DN 40 M 2 "for D-SA 250 - DN 50

**ATTENTION!** The pump group is not equipped with shut-off valves. We recommend the installation of standard commercially available products, i.e. ball valves on the installation side, DN 50 dampers on the boiler side.

Type	Catalog number
Group D-SA 250 - DN 40 (1 1/2 ") with insulation, without pump, pump installation length 250mm	629052
Group D-SA 250 - DN 40/32 (1 1/2 ") with insulation, without pump, with connection for a threaded pump DN 32 (180 mm)	629059
Group D-SA 250 - DN 40/25 (1 1/2 ") with insulation, without pump, with connection for a threaded pump DN 25 (180 mm)	629058
Set of distance extensions RG 40 250 mm / 220 mm for the installation of DN 40 pumps with a length of 220 mm - price per set. - 2 pcs.	629090
Type	Catalog number
Grupa D-SA 250 - DN 50 (2 ") with insulation, without pump, pump installation length 280mm	639052
Grupa D-SA 250 - DN 50/40 (2 ") with insulation, without pump, with connection for a flanged pump DN 40 (250 mm)	639057
Grupa D-SA 250 - DN 50/32 (2 ") with insulation, without pump, with connection for a threaded pump DN 32 (180 mm)	639059
Grupa D-SA 250 - DN 50/25 (2 ") with insulation, without pump, with connection for a threaded pump DN 25 (180 mm)	639058
Set of distance extensions RG 50 280 mm / 240 mm for installation of DN 50 pumps with a construction length of 240 mm - price per set. - 2 pcs.	629091



## Pump group D-SMT 250 - DN 40, DN 50




Compact mixing and pump group **D-SMT 250 - DN 40, 50** is equipped with a set of steel connectors, check valve, oblique filter, mixing valve MIX M, two thermometers and additional outputs 1/2 "GW on the supply and return and insulation. Additionally, to ensure automatic operation of the mixing valve, the group should be equipped with an **MP 10 - 10 Nm** actuator.

Technical data:

Maximum pressure:	6 bar
Maximum temperature:	110 °C
Wheelbase:	250 mm
Seals:	VITON or EPDM
Connection: boiler side:	flange DN 50, PN 16
installation side:	M 1 1/2 "for D-SMT 250 - DN 40 M 2 "for D-SMT 250 - DN 50

**ATTENTION!** The pump group is not equipped with shut-off valves. We recommend the installation of standard commercially available products, i.e. ball valves on the installation side, DN 50 dampers on the boiler side.

Type	Catalog number
Group D-SMT 250 - DN 40 (1 1/2 ") with insulation, without pump, pump installation length 250mm	669052
Group D-SMT 250 - DN 40 (1 1/2 ") with insulation, without pump, with connection for a threaded pump DN 32 (180 mm)	669059
Group D-SMT 250 - DN 40 (1 1/2 ") with insulation, without pump, with connection for a threaded pump DN 25 (180 mm)	669058
Set of distance extensions RG 40 250 mm / 220 mm for the installation of DN 40 pumps with a length of 220 mm - price per set. - 2 pcs.	629090
Type	Catalog number
Group D-SMT 250 - DN 50 (2 ") with insulation, without pump, pump installation length 280mm	679052
Group D-SMT 250 - DN 50 (2 ") with insulation, without pump, with connection for a flanged pump DN 40 (250 mm)	679057
Group D-SMT 250 - DN 50 (2 ") with insulation, without pump, with connection for a threaded pump DN 32 (180 mm)	679059
Group D-SMT 250 - DN 50 (2 ") with insulation, without pump, with connection for a threaded pump DN 25 (180 mm)	679058
Set of distance extensions RG 50 280 mm / 240 mm for installation of DN 50 pumps with a construction length of 240 mm - price per set. - 2 pcs.	629091



## System accessories up to 700 kW

Brackets for mounting manifold on the floor



Actuator MP



Connector distance



Angle connector 90°  
DN 50, 65, 80, 100, 125



Connection DN 50 (Flange) x  
(Nut G 2")



Blanking flanges



Type	Catalog number
Actuator <b>MP 10</b>	401011
Brackets for mounting manifold on the floor (1 set = 2 pcs)	607040
Brackets for mounting cascade manifold on the floor (1 set = 2 pcs)	607050
Angle connector 90° - <b>DN 50</b> with 4 mounting screws and a gasket EPDM DN 50	699010
Angle connector 90° - <b>DN 65</b> with 4 mounting screws and a gasket EPDM DN 65	699011
Angle connector 90° - <b>DN 80</b> with 4 mounting screws and a gasket EPDM DN 80	699012
Angle connector 90° - <b>DN 100</b> with 4 mounting screws and a gasket EPDM DN 100	699013
Angle connector 90° - <b>DN 125</b> with 4 mounting screws and a gasket EPDM DN 125	699014
Connection <b>DN 50 (Flange) x 1" (Nut G 1 1/2")</b> - to connect groups DN 25 with zone manifolds	699001
Connection <b>DN 50 (Flange) x 1" (Nut G 1 1/2")</b> with check valve - to connect groups DN 25 with zone manifolds	699002
Connection <b>DN 50 (Flange) x 1 1/4" (Nut G 2")</b> - to connect groups DN 32 with zone manifolds	699003
Connection <b>DN 50 (Flange) x 1 1/4" (Nut G 2")</b> with check valve - to connect groups DN 32 with zone manifolds	699004
Blanking flange <b>DN 50</b> with 4 mounting screws and a gasket EPDM DN 50	699020
Blanking flange <b>DN 65</b> with 4 mounting screws and a gasket EPDM DN 65	699021
Blanking flange <b>DN 80</b> with 4 mounting screws and a gasket EPDM DN 80	699022
Blanking flange <b>DN 100</b> with 4 mounting screws and a gasket EPDM DN 100	699023
Blanking flange <b>DN 125</b> with 4 mounting screws and a gasket EPDM DN 125	699024
Blanking flange with muff <b>DN 50</b> with 4 mounting screws and a gasket EPDM DN 50	699030
Blanking flange with muff <b>DN 65</b> with 4 mounting screws and a gasket EPDM DN 65	699031
Blanking flange with muff <b>DN 80</b> with 4 mounting screws and a gasket EPDM DN 80	699032
Blanking flange with muff <b>DN 100</b> with 4 mounting screws and a gasket EPDM DN 100	699033
Blanking flange with muff <b>DN 125</b> with 4 mounting screws and a gasket EPDM DN 125	699034
Connector distance <b>DN 50 (L-230)</b> with 4 mounting screws and a gasket EPDM DN 50	699050
Connector distance <b>DN 65 (L-290)</b> with 4 mounting screws and a gasket EPDM DN 65	699051
Connector distance <b>DN 80 (L-310)</b> with 4 mounting screws and a gasket EPDM DN 80	699052
Connector distance <b>DN 100 (L-350)</b> with 4 mounting screws and a gasket EPDM DN 100	699053
Connector distance <b>DN 125 (L-400)</b> with 4 mounting screws and a gasket EPDM DN 125	699054
Butterfly valve	page 58



## Heat pump or air conditioner WM stand / bracket



The stands (supports) WM II and WM III intended for heat pumps or air conditioners are made of steel. The stability of the stand has been increased by the use of adjustment fasteners on both sides. The design of the stand guarantees that it can be used with any heat pump or air conditioner. The brackets are equipped with vibration isolators to catch vibrations of the device and feet, together with a handle that allows the stand to be anchored. The bracket with the device should be placed on a permanently leveled base that can carry five times the weight of the device. Possible unevenness can be eliminated by a foot with an adjusting screw.

Set contains:

- Steel elements of the stand
- Vibro-isolators with nuts
- Adjustable feet with the possibility of anchoring to the ground
- Mounting screws

In case of doubts about the matching of the WM stand to the device being used, please contact us by e-mail at [export@womix.pl](mailto:export@womix.pl).

Type	Catalog number
Heat pump or air conditioner stand / bracket WM II 42/92	610951
Heat pump or air conditioner stand / bracket WM II 52/92	610955
Heat pump or air conditioner stand / bracket WM II 52/135	610956
Heat pump or air conditioner stand / bracket WM III 42/135	610962

## Mounting frame for the RK wall-hung boiler




The mounting frame is designed to facilitate the installation of hanging boilers. To connect the two frames you need a set of bolts and plates. Frame in white.

Due to the different width of the boilers, their mounting and the need to adapt the frame to the spacing of the manufacturer's chimney systems, please send data of the boiler used (name / catalog card) in order to prepare a frame suitable for the boiler.

Type	Catalog number
Mounting frame for the RK wall-hung boiler (one frame = one boiler)	610910
A set of screws and sheets for joining two RK assembly frames	610900

## Magnetic filter with strainer FM



The **FM** magnetic filter is a device designed to trap solid pollutants carried by water in central heating installations, heating networks, heat centers, boiler rooms, as well as in glycol installations in air-conditioning systems. Their use allows for the proper operation of heat exchangers, pumps, boilers and other system devices, preventing the deposition of impurities that remain in the desilter and are easy to remove. Contrary to systems without a filter separator, the sedimentation of sludge and limescale effectively reduces the efficiency of devices operating in such conditions. This is especially important for heat exchangers.

Advantages of using a magnetic filter with strainer:

- securing and significantly reducing the risk of damage to the installation and its components,
- silencing the operation of the installation,
- exceptional simple removal of the separator contamination, removal of contamination without the need to shut down the installation.

Type	Catalog number
Magnetic filter with strainer <b>FM 65 - DN 25</b> with insulation, with equipment	611091
Magnetic filter with strainer <b>FM 80 - DN 32</b> with insulation, with equipment	611092
Magnetic filter with strainer <b>FM 100 - DN 40</b> with insulation, with equipment	611093
Magnetic filter with strainer <b>FM 150 - DN 50</b> with insulation, with equipment	611094

### Hydraulic separator XP 80 ELEC



#### Equipment:



### Flow heating tube HP 100 - DN 40



#### Equipment:



Hydraulic separator **XP 80 ELEC** for heating systems is made of steel. Factory equipped with an automatic air vent, a immersion sleeve for connecting a temperature sensor and EPP insulation and thermometer.

**Attention! The product does not contain a heater.**


Flow heating tube **HP 100 - DN 40** for heating installations is made of steel. The factory is equipped with an automatic air vent, EPP insulation and thermometer.

**Attention! The product does not contain a heater.**


**Attention! To prevent damage to the heater during operation, a constant flow of medium through the device must be ensured.**

Type	Catalog number
Hydraulic separator <b>XP 80 ELEC</b> with insulation, with equipment	609305
Flow heating tube <b>HP 100 - DN 40</b> with insulation, with equipment	609310

## Hydraulic separator CPN 70 2F - DN 25 (1") - for 2 heat sources



## Hydraulic separator CPN 100 2F - DN 32 (1 1/4") - for 2 heat sources



## Hydraulic separator CPN 100 2F - DN 40 (1 1/2") - for 2 heat sources



Hydraulic separator **CPN 70 2F - DN 25** is made of steel. It is factory-equipped into insulation, on the upper side into a connection for a vent and a built-in pipe for the temperature sensor, and on the lower side into a drain connection. The set includes air vent with check valve, drain valve, four 1" cast iron fittings and wall brackets.

Hydraulic separator **CPN 100 2F - DN 32** is made of steel. The factory is equipped with insulation, on the upper side with two connections for a temperature sensor and a vent and on the lower side with a drain connection. Included There are a air vent with check valve, a plunger sleeve for connecting a temperature sensor, a drain valve, two 1 1/4 " cast iron fittings and wall brackets.

Hydraulic separator **CPN 100 2F - DN 40** is made of steel. The factory is equipped with insulation, on the upper side with two connections for a temperature sensor and a vent and on the lower side with a drain connection. The set includes a air vent with check valve, plunger sleeve for connecting a temperature sensor, two 1 1/2" cast iron screw connections and a mounting foot.

Type	Catalog number
Hydraulic separator <b>CPN 70 2F - DN 25</b> with insulation, with equipment	606001
Hydraulic separator <b>CPN 100 2F - DN 32</b> with insulation, with equipment	617001
Hydraulic separator <b>CPN 100 2F - DN 40</b> with insulation, with equipment	617002

## Hydraulic separator **XPN**



Hydraulic separator **XPN** are made of steel. They are factory-equipped with insulation, on the upper side with a connection for a vent and a place for mounting the temperature sensor, and on the lower side with a drain connection. The set includes a air vent with a check valve and a drain valve.

Attention!!



Hydraulic separator are intended for vertical mounting only.

### Equipment:



Type	Flow [m <sup>3</sup> /h]	Volume [l]	Catalog number
Hydraulic separator <b>XPN 60 - DN 25</b> with insulation, with equipment	1,80	1,1	611051
Hydraulic separator <b>XPN 60 - DN 32</b> with insulation, with equipment	2,30	1,6	611052

## Hydraulic separator XP



Hydraulic separator **XP** are made of steel. They are factory-equipped with insulation, on the upper side with a connection for a vent and a place for mounting the temperature sensor, and on the lower side with a drain connection. The set includes air vent with check valve and drain valve.

### Technical data:

Maximum pressure: 8 bar  
 Maximum temperature: 110 °C  
 Insulation: EPP black 40 g/l

### Attention!!

Hydraulic separators are intended for vertical mounting only.

### Equipment:



	XP 65 - DN 25	XP 80 - DN 32	XP 100 - DN 40	XP 150 - DN 50
A <sub>1</sub> (mm)	300	300	300	350
A <sub>2</sub> (mm)	340	340	340	440
B <sub>1</sub> (mm)	155	155	190	250
B <sub>2</sub> (mm)	200	200	250	300
L (mm)	520	520	520	680
DN	65	80	100	150
G	GW 1"	GW 1 1/4"	GW 1 1/2"	GW 2"

50 kW

80 kW

120 kW

180 kW

Type	Flow [m <sup>3</sup> /h]	Volume [l]	Catalog number
Hydraulic separator <b>XP 65 - DN 25</b> with insulation, with equipment	2,3	1,6	611081
Hydraulic separator <b>XP 80 - DN 32</b> with insulation, with equipment	4,2	2,5	611082
Hydraulic separator <b>XP 100 - DN 40</b> with insulation, with equipment	5,7	3,8	611083
Hydraulic separator <b>XP 150 - DN 50</b> with insulation, with equipment	9,0	11,2	611084

## Pump group with plate heat exchanger BW



Compact pump group BW - DN 25 is equipped with two brass ball valves with supply and return water thermometers, coupler, check valve, plate heat exchanger, safety group 2.5 bar with pressure gauge 0-4 bar, two drain valves, handles wall and insulation.

### Technical data:

Max pressure:	8 bar
Max temperature:	120°C
Insulation material:	EPP black 40 g/l
Axle spacing:	125 mm
Gaskets material:	VITON or EPDM
Connections:	1" F
Installation length of pump:	180mm
Number of plates:	20 or 30

Type	Catalog number
Pump grup <b>BW 20</b> with 20-plates heat exchanger, without pump	606155
Pump grup <b>BW 30</b> with 30-plates heat exchanger, without pump	606156
Pump grup <b>BW 20</b> with 20-plates heat exchanger, with pump <b>Wilo Yonos Para 25/6</b>	616157
Pump grup <b>BW 30</b> with 30-plates heat exchanger, with pump <b>Wilo Yonos Para 25/6</b>	616167
Pump grup <b>BW 20</b> with 20-plates heat exchanger, with pump <b>Grundfos UPM3S AUTO 25 - 60</b>	616152
Pump grup <b>BW 30</b> with 30-plates heat exchanger, with pump <b>Grundfos UPM3S AUTO 25 - 60</b>	616162
Pump grup <b>BW 20</b> with 20-plates heat exchanger, with pump <b>DAB Evosta2 65/180</b>	616158
Pump grup <b>BW 30</b> with 30-plates heat exchanger, with pump <b>DAB Evosta2 65/180</b>	616168

## Wafer butterfly valve with an electric actuator



### Technical data of the throttle:

Pressure:	PN 6
Working temperature:	0 ° C to + 120 ° C

### Technical data of the actuator:

Supply voltage:	230 VAC
Control:	three-point or close / open
Torque at rated voltage:	20 Nm for SR 230 40 Nm for GR 230

Manual override Gear disengagement button (temporary or permanent release)

Movement time:	90 sec / 90 °
Noise level:	Max.45 dB (A) (without valve)
Position indicator	Mechanical, integrated
Protection class	II (fully insulated)
IP 54	in any mounting position
Ambient temperature range:	0 ... + 50 ° C

Type	Catalog number
Butterfly valve <b>DN 40</b> with electric actuator <b>SR 230</b>	005203
Butterfly valve <b>DN 50</b> with electric actuator <b>SR 230</b>	005204
Butterfly valve <b>DN 65</b> with electric actuator <b>SR 230</b>	005205
Butterfly valve <b>DN 80</b> with electric actuator <b>SR 230</b>	005206
Butterfly valve <b>DN 100</b> with electric actuator <b>GR 230</b>	005207
Butterfly valve <b>DN 125</b> with electric actuator <b>GR 230</b>	005208

Type	Catalog number
Butterfly valve <b>DN 50</b>	005002
Butterfly valve <b>DN 65</b>	005003
Butterfly valve <b>DN 80</b>	005004
Butterfly valve <b>DN 100</b>	005005
Butterfly valve <b>DN 125</b>	005006



**womix**  
Comfort Controls

Poland, Szubin 89-200  
Sportowa 31



**Contact  
us:**



**Michał Górecki**  
tel. + 48 570 108 498  
export@womix.pl

## Terms of cooperation

### §1. Introduction.

- 1.1. The sales contracts entered into by WOMIX. (hereinafter the „seller”) while conducting its business activities are governed by these general terms and conditions, unless there are exceptions resulting from an explicit written agreement and expressly approved in writing by the Sales Office of the seller.
- 1.2. Any terms and conditions of the buyer and in particular conditions of purchase, will not apply to the relationships between the parties unless expressly accepted in writing and approved in the same form by the Sales Office of the seller: in this case, however, unless waived in writing, these terms and conditions still remain in effect.
- 1.3. The possible invalidity of one or more provisions of these general conditions of sale will not affect the validity of the contract as a whole.
- 1.4. These general conditions of sale are considered to be fully read and accepted by the buyer upon order placement.

### §2. Formation of the contract and its execution.

- 2.1. Orders taken or commitments made by representatives, agents or other collaborators of WOMIX cannot bind the seller in any way; it follows that all orders processed by the aforementioned representatives, agents and collaborators become valid and effective only upon written confirmation from the seller and the written approval by the Sales Office of the seller.
- 2.2. Any changes to the order will be effective only upon written confirmation and written approval by the Sales Office of the seller.

### §3. Purpose and prices.

- 3.1. The data, measurements, articles, prices, features, performance and all other data shown in our catalogues, price lists, prospectuses, circulars etc. are given only as indications; they may be changed without any warning and are only considered binding for the seller in the event of their explicit mention in the acceptance or confirmation of the order.
- 3.2. The price lists of the seller are not offers; they are only approximate and may be modified unilaterally by the seller without notice.
- 3.3. The prices are considered to be standard, unless otherwise agreed, „ex-works of the seller”, packaging excluded. Fees, taxes and duties in force at the time of delivery are the responsibility of the buyer. Prices do not include services or charges not mentioned.
- 3.4. Insurance expenses for the goods are to be borne by the buyer, as well as any expenses and customs duties due to delays in custom clearance or other reasons.

### §4. Payments.

- 4.1. Barring written exceptions, all payments must be made at the offices of WOMIX in Euro.
- 4.2. Payment for the goods is made in the form of a prepayment.
- 4.3. The date of payment shall be the date the influence of the amount indicated on the invoice VAT on the Seller's bank account.

### §5. Delivery and transfer of risk.

- 5.1. The seller will notify by letter or telegram or telefax or e-mail or certified mail (certified email address) that the goods are available to the buyer at the seller's premises.
- 5.2. The delivery of material is considered “free on board”. The responsibility of the seller stops with delivery to the buyer or carrier; consequently the material is transported at the risk of the buyer. In cases in which, due to specific buyer interventions, the material is sold “free delivery”, no disputes will be accepted for any thefts, damages or tampering. Any agreements with forwarding agents, including the amount and payment of the cost of transportation are considered settled in the name of and on behalf of the buyer who, from that moment onward, accepts and approves the conduct of the seller.

### §6. Transport and packaging.

- 6.1. The cost of transporting material from the seller's premises to the place of destination is normally intended to be borne by the seller, unless otherwise agreed in the order confirmation. Transport costs are, in any case, to be borne by the buyer. The buyer assumes all risks inherent in the transportation starting from the delivery of the goods to the shipper or carrier, even if the right to property is reserved.
- 6.2. The seller will provide the packaging according to the rules of use. The seller is exempt from any liability for loss or damage which does not result from intentional or gross negligence by the seller and is not the direct and immediate consequence of its conduct. For specific types of packaging, the extra amounts indicated in the price list or in the order confirmation will be included in the invoice.
- 6.3. Any transport costs are determined individually, depending on the number, type and weight of the shipment.

### §7. Testing and warranty.

- 7.1. Unless otherwise stated, supplies by the seller are regulated by the rules and details contained in the WOMIX catalogue.
- 7.2. All the products of the seller are carefully tested on site; they are therefore covered by a warranty for a period of two from the date of issue of the invoice.
- 7.3. The seller's warranty is limited to pure and simple replacement of the defective part, which must first be returned to the seller (and therefore any expenses, damages, interest or compensation of any kind are strictly excluded from the warranty). In any case, the components produced by the seller recognised as being faulty, preceded by a complaint made by the buyer within the maximum time period set forth by existing regulation, will be replaced only by the seller. Nevertheless the liability of the seller is limited to faults which appear under normal working conditions and during correct product use.
- 7.4. Any damage caused by incorrect product operation must be made known within 24 hours, providing the name of the damaged part and the approximate amount of the damage. Subsequently photographs showing the damage must be sent, together with the product which caused the alleged damage, for examination in the laboratory. Anything which may provide evidence of the extent of the damage must be made available to the seller until the case is closed.
- 7.5. The seller refuses all responsibility for any damage or injury to persons, animals or property derived from the use of the appliances without observing the safety provisions or from appliances which are not installed correctly and/or were installed without performing the appropriate operation checks.

### §8. Terms of delivery and return of goods.

- 8.1. The terms of delivery go into effect on the day following that on which the agreement is reached on each element of the contract and all information necessary for execution is received by the seller. In any case it is understood that the terms of delivery specified in the seller's offers only serve as guidelines and are not binding.
- 8.2. If an import licence is requested from the country of the buyer, the delivery terms will go into effect from the moment the seller has been informed in writing of the granting of the licence.
- 8.3. The seller assumes no responsibility for any delays in delivery. Deliveries of goods, even if partial, cannot be refused by the buyer; partial deliveries of goods do not give the buyer the right to cancel the order.

- 8.4. No liability will be due to the seller, and therefore nothing will be due to the buyer, if the delay is not attributable to the seller - as in the case of delays by third parties, including suppliers and subcontractors, due to force majeure such as demonstrations, riots, strikes or lockouts, wars, epidemics, closure, accidents or failures of machinery or tools, fires, collapses, floods, earthquakes, extreme temperatures, weather events and generally in any other case involving partial or total inactivity of the premises of the seller and production stoppage or slowdown.

- 8.5. In any case, the buyer cannot use the delay in delivery to terminate the contract.

- 8.6. Except as provided for in number 8. on the subject of warranty, the client cannot for any reason return delivered material without the express written permission of the seller. To obtain consent for return and be entitled to a refund of the purchase price already paid, the buyer must return the material as follows:

- the material must be unused and returned in the same condition in which the buyer received it;
- the material must be returned within fifteen days (15) of the date of the invoice;
- the material must be returned to WOMIX - at the expense and risk of the buyer - to the headquarter in Poland, 89-200 Szubin ul. Sportowa 31

### §9. Withdrawal and suspension of supply.

- 9.1. In case of unforeseen circumstances, force majeure and fortuitous events (such as but not limited to strikes or lockouts, missed or reduced supply of raw materials, difficulty of transport, wars, insurrection, interruption of communications, however caused, plant breakdowns etc.) the seller has the right to withdraw from this agreement and/or suspend the current supply when these unexpected events, wherever they take place, substantially alter the state of the markets, the value of money, Polish industry conditions or circumstances arise, even endogenous, that according to the incontestable judgement of the Seller, do not allow for the useful continuation of the supply relationship.
- 9.2. In any case, under these general conditions of sale regarding withdrawal from the contract and/or suspension of the supply of material, the buyer will not be entitled to reparation, compensation, reimbursement or damages.

### §10. Intellectual property rights.

- §10. Any drawing or technical document related to products of the seller, even if given to the buyer, remains the exclusive property of the seller and cannot be used by the buyer or copied, reproduced, transmitted or communicated to third parties without the prior written authorisation of the seller.

### §11. Complaints.

- 11.1. The buyer is required to examine the goods carefully when it receives delivery and notify the seller within five (5) days from the delivery/receipt, of any defects or quality issues found in the product.
- 11.2. Any complaints and/or disputes about defects or quality issues of the product do not give the buyer the right to omit or delay payments of the supply.




Check on  
Facebook

Check  
our products on



## Configurator of pump groups systems




[www.womix.pl/en](http://www.womix.pl/en)

Device selection has  
never been so easy

search the website  
[www.womix.pl/en](http://www.womix.pl/en)

CHECK →



✉ [export@womix.pl](mailto:export@womix.pl)

**WOMIX**

Sportowa 31 89-200 Szubin

tel. +48 52 382 44 50

mobile: +48 570 108 498



[www.facebook.com/WomixPolska/](https://www.facebook.com/WomixPolska/)

[www.womix.pl](http://www.womix.pl)