

05/2023

CATALOGUE

wiper®



CONTENTS

Linear showerdrains	4–31
INTENSI 316 UNO – NEW	4
INTENSI 316 DUO – NEW	6
PREMIUM	8
PREMIUM GLASS – NEW	10
PREMIUM ZK	12
PREMIUM ZK GLASS – NEW	14
PREMIUM SLIM	16
INVISIBLE	18
INVISIBLE SLIM	20
ELITE	22
ELITE SLIM	24
VINYL FLOOR – NEW	26
CLASSIC	28
EYE-DRAIN	30
Custom versions	32–37
PREMIUM ZKL / ZKPL / ZKP	32
S-LINE	34
LINEAR DRAINS IN ANY LENGTH AND WITH OFFSET DRAIN TRAPS	36
Point drains	38–45
WP PREMIUM	38
WP CLASSIC	40
WP INVISIBLE	42
WIPER TOP	44
Shower screens	46–47
VERRE – NEW	
Shower trays	48–49
SOLID EYE	
Shower slabs	50–61
SHOWERLAY	50
SHOWERLAY ONEWAY	52
SHOWERLAY ELITE – NEW	54
SHOWERBASE	56
SHOWERBASE ELITE – NEW	58
SHOWERBASE VF – NEW	60
Water-proofing systems	62–65
SYSTEM ISOL-ONE	62
TANKIGN KIT FOR SHOWER CABIN	64
Underfloor heating	66–69
SUNFLOOR – HEATING MAT	66
SUNFLOOR – HEATING FOIL – NEW	68
Accessories	70–73
WIPER SOUND STOP – SOUNDPROOF MAT	70
DRAIN TRAPS	72
Hygiene Certyfication	74
Configuration selection table	75


INTENSI 316 UNO

INTENSI 316 UNO shower tray was designed with the latest trends and market expectations in mind. Its very low build-up allows installation in difficult conditions. The shower tray is available in two variants with the possibility of cutting it to the required length, which makes it fit perfectly into the size of the shower tray. It is equipped with a SNAKE BEAN siphon. It receives water along its entire length. The standard length of the base is 300 mm, while the gutter and grate set is 1200 and 1500 mm long. The whole is made of certified steel grade 316 polished, ground or matte.

PVD (Physical Capour Deposition) is a process of physical deposition of thin layers from the gas phase, carried out under conditions of high vacuum. The coating formed in this process, is characterized by versatile properties. The most important of these are: excellent color quality and a wide range of colors, high abrasion and corrosion resistance, high thermal stability and chemical inertness.







wiper®



Discharge pipe dia. $\varnothing 40$ or $\varnothing 50$ if installed with the included reducer (adapter) piece

- The gutter **can be cut** to any size within the range of $400 \div 1200$
 $400 \div 1500$

- Water flow rate acc. EN 1253 Q [l/min]:
31 - single bean trap



insulation flange



surface finish



STAINLESS STEEL



DURABILITY



GOOD QUALITY



CLEANABLE



100% RESISTANCE



CAPACITY



LOW HEIGHT




120°C



EASY INSTALLATION


SILVER

LIN / LAN




HONEY GOLD

LIN / LAN




GOLD

LIN / LAN



BRIGHT GOLD

LIN / LAN



GRAPHIT BLACK


LIN / LAN



NEW

COPPER

LIN / LAN



INTENSI 316 DUO



INTENSI 316 DUO shower tray was designed with the latest trends and market expectations in mind. Its very low build-up allows installation in difficult conditions. The shower tray is available in two variants and can be cut to the desired length, which makes it perfectly adapted to the size of the shower tray. It is equipped with a new double siphon SNAKE BEAN. It collects water along its entire length. The standard length of the base is 300 mm, while the gutter and grate set is 1200 and 1500 mm long. The whole is made of certified steel grade 316 polished, ground or matte.

PVD (Physical Capour Deposition) is a process of physical deposition of thin layers from the gas phase, carried out under conditions of high vacuum. The resulting coating is characterized by versatile properties.

The most important of these are: excellent color quality and a wide range of colors, high abrasion and corrosion resistance, high thermal stability and chemical inertness.







wiper®



Discharge pipe dia. $\varnothing 40$ or $\varnothing 50$ if installed with the included reducer (adapter) piece

- The gutter **can be cut** to any size within the range of $400 \div 1200$
 $400 \div 1500$

- Water flow rate acc. EN 1253 Q [l/min]:
52,5 - double bean trap



insulation flange



surface finish



STAINLESS STEEL



DURABILITY



GOOD QUALITY



CLEANABLE



100% RESISTANCE



CAPACITY



LOW HEIGHT



120°C



EASY INSTALLATION

SILVER

LIN / LAN

HONEY GOLD

LIN / LAN

GOLD

LIN / LAN

BRIGHT GOLD

LIN / LAN

GRAPHIT BLACK

LIN / LAN

NEW

COPPER

LIN / LAN


PREMIUM

The PREMIUM linear shower drains are a series of WIPER linear drains complete with a sealing flange that helps with installation of the product in a floor system which features a water-proofing layer. An optional membrane can be used to greatly facilitate installation. The finished installation provides a smartly refined grate and frame of stainless steel, 84 mm wide and as long as ordered, which means virtually any length desired. The product is available in many versions to suit the needs of diverse projects.

wiper®




PREMIUM



○ Discharge pipe dia. \varnothing 40 or \varnothing 50 if installed with the included reducer (adapter) piece

- Standard lengths L [mm]:
500, 600, 700, 800, 900, 1000, 1100, 1200

- Water flow rate acc. EN 1253 Q [l/min]:
36 - siphon SNAKE
48 - siphon DROP 35 and DROP 50



NEW



Option with siphons also available

DROP 35 and DROP 50

More info on page 50-53

flange



surface finish



STAINLESS-STEEL



DURABILITY



GOOD QUALITY



CLEANABLE



100% RESISTANCE



CARRY



LOW HEIGHT



120°C



EASY INSTALLATION

PONENTE

PURE

ZONDA

MISTRAL

SIROCCO

TIVANO



PREMIUM GLASS

PREMIUM shower gutters are a series of WIPER linear shower drains equipped with a flange insulating collar, useful for installation in the floor with an insulating layer. Optionally, an insulation cuff can be used, which greatly facilitates installation. The PREMIUM GLASS gutter is topped with an elegant stainless steel grille with a top layer of tempered glass 8mm thick. Two color options are available: glass in delicate white (Glass White) and deep black (Glass Black).



PREMIUM GLASS



○ Discharge pipe dia. \varnothing 40 or \varnothing 50 if installed with the included reducer (adapter) piece

- Standard lengths L [mm]:
500, 600, 700, 800, 900, 1000, 1100, 1200

- Water flow rate acc. EN 1253Q [l/min]:
36 - siphon SNAKE
48 - siphon DROP 35 and DROP 50



For this product you can buy:

- SEALING MEMBRANE
- ADJUSTABLE LEGS
- TANKING KIT


NEW PRODUCT



Option with siphons also available

DROP 35 and DROP 50

More info on page 50–53



insulation flange



STAINLESS STEEL



DURABILITY



GOOD QUALITY



CLEANABLE



100% RESISTANCE



CAPACITY




LOW HEIGHT



120°C



EASY INSTALLATION



PREMIUM ZK

NEW

The PREMIUM ZK linear shower drains are a series of WIPER linear drains complete with a sealing flange that helps with installation of the product in a floor system which features a water-proofing layer. The flange is bent vertically (and with many options available) which facilitates installation at the floor-to-wall corners with an optimum offset between the grate and the wall tiles. The finished installation provides a smartly refined grate and frame of stainless steel, 84 mm wide and as long as ordered, which means virtually any length desired. The product is available in many versions to suit the needs of diverse projects.

wiper®



PREMIUM ZK



For this product you can buy:

- SEALING MEMBRANE
- ADJUSTABLE LEGS PCL-1
- TANKING KIT s. 44

NEW



Option with siphons also available

DROP 35 and DROP 50

More info on page 50–53

○ Discharge pipe dia. \varnothing 40 or \varnothing 50 if installed with the included reducer (adapter) piece


• Standard lengths L [mm]:

500, 600, 700, 800, 900, 1000, 1100, 1200

• Water flow rate acc. EN 1253 Q [l/min]:

36 - siphon SNAKE

48 - siphon DROP 35 and DROP 50



bent flange



surface finish



STAINLESS-STEEL



DURABILITY



GOOD-QUALITY



CLEANABLE



100% RESISTANCE



CAPACITY



LOW-HEIGHT



120°C



EASY-INSTALLATION

PONENTE



PURE




ZONDA



MISTRAL



SIROCCO



TIVANO



PREMIUM GLASS

PREMIUM shower gutters are a series of WIPER linear shower drains equipped with a flange insulating collar, useful for installation in the floor with an insulating layer. Optionally, an insulation cuff can be used, which greatly facilitates installation. The PREMIUM GLASS gutter is topped with an elegant stainless steel grille with a top layer of tempered glass 8mm thick. Two color options are available: glass in delicate white (Glass White) and deep black (Glass Black).





○ Discharge pipe dia. \varnothing 40 or \varnothing 50 if installed with the included reducer (adapter) piece


• Standard lengths L [mm]:

500, 600, 700, 800, 900, 1000, 1100, 1200

• Water flow rate acc. EN 1253Q [l/min]:

36 - siphon SNAKE

48 - siphon DROP 35 and DROP 50



STAINLESS STEEL



DURABILITY



GOOD QUALITY



CLEANABLE



100% RESISTANCE



CAPACITY



LOW/HEIGHT



120°C



EASY INSTALLATION



For this product you can buy:

- SEALING MEMBRANE
- ADJUSTABLE LEGS
- TANKING KIT

NEW PRODUCT




Option with siphons also available

DROP 35 and DROP 50

More info on page 50–53

bent flange



PREMIUM SLIM

The PREMIUM SLIM linear shower drains are a series of WIPER linear drains complete with a sealing flange that helps with installation of the product in a floor system which features a water-proofing layer. An optional membrane can be used to greatly facilitate installation. The finished installation provides a smartly refined grate and frame of stainless steel, 58 mm wide and as long as ordered, which means virtually any length desired. The drains set feature the SMART TRAP®, a new, patented stainless-steel drain trap with a throughput of 26 l/min and the EASY CLEAN system. The product is available in many versions to suit the needs of diverse projects.

wiper®



PREMIUM SLIM



○ Discharge pipe dia. \varnothing 40 or \varnothing 50 if installed with the included reducer (adapter) piece

• Standard lengths L [mm]:
500, 600, 700, 800, 900, 1000, 1100, 1200


• Water flow rate acc. EN 1253 Q [l/min]:
26 - EN1253

• System EASY CLEAN

steel siphon



flange



surface finish



STAINLESS STEEL



DURABILITY



GOOD QUALITY



CLEANABLE



100% RESISTANCE



CAPACITY



LOW HEIGHT



120°C



EASY INSTALLATION


PONENTE




PURE



MISTRAL



SIROCCO



INVISIBLE

The INVISIBLE linear shower drains are the concept of a visually minimalist take on standard linear drains. When installed, its parts are perfectly invisible. The only visible feature are the drain slots in the floor to accept the water through. This solution is recommended for floorings made of materials which can be cut and trimmed to obtain an aesthetic finish (like vitrified tiles or granite stone). The product kit includes a degreasing wipe to clean the substrate before adhesive bonding.

wiper®



INVISIBLE



○ Discharge pipe dia. \varnothing 40 or \varnothing 50 if installed with the included reducer (adapter) piece

- Standard lengths L [mm]:
500, 600, 700, 800, 900, 1000, 1100, 1200

- Water flow rate acc. EN 1253 Q [l/min]:
36 - siphon SNAKE
48 - siphon DROP 35 and DROP 50


NEW



Option with siphons also available

DROP 35 and DROP 50

More info on page 50–53



flange



DRAIN PERFECT FOR USE WITH*:



* The manufacturer provides only the drain. The solutions referred to above are only demonstrative propositions.

INVISIBLE SLIM

The INVISIBLE SLIM linear shower drains are the concept of a visually minimalist take on standard linear drains. When installed, its parts are perfectly invisible. The only visible feature are the drain slots in the floor to accept the water through. This solution is recommended for floorings made of materials which can be cut and trimmed to obtain an aesthetic finish (like vitrified tiles or granite stone). The kitted linear drains feature the SMART TRAP®, a new, patented stainless-steel drain trap with a throughput of 26 l/min, the EASY CLEAN system, and a degreasing wipe to clean the substrate before adhesive bonding.

wiper®



INVISIBLE SLIM



For this product you can buy:

- SEALING MEMBRANE
- ADJUSTABLE LEGS PCL-1
- TANKING KIT s. 44



Discharge pipe dia. \varnothing 40 or \varnothing 50 if installed with the included reducer (adapter) piece

- Standard lengths L [mm]:
500, 600, 700, 800, 900, 1000, 1100, 1200


- Water flow rate acc. EN 1253 Q [l/min]:
26 - EN1253

- System EASY CLEAN

steel siphon



flange



STAINLESS STEEL



DURABILITY



GOOD QUALITY



CLEANABLE



100% RESISTANCE



CAPACITY



LOW HEIGHT



120°C



EASY INSTALLATION

DRAIN PERFECT FOR USE WITH*:

granite



marble



concrete



exotic wood



tempered glass



ELITE

The ELITE linear shower drains are modern drain units with sealing flanges. The ELITE drains feature frames with height adjustment from 8 to 12 mm (or up to 50 mm for thick flooring) and a 58 mm wide grate (with a 72 mm wide frame). An optional, perforated membrane is available to improve the adhesion to the installation substrate and reduce the setting time of the glue. The product is available in many versions to suit the needs of diverse projects.

wiper®



ELITE

NEW




Option with siphons also available

DROP 35 and DROP 50

More info on page 50–53

- adjustable height of space for tiles
- double drainage



* option

flange



surface finish



25 YEAR GUARANTEE

For this product you can buy:

- SEALING MEMBRANE
- ADJUSTABLE LEGS PCL-1
- TANKING KIT s. 44

○ Discharge pipe dia. \varnothing 40 or \varnothing 50 if installed with the included reducer (adapter) piece


• Standard lengths L [mm]:

500, 600, 700, 800, 900, 1000, 1100, 1200

• Water flow rate acc. EN 1253 Q [l/min]:

36 - siphon SNAKE

48 - siphon DROP 35 and DROP 50



STAINLESS STEEL



DURABILITY



GOOD QUALITY



CLEANABLE



100% RESISTANCE



CAPACITY



LOW HEIGHT



120°C



EASY INSTALLATION

PONENTE




PURE

ZONDA

MISTRAL

SIROCCO

TIVANO



ELITE SLIM

The ELITE SLIM linear shower drains are modern drain units with sealing flanges. The ELITE SLIM drains feature a low installation height of 64 mm up to the flange, frames with height adjustment from 8 to 12 mm (or up to 50 mm for thick flooring), and modern design lines, with the grate 34 mm wide only (with a 48 mm wide frame). The ELITE SLIM linear drains feature the SMART TRAP®, a new, patented stainless-steel drain trap with a flow rate of 26 l/min and the EASY CLEAN system. An optional, perforated sealing sleeve is available to improve the adhesion to the installation substrate and reduce the setting time of the glue.


wiper®



ELITE SLIM



- adjustable height of space for tiles
- double drainage



* option

steel siphon



flange



surface finish



○ Discharge pipe dia. \varnothing 40 or \varnothing 50 if installed with the included reducer (adapter) piece


• Standard lengths L [mm]:

500, 600, 700, 800, 900, 1000, 1100, 1200

• Water flow rate acc. EN 1253 Q [l/min]:

26 - EN1253

• System EASY CLEAN



STAINLESS STEEL



DURABILITY



GOOD QUALITY



CLEANABLE



100% RESISTANCE



CAPACITY



LOW HEIGHT



120°C



EASY INSTALLATION

PONENTE



PURE



SIROCCO



VINYL FLOOR

VINYL FLOOR shower gutters are specially designed linear drainage for installation in floors, which are to be covered with PVC flooring. Vinyl flooring is constantly gaining in popularity and for years has been used primarily in medical and beauty salons, hospitals, but also in offices and increasingly also in homes.

This trend has necessitated the creation of a completely new drain with a special snap-on design, which will allow the safe installation of a linear drain in a bathroom with PVC flooring. Vinyl Floor is made of high quality steel and crafted with high attention to detail so as to provide discerning customers with a luxury product that will last for years.



wiper®


VINYL FLOOR



○ Discharge pipe dia. \varnothing 40 or \varnothing 50 if installed with the included reducer (adapter) piece

- Standard lengths L [mm]:
500, 600, 700, 800, 900, 1000, 1100, 1200

- Water flow rate acc. EN 1253 Q [l/min]:
36 - siphon SNAKE
48 - siphon DROP 35 and DROP 50



For this product you can buy:

- TANKING KIT s. 54

NEW PRODUCT



Option with siphons also available
DROP 35 and DROP 50

More info on page 50-53

insulation flange



surface finish



STAINLESS STEEL



DURABILITY



GOOD QUALITY



CLEANABLE



100% RESISTANCE



CAPACITY



LOW HEIGHT



128°C



EASY INSTALLATION

PONENTE

LINE

MISTRAL

SIROCCO

BUBBLE

SPRINKLE




CLASSIC

The CLASSIC linear shower drains are a series of WIPER linear drains for installation in floors without a waterproofing layer. The finished installation provides a smartly refined grate and frame of stainless steel, 84 mm wide and as long as ordered, which means virtually any length desired. The product is available in many versions to suit the needs of diverse projects.

wiper®



CLASSIC



○ Discharge pipe dia. \varnothing 40 or \varnothing 50 if installed with the included reducer (adapter) piece

- Standard lengths L [mm]:
500, 600, 700, 800, 900, 1000, 1100, 1200

- Water flow rate acc. EN 1253 Q [l/min]:
36 - siphon SNAKE
48 - siphon DROP 35 and DROP 50



For this product you can buy:

- ADJUSTABLE LEGS PCL-1
- TANKING KIT s. 44

NEW



Option with siphons also available


DROP 35 and DROP 50

More info on page 50–53

no flange



surface finish



EYE-DRAIN

The EYE-DRAIN linear shower drains feature an all-new shape with sleek, refined lines to achieve a unique visual finish and the maximum functional performance and virtually unlimited service life. The WIPER Eye-drain is an innovative PREMIUM-class linear shower drains. It goes perfectly well with mosaic flooring patterns and natural stone. The kit includes a fitting membrane and height adjustment feet.



wiper®

EYE-DRAIN



Set contains:

- SEALING MEMBRANE
- ADJUSTABLE LEGS PCL-1

For this product you can buy:

- TANKING KIT s. 44

○ Discharge pipe dia. $\varnothing 40$ or $\varnothing 50$ if installed with the included reducer (adapter) piece


• Standard lengths L [mm]:

500, 600, 700, 800, 900, 1000, 1100, 1200

• Water flow rate acc. EN 1253

Q [l/min]: 29*

* value for A0



flange



surface finish



STAINLESS STEEL



DURABILITY



GOOD QUALITY



CLEANABLE



100% RESISTANCE



CAPACITY



LOW HEIGHT



120°C



EASY INSTALLATION



A4



A2L



A2



A1



A0

PREMIUM

ZKL / ZKPL / ZKP

The PREMIUM ZK linear shower drains are a series of WIPER linear drains complete with a membrane that helps with installation of the product in a floor system which features a water-proofing course. The flange is bent vertically (and with many options available) which facilitates installation at the floor-to-wall corners with an optimum offset between the grate and the wall tiles. The finished installation provides a smartly refined grate and frame of stainless steel, 84 mm wide and as long as ordered, which means virtually any length desired. The product is available in many versions to suit the needs of diverse projects.



PREMIUM ZKL / ZKPL / ZKP



ZKL



ZKPL



ZKP



• Water flow rate acc. EN 1253 Q [l/min]:

36 - siphon SNAKE

48 - siphon DROP 35 and DROP 50

⊙ Discharge pipe dia. \varnothing 40 or \varnothing 50 if installed with the included reducer (adapter) piece

NEW



Option with siphons also available

DROP 35 and DROP 50

More info on page 50–53

bent flange



surface finish



STAINLESS STEEL



DURABILITY



GOOD QUALITY



CLEANABLE



100% RESISTANCE



CAPACITY



LOW HEIGHT



120°C



EASY INSTALLATION

PONENTE




PURE




ZONDA



MISTRAL



SIROCCO



TIVANO




S-LINE

The S-LINE linear shower drains are an innovative solution unlocking freedom of shape of the drain embedded in the flooring. This product can be installed along a jacuzzi, a curved pool, or along any shape for a unique architectural design effect.



wiper®

S-LINE



For this product you can buy:

- SEALING MEMBRANE
- ADJUSTABLE LEGS PCL-1
- TANKING KIT s. 44

NEW



- Water flow rate acc. EN 1253 Q [l/min]:

36 - siphon SNAKE


48 - siphon DROP 35 and DROP 50

○ Discharge pipe dia. \varnothing 40 or \varnothing 50 if installed with the included reducer (adapter) piece


Option with siphons also available

DROP 35 and DROP 50

More info on page 50-53



flange



surface finish



STAINLESS-STEEL



DURABILITY



GOOD QUALITY



CLEANABLE



100% RESISTANCE



CAPACITY



LOW WEIGHT



120°C



EASY INSTALLATION

PONENTE


PURE

ZONDA

MISTRAL

SIROCCO

TIVANO



LINEAR DRAINS IN ANY LENGTH AND WITH OFFSET DRAIN TRAPS

The custom drains are available in any specified length and with an offset (a.k.a. side) trap. Each custom version requires individual pricing and a longer delivery time.

wiper®



LINEAR DRAINS...



○ Discharge pipe dia. \varnothing 40 or \varnothing 50 if installed with the included reducer (adapter) piece

• Water flow rate acc. EN 1253 Q [l/min]:

36 - siphon SNAKE

48 - siphon DROP 35 and DROP 50

For this product you can buy:

- SEALING MEMBRANE
- ADJUSTABLE LEGS PCL-1
- TANKING KIT s. 44

NEW




Option with siphons also available

DROP 35 and DROP 50

More info on page 50–53

flange



X, L – according to the order

surface finish



STAINLESS STEEL



DURABILITY



GOOD QUALITY



CLEANABLE



100% RESISTANCE



CAPACITY



LOW HEIGHT



120°C



EASY INSTALLATION

PONENTE



PURE

ZONDA

MISTRAL

SIROCCO

TIVANO



WP PREMIUM

WP PREMIUM is a series of WIPER point drains complete with a sealing flange that helps with installation of the product in a floor system which features a water-proofing course. An optional membrane can be used to greatly facilitate installation. The refined frame and the stainless steel grate crown the finish. The product is available in many versions to suit the needs of diverse projects.

wiper®





For this product you can buy:

- SEALING MEMBRANE
- ADJUSTABLE LEGS PCL-1
- TANKING KIT s. 44

NEW



• Measurements [mm]:

WP100 – 100 x 100

WP120 – 120 x 120

WP150 – 150 x 150

• Water flow rate acc. EN 1253 Q [l/min]:

36 - siphon SNAKE

48 - siphon DROP 35 and DROP 50

Option with siphons also available



DROP 50

More info on page 50–53

flange



surface finish



H _A - DROP 35	71 mm
H _B - DROP 50	83 mm



STAINLESS STEEL



DURABILITY



GOOD QUALITY



CLEANABLE



100% RESISTANCE



CAPACITY



LOW HEIGHT



120°C



EASY INSTALLATION

PONENTE



PURE




ZONDA



MISTRAL



SIROCCO



TIVANO



Only available with a siphon
McAlpine



WP CLASSIC

WP CLASSIC is a modern, minimalist shower floor system designed for easy installation in any bathroom. The refined design and high-quality materials crown the finished shower, offering a range of versions to suit your needs.

wiper®

WP CLASSIC is a series of WIPER point drains for installation in floors without a waterproofing layer. The refined frame and the stainless steel grate crown the finish. The product is available in many versions to suit the needs of diverse projects.



wiper®



• Measurements [mm]:

WP100 – 100 x 100

WP120 – 120 x 120

WP150 – 150 x 150

• Water flow rate acc. EN 1253 Q [l/min]:

48 - siphon DROP 35 i DROP 50

26 - siphon McAlpine CD-HC26-65



For this product you can buy:

- TANKING KIT s. 44

NEW



Option with siphons also available



DROP 50

More info on page 50–53

no flange



surface finish



H _A - DROP 35	71 mm
H _B - DROP 50	83 mm



STAINLESS STEEL



DURABILITY



GOOD QUALITY



CLEANABLE



CAPACITY



LOW HEIGHT



120°C



EASY INSTALLATION

PONENTE




PURE



ZONDA



MISTRAL



SIROCCO



TIVANO



Only available with a siphon
McAlpine

WP INVISIBLE

NEW

The WP INVISIBLE shower drains are the concept of a visually minimalist take on standard linear drains. When installed, the components are perfectly invisible. The only visible feature are the drain slots in the floor to accept the water through. This solution is recommended for floorings made of materials which can be cut and trimmed to obtain an aesthetic finish (like vitrified tiles or granite stone). The product kit includes a degreasing wipe to clean the substrate before adhesive bonding.

wiper®





For this product you can buy:

- SEALING MEMBRANE
- ADJUSTABLE LEGS PCL-1
- TANKING KIT s. 44

NEW



Option with siphons also available

DROP 50

More info on page 50–53

• Measurements [mm]:



WP100 – 100 x 100

WP120 – 120 x 120

WP150 – 150 x 150

• Water flow rate acc. EN 1253

Q [l/min]: 48



H _A - DROP 35	71 mm
H _B - DROP 50	83 mm

flange



STAINLESS STEEL



DURABILITY



GOOD QUALITY



CLEANABLE



100% RESISTANCE



CAPACITY



LOW HEIGHT



120°C



EASY INSTALLATION

DRAIN PERFECT FOR USE WITH*:

granite



marble



concrete

exotic wood

tempered glass

wiper®

wiper®



wiper®

WIPER TOP



○ Discharge pipe dia. \varnothing 40 or \varnothing 50 if installed with the included reducer (adapter) piece



For this product you can buy:

- TANKING KIT s. 44



• Measurements [mm]:

122 x 122

• Water flow rate acc. EN 1253

Q [l/min]: 30

Included:
dedicated sealing membrane and
steel flange



surface finish



STAINLESS-STEEL



DURABILITY



GOOD QUALITY



CLEANABLE



100% RESISTANCE



CAPACITY








LOW HEIGHT



120°C



EASY INSTALLATION




SHOWER SCREEN

VERRE

VERRE walk-in shower cabin comes in two color variants: VERRE BRIGHT timeless silver in gloss version and VERRE BLACK elegant modern black in matte version. The wall is made of 8 mm thick tempered glass with applied hybrid Active Shield coating protecting against dirt deposition and making it easier to keep clean. The wall mounting profile and stabilizing bracket with length adjustment up to 120 cm and angle adjustment of 180° make installation extremely easy and intuitive. The model of the cabins is universal and allows left and right installation.

wiper®






Advantages:

- glass: 8 mm toughened clear glass with Active Shield coating
- transparent glass does not optically take up space in the wet room
- easy to assemble
- surface finish: polish
- stainless steel stabilizing bracket with adjustable length up to 120 cm and 180° angle
- the door-less system offers plenty of space when showering

Works perfectly with:



• linear/square drains



• Solid Eye trays



• Showerlays



• tanking kits

BLACK



BRIGHT



Standard lengths [cm]:

A	H	B* max
50	200	120
60	200	120
70	200	120
80	200	120
90	200	120
100	200	120
110	200	120
120	200	120
130	200	120
140	200	120
150	200	120
160	200	120

*maximum length of mounting arm

SOLID EYE

NEW

A shower tray characterized by an elegant, modern design and a timeless form with an exclusive masking frame with an unprecedented innovative shape. Standard size is 1200 x 900 x thickness 30 mm. The surface has perfect/subtle slopes from and corner of the tray to the drain which provides effortless drainage. The Shower tray can be installed on an existing tiled surface or a screed with tiles layed up to the Shower tray.



SOLID EYE

Set consist of:

1. Composite shower tray
2. Eye-cover, stainless steel, polished surface
3. BRIDGE 90 siphon , 100% polypropylene



For this product you can buy:



- TANKING KIT s. 44

Solid Surface material

The shower tray is made of very durable Solid material Surface and is the latest generation of mineral-acrylic. It guarantees durability and high resistance to impact and abrasion. The shower tray area is easily renewable, Solid material in case of damage Surface allows for grinding and polishing, because it is uniform in cross-section and is characterized by its absence of pores. This composite material does not allow for the formation of fungi or bacterial growth and is resistant to the action of UV. Although it looks like it natural stone, unlike it, it gives very comfortable feeling of warmth.

Advantages:

- antibacterial properties
- easy to keep clean
- durable
- easy to renovate
- unchanging appearance over many years of use
- Eye cover - made of certified stainless steel
- Cover finish - super polished, the mirror effect, the highest quality available on the market
- the shower tray blends in perfectly with glass, wood and tiles
- new, modern, trendy solution



SHOWERLAY

The SHOWERLAY underfloor shower panels comprise an XPS board with a plastic reinforcing mesh, coated with a double coat of a dedicated cement mortar. The product includes a linear shower drain, complete with a cover, and a matching DROP35 drain trap. The essential advantages of the SHOWERLAY include: waterproofing, a slope towards the linear drain, perfect adhesion to top board layer, the top board layer strength sufficient for safe laying of even the finest mosaic tiles, and high acoustic insulation performance.



wiper®



For this product you can buy:





- TANKING KIT s. 44

The properties of the WIPER SHOWERLAY prefabricated panels:

- 100-percent efficient waterproofing
- Downgrade towards the linear/point drain
- Perfect adhesion to top board layer
- The top board layer strength sufficient for safe laying of even the finest mosaic tiles
- High acoustic insulation performance
- Available panel thickness: 20, 30, 40, or 50 mm
- The XPS board needs to be supported under the full surface after the installation
- We can produce other sizes and arrangements of drains on custom order

To specify your order, provide these details:

1. The shower tray thickness (20, 30, 40, or 50 mm)
2. Shower tray type (LINE – with a linear drain or POINT – with a point drain)
3. Overall shower tray size in plan: X and Y
4. Linear/point drain grate design



STAINLESS STEEL



LOW/HIGH



DURABILITY



120°C




GOOD QUALITY



EASY INSTALLATION



CLEANABLE



HEAT INSULATION



100% RESISTANCE



SLOPE SURFACE



CAPACITY



ACOUSTIC INSULATION

SHOWERLAY ONEWAY

NEW

OneWay underfloor single-pitched showerlay were created in response to customer demand. They are made of XPS board in a set with a factory-mounted and sealed stainless steel linear drain with a grate in a pattern to choose from and a DROP 35 drain siphon. Simple and modern solution for creating a walk-in shower tray.





For this product you can buy:



- TANKING KIT s. 44

The properties of the WIPER SHOWERLAY prefabricated panels:

- 100-percent efficient waterproofing
- Slope towards the linear drain
- Perfect adhesion to top board layer
- The top board layer strength sufficient for safe laying of even the finest mosaic tiles
- High acoustic insulation performance
- Available panel thickness: 30 or 40 mm
- The XPS board needs to be supported under the full surface after the installation
- We can produce other sizes and arrangements of drains on custom order

To specify your order, provide these details:

1. The shower tray thickness (30 or 40 mm)
2. Overall shower tray size in plan: X and Y
3. Linear drain grate design



STAINLESS STEEL



LOW HIGH



DURABILITY



120°C



GOOD QUALITY



EASY INSTALLATION



CLEANABLE



HEAT INSULATION



100% RESISTANCE



SLOPE SURFACE



max

CAPACITY



ACOUSTIC INSULATION

SHOWERLAY ELITE

Showerlay Elite underfloor shower panels are the ideal solution for custom height tiles. The integrated XPS slab along with the Elite linear shower drain features a reliable dual drainage system, so the user can be sure that no water will collect under the tiles. The drain is available in five color versions so that it gives the room an elegant look that matches the rest of the fixtures.



wiper®

SHOWERLAY ELITE



For this product you can buy:






• TANKING KIT

The properties of the WIPER SHOWERLAY ELITE prefabricated panels:


- 100-percent efficient waterproofing
- Dual drainage system
- High acoustic insulation performance
- Perfect adhesion to top board layer
- The top board layer strength sufficient for safe laying of even the finest mosaic tiles
- Available panel thickness: 20, 30, 40, or 50 mm
- The XPS board needs to be supported under the full surface after the installation
- Five color versions of the drain (gold, honey gold, bright gold, silver, black)
- We can produce other sizes and arrangements of drains on custom order

To specify your order, provide these details:

1. The shower tray thickness (20, 30, 40, or 50 mm)
2. Overall shower tray size in plan: X and Y
3. Linear drain grate design



* option



SHOWERBASE

SHOWERBASE underfloor shower trays include an XPS slab with an adhered sealing mat, a shower gutter including a grid in a pattern of your choice, and a corresponding DROP35 drain trap. The main advantages of SHOWERBASE are: 100% double waterproofing, profiled slope towards the drain gutter, excellent adhesion of glue to the top layer of the board, hardness of the top layer allowing gluing even very small mosaics, high sound insulation, increased size of the mat in relation to the board allowing good sealing.



wiper®



For this product you can buy:





- TANKING KIT

The properties of the WIPER SHOWERBASE prefabricated panels:

- 100-percent efficient waterproofing
- Downgrade towards the linear/point drain
- Perfect adhesion to top board layer
- The top board layer strength sufficient for safe laying of even the finest mosaic tiles
- High acoustic insulation performance
- Available panel thickness: 20, 30, 40, or 50 mm
- The XPS board needs to be supported under the full surface after the installation
- We can produce other sizes and arrangements of drains on custom order

To specify your order, provide these details:

1. The shower tray thickness (20, 30, 40, or 50 mm)
2. Shower tray type (LINE – with a linear drain or POINT – with a point drain)
3. Overall shower tray size in plan: X and Y
4. Linear/point drain grate design



STAINLESS STEEL



LOW HIGH



DURABILITY



120°C




GOOD QUALITY



EASY INSTALLATION



CLEANABLE



HEAT INSULATION



100% RESISTANCE



SLOPE SURFACE



CAPACITY



ACOUSTIC INSULATION

SHOWERBASE ELITE

Showerbase Elite is a combination of functionality (dual drainage system, adjustable drain height, 100% waterproofing) and an affordable floor slab installation process. The slab is available in a variety of sizes and four basic thicknesses, which make it possible to achieve a properly contoured slope towards the drainage. Take advantage of Showerbase Elite floor slab if you need a reliable solution for your bathroom.


wiper®





For this product you can buy:

- TANKING KIT
- adjustable tile space height
- dual drainage system








* option

The properties of the WIPER SHOWERLAY ELITE prefabricated panels:

- 100-percent efficient waterproofing
- Dual drainage system
- High acoustic insulation performance
- Perfect adhesion to top board layer
- The top board layer strength sufficient for safe laying of even the finest mosaic tiles
- Available panel thickness: 20, 30, 40, or 50 mm
- The XPS board needs to be supported under the full surface after the installation
- Five color versions of the drain (gold, honey gold, bright gold, silver, black)
- We can produce other sizes and arrangements of drains on custom order

To specify your order, provide these details:

1. The shower tray thickness (20, 30, 40, or 50 mm)
2. Overall shower tray size in plan: X and Y
3. Linear drain grate design



SHOWERBASE VF

Showerbase VF is a lightweight panel made of extruded polystyrene (XPS) additionally coated with a flexible cement adhesive and a waterproof sealing membrane. Installed in the shower tray, the stainless steel Wiper VF drain is a special snap-in design for use with vinyl liners. Installation is done by clamping the liner frame into the drain.

wiper®





Do tego produktu możesz dokupić:

- TANKING KIT

insulation flange








The properties of the WIPER SHOWERLAY VF prefabricated panels:

- 100-percent efficient waterproofing
- Ideal for a vinyl floor covering.
- High acoustic insulation performance
- Perfect adhesion to top board layer
- Shower tray can be easily trimmed on-site
- Available panel thickness: 20, 30, 40, or 50 mm
- The XPS board needs to be supported under the full surface after the installation
- Mechanical locking system, allowing the edges of the vinyl being clamped and protected
- We can produce other sizes and arrangements of drains on custom order

To specify your order, provide these details:

1. The shower tray thickness (20, 30, 40, or 50 mm)
2. Overall shower tray size in plan: X and Y
3. Linear drain grate design




SYSTEM ISOL-ONE

ISOL-ONE is a complete system of waterproofing and sealing products for wet rooms and surfaces which require waterproofing layer: bathrooms and shower units in private homes, hotels, and public buildings. The ISOL-ONE sealing mat is made of polyethylene film, both sides of which are coated with a specially formulated cloth for better bonding of the adhesive. It is recommended for installation in all rooms which require this sealing and waterproofing method. The mat is impervious to substrate cracking, ensures a secure waterproof seal over its whole surface of coverage, and reduces the installation time by allowing tile laying directly after adhesive bonding of the mat. Flexible quick-setting adhesives are recommended for the installation process, e.g. PCI Rapid Light.



SYSTEM ISOL-ONE


ISOL-ONE M100
ISOL-ONE M200
sealing mat




ISOL-ONE T
sealing tape





ISOL-ONE NZ
internal sealing corner



ISOL-ONE NW
external sealing corner



ISOL-ONE O
pipe collar



For this product you can buy:

- TANKING KIT s. 44

The ISOL-ONE installation sealing mat is made of polyethylene film, both sides of which are coated with a specially formulated cloth for better bonding of the adhesive. It is recommended for installation in all rooms which require this sealing and waterproofing method. The ISOL-ONE mat is light-weight and resists corrosion and decomposition, ensures a level thickness of the waterproofing layer, resists cracking of the substrate, ensures a secure waterproof seal over its whole surface of coverage, and reduces the installation time by allowing tile laying directly after adhesive bonding of the mat. The components are made of thermoplastic elastomer coated with cloth on both sides. This endows the product with high flexibility and resistance to aggressive media. The mat highly protects corners, edges, superficial cracks, and plumbing penetrations against ingress of moisture by forming elastic and durable joints.

PROPERTIES:

- Watertight
- Plastic
- Bridges cracks
- Ready to use
- Reduced time to proceed with downstream work

ADVANTAGES:

- Binds with every tile laying system
- Seals corner grout in wet rooms by forming flexible and durable joints

APPLICATION:

- Indoor and outdoor
- For walls and floors
- For wet rooms, e.g. bathrooms and shower units in private homes, hotels, and public buildings (moisture load classes A01, A02, A1, and A2)
- Balconies and patios
- For water-sensitive surfaces, e.g. gypsum plaster, gypsum blocks and panels, drywall panels, and chipboards
- For installation on water-absorbing mineral substrates, e.g. concrete, screed, cement render, cellular concrete, cement-based putties, and levelling compounds



DURABILITY



GOOD QUALITY



100% RESISTANCE



ELASTICITY

TANKING KIT FOR SHOWER CABIN

The sealing kit is intended for waterproofing of substrates to be clad in ceramic tiles inside of wet rooms. It is recommended for locations which require a high waterproof performance in presence of high moisture levels (like shower units, bathrooms, toilets, laundry rooms, kitchens, etc.). The waterproofing solution is suitable for all substrate types: drywall panels, plastered walls, gas concrete masonry walls, engineered wood, old cladding of ceramic or stone, and more.

wiper®



TANKING KIT

TANKING KIT INCLUDES:

- tanking liquid 4 kg




- primer 1 l




- sealing tape 10 m



- pipe collar 2 pcs.



- corners 2 pcs.



TANKING LIQUID:

The tanking liquid is a ready-to-use, one-component solvent free sealing compound based on a dispersion of polymers, fillers, and modifiers. When applied to the substrate and set, the product forms a waterproofing coating. The product is intended for permanently occupied interiors, predominantly wet rooms (like bathrooms, kitchens, and laundry rooms), for waterproofing underneath cladding and flooring made with ceramic tiles, glazed tiles, terracotta, timber and wooden panel floorings, and synthetic carpets.

PRIMER:

The product is intended for priming of absorbing, porous substrates indoors and outdoors. It is especially recommended for lime and cement plaster, gas concrete, drywall panels, and cement render. The primer highly penetrates the substrate which deeply absorbs it, becoming stronger and still breathing vapours. These advantages improve the structure of the substrates which have degraded over time. The priming solution improves adhesion of materials to be applied to the sealed substrate. By reducing the absorptivity of the substrate, the yield of applied emulsion paints, adhesives, and mineral putties is improved. The solution contains a biocidal and a fungicidal which preserves the substrate against mould and bacterial growth in the product container.



DURABILITY



GOOD QUALITY



100% RESISTANCE



EASY APPLICATION



RAPID BINDING



HIGH PERFORMANCE

SUNFLOOR HEATING MATS

NEW

The SUNFLOOR heating mat is a modern, easy to install solution to provide the primary or auxiliary heating system at your home. It is thin (4 mm), which makes it easy to install without making the flooring system thicker. The heating mat can be easily embedded in a layer of levelling screed or adhesive mortar, directly under the tiles, without raising the floor surface.



wiper®

SUNFLOOR HEATING MATS



Product kitting:

- 50 cm x 2 ÷ 30 m heating mat
- Thermostat with Wi-Fi connectivity (optional)
- Floor temperature sensor
- Shielding zip tube
- Mobile app
- Detailed instructions

The roll width is 50 cm. Thanks to this, the mat can be easily laid out in small rooms, like bathrooms. The mesh to which the cable is attached can be freely trimmed to size and make turns, U-turns, or bypass furniture or other fittings. Do not damage the heating cable while cutting the product to size. The mesh is coated with an adhesive for much easier initial layout fitting. When finally aligned, the mat can be bonded in place with self-adhesive strips.

The digital controller offered for Sunfloor heating system is a modern digital device with Wi-Fi connectivity for convenient operation with mobile devices. The controller features a modern, minimalist design for a discreet match for any bathroom style. The intuitive touch control panel makes operation user-friendly. The compact front face size of 8.5 x 8.5 cm and a low depth make flush installation easy. The controller provides plenty of convenient features, like open window detection, night mode, anti-freezing mode, and much more. A single unit supports a system of 3600 watts maximum (max. load of 16 amps, which is approximately 23 m²).

The manual controller has two temperature sensors (built-in air and floor sensors for connection), thanks to which it is possible to precisely determine the room temperature in depending on the situation. The device has two visible buttons (switch and control knob temperature), making it very easy to use. In addition, the driver has the appropriate safeguards that prevent damage to the heating system. Choosing air temperature sensor option with floor temperature limit during device installation, you can easily protect e.g. a wooden floor against overheating.

The Warmme app is very simple to configure, intuitive software that allows you to remotely monitor and set the heating temperature with a mobile phone connected to the same Wi-Fi network as the thermostat control. The app allows you to configure separate temperature settings for different rooms. You can define an advanced heating schedule to reduce energy consumption when no one is at home or when a lower indoor temperature is required at night. You can download the Warmme mobile app to your phone from Google Play or Apple App Store by scanning the QR code from the manual sheet included with the controller.



SUNFLOOR HEATING FOIL

Sunfloor heating film is the ideal solution for providing additional heating under the panels in any home. The biggest advantage of the heating film is the fact that it is installed in a dry system, i.e. without forging in the floor and subsequent sinking into the screed or glue. The foil is efficient, yet economical. It heats up quickly and gives a pleasant, natural heat radiating from the lowest parts of the room.



wiper®

**Skład zestawu:**

- heating foil on a roll
- flexible sensor tube
- insulation tape
- connection terminals
- connection leads
- clear step-for-step installation instruction
- pressure distribution and crimping pliers

The heating foil is designed for use under laminate, wood panels, planks and parquet. It is installed in a dry system, that is, without the need for forging in the floor and subsequent sinking into the screed or glue as in the case of heating mats. It is ideal as an additional source of heat in living rooms, hallways, corridors, bedrooms or offices.

The foil is efficient, yet economical. It heats up quickly and gives a pleasant, natural heat radiating from the lowest parts of the room. Unlike other types of heating such as air conditioners or stoves or radiators, it requires no additional operation or maintenance and is completely invisible. Underfloor heating offers the most human-friendly, even temperature distribution in the room and is a type of heating recommended for allergy sufferers due to less convective movement, which translates into less dust circulating in the air.



The Warmme app is very simple to configure, intuitive software that allows you to remotely monitor and set the heating temperature with a mobile phone connected to the same Wi-Fi network as the thermostat control. The app allows you to configure separate temperature settings for different rooms. You can define an advanced heating schedule to reduce energy consumption when no one is at home or when a lower indoor temperature is required at night. You can download the Warmme mobile app to your phone from Google Play or Apple App Store by scanning the QR code from the manual sheet included with the controller.



WIPER SOUND STOP

SOUNDPROOF MAT



NEW

The Wiper Sound Stop sound insulating mat is recommended for acoustic insulation between two adjacent building floors. It effectively absorbs noise and vibration in every shower unit. Sound insulation is recommended for shower units with a low installation height, which results in higher noise due to the acoustic layer originally missing from the separating floor plans.

wiper®



WIPER SOUND STOP



The mat size is 125 x 125 cm with a thickness of mere 0.6 cm. The normal sound reduction over a 35 mm thick screed coat is 19 dB(A). The material is reprocessed rubber with a dedicated PUR elastomer binder. Compared to other acoustic insulation systems, it is extremely resistant to pressure and compression.

Material:
Granulated rubber with PUR elastomer binder

Surface:
Smooth with a grainy texture

Surface unit weight:
3.870 to 4.730 g/m²

Density:
680 to 750 kg/m³

Compressibility:
(DIN EN 12431) < 1.0 mm

Dynamic stiffness:
< 70 MN/m³

Max. pressure:
(EN 826) 0.2 N/mm²

Tensile strength:
(ISO 1798) approx. 0.4 N/mm²

Ultimate elongation:
(ISO 1798) approx. 50%

Temperature range:
-30 °C to 80 °C


Heat transfer coefficient:
(ISO 8302) 0.05 m² K/W

Flammability class:
(ISO 13501) E

Impact sound reduction:
 $\Delta LW = 19 \text{ dB}$ at 6 mm
(over 35mm thick screed)

Emission level:
AgBB program compliant

Diagram of the assembly of the soundproofing mat:



1. leveled substrate
2. soundproof mat
3. isolation foil PE

4. screed
5. waterproofing

6. tile adhesive
7. flooring

SIPHONS

shower trap siphon BRIDGE 90



- **Material**
Hostalen PP
(Polipropylene 100 %)
- **Water seal**
25 mm
- **Height**
45 mm
- **Filter**
Polipropylene
- **Drain diameter**
fi 40 mm
- **Connection**
fi 90 mm
- **Capacity**
32 l/min acc. EN 1253
- **Reducer**
fi 40 mm / 50 mm

NEW

siphon H+M SNAKE



- **Material**
Hostalen PP
(Polipropylene 100 %)
- **Capacity**
36 l/min acc. EN 1253
- **Reducer**
fi 40 mm / 50 mm
- **Filter**
Polipropylene
- **Water seal**
30 mm
- **Height**
45 mm
- **Sealing**
Evopren
- **Drain diameter**
fi 40 mm



- **OPTIONAL dry trap**
A replacement for the inspection tube, it is an inner insert with an odor-stopping membrane to prevent foul smell if the water evaporates.
Capacity 22 l/min

siphon H+M DROP 35



- **Material**
Hostalen PP
(Polipropylene 100 %)
- **Capacity**
48 l/min acc. EN 1253
- **Height**
66 mm
- **Filter**
Polipropylene
- **Water seal**
35 mm
- **Sealing**
Evopren
- **Drain diameter**
fi 50 mm

siphon H+M DROP 50



- **Material**
Hostalen PP
(Polipropylene 100 %)
- **Capacity**
48 l/min acc. EN 1253
- **Height**
78 mm
- **Filter**
Polipropylene
- **Water seal**
50 mm
- **Sealing**
Evopren
- **Drain diameter**
fi 50 mm

siphon H+M PUSH 35



- **Material**
Hostalen PP
(Polipropylene 100 %)
- **Drain diameter**
fi 50 mm

- **Capacity**
48 l/min acc. EN 1253
- **Height**
62 mm

- **Water seal**
35 mm

siphon H+M PUSH 50



- **Material**
Hostalen PP
(Polipropylene 100 %)
- **Drain diameter**
fi 50 mm

- **Capacity**
48 l/min acc. EN 1253
- **Height**
76 mm

- **Water seal**
50 mm

stub / siphon VERTI 50



- **Material**
Polipropylene
- **Height**
57 mm

- **Filter**
Polipropylene

- **Drain diameter**
fi 50 mm

siphon MCALPINE F HC2730LCPN-PB



- **Material**
Polipropylene
- **Water seal**
40 mm

- **Filter**
Polipropylene
- **Drain diameter**
fi 50 mm

- **Capacity**
31 l/min acc. EN 1253
- **Height**
88 mm

siphon MCALPINE HC26-Wiper-65



- **Material**
Polipropylene
- **Water seal**
20 mm

- **Filter**
Polipropylene
- **Drain diameter**
fi 50 mm

- **Capacity**
26 l/min acc. EN 1253
- **Height**
68 mm

siphon MCALPINE N CD-HC26-65



- **Material**
Polipropylene
- **Water seal**
20 mm

- **Filter**
Polipropylene
- **Drain diameter**
fi 50 mm

- **Capacity**
26 l/min acc. EN 1253
- **Height**
68 mm

siphon MCALPINE HC26-Wiper-V50-CD



- **Material**
Polipropylene
- **Water seal**
20 mm

- **Filter**
Polipropylene
- **Drain diameter**
fi 50 mm

- **Capacity**
53 l/min acc. EN 1253
- **Height**
132 mm

HYGIENIC CERTIFICATE

All WIPER brand linear shower drains are Hygiene-Certified by PZH-NIH, the Polish National Institute of Hygiene under its "Certified Product" program.



TABLE OF POSSIBLE CONFIGURATIONS

	PREMIUM	PREMIUM ZK	PREMIUM SLIM	INVISIBLE	INVISIBLE SLIM	ELITE	ELITE SLIM	CLASSIC	EYE-DRAIN	WP PREMIUM	WP INVISIBLE	WP CLASSIC	WIPER TOP
Standard sizes	500÷1200	500÷1200	500÷1200	500÷1200	500÷1200	500÷1200	500÷1200	500÷1200	500÷1200	100 x 100 120 x 120 150 x 150	100 x 100 120 x 120 150 x 150	100 x 100 120 x 120 150 x 150	120 x 120
Custom sizes	○	○	○	○	○	○	○	○	○	×	×	×	×
Sealing membrane	○	○	○	○	○	○	○	×	●	○	○	×	●
Integrated sealing membrane	○	○	○	○	○	○	○	×	○	○	○	×	×
Adjustable legs	○	○	○	○	○	○	○	○	○	○	○	×	×
Siphon SNAKE	●	●	×	●	×	●	×	●	×	×	×	×	×
Siphon DROP 35	●	●	×	●	×	●	×	●	×	●	●	●	×
Siphon DROP 50	●	●	×	●	×	●	×	●	×	●	●	●	×
Horizontal siphon McAlpine HC26	●	●	×	●	×	●	×	●	●	●	●	●	×
Horizontal stainless steel siphon SMART TRAP	○	○	●	○	●	○	●	○	○	○	○	○	×
Vertical stainless steel siphon SLIM	○	○	○	○	○	○	○	○	○	○	○	○	×
Second siphon	○	○	○	○	○	○	○	○	○	×	×	×	×
Surface polish/ brush/ matt	●	●	●	×	×	●	●	●	●	●	×	●	●
Bent flange	○	○	○	○	○	○	○	×	×	×	×	×	×



standard



option available at extra charge



not available



WIPER Sp. z o.o.
ul. Kolejowa 2
43-190 Mikołów
POLAND

+48 (32) 738 5000
poczta@wiper.pl

www.wiper.pl