





Model 60


Front




Side




Model R



Model L



Bottom



- Outdoor air (1) ● Supply air (2) ● Extract air (3)
- Exhaust air (4) ● Kitchen bypass (5)
- Condensate outlet (6)

Dimensions (width x height x depth)	558 x 450 x 558
Weight	41 kg
Duct outlets	4 x 160, 1 x 125
Kitchen bypass	Vakiovaruste
Condensate fitting	Centre, 66 mm from rear edge
Condensation water tray	Tilted condensation water tray
Max. extract air flow rate (100 Pa)	385 m ³ /h (107 dm ³ /s)
Max. supply air flow rate (100 Pa)	356 m ³ /h (99 dm ³ /s)
Specific energy consumption (SEC) in a cold climate	A+
Specific energy consumption (SEC) in an average climate	A
Extract air heat recovery annual efficiency class	A+/A (kitchen bypass in use)
Air handling unit's specific electrical power class at rated air flow	A
Electricity	230 V, 50 Hz, 10 A, max.1165 W: Plug
Apartment size max. m ² *	200 m ²

Summer/winter function

Automatic, adjustable	Standard equipment
-----------------------	--------------------

Defrosting automation

Continuous supply air, AFPS	Standard equipment
-----------------------------	--------------------

Post heater

920 W (electric)

Equipment

Ceiling mount bracket	Accessory
Wall mount bracket	Accessory
Stand	Not available
Vapour barrier filler plate	Accessory
Humidity transmitter (internal)	Standard equipment
Humidity transmitter	Accessory
Carbon-dioxide transmitter	Accessory
Cooling radiators	Accessory
Filter guard	Accessory
Constant pressure control	Accessory
Spring return damper	Accessory
Airfi KNX adapter	Accessory

Controls

Uno, Sento, Mille-Wire, Mille-Wifi	Standard equipment
Control hoods	Standard equipment
VAK, DDC, 10VDC, Transmitter controls Modbus RTU/TCP, Ethernet	Standard equipment

*Implementation according to designer's ventilation plan.

Models

Models	Product code	HVAC number
Model 60 (R) Electric	10 060 011	7916041
Model 60 (L) Electric	10 060 021	7916042