

Transmitter overview

Making fresh air sustainable



Model name		Pressure	Temperature	Humidity	CO ₂	VOC	Field scalable	Supply voltage	Analog output 2-wire	Analog output 3-wire	Digital output	IP Rating
Feel 	Best for accuracy, most options	1, 10, 100, 1000 hPa 0.2 % 0.5 % 1 % Full Scale	-40 ... +80 °C 0.2 K	0 ... 100 % r. H. 2 % Full Scale	2000 or 5000 ppm 50 ppm +2 or +3 %	0 ... 500 VOC 15 % Full Scale	DIP-Switch PC Software	24 V ac/dc	-	0-10 V 2-10 V 4-20 mA 0-20 mA	Modbus RTU	IP 65
Base  new!	Best price in high volume	30 Pa ... 1000 hPa 1 % Full Scale	-20 ... +80 °C 0.2 K	0 ... 100 % r. H. 2 % Full Scale	-	-	PC Software	24 V ac/dc	-	0-10 V 2-10 V 4-20 mA 0-20 mA	-	IP 65
PrimAtue 	Best for industrial 230 V	30 Pa ... 1000 hPa 0.2 % 0.5 % 1 % Full Scale	-	-	-	-	-	24 V ac/dc optional 230 V ac	-	0-10 V 2-10 V 4-20 mA 0-20 mA	Modbus RTU	IP 65
DS01+ 	Best for distributors	1, 10, 100 hPa 1 % Full Scale	-	-	-	-	DIP-Switch	19 ... 31 V dc	4-20 mA	0-10 V 2-10 V 4-20 mA 0-20 mA	-	IP 65
BAP  new!	Best for barometric applications	500 ... 1200 hPa abs. 1 % Full Scale	-	-	-	-	DIP-Switch	19 ... 31 V dc	4-20 mA	-	-	IP 65