

## Models MIGI 502 HB and MIGI 502 HBE

### INTEGRATED GENERATOR WITH COMPRESSOR

|                  |                                 |
|------------------|---------------------------------|
| Engine           | HONDA mod. GX 390               |
| Power / RPM      | 6,4 kW (8,6 HP) / 3.000 rev/min |
| Fuel             | Gasoline                        |
| Fuel Tank        | 6,1 l                           |
| Fuel Consumption | 3,5 l/h                         |
| Ignition         | Manual                          |
| Ignition         | Electric (Optional)             |
| Cooling          | Forced Air                      |

### GENERATOR

|                        |                               |
|------------------------|-------------------------------|
| Alternator             | 115/230 V Single-Phase        |
| Alternator             | 400 V Three-Phases (Optional) |
| Power / Frequency      | 7,0 kVA / 50 Hz               |
| Power Factor           | Cos $\phi$ 0,8                |
| Power with AUX Service | 3,0 kVA                       |

### AIR COMPRESSOR

|                              |                                  |
|------------------------------|----------------------------------|
| Air Compressor               | Two Cylinders                    |
| Revolutions per Minute (RPM) | 1,420 rev/min                    |
| Air Production               | 360 l/min – 22 m <sup>3</sup> /h |
| Max Pressure                 | 10 bar - PSI 145                 |
| Internal Tank (Aluminium)    | 10 l                             |
| External Tank (Aluminium)    | 60 l (Optional)                  |

### GENERAL FEATURES

|                                               |                      |
|-----------------------------------------------|----------------------|
| Dimension L x W x H                           | 1,100 x 610 x 680 mm |
| Weight 220 V Single-Phase (Manual Ignition)   | 160 kg               |
| Weight 220 V Three-Phases (Electric Ignition) | 170 kg               |
| Weight 400 V Single-Phase (Manual Ignition)   | 175 kg               |
| Weight 400 V Three-Phases (Electric Ignition) | 185 kg               |
| Noise Level                                   | LWA 95 dB            |
| Protection Class                              | IP 23                |



Model MIGI 502 HB / HBE

**60 l** capacity aluminum tank (Ø 310 x 1,000 mm, weight 12 kg) complete with quick connections, safety valve and pressure gauge

