



PRODUCT CATALOGUE **2024**



**TRANSPARENT
SOLUTIONS**



VALUE QUALITY RESPECT PRICE

32 years of experience

70 products

20 export countries around the world

100 distributors

The beginning of our experience on international Car Refinish market date back to 1992. Based on extensive knowledge, experience and continuous development on the Polish and European paint market Exlak specialised in production of transparent and colorless products for Car Refinish. We realize our production based on the Quality Management System according to ISO 9001 and the Environmental Management System according to ISO 14001. In order to meet the needs of the market, we establish cooperation both on the basis of distributing our brand and give the opportunity to sell our products under a private brands.

Clearcoats		Hardeners	6
Thinners		Silicone Removers	18
Additives		Primers	23
Binders		Universal hardeners	27

**ONLY REPUTABLE
MANUFACTURERS**

We focus on careful selection
of raw chemical materials
in our production process

They come only from recognized and reputable producers of the global chemical market. Thanks to this policy, we are able to produce and offer high-quality products, which, combined with technical knowledge and over 32 years of experience, we offer at attractive prices.

**CREATE YOUR
BRAND WITH US**







Would you like your logo to appear
on our products? It's a great solution
to promote your own business.

**CREATE YOUR
BRAND WITH US**

Unseen, but effective protection for your car

Clearcoat is an invisible and important protection of the car body against mechanical factors and weather conditions. It also gives the vehicle an aesthetic value through the high gloss effect and color depth. Depending on the desired final effect and properties during the use of the product, we offer various types of clearcoats.



 2:1 + 8 - 9%	 15 h - 20°C 45 min - 50°C
 2 layers 2 - 2.5 bar Ø 1.2 - 1.4 mm	 10 - 12 min





Clearcoat Optimal MS

- › Medium solid content and high density
- › Excellent flow and easy application
- › Good gloss
- › Good resistance to UV rays and weather conditions
- › Ideal for hot climates
- › Easy to polish

NAME	VOLUME	PACKAGE
Clearcoat	1 l	12 pcs
Clearcoat	5 l	4 pcs
Hardener normal	0.5 l / 2.5 l	12 / 4 pcs
Hardener rapid	0.5 l / 2.5 l	12 / 4 pcs
Hardener slow	0.5 l / 2.5 l	12 / 4 pcs

For individual orders we provide sets of 0.4 l + 0.2 l or 0.5 l + 0.25 l



 2:1 + 0 - 5%	 15 h - 20°C 45 min - 50°C
 2 layers 2 - 2.5 bar Ø 1.2 - 1.4 mm	 10 - 12 min

Clearcoat Optimal PLUS

- › Fast drying
- › Easy application
- › Easy to polish
- › Good gloss
- › Can be applied without adding thinner
- › Good resistance to UV rays and weather conditions
- › Yellowing resistant

NAME	VOLUME	PACKAGE
Clearcoat	1 l	12 pcs
Clearcoat	5 l	4 pcs
Hardener normal	0.5 l / 2.5 l	12 / 4 pcs
Hardener rapid	0.5 l / 2.5 l	12 / 4 pcs
Hardener slow	0.5 l / 2.5 l	12 / 4 pcs

For individual orders we provide sets of 0.4 l + 0.2 l or 0.5 l + 0.25 l




Clearcoat CAR


- › Fast drying
- › Easy application
- › Easy to polish
- › Good gloss
- › Can be applied without adding thinner
- › Good resistance to UV rays and weather conditions
- › Yellowing resistant

NAME	VOLUME	PACKAGE
Clearcoat	1 l	12 pcs
Clearcoat	5 l	4 pcs
Hardener normal	0.5 l / 2.5 l	12 / 4 pcs
Hardener rapid	0.5 l / 2.5 l	12 / 4 pcs
Hardener slow	0.5 l / 2.5 l	12 / 4 pcs


For individual orders we provide sets of 0.4 l + 0.2 l or 0.5 l + 0.25 l




2 : 1 + 0 – 5%



14 h – 20°C
45 min – 50°C



2 layers
2 – 2.5 bar
Ø 1.2 – 1.4 mm



10 – 12 min




Clearcoat CARLUX


- › Fast drying
- › Good gloss
- › Can be applied with up to 15% of thinner
- › Easy application
- › Easy to polish
- › Good resistance to UV rays and weather conditions
- › Yellowing resistant

NAME	VOLUME	PACKAGE
Clearcoat	1 l	12 pcs
Clearcoat	5 l	4 pcs
Hardener normal	0.5 l / 2.5 l	12 / 4 pcs
Hardener rapid	0.5 l / 2.5 l	12 / 4 pcs
Hardener slow	0.5 l / 2.5 l	12 / 4 pcs


For individual orders we provide sets of 0.4 l + 0.2 l or 0.5 l + 0.25 l




2 : 1 + 10 - 15%



14 h – 20°C
45 min – 50°C



2 layers
2 – 2.5 bar
Ø 1.2 – 1.4 mm



10 – 12 min




Clearcoat AT-100 MS


- › Fast drying
- › Easy application
- › Easy to polish
- › Very good gloss
- › Can be applied without adding thinner
- › Very good durability and resistance to UV rays and weather conditions
- › Yellowing resistant

NAME	VOLUME	PACKAGE
Clearcoat	1 l	12 pcs
Clearcoat	5 l	4 pcs
Hardener normal	0.5 l / 2.5 l	12 / 4 pcs
Hardener rapid	0.5 l / 2.5 l	12 / 4 pcs
Hardener slow	0.5 l / 2.5 l	12 / 4 pcs


For individual orders we provide sets of 0.4 l + 0.2 l or 0.5 l + 0.25 l




2 : 1 + 0 – 5%



15 h – 20°C
45 min – 50°C



2 layers
2 – 2.5 bar
Ø 1.2 – 1.4 mm



10 – 12 min




Clearcoat AT-100 PLUS


- › Fast drying
- › Easy application
- › Similar to AT-100 MS with higher viscosity
- › Very good gloss
- › Can be applied with up to 6% of thinner
- › Very good durability and resistance to UV rays and weather conditions
- › Yellowing resistant

NAME	VOLUME	PACKAGE
Clearcoat	1 l	12 pcs
Clearcoat	5 l	4 pcs
Hardener normal	0.5 l / 2.5 l	12 / 4 pcs
Hardener rapid	0.5 l / 2.5 l	12 / 4 pcs
Hardener slow	0.5 l / 2.5 l	12 / 4 pcs


For individual orders we provide sets of 0.4 l + 0.2 l or 0.5 l + 0.25 l




2 : 1 + 4 – 6%



14 h – 20°C
45 min – 50°C



2 or 1.5 layer
2 – 2.5 bar
Ø 1.2 – 1.4 mm



10 – 12 min




Clearcoat MS (8080)


- › Easy application
- › Easy to polish
- › Very good gloss
- › Can be applied with up to 12% of thinner
- › Very good durability and resistance to UV rays and weather conditions
- › Yellowing resistant

NAME	VOLUME	PACKAGE
Clearcoat	1 l	12 pcs
Clearcoat	5 l	4 pcs
Hardener normal	0.5 l / 2.5 l	12 / 4 pcs
Hardener rapid	0.5 l / 2.5 l	12 / 4 pcs
Hardener slow	0.5 l / 2.5 l	12 / 4 pcs


For individual orders we provide sets of 0.4 l + 0.2 l or 0.5 l + 0.25 l




2 : 1 + 12%



14 h – 20°C
45 min – 50°C



2 layers
2 – 2.5 bar
Ø 1.2 – 1.4 mm



10 – 12 min




Clearcoat R 350 HS


- › Easy application
- › Easy to polish
- › Very good gloss
- › Can be applied up to without adding thinner
- › Very good durability and resistance to UV rays and weather conditions
- › Yellowing resistant

NAME	VOLUME	PACKAGE
Clearcoat	1 l	12 pcs
Clearcoat	5 l	4 pcs
Hardener normal	0.5 l / 2.5 l	12 / 4 pcs
Hardener rapid	0.5 l / 2.5 l	12 / 4 pcs
Hardener slow	0.5 l / 2.5 l	12 / 4 pcs


For individual orders we provide sets of 0.4 l + 0.2 l or 0.5 l + 0.25 l




2 : 1 + 0 – 4%



14 h – 20°C
45 min – 50°C



2 layers
2 – 2.5 bar
Ø 1.2 – 1.4 mm



10 – 12 min




Clearcoat CRISTAL HS


- › Very high gloss and transparency
- › High resistance to scratches
- › Fast drying
- › Can be applied without adding thinner
- › Very good durability and resistance to UV rays and weather conditions
- › Yellowing resistant

NAME	VOLUME	PACKAGE
Clearcoat	1 l	12 pcs
Clearcoat	5 l	4 pcs
Hardener normal	0.5 l / 2.5 l	12 / 4 pcs
Hardener rapid	0.5 l / 2.5 l	12 / 4 pcs
Hardener slow	0.5 l / 2.5 l	12 / 4 pcs


For individual orders we provide sets of 0.4 l + 0.2 l or 0.5 l + 0.25 l




2 : 1 + 0 – 6%



14 h – 20°C
45 min – 50°C



2 layers
2 – 2.5 bar
Ø 1.2 – 1.4 mm



10 – 12 min




Clearcoat DUXOL HS


- › Fast drying
- › Very good gloss
- › Depending on amount of thinner (0 – 10%) painter can obtain different types of structures
- › Easy to polish
- › Very good durability and resistance to UV rays and weather conditions
- › Yellowing resistant

NAME	VOLUME	PACKAGE
Clearcoat	1 l	12 pcs
Clearcoat	5 l	4 pcs
Hardener normal	0.5 l / 2.5 l	12 / 4 pcs
Hardener rapid	0.5 l / 2.5 l	12 / 4 pcs
Hardener slow	0.5 l / 2.5 l	12 / 4 pcs


For individual orders we provide sets of 0.4 l + 0.2 l or 0.5 l + 0.25 l




2 : 1 + 5 – 10%



14 h – 20°C
45 min – 50°C



2 layers
2 – 2.5 bar
Ø 1.2 – 1.4 mm




10 – 12 min




Clearcoat HS 760 SPEED

- › Fast curing, fast polishability
- › Suitable for whole car repairs
- › Very good gloss
- › Can be applied up to without adding thinner
- › Very good durability and resistance to UV rays and weather conditions
- › Yellowing resistant


NAME	VOLUME	PACKAGE
Clearcoat	1 l	12 pcs
Clearcoat	5 l	4 pcs
Hardener normal	0.5 l / 2.5 l	12 / 4 pcs




2 : 1 + 0 – 5%



6 – 7 h – 20°C
45 min – 50°C



1.5 layers
2 – 2.5 bar
Ø 1.2 – 1.4 mm



8 – 10 min


For individual orders we provide sets of 0.4 l + 0.2 l or 0.5 l + 0.25 l




Clearcoat HS PLATINIUM

- › Very high gloss and transparency
- › Very high resistance to scratches
- › Can be applied without adding thinner
- › Very good durability and resistance to UV rays and weather conditions
- › Yellowing resistant


NAME	VOLUME	PACKAGE
Clearcoat	1 l	12 pcs
Clearcoat	5 l	4 pcs
Hardener normal	0.5 l / 2.5 l	12 / 4 pcs
Hardener rapid	0.5 l / 2.5 l	12 / 4 pcs
Hardener slow	0.5 l / 2.5 l	12 / 4 pcs




2 : 1 + 5 – 10%



14 h – 20°C
45 min – 50°C



2 or 1.5 layer
2 – 2.5 bar
Ø 1.2 – 1.4 mm



10 – 12 min


For individual orders we provide sets of 0.4 l + 0.2 l or 0.5 l + 0.25 l




Clearcoat HS CERAMIC

- › Very high gloss with mirror effect
- › Extremely good flow and levelling
- › Easy application
- › High hardness and scratch resistance
- › Very good durability and resistance to UV rays and weather conditions
- › Yellowing resistant


NAME	VOLUME	PACKAGE
Clearcoat	1 l	12 pcs
Clearcoat	5 l	4 pcs
Hardener normal	0.5 l / 2.5 l	12 / 4 pcs
Hardener rapid	0.5 l / 2.5 l	12 / 4 pcs
Hardener slow	0.5 l / 2.5 l	12 / 4 pcs




2 : 1 + 0 – 5%



14 h – 20°C
45 min – 50°C



2 or 1.5 layer
2 – 2.5 bar
Ø 1.2 – 1.4 mm



10 – 12 min

For individual orders we provide sets of 0.4 l + 0.2 l or 0.5 l + 0.25 l




Clearcoat HS 5900

- › Very high gloss, transparency, high body build and color depth effect
- › Depending on amount of thinner (0 – 10%)
- › painter can obtain different types of structures
- › Very good durability and resistance to UV rays and weather conditions
- › Yellowing resistant

NAME	VOLUME	PACKAGE
Clearcoat	1 l	12 pcs
Clearcoat	5 l	4 pcs
Hardener normal	0.5 l / 2.5 l	12 / 4 pcs
Hardener rapid	0.5 l / 2.5 l	12 / 4 pcs
Hardener slow	0.5 l / 2.5 l	12 / 4 pcs




2 : 1 + 0 - 10%



14 h – 20°C
45 min – 50°C



2 or 1.5 layer
2 – 2.5 bar
Ø 1.2 – 1.4 mm



10 – 12 min

For individual orders we provide sets of 0.4 l + 0.2 l or 0.5 l + 0.25 l




Clearcoat

VHS ACTIVE PRO


- › Very high gloss with mirror effect
- › Extremely good flow and levelling
- › Easy application
- › High hardness and scratch resistance
- › Very good durability and resistance to UV rays and weather conditions
- › Yellowing resistant

NAME	VOLUME	PACKAGE
Clearcoat	1 l	12 pcs
Clearcoat	5 l	4 pcs
Hardener normal	0.5 l / 2.5 l	12 / 4 pcs
Hardener rapid	0.5 l / 2.5 l	12 / 4 pcs
Hardener slow	0.5 l / 2.5 l	12 / 4 pcs


For individual orders we provide sets of 0.4 l + 0.2 l or 0.5 l + 0.25 l




2 : 1%



14 h – 20°C
45 min – 50°C



1.5 layers
2 – 2.5 bar
Ø 1.2 – 1.4 mm



10 – 12 min




Clearcoat

VHS RC 08


- › Very high gloss, transparency, high body build and color depth effect
- › High stability on vertical surfaces
- › Sagging resistant
- › Easy application
- › Very good durability and resistance to UV rays and weather conditions
- › Yellowing resistant

NAME	VOLUME	PACKAGE
Clearcoat	1 l	12 pcs
Clearcoat	5 l	4 pcs
Hardener normal	0.5 l / 2.5 l	12 / 4 pcs
Hardener rapid	0.5 l / 2.5 l	12 / 4 pcs
Hardener slow	0.5 l / 2.5 l	12 / 4 pcs


For individual orders we provide sets of 0.4 l + 0.2 l or 0.5 l + 0.25 l




2 : 1



14 h – 20°C
45 min – 50°C



1.5 layers
2 – 2.5 bar
Ø 1.2 – 1.4 mm



10 – 12 min




Clearcoat

HS XC-06


- › Rapid curing and easy to polish
- › Perfect for full car repairs
- › Good gloss and body build
- › High hardness and scratch resistance
- › Very good durability and resistance to UV rays and weather conditions
- › Yellowing resistant

NAME	VOLUME	PACKAGE
Clearcoat	1 l	12 pcs
Clearcoat	5 l	4 pcs
Hardener normal	0.5 l / 2.5 l	12 / 4 pcs


For individual orders we provide sets of 0.4 l + 0.2 l or 0.5 l + 0.25 l




2 : 1 + 0 – 5%



3 – 4 h – 20°C
5 min – 50°C



2 layers
2 – 2.5 bar
Ø 1.2 – 1.4 mm



8 – 10 min




Clearcoat

VHS XC-01


- › Extremely fast curing and polishability
- › Suitable for whole car repairs
- › Very good gloss and body build
- › High hardness and scratch resistance
- › Very good durability and resistance to UV rays and weather conditions
- › Yellowing resistant

NAME	VOLUME	PACKAGE
Clearcoat	1 l	12 pcs
Clearcoat	5 l	4 pcs
Hardener normal	0.5 l / 2.5 l	12 / 4 pcs


For individual orders we provide sets of 0.4 l + 0.2 l or 0.5 l + 0.25 l




2 : 1



3 h – 20°C
5 min – 50°C



1.5 layer
2 – 2.5 bar
Ø 1.2 – 1.4 mm



8 – 10 min



2 : 1 + 6 – 8 %

14 h – 20°C
45 min – 50°C

2 layers
2 – 2,5 bar
ø 1.3 – 1.4 mm

10 – 12 min

Clearcoat ALUM

- › Special clear coat with excellent adhesion to difficult surfaces like aluminum
- › Apply directly on cleaned and degreased aluminum
- › Not suitable for surfaces like polished aluminum

NAME	VOLUME	PACKAGE
Clearcoat	1 l	12 pcs
Hardener normal	0.5 l / 2.5 l	12 / 4 pcs
Hardener rapid	0.5 l / 2.5 l	12 / 4 pcs
Hardener slow	0.5 l / 2.5 l	12 / 4 pcs



2 : 1

14 h – 20°C
45 min – 50°C

2 layers
2 – 2.5 bar
ø 1.2 – 1.4 mm

10 – 12 min

Clearcoat MAT

- › Semi-gloss / semi-matt surface effect
- › Easy application
- › Very good durability and resistance to UV rays and weather conditions
- › Yellowing resistant

NAME	VOLUME	PACKAGE
Clearcoat	1 l	12 pcs
Hardener normal	0.5 l / 2.5 l	12 / 4 pcs
Hardener rapid	0.5 l / 2.5 l	12 / 4 pcs
Hardener slow	0.5 l / 2.5 l	12 / 4 pcs

THINNERS SILICONE REMOVERS



High standard of dilution and degreasing

The purpose of using thinners is to adjust the viscosity of used paint to different temperature conditions and size of painted elements. Our offer includes many types of customized thinners for the various products used in Car Refinish. Silicone removers are an effective help in removing various types of dirt, including grease and silicone, which remain on metal and varnished surfaces.



TYPES OF THINNER

Slow	> 28°C
Standard	15°C – 28°C
Rapid	< 15°C

Product is also available in special custom versions

Acrylic THINNER

A mixture of properly selected organic solvents used for diluting high-quality acrylic and polyurethane varnishes. It can be used with acrylic and polyurethane colour paints and clearcoats, as well as with one and two-component acrylic primers / fillers.

NAME	VOLUME	PACKAGE
Thinner	1 l	12 pcs
Thinner	5 l	4 pcs

For individual orders we provide packaging for various volumes e.g.: 0.5 l



TYPES OF THINNER

Slow	> 28°C
Standard	15°C – 28°C
Rapid	< 15°C

Product is also available in special custom versions

Basecoat THINNER

A mixture of properly selected organic solvents used for diluting basecoats with metallic, non-metallic and pearl effect. It is fully compatible with all basecoats in our market. Specially selected solvents allow proper application of basecoat layer with correct orientation of aluminium flakes before the complete evaporation.

NAME	VOLUME	PACKAGE
Thinner	1 l	12 pcs
Thinner	5 l	4 pcs

For individual orders we provide packaging for various volumes e.g.: 0.5 l



Universal THINNER

Special mixture of organic solvents used for diluting acrylic paints/varnishes, polyurethane varnishes and basecoats. It can be used with basecoats (metallic, pearl and non-metallic effect), polyurethane and acrylic paints.

TYPES OF THINNER

Slow	> 28°C
Standard	15°C – 28°C
Rapid	< 15°C

Product is also available in special custom versions

NAME	VOLUME	PACKAGE
Thinner	1 l	12 pcs
Thinner	5 l	4 pcs

For individual orders we provide packaging for various volumes e.g.: 0.5 l



Epoxy THINNER

A mixture of properly selected organic solvents intended for thinning epoxy products. It can be used for effective cleaning paint spray guns and tools from the residues of epoxy products like epoxy paints or epoxy primers.

NAME	VOLUME	PACKAGE
Thinner	1 l	12 pcs
Thinner	5 l	4 pcs

For individual orders we provide packaging for various volumes e.g.: 0.5 l



Fade out THINNER

The fade out thinner is a mixture of proper organic solvents used for reducing differences created on the edge of merger of old coating and new coating of clearcoat, acrylic or polyurethane coloured paints.

NAME	VOLUME	PACKAGE
Thinner	0.5 l	12 pcs
Thinner	1 l	12 pcs

For individual orders we provide packaging for various volumes e.g.: 0.5 l



Silicone REMOVER

Effectively removes all dirt including silicone and grease remaining on metal and painted surfaces. The product does not leave white dust on the cleaned surface and has no unpleasant smell of gasoline.

TYPES OF SILICONE REMOVER

Rapid
Standard
Slow

NAME	VOLUME	PACKAGE
Silicone remover	1 l	12 pcs
Silicone remover	5 l	4 pcs



Antistatic SILICONE REMOVER

Special product which effectively removes all dirt including silicone and grease remaining on plastic or painted surfaces. The product does not leave white dust on the cleaned surface and has no unpleasant smell of gasoline. Special additives cause, that the wiping and washing plastic car body parts does not result in the unpleasant phenomenon of being full of static.

NAME	VOLUME	PACKAGE
Silicone remover	1 l	12 pcs
Silicone remover	5 l	4 pcs



ADDITIVES
PRIMERS



Modifying paint and surface properties

Non-standard and difficult surfaces need special modifications to ensure correct adhesion and properties of the coating. Proper selection of additives enables modification of paint surface properties or changing the its mechanical properties.



Primer PLASTIC

One-component colourless primer for application by brush or spray gun on car body parts made of plastic. In Car Refinish used as a primer coating and forming micro film to obtain good adhesion topcoat to plastic.

 1 K

 30 – 40 min – 50°C

 2 layers
2 – 2.5 bar
Ø 1.2 – 1.4 mm

 20 min

NAME	VOLUME	PACKAGE
Primer plastic	0.5 l	12 pcs
Primer plastic	1 l	12 pcs



Matting PASTE

It is a special additive to paints, which allows to matt the paintwork and obtain a “non-glossy” surface. This effect is achieved by mixing the paste with any type of paint to obtain a gloss-free surface.

NAME	VOLUME	PACKAGE
Mating paste	1 l	12 pcs



Elastifikator ELASTICITY ADDITIVE

Additive for paints and varnishes used to increase elasticity of coating. Used mainly on elements made of plastic, which are exposed to frequent deformation which can cause cracks and chipping off the coating.

NAME	VOLUME	PACKAGE
Elastifikator	0.5 l	12 pcs
Elastifikator	1 l	12 pcs



Accelerating AGENT

Catalyst is fully professional accelerator of hardening and drying processes of twocomponent polyurethane and acrylic products. Used as additive to paints and varnishes.

NAME	VOLUME	PACKAGE
Accelerator	0.5 l	12 pcs

For individual orders we provide packaging for various volumes



Antisilicone TO PAINTS

Additive used to prevent the formation of silicone craters as a result of the deposition of silicone on layer of varnish. This causes breaking the surface tension forming cavities commonly known as “fish eyes”. Ready to use. Usage by pouring and thorough mixing with varnish.

NAME	VOLUME	PACKAGE
Matting paste	1 l	12 pcs



Adhesion PROMOTER

Special additive increasing varnish adhesion to difficult substrates. Additive is designed for application with all types of solventbased paints, increasing adhesion to substrates such as: aluminium, steel, galvanized steel, stainless steel.

NAME	VOLUME	PACKAGE
Adhesion Promoter	0.5 l	12 pcs

For individual orders we provide packaging for various volumes



BINDERS
HARDENERS



High gloss pigmented solutions

High-quality binder that combines pigments in two-component acrylic paints plays a key role in the durability of coating and its gloss. It has strong influence on ease of application and final appearance of coating. Correctly selected hardener will ensure good flow and leveling, as well as correct cross-linking of coating ensuring proper resistances and hardness.



Industrial 2K ACRYLIC BINDER

Medium Solid binder which merges pigments to form a two-component topcoat. It is a mixture of resins and solvents, to which a colouring pigment is added. Obtained in this way varnish has a proper flow and suitable gloss and hardness for industrial paints. Resin is used for the manufacture of industrial paints and varnishes.

NAME	VOLUME	PACKAGE
Binder	5 l	4 pcs

For individual orders we provide packaging for various volumes e.g.: 200 l drums



EXPRESS 2K ACRYLIC BINDER

High Solid binder used for merging pigments. Thanks to the use of very fast resins, the coating of colored acrylic paint is ready for installation after 3-4 hours after spraying, which significantly shortens repair time.

NAME	VOLUME	PACKAGE
Clearcoat	1 l	12 pcs

For individual orders we provide packaging for various volumes e.g.: 200 l drums



HQR 2K ACRYLIC BINDER

High Solid binder used for merging pigments. When mixed with pigments, form a two-component topcoat commonly known as acrylic varnish. It is made of acrylic and polyurethane resins and a range of solvents suspending the pigment, giving in a result coloured topcoat. Its surface has excellent flow, high gloss and appropriate hardness. Acryl resin HQR is used for the manufacture of high-quality paints and varnishes. It is compatible with pigment systems available in our market.

NAME	VOLUME	PACKAGE
Binder	5 l	4 pcs

For individual orders we provide packaging for various volumes e.g.: 200 l drums



Universal Hardener

Composition of solvents and resins specially prepared for hardening acrylic and polyurethane varnishes. Effectively hardens all pigmented varnishes sold in the 2 : 1 system. Hardened coating gets a high gloss and excellent hardness.

TYPES OF THINNER

Extra slow
Slow
Standard
Rapid

NAME	VOLUME	PACKAGE
Hardener	0.5 l	12 pcs
Hardener	1 l	4 pcs
Hardener	2.5 l	4 pcs
Hardener	5 l	4 pcs




Universal

Hardener TRO

Used for hardening acrylic and polyurethane varnishes. It is properly selected isocyanate resin and solvents solution. Economical solution for hardening coloured varnishes designed for MS acrylic paints systems.



Exlak Sp.z o.o.
ul. Kozielska 14
44-153 Sośnicowice
Poland

 +48 32 238 41 81

 grupa.exlak@interia.pl