## **SP-5.3** 3 PHASE DOUBLE PULSE MIG WELDER





	Technical	Technical Specifications		
	Input Voltage:	3 ph. 220 - 400V 30A 50/60 Hz		
	Amp/Volts Min-Max:	MMA - 5A/20.2V - 270A/30.8V TIG - 5A/10.2V - 350A/24V MIG - 20A/15V - 350A/31.5V		
	Protection:	IP 23S		
	Cooling:	Fan Cooled		
	Insulation:	Н		
	System Weight:	137lbs (62kg)		

The NEW Pro Spot SP-5.3 Double Pulse MIG Welder was designed with microprocessor controls and weld programs specifically geared for the collision repair industry. Applications include Aluminum MIG, MIG Brazing, Steel MIG/MAG, Root Welding, TIG, MMA/Stick Welding, etc.

## Features:

<u>Multi-Torch System</u> - 3 dedicated MIG torches and spools that make switching materials as easy as grabbing a torch!

<u>Double Pulse Technology</u> - Allows for precise heat control and weld aesthetics. Great for vertical welding!

<u>3 Phase Power</u> - Maintain arc stability on the thickest to the thinnest materials.

<u>SMART Software</u> - Welding is as easy as grabbing the torch and clicking the trigger, the software changes to the correct weld settings and gas automatically.

<u>Updates & Upgrades</u> - Keep your welder updated via USB port.

<u>User Defined Memories</u> - Save and recall more than 200 working points and store them in a customized job list.



	Front Panel Controls		
GIC I Ma day Mano	1. Process Selection: - MIG/MAG Double Pulsed - MIG/MAG Pulsed - Root Welding - MIG/MAG Synergic - MIG/MAG Manual - TIG DC Lift - MMA	<ol> <li>Large LCD Display</li> <li>Navigation Key (Menu Setting)</li> <li>Regulation Knobs</li> <li>Power Knob</li> <li>Save &amp; Recall Parameters</li> </ol>	





info@prospot.com

www.prospot.com

Pro Spot International, Inc. U.S.A. 5932 Sea Otter Place Carlsbad, CA 92010

Toll free (US only): 877 PRO-SPOT (776-7768)