WORLD CLASS
Hans®
Tools

NEW Torque wrench system

1.Torque ranges: 5-1000 Nm
2.Accuracy
± 4% of the scale value
according to DIN EN ISO 6789
3.Double scale for Nm and FT-LB.
4.One more micro scale for exact adjustment.
5.Easy turning and setting torque due
by ergonomically handle grip.
6.Safety and easy-turning lock system.
7.Audible and traceable signals.
8.Quick release and switch-over ratchet.

According to
DIN 3120,ISO 1174-1
DIN EN ISO 6789

1/4" 3/8" 1/2" 3/4" 1" DR.

TORQUE WRENCH
LLAVES DINAMOMÉTRICA
CLÉS DYNANOMÉTRIQUE
扭力扳手

1/4"
3/8"
1/2"

Dr.	ITEM NO.	Nm. CAPACITY	FT-LB CAPACITY	L mm / inch	(g)
1/4"	21770G	5-25N·m	4-18FT·LB	290/11-3/8″	420
3/8"	31770G	10-50N·m	8-35FT·LB	360/11″	910
3/8"	31771G	20-100N·m	15-70FT·LB	405/16″	1020
1/2"	41775G	20-100N·m	15-70FT·LB	405/16″	1020
1/2"	41770G	40-200N·m	30-140FT·LB	500/19-11/16″	1200
1/2"	41771G	60-300N·m	45-220FT·LB	595/23-3/8″	1330
1/2"	41772G	80-400N·m	60-290FT·LB	680/26-9/64″	1820

FT-LB SCALE ONLY FOR TORQUE CONVERSION

BLOW CASE FOR EACH

TORQUE WRENCH
LLAVES DINAMOMÉTRICA
CLÉS DYNANOMETRIQUE
扭力扳手

3/4"
1"

Dr.	ITEM NO.	Nm. CAPACITY	FT-LB CAPACITY	L mm / inch	(g)
3/4"	61770G	110-550N·m	85-405FT·LB	970/38″	3700
3/4"	61771G	150-750N·m	115-550FT·LB	1150/45-9/32″	5600
3/4"	61772G	200-1000N·m	150-735FT·LB	1250/49″	7200
1"	81770G	200-1000N·m	150-735FT·LB	1250/49″	7200

BLOW CASE FOR EACH

TORQUE WRENCH
LLAVES DINAMOMÉTRICA
CLÉS DYNANOMETRIQUE
扭力扳手

(9x12mm ▬)
(14x18mm ▬)

▬	ITEM NO.	Nm. CAPACITY	FT-LB CAPACITY	L mm / inch	(g)
9x12	21770GNC	5-25N·m	4-18FT·LB	280/11″	400
9x12	31770GNC	10-50N·m	8-35FT·LB	334/13″	700
9x12	31771GNC	40-200N·m	30-140FT·LB	468/18-3/8″	1200
9x12	31772GNC	20-100N·m	15-70FT·LB	380/15	1020
14x18	41773GNC	20-100N·m	15-70FT·LB	385/15-11/64″	1020
14x18	41770GNC	40-200N·m	30-140FT·LB	475/18-45/64″	1200
14x18	41771GNC	60-300N·m	45-220FT·LB	568/22-23/64″	1330
14x18	41772GNC	80-400N·m	60-290FT·LB	657/25-7/8	1820

BLOW CASE FOR EACH

TORQUE WRENCH

LLAVES DINAMOMÉTRICA
CLÉ DYNANOMÉTRIQUE
扭力扳手

1.Accuracy ± 4% of the scale value according to DIN EN ISO 6789
2.THREE-digit, big figures for torque value setting
3.Big and convex window perfects the reading
4.Easy turning and setting torque due by ergonomically handle grip.
5.Safety and easy-turning lock system.
6.Audible and traceable signals.
7.Quick release and switch-over ratchet.

2.THREE-digit, big figures for torque value setting
3.Big and convex window perfects the reading

Dr.	ITEM NO.	Nm. CAPACITY	L mm / inch	(g)
1/2"	41795	20-100N·m	417/16-3/8″	1100
1/2"	41790	40-200N·m	508/20″	1270
1/2"	41791	60-300N·m	600/23-5/8″	1370
1/2"	41792	80-400N·m	690/27″	1850

BLOW CASE FOR EACH

TORQUE WRENCH
LLAVES DINAMOMÉTRICA
CLÉS DYNANOMETRIQUE
扭力扳手

1/4" 3/8" 1/2" 3/4"

Dr.	ITEM NO.	Nm. CAPACITY	ITEM NO.	FT-LB CAPACITY	L mm / inch	(g)
1/4"	2170Nm	5-25N·m	2170NI	35-200INCH·LB	280/11″	580
3/8"	3170Nm	5-25N·m	3170NI	35-200INCH·LB	275/11″	580
3/8"	3171Nm	20-110N·m	3171NF	15-80FT·LB	360/14-3/8″	820
1/2"	4175Nm	20-110N·m	4175NF	15-80FT·LB	360/14-3/8″	830
1/2"	4170Nm	40-210N·m	4170NF	30-150FT·LB	465/18″	1340
1/2"	4171Nm	70-350N·m	4171NF	50-250FT·LB	630/24-13/16″	2400
3/4"	6170Nm	65-450N·m	6170NF	50-300FT·LB	850/33-1/2″	3840

BLOW CASE FOR EACH

TORQUE WRENCH
LLAVES DINAMOMÉTRICA
CLÉS DYNANOMETRIQUE
扭力扳手

3/4" 1"

Dr.	ITEM NO.	Nm. CAPACITY	ITEM NO.	FT-LB CAPACITY	L mm / inch	(g)
3/4"	6171Nm	140-700N·m	6172NF	100-600FT·LB	1080/42-1/2″	6160
3/4"	6173Nm	140-980N·m	6173NF	100-700FT·LB	1225/47-13/16″	6893
1"	8170Nm	140-980N·m	8170NF	100-700FT·LB	1230/47-13/16″	6893

BLOW CASE FOR EACH

TORQUE WRENCH
LLAVES DINAMOMÉTRICA
CLÉS DYNANOMETRIQUE
扭力扳手

1/4" 3/8" 1/2"

DR	ITEM NO.	CAPACITY	L=mm / inch	(g)
1/4"	2172G	BOTH 6-30N·m & 40-250INCH·LB	310/12″	1530
NEW 1/4"	2173G	BOTH 3-15N·m & 30-150INCH·LB	193/7-19/32	1530
3/8"	3172G	BOTH 20-100N·m & 15-75FT·LB	440/17-3/8″	1530
NEW 3/8"	3173G	BOTH 10-60N·m & 9-45FT·LB	390/15-23/64	1530
1/2"	4172G	BOTH 40-200N·m & 30-150FT·LB	530/21″	2000
NEW 1/2"	4173G	BOTH 60-320N·m & 60-230FT·LB	600/24″	2000

BLOW CASE FOR EACH

MICRO-TORQUE WRENCH
LLAVES DINAMOMÉTRICA
CLÉ DYNANOMETRIQUE
扭力扳手

1/4"
3/8"
1/2"
3/4"

Dr.	ITEM NO.	Nm. CAPACITY	ITEM NO.	FT-LB CAPACITY	L mm / inch	(g)
1/4"	2170GN	6-30N·m	2170GI	40-250INCH·LB	290 / 13-3/4″	900
3/8"	3170GN	6-30N·m	3170GI	40-250INCH·LB	295 / 13-3/4″	900
3/8"	3171GN	20-110N·m	3171GF	15-80FT·LB	380 / 15″	1180
1/2"	4170GN	40-210N·m	4170GF	30-150FT·LB	535 / 21″	2100
1/2"	4171GN	70-350N·m	4171GF	50-250FT·LB	650 / 25-1/2″	3110
3/4"	6170GN	100-500N·m	6170GF	50-300FT·LB	865 / 34″	4730

BLOW CASE FOR EACH

MICRO-TORQUE WRENCH
LLAVES DINAMOMÉTRICA
CLÉ DYNANOMETRIQUE
扭力扳手

3/4"
1"

Dr.	ITEM NO.	Nm. CAPACITY	ITEM NO.	FT-LB CAPACITY	L mm / inch	(g)
3/4"	6171GN	140-700N·m	6171GF	100-600FT·LB	1090 / 43″	7540
3/4"	6173GN	140-980N·m	6173GF	100-700FT·LB	1230 / 48-1/2″	8200
1"	8170GN	140-980N·m	8170GF	100-700FT·LB	1230/ 48-1/2″	8200

BLOW CASE FOR EACH

PROFESSIONAL PRE-SET
LLAVES DINAMOMÉTRICE
CLÉ DYNAMOMETRIQUE DE ARRANGEMENT PRÉCEDENT
預調式固定扭力扳手

1/4"
3/8"
1/2"

DR	ITEM NO.	Nm CAPACITY	FT-LB CAPACITY	L mm/inch	(g)	ITEM NO.	Nm CAPACITY	FT-LB CAPACITY	L mm/inch	(g)
1/4"	2170P12	2-12N·m	20-120in·LB	193	220	4170P200	30-200N·m	15-150FT·LB	508	1380
3/8"	3170P50	5-50N·m	4-40FT·LB	298	560	3170P100	20-100N·m	10-75FT·LB	365	760

OPEN ENDS PLUG

BOCA PLANA, CONEXION
EMBOUTS Á FOURCHE 9x12,14x18
開口扳手插頭

1557-9M (9x12mm ▬)

1557-14M (14x12mm ▬)

ITEM NO.	1557
9M (9x12mm▬)	7,8,10,11,12,13,14,15,16,17,18,19,21,22mm
14M(14x18mm▬)	13,14,15,16,17,18,19,21,22,24,26,27,29, 30,32,34,36,38,41mm NEW

RING ENDS PLUG

LLAVES POLIGONALES, CONEXION
EMBOUTS POLYGONÁUX

1057-9M /-14M

ITEM NO.	1057
9M (9x12mm▬)	7,8,9,10,11,12,13,14,15,16,17,18,19,21,22mm
14M(14x18mm▬)	13,14,15,16,17,18,19,21,22,24,27,29,30,32, 34,36,38,41mm

INSERT ADAPTER 10914

ADAPTADOR INSERTABLE
ADAPTAEUR MÂLE
轉換接頭

NEW

14x18 x 9x12

ITEM NO.	INSERT	DRIVE	L (mm)	(g)	(PCS)
10914	14x18 ➡	9x12	50	60	10

FLARE ENDS PLUG

LLAVES ESTRELLA, CONEXION
EMBOUTS CLÉS Á TUYAUTER
缺口螺帽扳手插頭

1558-9M /-14M

ITEM NO.	1558
9M (9x12mm▬)	10,11,12,13,14,16,17,18,19,21,22mm
14M(14x18mm▬)	24mm

INSERT TOOL HOLDER FOR BIT

HARRAMIENTA INSERTABLE
PARA PUNTAS DE DESTORNILLADOR
ATTACHE MÁLE POUR BITS

NEW

1052-9H1 /-9H2

ITEM NO.	HOLDER	DRIVE	L (mm)	(g)	(PCS)
9H1	⬡ 5/16″	(9x12mm)	42	52	10
9H2	⬡ 1/4″	(9x12mm)	42	52	10

11409

NEW

9x12 x 14x18

ITEM NO.	INSERT	DRIVE	L (mm)	(g)	(PCS)
11409	9x12 ➡	14x18	45	70	10

3/8" 3673

BY REQUEST

8 PCS	3673 3/8"
3171GNC	20-110Nm, TORUE WRENCH
3171H	RATCHET HEAD (9x12mm ▬)
1557-9M	8,10,12,14,17,19mm(OPEN HEAD)

1/2" 4673

BY REQUEST

11 PCS	4673 1/2"
4170GNC	40-210Nm, TORUE WRENCH
4171H	RATCHET HEAD (14x18mm▬)
1557-14M	13,14,15,17,19,22,24,27,30mm(OPEN HEAD)

3/8" 3674

SPECIAL FOR
FREEZING ENGINNER

BY REQUEST

8 PCS	3674 3/8"
3171GNC	20-110Nm, TORUE WRENCH
3171H	RATCHET HEAD (14x18mm▬)
1557-14M	17,22,24,26,27,29mm(OPEN HEAD)

NEW 3674-33

33 PCS	3674-33
3171GNC	20-110Nm,TORQUE WRENCH
3171H	3/8″ RATCHET HEAD (9x12mm ▬)
4171H1	1/2″ RATCHET HEAD (9x12mm ▬)
1557-9M	7,8,9,10,11,12,13,14,15,16,17,18,19mm
1057-9M	7,8,10,11,12,13,14,15,16,17,18,19,21,22mm
1052-9H1	1/4″ ⬡ (9x12mm) 1052-9H2 5/16″⬡(9x12mm)

INVERTIBLE-TORQUE WRENCH

LLAVES DINAMOMÉTRICA
CLÉ DYNANOMETRIQUE INVERSIBLE
扭力扳手，可翻轉–反絲用

1/4" 3/8" 1/2" 3/4"

Dr.	ITEM NO.	Nm. CAPACITY	ITEM NO.	FT-LB CAPACITY	L mm / inch	(g)
3/8"	3171-2GN	20-110N·m	3171-2GF	15-80FT·LB	380 / 15″	1180
1/2"	4170-2GN	40-210N·m	4170-2GF	30-150FT·LB	535 / 21″	2100
1/2"	4171-2GN	70-350N·m	4171-2GF	50-250FT·LB	650 / 25-1/2″	3040
3/4"	6170-2GN	100-500N·m	6170-2GF	50-300FT·LB	865 / 34″	4770

BLOW CASE FOR EACH

INVERTIBLE-TORQUE WRENCH

LLAVES DINAMOMÉTRICA
CLÉ DYNANOMETRIQUE INVERSIBLE
扭力扳手，可翻轉–反絲用

3/4" 1"

Dr.	ITEM NO.	Nm. CAPACITY	ITEM NO.	FT-LB CAPACITY	L mm / inch	(g)
3/4"	6171-2GN	140-700N·m	6171-2GF	100-600FT·LB	1090 / 43″	7540
3/4"	6173-2GN	140-980N·m	6173-2GF	100-700FT·LB	1230 / 48-1/2″	8020
1"	8170-2GN	140-980N·m	8170-2GF	100-700FT·LB	1230/ 48-1/2″	8020

BLOW CASE FOR EACH

PIPE TORQUE WRENCH

LLAVE DINAMOMETRICA DE TUBO
CLÉ DYNAMOMÉTRIQUE A GRIFFE 90°
管道扭力扳手

NEW

ITEM NO.	Nm. CAPACITY	MAX. OPEN (mm)	L mm / inch	(g)
1994GN-210	40-210 N·m	48	590/ 24″	2960
1994GN-350	70-350 N·m	63	825/ 33″	3700
1994GN-500	100-500 N·m	63	920/ 37″	4300

INVERTIBLE-TORQUE WRENCH

LLAVES DINAMOMTRICA
CLÉ DYNAMOMÉTRIQUE INVERSIBLE
扭力扳手,可翻轉–反絲用

1/4"
3/8"
1/2"

Dr.	ITEM NO.	Nm. CAPACITY	ITEM NO.	FT-LB CAPACITY	L mm / inch	(g)
1/4"	2174GN-11	2.5-11 N·m	2174GF-08	2-8 FT·LB	338/13″	630
3/8"	3174GN-11	2.5-11 N·m	3174GF-08	2-8 FT·LB	338/13″	720
3/8"	3174GN-33	7-33 N·m	3174GF-24	5-24 FT·LB	425/16-3/4″	720
3/8"	3174GN-68	14-68 N·m	3174GF-50	10-50 FT·LB	500/20″	1050
1/2"	4174GN-68	14-68 N·m	4174GF-50	10-50 FT·LB	500/20″	1050
1/2"	4174GN-135	25-135 N·m	4174GF-100	20-100 FT·LB	556/21-3/4″	1600
1/2"	4174GN-225	50-225 N·m	4174GF-160	40-160 FT·LB	600/24″	2300
1/2"	4174GN-330	70-330 N·m	4174GF-250	50-250 FT·LB	805/32″	2600

BLOW CASE FOR EACH

INVERTIBLE-TORQUE WRENCH

LLAVES DINAMOMTRICA
CLÉ DYNAMOMÉTRIQUE INVERSIBLE
扭力扳手,可翻轉–反絲用

3/4"
1"

Dr.	ITEM NO.	Nm. CAPACITY	ITEM NO.	FT-LB CAPACITY	L mm / inch	(g)
3/4"	6174GN-560	140-560 N·m	6174GF-410	100-410 FT·LB	996/39″	7410
3/4"	6174GN-800	200-800 N·m	6174GF-600	140-600 FT·LB	1070/42″	7580
1"	8174GN-1000	200-1000 N·m	8174GF-740	140-740 FT·LB	1400/56″	12800

BLOW CASE FOR EACH

TORQUE WRENCH 1500 N.m

LLAVES DINAMOMTRICA
CLÉ DYNANOMETRIQUE
扭力扳手

1500N.m
PROFESSIONAL TORQUE WRENCH

3/4"
1"

POLE: 1020mm L. MAIN BODY: 1020mm L.

Dr.	ITEM NO.	Nm CAPACITY	ITEM NO.	FT-LB CAPACITY	L mm / inch	(g)
3/4"	6175GN	300-1500N·m	6175GF	200-1000FT·LB	1700	13500
1"	8175GN	300-1500N·m	8175GF	200-1000FT·LB	1700	13500

BLOW CASE FOR EACH

TORQUE WRENCH 2500 N.m

扭力扳手

1"

B+C+D POLE: 2305mm L. MAIN BODY: 2755mm L.

Dr.	ITEM NO.	Nm CAPACITY	FT-LB CAPACITY	L mm	(g)
1"	8176NM	500-2500N·m		2755	19600
1"	8176NF		400-2000FT·LB	2920	19600

BLOW CASE FOR EACH

TORQUE WRENCH

扭力扳手

3/8"
1/2"

Dr.	ITEM NO.	KGF-CM CAPACITY	GRADUATION CAPACITY	L mm	(g)
3/8"	3173K-250	50-250	2.5	240	450
3/8"	3173K-1000	200-1000	10	342	800
1/2"	4173K-1000	200-1000	10	342	800
1/2"	4173K-2000	400-2000	20	498	1500

BLOW CASE FOR EACH

TORQUE MULTIPIER

MULTIPLICANDO DINAMOMETRICA
MULTIPLICATEUR DE DYNANOMÉTRIQUE
倍力器

6194/8194/8196

WITH LEVER ARM

(SIMPLE SET)

6194-4
6194-9
8196-4
8194-12
8194-16

NEW

(WHOLE SET WITH SPARE PARTS)

6194-45
6194-95
8196-45
8194-125
8194-165

6190/8190

6190-3
8190-3

WITH SPARE PARTS OF LEVER ARMS

6190/8190

NEW

6190-3/8190-3
(WITH LEVER ARM)

9296-5

9296-5

ITEM NO.	F (HORSE)	M (SQUARE)	GEAR RATIO	TORQUE RATIO	W (mm)	H (mm)	L (mm)	INPUT TORQUE(N.m)	OUTPUT TORQUE(N.m)	(g)
6194-4(5)	1/2 DR.	3/4 DR.	1: 4	1: 3.3	70	78	428	MAX: 303	MAX: 1000	2250
6194-9(5)	1/2 DR.	3/4 DR.	1: 9	1: 6.5	82	97	480	MAX: 231	MAX: 1500	4200
8196-4(5)	3/4 DR.	1″ DR.	1: 4	1: 3.3	96	111	500	MAX: 758	MAX: 2500	5660
8194-12(5)	1/2 DR.	1″ DR.	1: 12	1: 9	82	110	480	MAX: 222	MAX: 2000	4500
8194-16(5)	1/2 DR.	1″ DR.	1: 16	1: 12	96	134	500	MAX: 208	MAX: 2500	5850
6190(-3)	1/2 DR.	3/4 DR.	1: 3	1: 3	73	84	425	MAX: 500	MAX: 1500	2350
8190(-3)	3/4 DR.	1″ DR.	1: 3	1: 3	91	113.5	500	MAX: 1000	MAX: 3000	4850
9296-5	3/4 DR.	1-1/2″ DR.	1: 5.5	1: 4.8	137	168	377.5	MAX: 938	MAX: 4500	11500

TORQUE MULTIPLIER SET

MULTIPLICANDO DINAMOMETRICA
MULTIPLICATEUR DE DYNANOMÉTRIQUE
倍力器

9290/9291

NEW

9290-10 WITH ONE
814804 ⊔1-1/2″×1″⊔

ITEM NO.	F (HORSE)	M (SQUARE)	GEAR RATIO	TORQUE RATIO	W (mm)	H (mm)	L (mm)	INPUT TORQUE(N.m)	OUTPUT TORQUE(N.m)	(g)
9290-10	1/2 DR.	1-1/2″ DR.	1: 10	1: 10	110	253.6	265	MAX: 400	MAX: 4000	8900
9291-10	3/4 DR.	1-1/2″ DR.		1: 30	186	176	490	MAX: 335	MAX: 10000	30400

66194-4 / 66194-9

WITH
84400M
24, 27, 30, 32mm

66194-4

WITH
84400M
24, 27, 30, 32mm

66194-9

6193-16

WITH
84400M
24, 27, 30, 32mm

66193-16

To fix it with the screw and the required socket as the piclure above.

Lever arms can be adjusted to use with normal and deep socket.

Lever arms can be adjusted to use with normal and deep socket

ITEM NO.	GEAR RATIO	TORQUE RATIO	INTPUT TORQUE	OUTPUT TORQUE
66194-4	1 : 4	1:3.3	303N.m	1000Nm
66194-9	1 : 9	1:6.5	231N.m	1500Nm
BLOW CASE:385x305x85 mm				EVA FORM

ITEM NO.	GEAR RATIO	TORQUE RATIO	INPUT TORQUE(N.m)	OUTPUT TORQUE(N.m)	(KGS)
66193-16	1: 16	1: 9.5	MAX: 158	MAX: 1,500	4.3
BLOW CASE:385x305x85 mm					EVA FORM

DIGI-TORC-ADAPTOR

GONIÓMETRO DIGITAL PARA APRIETES
RAPPORTEUR NUMÉRIQUE POUR SERRAGES COUPLE
數位扭力接頭

3/8" **3878B**

1/2" **4878B**

ITEM NO.	DRIVE	TORQUE (N-m)	LENGTH (mm)	RANGE
3878B	3/8"	10-135	75	Nm FT-LB IN-LB kg-m kg-cm
4878B	1/2"	20-200	75	

2878D/3878D/4878D

1/4" 3/8" 1/2"

ITEM NO.	DRIVE	Nm	LENGTH (mm)	RANGE
2878D	1/4"	6-30Nm	75	Nm FT-LB IN-LB kg-m kg-cm
3878D	3/8"	27-135Nm	75	
4878D	1/2"	40-200Nm	75	

DIGI-TORC-ADAPTOR 1/2"DR. 4878A

WITH ANGLE METER FUNCTION
GONIÓMETRO DIGITAL PARA APRIETES PAR Y ÁNGULO
RAPPORTEUR NUMÉRIQUE POUR SERRAGES COUPLE ET ANGULAIRES
數位扭力接頭（角度儀）

ITEM NO.	Resolution (N-m)	DRIVE	TORQUE (N-m)	LENGTH (mm)
4878A-135	0.1	1/2″ DR.	6.8~ 135	80 ϕ
4878A-200	0.1	1/2″ DR.	10~ 200	80 ϕ
4878A-340	0.1	1/2″ DR.	17~ 340	80 ϕ

DIGI-TORC ADAPTOR 6878D

GONIÓMETRO DIGITAL PARA APRIETES
RAPPORTEUR NUMÉRIQUE POUR SERRAGES COUPLE
數位扭力接頭

NEW

3/4"

ITEM NO.	DRIVE	Nm	LENGTH (mm)
6878D	3/4"	70-813Nm	250mm

ANGLE METER ADAPTOR

LLAVES DE APRIETE ANGULAR
CLÉ DE SERRAGE ANGULAIRE
角度儀

NEW

00478 00678 00478MP

ITEM NO.	⊔ X ⊓	(g)	(PCS)
00478	1/2″x1/2″	160	12
00678	3/4″x3/4″	621	6
00478MP	1/2″x1/2″	250	6

DIGI-TORC-ANGLE METER MAGNET

GONIÓMETRO DIGITAL PARA APRIETES ANGULARES
RAPPORTEUR NUMÉRIQUE POUR SERRAGES ANGULAIRES
數位角度儀

0078A

± 1% ANGEL ACCURACY 250 SETS DATA MEMORY

MAGNET TO ATTACH EASILY

YouTube TO Hanstoolmedia

TORQUE DRIVER
DESTORNITORNILLADOR DINAMOMÉTRICO
TOURNEVIS DYNAMOMÉ TRIQUES
扭力起子

0178-5N

NEW

ITEM NO.	Capacity	L (mm)	(g)
0178-5N	1-5N	196	220

14PCS TORQUE DRIVER SET
扭力起子組

06178-14

NEW

14 PCS	06178		
0178-5N	TORC-SCREWDRIVER 1~10Nm		
011-2	4, 5, 6 mm	021-2	#1, #2, #3
041-2	T15, T20 ,T25	061-2	4, 5, 6 mm

TORQUE DRIVER
DESTORNITORNILLADOR DINAMOMÉTRICO
TOURNEVIS DYNAMOMÉ TRIQUES
扭力起子

0178-10N

ITEM NO.	Capacity	L (mm)	(g)
0178-10N	2-10N	240	440

7PCS TORQUE DRIVER SET FOR TPMS
DESTORNITORNILLADOR DINAMOMÉTRICO
TOURNEVIS DYNAMOMÉ TRIQUES
固定式扭力扳手組

06178

041-3

7 PCS	06178
2300M	1/4 DR. DEEP SOCKET 11, 12mm
0178-10N	TORC-SCREWDRIVER 2~10Nm
2000	1/4″ HEX BIT HOLDER
041-3	1/4″ HEX BIT T10, T15, T20

DIGI-TORC-MINI SERIES
DIGI-TORC 1/4″ DR. LEVER TYPE
DIGITALER DREHMOMENTSCHLÜSSEL
LLAVE DINAMOMÉTRZCA DIGITAL
CLÉ DYNAMOMETRIQUE NUMÉRIQUE
數位微型扭力扳手

Best Choice ....± 3% **DIGI-TORC** Intellectual Wrenches

ITEM NO.	HEAD TYPE	TORQUE	LENGTH	UNIT
2178MD3-6	1/4″ DR. RATCHET	1.2-6N-m	216mm	N-m, Ft-lb, In-lb kg-cm
2178MD3-12		2.4-12N-m		
2178MD3-20		4-20N-m		

DIGI-TORC-MINI SERIES
DIGI-TORC BIT HOLDER
1/4″ HEXAGON
DIGITALER DREHMOMENT BITHALTER
LLAVE PORTAPUNTA DIGITAL
PORTE-EMBOUT
DYNAMOMETRIQUE NUMÉRIQUE
數位微型扭力扳手

Best Choice ....± 3% **DIGI-TORC** Intellectual Wrenches

ITEM NO.	HEAD TYPE	TORQUE	LENGTH	UNIT
2178MDB-6	1/4″ BITS HOLDER	1.2-6N-m	216mm	N-m, Ft-lb, In-lb kg-cm
2178MDB-12		2.4-12N-m		
2178MDB-20		4-20N-m		

※CCW±5%

DIGI-TORC-MINI SERIES
DIGI-TORC-SCREWDRIVER
DIGALER DREHMOMENTSCHRAUBER
DIGALER DESTORNILLADORE
DINAMOMETRICA DIGTAL
TOÚRNEVIS DYNAMOMETRIQUE NUMÉRIQUE
數位扭力起子

Best Choice ....± 2.5% **DIGI-TORC** Intellectual Screwdriver

ITEM NO.	HEAD TYPE	TORQUE	LENGTH	UNIT
0178-55C	1/4″ BITS HOLDER	10-55CN-m	203mm	CN-m, In-lb kg-cm
0178-200C		40-200CN-m		
0178-400C		80-400CN-m		

※CCW±3.5%

DIGI-TORC D1/D2 SERIES

HANS TORQUE WRENCHES-DIGITAL

LLAVE DINAMOMÉTRICA DIGITAL
CLÉ DYNAMOMETRIQUE NUMÉRIQUE
數位扭力扳手

* Data Input to connecting with PC & to telecommuting accuracy re-calibration via inter-net & function update.
* Data Output for the memory of torsion value for data saving purpose.

D1 Series

Best Choice ··· ±1% DIGI-TORC Intellectual Torque Wrenches

ITEM NO.	SQUARE	TORQUE	LENGTH	UNIT
2178D1-30	1/4″DR.	3-30N-m	390mm	N-m, Ft-lb, In-lb, kg-cm
3178D1-100	3/8″DR.	6.8-135N-m	415mm	
4178D1-135	1/2″DR.	6.8-135N-m	450mm	
4178D1-200	1/2″DR.	20-200N-m	530mm	
4178D1-340	1/2″DR.	30-340N-m	650mm	

※CCW±2%

D2 Series

Economical Choice ··· ±2% DIGI-TORC Intellectual Torque Wrenches

ITEM NO.	SQUARE	TORQUE	LENGTH	UNIT
2178D2-30	1/4″DR.	3-30N-m	390mm	N-m, Ft-lb, In-lb, kg-cm
3178D2-100	3/8″DR.	6.8-135N-m	415mm	
4178D2-135	1/2″DR.	6.8-135N-m	450mm	
4178D2-200	1/2″DR.	20-200N-m	530mm	
4178D2-340	1/2″DR.	30-340N-m	650mm	
6178D2-500	3/4″DR.	50-500N-m	900mm	
6178D2-850	3/4″DR.	85-850N-m	1200mm	

※CCW±3.5%

DIGI-TORC DC3 SERIES

DIGITAL TORQUE WRENCHES-ROUND HEAD RATCHET INSERT

LLAVE DINAMOMÉTRZCA DIGITAL
CLÉ DYNAMOMETRIQUE NUMÉRIQUE
可換頭數位式扭力扳手

Best Choice ....± 3% **DIGI-TORC** Intellectual Torque Wrenches

ITEM NO.	SQUARE	▬	TORQUE	LENGTH	UNIT
2178DC3-30	1/4″DR.	9 ×12	3-30N-m	390mm	N-m, Ft-lb, In-lb kg-cm
3178DC3-135	3/8″DR.	9 ×12	6.8-135N-m	415mm	
4178DC3-135	1/2″DR.	9 ×12	6.8-135N-m	415mm	
4178DC3-200	1/2″DR.	14×18	20-200N-m	530mm	
4178DC3-340	1/2″DR.	14×18	30-340N-m	650mm	

※CCW± 5%

BY REQUEST

DIGI-TORC-1178D3-135 SERIES

DIGI-TORC ADJUSTABLE

LLAVE INGLESA DINAMOMÉTRZCA DIGITAL
CLÉ AMOLETTE DYNAMOMETRIQUE NUMÉRIQUE
數位扭力活動扳手

± 3% **DIGI-TORC** Intellectual Torque Wrenches

ITEM NO.	OPEN END SIZE	HEAD TYPE	ALARM SETTING RANGE	GUARANTEE ACCURACY RANQ	BRIGHT LED	LENGTH
1178D3-135	31	ADJUSTABLE SPANNER	6.8-135N-m	27-135N-m	12LEDS	525

WIRELESS
Digital Torque Wrench

ONLINE CALIBRATION
EXCLUSIVELY ON
HANS TOOL Specialized
DIGITAL TORQUE WRENCH

ROTATIONAL TRANSDUCERS CALIBRATION EQUIPMENT

CAPTADOR DE ROTACION Y INSTALACIONES DE CALIBRACION
CAPTEURS DE MESURES, SYSTEME DE CALIBRAGE
扭力扳手扭力校驗設備

NOTE BOOK &TORQUE WRENCH DO NOT INCLUDE WITH CALIBRATION EQUIPMENT.

ITEM NO.	CAPACITY MAX. TORQUE	L	D	H	KG
RT-400	400N-m	900	330	570	100
RT-1000	1000N-m	1500	330	610	
RT-2500	2500N-m	2500	560	755	

- DIGITAL DISPLAY
- AC/DC RECHARGEABLE
- RECHARGEABLE BATTERY
- DATA MEMORY 250 SETS
- USB PC CONNECTIVITY
- LED BRIGHT LIGHT

ITEM NO.	FEMALE SQUARE	CAPACITY Nm	ACCURACY & DISPLAY	UNIT	ADAPTOR MALE × FEMALE	KG
DS-50	3/8″	5.00 ~ 50.00N-m	± 0.5% or ± within 3 digit (CW/CCW)	N-m、In-lb Ft-lb、Kg-cm N-m、In-lb	3/8″ × 1/4″	0.60
DS-220	1/2″	22.0 ~ 220.0N-m			1/2″ × 1/4″ 1/2″ × 3/8″	0.90
DS-550	3/4″	55.0 ~ 550.0N-m			3/4″ × 3/8″ 3/4″ × 1/2″	2.30
DS-2200	1″	220 ~ 2200N-m			1″ × 3/4″	4.20

HDS-15/ HDS-30

NEW

TORQUE TESTER, ELECTRONIC

COMPROBADOR DINAMOMÉTRICO ELECTRÓNIC
APPAREIL DE CONTRÔLE DE COUPLE, ÉLECTRONIQUE
扭力測試機

ITEM NO.	Capacity	Dimension (mm)	(g)	(PCS)
HDS-15	1-15Nm	205(D)x155(W)x76(H)	2.94	1
HDS-30	1.5-30Nm	205(D)x155(W)x76(H)	2.94	1
HDS-150	7.5-150Nm	205(D)x155(W)x76(H)	3.44	1
HDS-500	25-500Nm	205(D)x155(W)x76(H)	4.06	1
HDS-1000	50-1000Nm	205(D)x155(W)x76(H)	4.06	1
HDS-2000	100-2000Nm	205(D)x155(W)x76(H)	4.56	1

HDS-150/ HDS-500/HDS-1000/HDS-2000