

### ATA-7014

#### **HOOD PROP**

- NEW TELESCOPIC TIP MAKES THE TOOL MORE STABLE WHILE USING
- WORKS ON ALL MAKES OF CARS AND TRUCKS
- THE TELESCOPING DESIGN ALLOWS THE MECHANIC
- TO HOLD THE HOOD IN THE DESIRED POSITION
- ALSO GOOD FOR REPAIRING WORK ON DOOR, TRUNK LID, OR HATCHBACK
- THE TOOL TELESCOPES FROM 18 1/2" to 46 1/2"

1 10 5



### **ATP-2208**

#### 

<sup>2023</sup> **LICOTA** 

#### **AUTOMOTIVE SMOKE LEAK DETECTOR**

- THIS KIT USES SMOKE TO DIAGNOSE LEAKS ON EVAP SYSTEM, INTAKE SYSTEM, EGR AND EXHAUST SYSTEM, VACUUM LEAKS AND LOW PRESSURE TURBO LEAKS.
- IT ALSO DETECTS WORN GASKETS, WORN RUBBER/SEAL AND CONNECTERS ON ALL SYSTEMS.
- SUITABLE FOR ALL KINDS OF VEHICLES.
- FILL WITH USP GRADE MINERAL OIL OR BABY OIL, ATTACH POWER CABLE TO CAR BATTERY AND CONNECT TO AIR COMPRESSOR TO MAKE THE KIT WORKS.
- EQUIPPED WITH A PRESSURE RELIEF VALVE.



### **ATG-3406**


2023 LICOTA

2023 LICOTA

#### SEAL REMOVAL AND FITTING SET

- MATERIAL:S45C
- A 15 PIECE KIT FOR THE REMOVAL & FITTING OF OIL SEALS WITHOUT DAMAGING THE REPLACEMENT SEAL OR HOUSING.
- A COMPREHENSIVE KIT WITH A RANGE OF ADAPTOR SIZES TO FIT MOST MODE.
- 8 ADAPTORS, SIZES (INNER x OUTER): 36 x 46MM, 38 x 48MM, 40 x 50MM, 40 x 52MM, 42 x 54MM, 44 x 56MM, 46 x 58MM, 48 x 60MM.
- 2 SPACER ADAPTORS, SIZES (L x DIA):35 x 45MM, 65 x 45MM; 2 SCREW THREADS: M10 & M12, INCLUDING WASHER AND NUT. NUT SECURED USING 19MM SOCKET OR SPANNER (NOT INCLUDED).
- 2 SEAL REMOVERS WITH DIFFERENT LENGTHS AND ANGLES, IDEAL FOR REMOVING SEALS IN TIGHT SPACES.
- BLACK PHOSPHATE FINISH.

ATA-2303





- MATERIAL: CR-MO STEEL
- FOR THE INSTALLATION AND REMOVAL OF DRIVELINE AND NON-DRIVELINE PARTS.
- ANY SOCKET WITH 1/4",3/8", 1/2"AND 3/4" DRIVE CAN BE USED IN ANY COMBINATION FOR USE ON VIRTUALLY ALL CARS, ATV/UTV/SXS, LIGHT DUTY TRUCKS AND FARM MACHINERY
- SET INCLUDES FLAT ANVIL ATTACHMENTS FOR GENERAL PRESSING JOBS.
- DURABLE STEEL FRAME CONSTRUCTION TESTED AT LOADS EXCEEDING 2.5 TONS.
- VERSATILE 3.5" THROAT DEPTH FOR WIDER CARDAN JOINTS.
- FORCING SCREW: 6.5"



## ATA-3518

#### **AIR VIBRATION INJECTOR PULLER SET**

- MATERIAL:CR-V+S45C STEEL PH BLACK FINISH.
- MALE DRIVE:M18x1.5 AIR PRESURE:6-9 BAR TWO SPEED DESIGNS.
- SPECIAL DESIGN FOR VIBRATING THE STUCK INJECTOR TO PULL OUT FROM ENGINE
- 1PC SWIVEL ADAPTOR M18x1.5
- ADAPTOR: M14x1.5 FOR DELPHI
- ADAPTOR: M17x1 FOR BOSCH
- ADAPTOR: M20 x 1 FOR DENSO
- ADAPTOR: M25 x 1 FOR SIEMENS
- ADAPTOR: M27 x 1 FOR SIEMENS



## **ATP-0108**

#### 2023 **LICOTA**

#### **UNIVERSAL COOLING SYSTEM PRESSURE TESTER**

- FOR JAPANESE CAR MODELS
- EASY TO OPERATE AND ASSEMBLE
- ERGONOMIC DESIGN FOR HUMAN FRIENDLY OPERATION, SAFE, QUICK AND PRECISE TESTING.





## ATS-3016

<sup>2023</sup> **LICOTA** 

#### **PNEUMATIC FLUID EXTRACTOR / 18L**

- BOX SIZE : 71 X 35 X 35 CM
- US GALLON (LIQUID): 4.7
- LITERS:18
- WORKING PRESSURE : >=90 PSL, >=6.3 KG / CM2, >=6.2 BAR
- AIR INLET : 1/4" NPT
- ACCESSORIES : MAIN TUBE, 9.8 X 1000 MM · EXTENSION TUBE, 6.7 X 850 MM, 5.8 X 850 MM



## **ATN-3001**



#### MAGNETIC RETRIEVING TOOLS

- TOTAL LENGTH : 560MM
- ATTRACTION STRENGTH: 0.5 KG
- TESTED TO 10,000 VOLT AND RATED FOR USE UP TO 1000 VOLT AC AND 1500 VOLT DC
- FLEXIBLE
- HIGH VISIBILITY ORANGE IN COLOR



### ATN-3002

#### **RETRIEVING TOOLS WITH MIRROR**

- TOTAL LENGTH : 560MM
- MIRROR DIA. 50MM
- TESTED TO 10,000 VOLT AND RATED FOR USE UP TO 1000 VOLT AC AND 1500 VOLT DC
- FLEXIBLE
- HIGH VISIBILITY ORANGE IN COLOR



## **ATN-3004**

<sup>2023</sup> LICOTA

#### **RETRIEVING TOOLS WITH LIGHT**

- MAGNETIC + LIGHT
- TOTAL LENGTH : 560MM
- ATTRACTION STRENGTH: 1.5 KG
- TESTED TO 10,000 VOLT AND RATED FOR USE UP TO 1000 VOLT AC AND 1500 VOLT DC
- FLEXIBLE
- HIGH VISIBILITY ORANGE IN COLOR



### **BNT10052**

2023 LICOTA

#### 4PCS STUD PULLER SOCKET (FOR POWER TOOLS)

- SET INCLUDE 6MM 8MM 10MM AND 12MM
- USED WITH POWER TOOLS
- SUITABLE FOR CONSTRUCTION WORK & WOOD-WORKING PROJECT



### **ATP-2169**



#### DIGITAL COMPRESSION TEST KIT

- SIDE RELEASE VALVE FOR QUICK RE-TESTING OF CYLINDER
- INCLUDED GAUGE AND 14MM/18MM SOLID SHORT ADAPTER, 14MM/18MM LONG FLEX, ADAPTER AND 14MM LONG REACH ADAPTOR.



### **ATP-2106B**



#### **DELUXE CYLINDER LEAK DETECTOR TESTER SET**

- KIT ALLOWS EASY IDENTIFICATION OF COMPRESSION PROBLEMS
- DETECTOR MEASURES EXACT LEAKAGE AMOUNT AND LOCATES LEAKS. TO INSPECT THE CAPACITY OF CYLINDER LEAKAGE, CAPACITY 0-7 BAR, .
- WHILE THE CYLINDER SYSTEM PRESSURIZES IT MUST REACH 7 BAR.
- M10x1.0 ADAPTOR-M12x1.25 ADAPTOR
- M14x1.25 EXTRA LONG ADAPTOR
   COMPRESSION TEST ADAPTOR 1-DESIGNED FOR 12MM SPARK PLUG.
- THIS ADAPTOR SUITABLE FOR FOLLOWING VEHICLES: - BMW 3351 E90, 2006 MODEL, N54 ENGINES - BMW MINI COOPER
- MERCEDES BENZ M156 (AMG MODEL MANUFCATURED FROM 2006 AND ONWARDS) PEUGEOT 207, 307 RENAULT 1.2 16 VALVE
- COMPRESSION TEST ADAPTOR 2-14MM SPARK PLUG SPECAILLY USE ON V6 AND
- 16 VALVE ENGINES WITH DEEP-SEATED SPARK PLUG PORT. 25" RUBBER HOSE WITH ADAPTOR FIT 14 AND 18MM SPARK PLUG HOLE.



### ATP-2075H

2023LICOTA

#### DIGITAL COMPRESSION TESTER

- DIGITAL MANOMETER WITH QUICK COUPLING, 0-300 PSI, DISPLAY IN KPA/BAR/MPA /PSI/KG/CM2 SUPPLIED WITH ADAPTERS SUITABLE FOR SPARK PLUG THREADS.
  - M10 x 1.0 ADAPTER
  - M12 x 1.25 ADAPTER
  - M14 x 1.25 ADAPTER
  - M18 x 1.5 ADAPTER
- BENT AND STRAIGHT RUBBER-SEALED PRESSURE PIECES FOR MANUAL USE



### **ATG-3305**

<sup>2023</sup> **LICOTA** 

#### **ALUMINUM BODY HAMMER & DOLLY SET**

- ALUMINUM HAMMERS HELP PREVENT CROSS CONTAMINATION & PROVIDE MORE FORGIVING STRIKES ONALUMINYM BODIED VEHICLES.
- · POM DOLLIES PROVIDE A LIGHTER OPTION WHEN ACCESSING A TIGHT, CONFINED LOCATION BEHIND AN ALUMINUM PANEL.



### NA

<sup>2023</sup> **LICOTA** 

#### SPARK PLUG SOCKET SET WITH 3/8" QUICK RELEASE SWIVEL EXTENSION BAR

- MADE OF DURABLE HEAT-TREATED CR-V STEEL.
- INCLUDING THREE 3/8" DRIVE SPARK PLUG SOCKET" 5/8", 3/4" AND 13/16.
- THE UNIQUE 5 INCH LONG, 3/8" DRIVEL SWIVEL EXTENSION BAR WITH SOCKET LOCKING AND QUICK RELEASE FUNCTION.
- NEW PUSH-TO-LOCK SYSTEM FITS ON ANY 3/8" DRIVE SOCKET.
- SWIVEL EXTENSION BAR WITH SOCKET LOCKING SYSTEM ALLOW MECHANIC TO USE IN HARD-TO-REACH AREAS ON VARIOUS VEHICLES WITHOUT THE RISK OF SOCKET LOOSE.



## ATS-3015

<sup>2023</sup> **LICOTA** 

#### **ELECTRIC OIL EXTRACTOR PUMP**

- ELECTRIC OIL SUCTION TOOL SET POWERED BY 12V BATTERY (NOT INCLUDED), EASY TO USE, AND NO NEED FOR AN AIR COMPRESSOR.
- SPECIAL LEVEL DETECTION MECHANISM THAT SHUTS OFF THE PUMP AUTOMATICALLY
  WHEN FLUID LEVEL REACHES TO 4.3L TO PREVENT THE TANK FROM BEING OVERFILLED.
- TANK CAPACITY: 5.5 LITER / 5.8 QUART. SPECIAL MATERIALS THAT CAN BE MADE TRANSPARENT, HEAT RESISTANT AND SUITABLE FOR EXTRACTING ENGINE OIL, COOLANT, AND ATF
- EXTENSION TUBES WITH OUTER DIAMETERS IN Ø 4MM, 6MM, 8MM, SUITABLE FOR OIL DIPSTICK TUBES ON DIFFERENT CAR MAKES.
- TOTAL TUBE LENGTH 2,700 MM / 8.9 FT (MAIN TUBE CONNECTED WITH AN EXTENSION TUBE) CAN REACH OIL DIPSTICKS ON TALL ENGINE BAYS ON SUVS, PICKUPS, AND LIGHT TRUCKS
   EXTENSION TUBE STORAGE SYSTEM AND TANK LID CAN BE DETACHED EASILY FOR
- EXTENSION TOBE STORAGE SYSTEM AND TANK LID CAN BE DETACHED EASILY FOR CLEANING PURPOSES
- STURDY ROUND BASE THAT HOLDS THE TANK IN PLACE AND AVOID WOBBLING



## **ATS-4301**

2023 **LICOTA** 

# 12V BRAKE FLUID EXCHANGE MACHINE WITH PULSATING EFFECT

- ELECTRIC BRAKE BLEEDER
- AUTOMATIC POWER OFF AS BREAK FLUID RUNS LOWER 200ML
- SELF PURGE FUNCTION TO PREVENT BUBBLE CAUSED
- CAR BATTERY APPLIED
- GUAGE READING FROM 0-7 BAR / 0-100 PSI
- RECOMMENDED WORKING PRESSURE 1-2 BAR / 14.5-29 PSI
- MAXIMUM PRESSURE 3.5 BAR / 50.7 PSI
- NET WEIGHT 6.5 KGS