

Oil & Lubricants

Ultimate Engine Performance



Your Partner In Progress
"Total Reliability With Stanley Lubricants"



AUTOMOTIVE
LUBRICANTS



MARINE
LUBRICANTS



AUTOMOTIVE
GREASE



ADDITIVE
& CHEMICALS



BRAKE FLUID
& COOLANT



BASE OIL





About Us

STANLEY GROUP is fastest growing group of companies in Middle East Asia & our activities are focused to Petroleum Products in United Arab Emirates & we are leading producers of Automotive Lubricants, Automotive Greases, Industrial Lubricants, Insulating Oils, Brake Fluids, specialty Lubricants. STANLEY Group is also trading petroleum derivatives viz. Base Oils, Additives, Polymers and specialty chemicals viz. Highly Re-Refined Base Oils, Group I, Group II, Group III, Group IV and Group V; our quality and commitments are the main driving factors of our growth. STANLEY is a premium brand of STANLEY GROUP.

STANLEY has grown from strength to strength in the past decade and is recognized as an well-reputed organization with many offices, plants and huge storage capacity tanks in UAE and abroad, our manufacturing facilities are in UAE and currently we are producing huge quantities of Automotive Lubricants, Industrial Lubricants, Food Grade Lubricants ,our plant is certified with ISO 9001:2008 & our products are endorsed by ESMA “Emirates Authority For Standardization & Metrology” (HIGHEST STANDARDISATION ORGANIZATION IN UAE), and goes through stringent quality parameters of Original Equipment Manufacturer, Society of Automobile Engineers, American Petroleum Institute and ACEA; our quality products are exported globally.

STANLEY GROUP is managed by highly qualified, skilled and experienced teams in respective departments and our “blending excellence” transformed into “TOTAL RELIABILITY” to customers and partners globally.

“TOTAL REALIBILITY WITH STANLEY LUBRICANTS”



4-Stroke Motorcycle Oil 4T 5500 SAE 20W-50 API SN JASO MA2

STANLEY MOTO 4T SAE 20W-50 API SN JASO MA2 is a synthetic 4-Stroke engine lubricant. It has excellent shear resistance protecting engine and gearbox and smooth shifting of clutches meets JASO MA2 specifications for optimal wet clutch performance. It is specially formulated with highly refined base stock, and proprietary additives.

- Outstanding thermal and oxidation stability
- Outstanding low temperature properties
- Excellent detergent/dispersant capability
- Consistent power due to reduced frictional losses

AVAILABLE PACKS
1L 2L 208L



Motor Engine Oil SAE 20W-50 API SN

STANLEY SAE 20W-50 API SN is a synthetic engine oil for gasoline passenger's cars engines, particularly suitable for turbo compressed, multi-valve and direct injection engines. It can be used in the most difficult operating conditions and is appropriated for all driving types. Especially adapted to long oil change intervals. Europe, Japan or other Asian countries.

APPLICATION BENEFITS:

- Strong protection throughout a long drain interval
- Outstanding thermal and oxidation stability
- Outstanding low temperature properties
- Excellent detergent/dispersant capability

AVAILABLE PACKS
1L 4L 5L 20L 208L



4-Stroke Motorcycle Oil 4T 7000 SAE 25W-60 API SN JASO MA2

STANLEY MOTO 4T SAE 25W-60 API SN JASO MA2 is a synthetic 4-Stroke engine lubricant. It has excellent shear resistance protecting engine and gearbox and smooth shifting of clutches meets JASO MA2 specifications for optimal wet clutch performance. It is specially formulated with highly refined base stock, and proprietary additives.

- Outstanding thermal and oxidation stability
- Outstanding low temperature properties
- Excellent detergent/dispersant capability
- Consistent power due to reduced frictional losses

AVAILABLE PACKS
1L 2L 208L



Motor Engine Oil SAE 5W-40 API SN

STANLEY SAE 5W-40 API SN is a fully synthetic engine oil for gasoline passenger's cars engines, particularly suitable for turbo charged, multi-valve and direct injection engines. It can be used in the most difficult operating conditions and appropriate for all driving terrain. Especially adapted to long oil change intervals.

APPLICATION BENEFITS:

- Strong protection throughout a long drain interval
- Outstanding thermal and oxidation stability
- Outstanding low temperature properties
- Excellent detergent/dispersant capability

AVAILABLE PACKS
1L 4L 5L 20L 208L



4-Stroke Motorcycle Oil 4T 7000 SAE 25W-50 API SN JASO MA2

It is developed with Synthetic oil and the latest additive technology to achieve exceptional resistance to oxidation and wear of cylinders, rings and valve train in high compression and high revolution 4-stroke engines while protecting the transmission gears, Its advanced technology in additives and oil provides benefits such as:

- Maximum Clutch Grip
- Friction Control Between Discs And Plates
- Maximum Transmission Protection
- Minimum Wear Of Rings And Bearings
- Maximum Internal Cleaning

AVAILABLE PACKS
1L 2L 208L



Motor Engine Oil SAE 10W-30 API SN

STANLEY SAE 10W-30 API SN is a fully synthetic engine oil for gasoline passenger's cars engines, particularly suitable for turbo charged, multi-valve and direct injection engines. It can be used in the most difficult operating conditions and suitable for all roads. Especially adapted to long oil change intervals.

APPLICATION BENEFITS:

- Strong protection throughout a long drain interval
- Outstanding thermal and oxidation stability
- Outstanding low temperature properties
- Excellent detergent/dispersant capability

AVAILABLE PACKS
1L 4L 5L 20L 208L



4-Stroke Motorcycle Oil 4T 7000 SAE 10W-40 API SN JASO MA2

STANLEY MOTO 4T SAE 10W-40 API SN JASO MA2 is a synthetic 4-Stroke engine lubricant. It has excellent shear resistance protecting engine and gearbox and smooth shifting of clutches meets JASO MA2 specifications for optimal wet clutch performance.

- Overall optimized balance of engine performance
- Friction Control Between Discs And Plates
- Ultimate confidence of protection throughout drain interval
- Minimum Wear Of Rings And Bearings
- Maximum Internal Cleaning

AVAILABLE PACKS
1L 2L 208L



Motor Engine Oil SAE 25W-60 API SN

STANLEY SAE 25W-60 API SN is a fully synthetic engine oil for gasoline passenger's cars engines, particularly suitable for turbo charged, multi-valve and direct injection engines. It can be used in the most difficult operating conditions and suitable for all roads. Especially adapted to long oil change intervals.

APPLICATION BENEFITS:

- Strong protection throughout a long drain interval
- Outstanding thermal and oxidation stability
- Outstanding low temperature properties
- Excellent detergent/dispersant capability

AVAILABLE PACKS
1L 4L 5L 20L 208L



Diesel Engine Oil SAE 15W-40 API CK-4

STANLEY SAE 15W-40 API CK-4 is extra high performance Heavy- Duty Diesel Engine Oil specially developed for use in modern, low emission diesel engines, including those fitted with Exhaust Gas Re-Circulation (EGR) systems.

APPLICATION BENEFITS:

- Strong protection throughout a long drain interval
- Outstanding low temperature properties
- Excellent detergent/dispersant capability
- Outstanding thermal and oxidation stability

AVAILABLE PACKS

1L 4L 5L 20L 208L



Gear Oil SAE 80W-90 API GL-5

STANLEY is Manufactured from selected additives in high quality refined mineral oil with additive treatment to provide oxidation and wear resistance. Can be used in gearbox application where a GL-5 oil is recommended. Provides wear protection over a wider range of temperature and performance.

BENEFITS:

- Maximum thermal stability
- Excellent protection against rust
- Excellent Lubricity to Gear
- Prime others Excellent Cleanliness & Detergency
- Increase parts Life

AVAILABLE PACKS

1L 4L 5L 20L 208L



Diesel Engine Oil SAE 25W-50 API CJ-4

STANLEY SAE 25W-50 API CJ-4 is extra high performance Heavy- Duty Diesel Engine Oil specially developed for use in modern, low emission diesel engines, including those fitted with Exhaust Gas Re-Circulation (EGR) systems.

APPLICATION BENEFITS:

- Strong protection throughout a long drain interval
- Outstanding low temperature properties
- Excellent detergent/dispersant capability
- Outstanding thermal and oxidation stability

AVAILABLE PACKS

1L 4L 5L 20L 208L



Gear Oil SAE 85W-140 API GL-4

"STANLEY GEAR OIL SAE 85W-140 API GL-4" is a premium grade gear lubricant in a wide range of automotive transmissions. This is formulated from excellent quality base stocks and performance proven extreme pressure additives to provide protection to gear components against wear, scoring, oxidation and rust.

BENEFITS:

- Maximum thermal stability
- Excellent protection against rust
- Excellent Lubricity to Gear
- Prime others Excellent Cleanliness & Detergency
- Increase parts Life

AVAILABLE PACKS

1L 4L 5L 20L 208L



Diesel Engine Oil SAE 25W-60 API CI-4

STANLEY 25W-60 is modern high technology based diesel engine oil exceeding the latest API CI-4 performance specification. Developed to provide maximum protection for use in modern passenger cars including low emission engines and high performance vehicles.

APPLICATION BENEFITS:

- Strong protection throughout a long drain interval
- Outstanding low temperature properties
- Excellent detergent/dispersant capability
- Outstanding thermal and oxidation stability

AVAILABLE PACKS

1L 4L 5L 20L 208L



Automatic Transmission Fluid ATF Dexron III

STANLEY ATF DEX III is Universal fully synthetic Automatic Transmission Fluid is formulated with synthetic base stocks and technologically advanced additives that provide oxidation and thermal stability, friction control, load-carrying ability, as well as corrosion and wear protection.

BENEFITS:

- Very good thermal stability.
- Excellent resistance to oxidation.
- Good shear strength.
- Excellent parts material compatibility
- Very low pour point

AVAILABLE PACKS

1L 4L 5L 20L 208L



Diesel Engine Oil SAE 15W-40 CI-4 / SL

STANLEY SAE 15W-40 API CI-4/SL is extra high performance Heavy- Duty Diesel Engine Oil. It is blended from selected base stocks and new generation performance additives. Shear stable performance helps maintain oil viscosity, handle higher soot level and protect engine parts against wear and corrosion.

BENEFITS:

- Strong protection throughout a long drain interval
- Outstanding thermal and oxidation stability
- Outstanding low temperature properties
- Excellent detergent/dispersant capability

AVAILABLE PACKS

1L 4L 5L 20L 208L



ATF CVT CONTINUOUSLY VARIABLE TRANSMISSION FLUID

STANLEY CVT FLUID is formulated with premium full synthetic base oils and technologically advanced additives. This high performance chemistry is specifically engineered for and unique to CVT applications; offering outstanding anti-shudder durability, friction stability, anti-wear protection, and advanced low and high temperature operation characteristics.

APPLICATION BENEFITS:

- Metal Anti-wear on pull-chain CVTs
- Good shear stability, anti-foaming and anti wear
- Effective foam control properties
- Good performance on high torque applications

AVAILABLE PACKS

1L 4L 5L 20L 208L





ANTIFREEZE COOLANT 50%

STANLEY Antifreeze is a superior quality coolant. It is an glycol based product that incorporates powerful additive technology to ensure year-round protection against freezing and corrosion. Our Antifreeze is free from Nitrites, Nitrates, Borates and Phosphates

PERFORMANCE FEATURES:

- Guards against corrosion and rust.
- Suitable for all water cooled petrol and diesel engines
- Improves efficiency and reduces operating costs.

AVAILABLE PACKS

1L 4L 5L 20L 208L



ANTIFREEZE COOLANT 100%

STANLEY Antifreeze is a concentrated superior quality coolant. It is an glycol based product that incorporates powerful additive technology to ensure year-round protection against freezing and corrosion. Our Antifreeze is free from Nitrites, Nitrates, Borates and Phosphates

PERFORMANCE FEATURES:

- Guards against corrosion and rust.
- Suitable for all water cooled petrol and diesel engines
- Improves efficiency and reduces operating costs.

AVAILABLE PACKS

1L 4L 5L 20L 208L



Brake Fluid DOT 4

STANLEY Super HD Brake Fluid DOT 4 is extra high performance poly glycol based brake fluid developed for superior braking performance in a wide range of vehicles including those operating at higher temperatures. It contains oxidation and corrosion inhibitors to resist oxidation at the high temperatures encountered in the disc braking systems and to provide superior protection against corrosion of metallic components of the brake system.

AVAILABLE PACKS

250G 500GM



Brake Fluid DOT 3

STANLEY Brake Fluid DOT 3 is a glycol-based brake fluid designed for use in hydraulic brake system of any commercial vehicles, passenger cars and motorcycles operating under moderate service conditions and requiring a DOT 3 type of fluid. It provides lubricity and system protection. Also, compatible with all seals and metals used in conventional braking systems.

AVAILABLE PACKS

250G 500GM



EP GREASE LITHIUM EP GREASE

A high quality multipurpose extreme pressure lithium soap based grease for use in a wide range of industrial applications. These are manufactured from highly refined base oils and performance additives to provide excellent wear protection, good structural stability, resistance to water washout and effective protection from corrosion.

Benefits: it protects from :

- * Water washout and bearing corrosion
- * Process water contamination
- * Extreme pressure

AVAILABLE PACKS

500G 1KG 3KG 15KG 180 KG



MULTIPURPOSE GREASE CALCIUM MP GREASE

Multipurpose calcium soap based grease is designed to lubricate automotive bearings in wet, normal-temperature and normal load applications. It is formulated to remain stable and perform well under all conditions.

Benefits:

- * Good corrosion protection.
- * Good low temperature fluidity.
- * Resistance to water washout.
- * Pumpability even in cold weather.

AVAILABLE PACKS

500G 1KG 3KG 15KG 180 KG



Hydraulic Oil ISO 68

Hydraulic oil ISO 68 range is high quality premium grade Hydraulic Oils, produced with unique technology to provide outstanding protection and performance. It is used in most hydraulic system of many mobile equipments.

Product Benefits:

1. Excellent wear protection and longer life to moving parts.
2. Rust and corrosion protections.
3. Excellent oxidation resistance to deforming properties.
4. Stable film strength for boundary lubrication.

AVAILABLE PACKS

1L 4L 5L 20L 208L



TRANSMISSION OIL 10W

STANLEY SAE 10W is a mineral oil used in engine and hydraulic system of payloaders, particularly suitable for transmission and direct injection engines. It can be used in the most difficult operating conditions and is appropriated for all load conditions.

BENEFITS:

- Strong protection throughout a long drain interval
- Outstanding thermal and oxidation stability
- Outstanding low temperature properties
- Excellent detergent/dispersant capability

AVAILABLE PACKS

208L



<p>UNITED ARAB EMIRATES MINISTRY OF INDUSTRY & Advanced Technology</p>		<p>الإمارات العربية المتحدة وزارة الصناعة والتكنولوجيا المتقدمة</p>
<p>شهادة Certification of Conformity SGS Gulf Limited</p>		
<p>معيمة من قبل وزارة الصناعة والتكنولوجيا المتقدمة Notified body by Ministry of Industry and Advanced Technology</p>		
		
<p>Certificate Number:</p>	<p>21-05-25682621-05-08573</p>	<p>الرقم الشهادة</p>
<p>Registration Date:</p>	<p>20-September-2021</p>	<p>التاريخ التسجيل</p>
<p>Valid Until:</p>	<p>29-September-2022</p>	<p>معدية حتى</p>
<p>Issued To:</p>	<p>Nasdaq International Lubricant Industry L.L.C.GBR</p>	<p>المصدر الى</p>
<p>Address:</p>	<p>P.O.Box Alkhayma, 5552, United Arab Emirates</p>	<p>العنوان</p>
<p>Section:</p>	<p>Petroleum products</p>	<p>المنتجات البترولية</p>
<p>Regulation:</p>	<p>Petroleum products</p>	<p>التشريع</p>
<p>Product Category:</p>	<p>Lubricating oil for Internal Combustion Engines</p>	<p>زيت التشحيم لمحركات الاحتراق الداخلي</p>
<p>Product Sub-Category:</p>	<p>Lubricating oil for Internal Combustion Engines</p>	<p>زيت التشحيم لمحركات الاحتراق الداخلي</p>
<p>Products details:</p>	<p>See Schedule of Certification</p>	<p>انظر الجدول الزمني للشهادة</p>
<p>Products listed in the attached Schedule of Certification are registered under the External Conformity Assessment Scheme (EICAS) based on compliance to the relevant standards.</p>		
<p>This is an electronic certificate and does not require display and signature. To verify the certification please use the QR-CODE. Any changes or modification on the certificate will affect its validity.</p>		
<p>EMISSA</p>	 <p>www.emissaglobal.com</p>	 <p>EMISSAG</p>

 **Afton**
Passion for Solutions

Statement of Quality

STANLEY UHPD SAE 15W-40 API CI-4/SL

We hereby confirm that **STANLEY UHPD SAE 15W-40 API CI-4/SL** Engine Oil formulated and blended with **Afton Chemical Ltd** additive package **VERTEC 12300** at 38.8% mass formulation code **LOB-017973-8** SAE 15W-40 meets the performance of:

**Caterpillar RCF-2
Caterpillar ECF-1a**

This statement is **invalidated** if the formulation and/or recommended blending procedures have been changed.


For Afton Chemical Ltd,

Karel Chygar
Customer Technical Service Specialist

January 2011



Afton Chemical Limited
Unit 10, Broomfield Industrial Estate, Watlington, Oxford OX12 2BA, UK
T: +44 (0) 1244 269141 F: +44 (0) 1244 269142 www.aftonchemical.com
Email: technical@aftonchemical.com
Afton Chemical Limited is a wholly owned subsidiary of Afton Chemical Corporation, a public company listed on the New York Stock Exchange.
Registered in the UK as a company limited by guarantee. Registered number: 02068231



AMERICAN
PETROLEUM
INSTITUTE

License No. 3463


SCHEDULE A - LICENSE AGREEMENT

The marks referred to and licensed under the Agreement between API and
HENKEL INTERNATIONAL LUBRICANT INDUSTRY LLC
 may be used through 31-Dec-2021 as follows:

API SERVICE SYMBOL

Licensee is authorized to use the API Certification Mark on the following products:


DRIVE/NAME	SAE VISCOSITY	API SERVICE CATEGORY	CLASSIFICATION
STANLEY SUPER	100-40	SL	
STANLEY SUPER	100-40	SL	
STANLEY SUPER	200-40	SL	
STANLEY SUPER	200-40	SL	
STANLEY SYNTH	100-30	SN	
STANLEY SYNTH	100-30	CA-50	
STANLEY UNF	100-40	CA-50	
STANLEY UNF	100-40	CA-50	
STANLEY UNF	100-40	CA-50	
STANLEY ULTRA	100-40	SL	
STANLEY ULTRA	200-40	SL	
STANLEY ULTRA PLUS	200-40	SP	Resource Consulting SA-100
SYNTHOL	200-40	SP	
SYNTHOL	200-40	SN	
SYNTHOL	200-40	SN	
SYNTHOL	200-40	SN	
SYNTHOL	200-40	SN	Resource Consulting SA-100
SYNTHOL	100-30	SL	
SYNTHOL	100-40	SL	
SYNTHOL	100-40	SL	
SYNTHOL	100-40	CA-50	
SYNTHOL	100-40	CA-50	


 Manager - EOL/CD/EN/CM
 Date: 16-Apr-2021

Engine Oil Licensing and Certification System

Engine Oil Licensing and Certification System is a service of API Lubricant Industry LLC, a subsidiary of API.

To verify the authenticity of this document, go to apiengineoil.org (enter API Certification Mark Number)



API
LUBRICATING
ENGINE OILS

License No. 2643


SCHEDULE A - LICENSE AGREEMENT

The marks referred to and contained under the Agreement between API and
HENKEL INTERNATIONAL LUBRICANT INDUSTRY LLC
 may be used through 31-03-2025 as per below:


AN OIL CERTIFICATION MARK

Licensee is authorized to display the API Certification Mark on the following product:

BRAND NAME	API VISCOSITY GRADE	USAC SPECIFICATION
PERM	100-20	GF-4
PERM	200-20	GF-4
STANLEY	100-20	GF-4
STANLEY	200-20	GF-4
SPYNOL	100-20	GF-4
SPYNOL	200-20	GF-4



**FOR
GASOLINE
ENGINES**



API
LUBRICATING
ENGINE OILS

[Signature]
Manager - ELOCESEF@HON
 Date: 14-May-2021

Engine Oil Licensing and Certification System

Copyright © 2000-2021 Henkel Adhesives Corporation. All Rights Reserved. Reproduction without written permission is prohibited.

To verify the authenticity of this document, go to api.org/apiapi or apiindia.com

