


REGUPOL ANTISLIP MATS


PRODUCT PASS

Show this pass at roadside checks


**REGUPOL
CARGO MAT 7210®**



**REGUPOL
CARGO MAT 9510®**



**REGUPOL
CARGO MAT 1000®**



	250 t/m ² ≈ 2.50 N/mm ²	350 t/m ² = 3.50 N/mm ²	630 t/m ² = 6.30 N/mm ²
Maximum load	at 8 mm thickness and 30 % vertical deformation acc. to VDI 2700, part 15, based on DIN EN ISO 3386-2. Test sample size 60 x 60 mm		
Colour	Black with dark green, light green and yellow particles	multicolored	Black with yellow particles
• Test value acc. to VDI 2700 [part 15]	0,75 μ	0,92 μ	0,82 μ
	Taking into account the safety factor of 5% according to VDI 2700, page 14		
• Value achieved in practice	0,6 μ	0,6 μ	0,6 μ
	Recommendation REGUPOL		
Weight	approx. 6.88 kg/m ²	approx. 8.1 kg/m ²	approx. 7.6 kg/m ²
	at 8 mm thickness		
Resistant to	UV light, sodium chloride, weak acids and alkaline solutions (swelling possible on contact with hydrocarbons, oils, fuels, etc.)		

REG ASM PP EN 082019
Printed August 2019

