



# RUGOPOL

POLYESTER PUTTY

# POLYESTER PUTTY RP-355 UNIVERSAL




- It can be used as a filling and probe paste.
- Easy to apply, it does not flow at the time of application and it does not make holes and lines.
- Dry quickly, even at low air temperatures, and it can be sanded after a short time.
- Soft and easy to sand.
- There is no risk of tearing.
- Elasticity and Impact Resistance is high.


After applying all kinds of 1K and 2K primers to it, any top coat of paint can be applied.




Clean  
Surface



Hardener



5-10 mins  
20°C




20-40 mins  
20°C



P - 80  
P - 180



Avoid  
sunlight



See  
Data Sheet

## USAGE AREA

- POLYESTER LAMINATES
- STEEL
- GALVANIZED STEEL
- ALUMINIUM
- 2 COMPONENT ACRYLIC PRIMERS
- OLD PAINT COATINGS

Gross Filling	Hardener	Pcs Per Box
1 Kg	15 Gr	12 Pcs
1,8 Kg	40 Gr	8 Pcs
2,5 Kg	50 Gr	6 Pcs
2,7 Kg	50 Gr	6 Pcs

Color: Light Yellow




# GALVANIZED PUTTY RP-390

- It can be used as a filling and probe paste.
- Easy to apply, does not flow, and does not create holes and lines at the time of application.
- Dry quickly,
- It can be sanded after a short time even at low air temperatures.

There is no risk of tearing, and it has high elasticity and impact resistance.




Clean  
Surface



Hardener



5-10 mins  
20°C




20-40 mins  
20°C



P - 80  
P - 180



Avoid  
sunlight



See  
Data Sheet



## USAGE AREA

- POLYESTER LAMINATES
- STEEL
- GALVANIZED STEEL
- ALUMINIUM
- 2 COMPONENT ACRYLIC PRIMERS
- OLD PAINT COATINGS

Gross Filling	Hardener	Pcs Per Box
1 Kg	15 Gr	12 Pcs
1,8 Kg	40 Gr	8 Pcs
2,5 Kg	50 Gr	6 Pcs
2,7 Kg	50 Gr	6 Pcs

Color: Light Grey




# POLYESTER PUTTY RP-633 PREMIUM



- Easy to apply it does not flow at the time of application, and it does not make holes and lines.
- Dry quickly, even at low air temperatures, and it can be sanded after a short time.
- Soft and easy to sand. There is no risk of tearing.
- Elasticity and Impact Resistance are high.




Clean  
Surface



Hardener



5-10 mins  
20°C




20-40 mins  
20°C



P - 80  
P - 180



Avoid  
sunlight



See  
Data Sheet

## USAGE AREA

- POLYESTER LAMINATES
- STEEL
- GALVANIZED STEEL
- ALUMINIUM
- 2 COMPONENT ACRYLIC PRIMERS
- OLD PAINT COATINGS

Gross Filling	Hardener	Pcs Per Box
1 Kg	15 Gr	12 Pcs
1,8 Kg	40 Gr	8 Pcs
2,5 Kg	50 Gr	6 Pcs
2,7 Kg	50 Gr	6 Pcs

Color: White




# POLYESTER PUTTY RP-375 SUPER

- It can be used as a filling and probe paste.
- Easy to apply, it does not flow at the time of application, and it does not make holes and lines.
- Dries quickly, even at low air temperatures, and it can be sanded after a short time.
- Soft and easy to sand.
- There is no risk of tearing.
- Elasticity and Impact Resistance is high.

After applying all kinds of 1K and 2K primers to it, any top coat of paint can be applied.




Clean  
Surface



Hardener



5-10 mins  
20°C




20-40 mins  
20°C



P - 80  
P - 180



Avoid  
sunlight



See  
Data Sheet

## USAGE AREA

- POLYESTER LAMINATES
- STEEL
- GALVANIZED STEEL
- ALUMINIUM
- 2 COMPONENT ACRYLIC PRIMERS
- OLD PAINT COATINGS



Gross Filling	Hardener	Pcs Per Box
1 Kg	15 Gr	12 Pcs
1,8 Kg	40 Gr	8 Pcs
2,5 Kg	50 Gr	6 Pcs
2,7 Kg	50 Gr	6 Pcs

Color: Light Grey

# FIBER PUTTY RP-333




Two-component polyester putty suitable for sheet metal surfaces used to close holes in the bodywork with its fiber content.

After applying of all kinds of 1K and 2K primers on it, any top coat of paint can be applied.




Clean  
Surface



Hardener



5-10 mins  
20°C




20-40 mins  
20°C



P - 80  
P - 180



Avoid  
sunlight



See  
Data Sheet

## USAGE AREA

- POLYESTER LAMINATES
- STEEL
- GALVANIZED STEEL
- ALUMINIUM
- 2 COMPONENT ACRYLIC PRIMERS
- OLD PAINT COATINGS

Gross Filling	Hardener	Pcs Per Box
1 Kg	15 Gr	12 Pcs
1,8 Kg	40 Gr	8 Pcs

Color: Light Grey




# ALUMINIUM POLYESTER PUTTY RP-396

- Contains a special aluminum metal pigment with high filling capacity
- Easy to apply, it does not flow at the time of application, and it does not make holes and lines.
- Dry quickly, even at low air temperatures, and it can be sanded after a short time.
- Easy to sand.
- There is no risk of tearing.
- Elasticity and Impact Resistance is high.




Clean  
Surface



Hardener



5-10 mins  
20°C




20-40 mins  
20°C



P - 80  
P - 180



Avoid  
sunlight



See  
Data Sheet



## USAGE AREA

- POLYESTER LAMINATES
- STEEL
- GALVANIZED STEEL
- ALUMINIUM
- 2 COMPONENT ACRYLIC PRIMERS
- OLD PAINT COATINGS

Gross Filling	Hardener	Pcs Per Box
1 Kg	15 Gr	12 Pcs
1,8 Kg	40 Gr	8 Pcs

Color: Light Grey



**Head Office:**

Mescit Mah. Demokrasi Cad.  
Birmes San. Sitesi B8 Blok No.1  
Tuzla/İstanbul Turkey

**Factory:**

Taşköprü Mah. Sanayiciler Cad.  
Yalova Sanayiciler Sitesi No.10  
Çiftlikköy/Yalova Turkey

+90 (216) 304 06 59  
info@yaskokompozit.com