



1-877-238-2095
www.standardlifts.com

SPRAY WASH CABINET

The SWE series spray wash cabinets are the parts cleaning equipment for manufacturing and maintenance work cells, or other heavy-duty industrial environments. This equipment sprays hi-pressure hot water to wash parts and clean grease, oil, grime, machine colorant, dirt, stamping oil, drawing compound and several other manufacturing soils from pans & components. Different powers available.

Features:

- **24VAC safety control panel power**
- **Low water level sensor and alarm** protects heating elements against low water levels
- **Stainless steel oil skimmer** allows longer use of solution whilst changing less frequently
- **7-day timer included** to eliminate early morning starts for you and your staff
- **Gear drive** that won't rob you of water pressure like water driven models can tend to do
- **Slow 5 rpm** gives a superior, more thorough cleaning performance
- **600L insulated solution tank** provides an ample supply of water for extra heavy-duty parts
- **Optional small parts baskets** allow for the containment of small parts
- **Full opening gasket free door** will often perish with long term exposure to steam
- **Removable tank filter screen** allows for quick and easy cleaning
- **Turntable jog switch** make loading & unloading the parts easily



Specification:

Model	SWE-6060/218	SWE-6060/236	SWE-3566/218	SWE-3566/236
Inside Job Height	60in/ 1,500mm	60in/ 1,500mm	60in/ 1,500mm	60in/ 1,500mm
Turntable Diameter	60in/ 1,500mm	60in/ 1,500mm	60in/ 1,500mm	60in/ 1,500mm
Overall Height	86in/ 2,185mm	86in/ 2,185mm	86in/ 2,185mm	86in/ 2,185mm
Load Capacity	3,300lbs/ 1,500kg	3,300lbs/ 1,500kg	3,500lbs/ 1,600kg	3,500lbs/ 1,600kg
Wash Cycle Timer	0-300 Minute	0-300 Minute	0-300 Minute	0-300 Minute
Skim Cycle Timer	0-300 Minute	0-300 Minute	0-300 Minute	0-300 Minute
Pump	10hp/ 7.5kW (Vertical)	10hp/ 7.5kW (Vertical)	15hp/ 11kW (Vertical)	15hp/ 11kW (Vertical)
Heating Element	3 x 6 kW	6 x 6 kW	3 x 6 kW	6 x 6 kW
Water Temperature	15°-90°C/ 60°-194°F	15°-90°C/ 60°-194°F	15°-90°C/ 60°-194°F	15°-90°C/ 60°-194°F
Solution Capacity	160Ga/ 600L	160Ga/ 600L	160Ga/ 600L	160Ga/ 600L
Number of Nozzle	52	52	52	52
Low Water Auto Refill	None	None	Included	Included
Power	3 Phase	3 Phase	3 Phase	3 Phase
Cabinet & Door	4.0mm thickness	4.0mm thickness	4.0mm thickness	4.0mm thickness

*Specifications Subject to Change Without Notice

*Power requirement: JPN 200V-220VAC/ EUR 220-240VAC/ 380-415VAC, AUS 240VAC/ 415VAC, USA 208-240VAC/ 480VAC

Standard Lift & Equipment, Inc
10505 Valley Blvd, STE #308, El Monte, CA 91731
www.standardlifts.com sales@standardlifts.com