

# About Us

Founded in 2008 in Tbilisi, Georgia, "OTO MOTORS" has become a prominent player in the local market.

What started as a modest enterprise, has grown exponentially over the years and has extended its presence throughout the region.

Presently, with 5 branches and over 150 employees, the company has achieved comprehensive coverage of the local market with its **high-quality products** 

Dedicated to achieving excellence in product quality and customer satisfaction, **OTO MOTORS** is resolute in its commitment to sincerity and continuous improvement.

The company aims to establish itself as a leader in the global market and seeks to foster greater collaboration with partners worldwide. Its team of professionals is highly adaptable and ensures expeditious and effective communication with customers worldwide, thereby facilitating prompt delivery of products and information.

**OTO MOTORS** continues to expand its market share both locally and globally through its diverse range of offerings, which includes **lubricants**, **batteries**, auto body parts, car accessories, service equipment, and many other products.









# • S太モ 0W-20 太PI SN/CF•

### FULLY SYNTHETIC

Takasaki **OW-20** is a full synthetic engine oil that uses premium quality full synthetic base oil and high-quality additives making this engine oil suitable for vehicles requiring **API SP/CF** and **ILSAC GF-6**.

Takasaki **DW-20** is designed for use in modern naturally aspirated, supercharged **&** turbocharged petrol, low emission engines and hybrids vehicles. It's also recommended for passenger cars,

4WD's and light commercial vehicles where Petrol, E10 and E85 fuels are used.

Packaging: Material - Metal ( Tin )
Packaging (L ): ILt; 4Lt; 6OLt; 20OLt





# • S太モ 5W-20 太PI SH/CF•

## FULLY SYNTHETIC

5W-20 is a premium synthetic engine oil formulated to meet the requirements of modern petrol and light-duty diesel engines. it is recommended for passenger cars (including multi-valve, supercharged & turocharged), 4WD's, and light commercial vechiles including those with a diesel particulate filter (DFP) or other emissions treatment devices.

Takasaki 5W-20 is low viscosity engine oil that meets the latest ACEA C5, API SN/CF, and ILSAC GF-5 specifications.

Packaging: Material - Metal (Tin)
Packaging (L): 1Lt: 4Lt: 60Lt: 200Lt

# • Z太モ**5W-3**0 太PI ZN/CF•

## FULLY SYNTHETIC

Takasaki **5W-30** is high efficient motor oil is used in modern four-stroke engines of light vechiles, minibuses and medium vans. It contributes to increase of engine life and fuel economy due to friction saving. Can be used for engines working on bio fuel. the oil is specially designed for meeting dexosl specifications standards.

Description:

SAE 5W30 synthetic Dil

API SN/CF & ILSAC GF-5

Packaging: Material - Metal ( Tin )
Packaging (L ): ILt; 4Lt; 6OLt; 20OLt







# • S太モ 5W-40 太PI SH/CF•

### FILLLY SYNTHETIC

Takasaki SAE 5W-40 fully synthetic engine oils is formulated to meet the new API SN standards. Dils which comply to the API SN service category have demonstrated in tests to provide greater protections of the emission systems and turbochargers, this top tier engine oil is much sough after for its outstanding performance protection, it is especially suited for high-rpm engines that may be running hotter

the specially selected synthetic components and the advanced additive technology of INVICIBLE SAE 5W-40 ensure tip-top performance over extended period of driving, this project is suitable for use in all modern gasoline engine cars and light trucks. It is a licensed product with API (American Petroleum Institute)

Packaging: Material - Metal (Tin )
Packaging (L): ILt; 4Lt; 6OLt; 20OLt

# •S太モ 10W-40 太PI SH/CF•

### SEMI SYNTHETIC

Takasaki **SAE IOW-40** is semi synthetic engine oil formulated to meet the new **API SN** standards. Dil which comply to the **API SN** service category have demonstrated in tests to provide greater protections of the emission systems and turbochargers. this top tier engine oil is much sought after for its outstanding performance protection.

specially selected synthetic components and the advanced additive technology of super-GT SAE IOW-40 ensure tip-top performance over extended period of driving, this project is suitable for use in all modern gasoline engine cars and light trucks, it is a licensed product with API (American Petroleum Institute)

Packaging: Material - Metal (Tin)
Packaging (L): 1Lt; 4Lt; 6OLt; 20OLt







# • ATF DEXRON VI •

## PREMIUM TRANSMISSION DIL

Takasaki ATF VI transmission fluid is formulated with synthetic base oils and an additive package suitably balanced in order to give the lubricant the properties required by the **Dexron VI**.

## Takasaki ATF VI gear oil guarantees:

Exceptional low temperature performance, improved thermal and oxidition stability, excellent fractional properties that provide smooth gear shifting at low temperatures and help to prevent transimission vibration, exceptional ressistance to the formation of sludge and deposits,

prolonged life of the fluid.

Packaging: Material - Metal ( Tin )
Packaging (L ): ILt; 4Lt; 6OLt; 20OLt





# • 太TF III •

## MILITI-MATIC FILLID

Takasaki ATF type III is a modern automatic transimission oil that complies with the most recent GM Dexron III specifications.

ATF type III is a semi-synthetic product with specially selected additives to give the product the following properties: extremely low viscosity at low temperatures.

Packaging: Material - Metal ( Tin )
Packaging (L ): 1Lt; 4Lt; 60Lt; 200Lt





# • ATF SP IV •

## MULTI-MATIC FLUID

Takasaki ATF type T-IV is a fully synthetic automatic transmission fluid specially engineered to exceed the service fill requirement of all TOYOTA and LEXUS vehicles installed with AISIN WARNER gearboxes, where ATF T-IV fluid is recommended.

Packaging: Material - Metal ( Tin )
Packaging (L ): ILt; 4Lt; 60Lt; 200Lt





# • CVT •

## CONTINUOUSLY VARIABLE

Takasaki CVT (Continuous Variable Transmissions) is a type of Automatic Transmission used in different Japanese and American cars. (some models from Toyota, Nissan, Ford etc etc) and it has different Dil (CVT Fluid). ATF (Automatic Transmission Fluid) is a oil used in Automatic Transmission other than CVT Transmissions.

Packaging: Material - Metal ( Tin )
Packaging (L ): 1Lt; 4Lt; 6OLt; 20OLt

# • 太下 日前前下 •

MILITI-MATIC FILLIN

Takasaki HMMF stands for Ultra Multi Matic Fluid (HMMF). It is fluid for continuously variable transmissions (CVT), oil for variable speed transmission honda cars, provides system CVT (HMM- one of its variants), based on the method of starting the clutch in cars HONDA, and has a longer life.

Packaging: Material - Metal (Tin)
Packaging (L): ILt; 4Lt; 6OLt; 20OLt



# FULL RANGE OF OUR PRODUCT

### AUTOMATIC TRANSMISSION FLUID

Takasaki ATF VI

GM Dexron VI , GMN 10060, MB 236.41

### PASSENGER VEHICLE MOTOR DILS

#### Takasaki SAE OW30 Fully Syntethic

API SM/SL/CF; ACEA AI/BI/A5/85/C2 VW 502.00 - 505.00 : BMW LL04 : GM LL 8-025 : Renault RN 0700/0710

#### Takasaki SAE OW2O Fully Synthetic

API SN/SM/CF : ACEA A5/B5

#### Takasaki SAE OW40 Fully Synthetic

API SN/SM/CF; ACEA A3/B4

#### Takasaki SAE 5W30 Fully Synthetic

API SN/CF : ACEA AI/BI/A5/B5

#### Takasaki SAE 5W40 Fully Synthetic

API SN/CF : ACEA A3/B3/B4-C3 : MB 229.3 : GM L L-B025 : VW 503.00 - 501.00 : GM LL B-025 : BMW LLDI

#### Takasaki SAE 10W30

API SM(SN)/CF : ACEA A3/B3

#### Takasaki SAE 10W40

API SL/CF ; ACEA A3/B3/B4 ; MB 229.1-229.3 ; VW 500.0 - 501.0 - 505.00 ; GM LL B-025 ; BMW LLDI

#### Takasaki SAE 15W40 Turbo

API SJ/CF : ACEA A2/82/E2 : MB 228.1 : VW 500.00 - 505.00 RVI RDI : MIL L 461520 - MIL L 2104E : Cateroillar TD2 : Allison C4 Fluid

#### MOTORCYCLE 2T & 4T MOTOR DILS - 2 STROKE & 4 STROKE

#### Takasaki 2T ( 2 Stroke ) Synthetic

API TC+ / JASO FC/FD; ISO-L-GD; TISI 1040

### Takasaki 2T ( 2 Stroke ) Semi Synthetic

API TC+ / JASO FC/FD ; ISO-L-GD ; TISI 1040

#### Takasaki 4T ( 4 Stroke ) 5W40

JASO T 903 MA2 ; API SL/CF

#### Takasaki 4T ( 4 Stroke ) 10W40

JASO T 903 MA2: API SJ/CF

## Takasaki 4T ( 4 Stroke ) 15W40

API SJ : JASO T903 MA2

## **BRAKE FLUIDS**

#### Takasaki DOT 3

SAE-J-1703 E; FMVSS 116; DOT3

#### Takasaki DOT 4

SAE-J-1703 FJ AN 956 DI; FMVSS 116

# GREAR DILS

### Takasaki 75W-80

API GL5; Mil-L-2105C/D; MAN 341

#### Takasaki 75W-90

API GL5, MIL-L-2105D

#### Takasaki 80W-90

API GL-3/GL-4/GL-5, MIL-L-2105D ; MB235.0

#### Takasaki SAE 140

API GL5, MIL-L-2105D

#### Takasaki ATF Dexron II

GM Dexron IID; MB 236.7; ZF-TE-ML 09-11-14
 Voith G607; Allison C4; Caterpillar T02; MAN 339C

#### Takasaki ATF Dexron III

GM Dexron II: DIII GIII: TASA: Ford Mercon M991006: Allison C4-TES 389
 MB 236-1-5-6-7-9-10: ZF-TE-ML 09-118-11A-02F-03D-04D-014A-014B-17C

#### Takasaki ATF SP III

 Mitsubishi SP II; SP III; Toyota T-III/T-IV/WS JASO I-A. 2A-02

#### Takasaki ATF SP IV

DEXRON / MERCON

Januari Nati 2017 M. BELL M. WIZE 12 W. ST. E. W. 60

BOR 17 M. 60 M. ST. M. WIZE 12 W. ST. E. W. 60

BOR 17 M. 60 M. ST. M. WIZE 12 W. ST. E. W. 60

BOR 17 M. 60 M. ST. M. 60 M. M.

#### Takasaki ATF CVT

Service 22 Delia 25 D

#### Takasaki HHMF HONDA MULTIMATIC FLUID (HHMF)

### Takasaki ATF WS

## ANTIFREEZE / COOLANT

#### Takasaki Concentrate GII

MB 325.2 ; MAN 324; GM 1899M; FORD EZE M-97B44-A

### Takasaki Concentrate G12

VW / Audi / Skoda TL 774 D/F (GI2+) ; MB 325.2; MAN 324 ; GM 1899 M ; Ford EZE M-97B44-A

#### Takasaki Concentrate GI3

W G13 : TL-774 J

