

PRODUCT CATALOG 2024

Alcon

www.alcon.com.tr

PERSONAL PROPERTY

ALCON reserves the right to revise the prices of some or all of the products in the price list according to current conditions due to foreign currency instability.

- VAT on our prices will be added. - Our cash sales are collected by cash, credit card or bank transfer.

- Our products are calculated from the MBDS rate on the invoice date.

- Specify the product codes in your orders.

- The shipping costs of the products belong to the customer.

- Our sales are on the basis of parcels, packages or pallets.

- Please call our company for your bulk purchases.

- For credit card payment option, please ask our sales representatives for informa tion.

ALCON can offer campaigns and special conditions in line with changing economic conditions. Our customers cannot claim retroactive rights by citing these special circumstances.

SALES CIRCULAR1
TECHNICAL GASKET MAKER2-3-4-5
PU 2621 MASTICS - SILICONE CARTRIDGES6-7-8-9
TECHNICAL SPRAYS10-11-12-13-14-15-16-17-18
EPOXY ADHESIVES19-20-21-22-23-24
INDUSTRIAL METAL-FILLED EPOXIES25-26-27-28-29
INDUSTRIAL TECHNICAL PRODUCTS
ANAEROBIC STEEL LOCK35-36-37
CYLINDER BLOCK & RADIATOR CARE
FUEL ADDITIVES-ENGINE&RADIATOR CARE PRODUCTS.41-42-43-44-45
AUTO CARE PRODUCTS
AUTO WIPER WATER ADDITIVES55-56



ALCON ENDÜSTRİYEL ÜRÜNLER SAN. ve TİC. LTD. ŞTİ T. GARANTİ BANKASI A.Ş (USD)

T. GARANTİ BANKASI A.Ş (EURO) : TR90 0006 2000 4760 0009 0866 88 : TR63 0006 2000 4760 0009 0866 89



Technical Gasket Maker



ANTRAS It is a assist * Neu * Stro * Disc Color Heat

ANTRASIL AUTOMATIC DOSE RTV GASKET MAKER

It is a new generation neutral gasket maker which is used as a direct, or other gasket assistant in engines and pumps.

* Neutral type new generation

- * Strong grip and covering
- * Disassembly when necessary

Color : Black/Red/Grey Heat Resistance : [-40 °C / +300 °C]

- * Permanent elasticity
- * Extra tightness
- * Automatic Dose

Product Name:	Product Code:	Packing:	Parcel:
ANTRASIL AUTOMATIC DOSE RTV GASKET MAKER (BLACK)	M-3321	200 ml. (ALUM. CARTRIDGE)	12
ANTRASIL AUTOMATIC DOSE RTV GASKET MAKER (RED)	M-3322	200 ml. (ALUM. CARTRIDGE)	12
ANTRASIL AUTOMATIC DOSE RTV GASKET MAKER (GREY)	M-3323	200 ml. (ALUM. CARTRIDGE)	12

ANTRASIL NEUTRAL RTV GASKET MAKER

It is a new generation neutral gasket maker which is used as a direct, or other gasket assistant in engines and pumps.

- * Neutral type new generation
- * Strong grip and covering
- * Disassembly when necessary

Color : Black/Red/Grey Heat Resistance : [-60 °C / +300 °C]

- * Permanent elasticity
- * Extra tightness

Product Name:	Product Code:	Packing:	Parcel:
ANTRASIL NEUTRAL GASKET MAKER (BLACK)	M-3320	90 g. (TUBE)	12
ANTRASIL NEUTRAL GASKET MAKER (RED)	M-3324	90 g. (TUBE)	12
ANTRASIL NEUTRAL GASKET MAKER (GREY)	M-3325	90 g. (TUBE)	12





HYPER-RTV AUTOMATIC DOSE GASKET MAKER

It is a gasket maker which is used as a direct or other gasket assistant in engines and pumps.

- * Permanent elasticity at different temperature grades
- * Strong grip * Disassembly when necessary

co

GRE

LCON

ALCON

Color : Black/Red/Grey

Heat Resistance : [-40 °C / +300 °C]

- * Resistant to vibrations
- * Pratical, fast and reliable
- * Automatic Dose

Product Name:	Product Code:	Packing:	Parcel:
HYPER-RTV AUTOMATIC DOSE GASKET MAKER (BLACK)	M-3326	200 ml. (ALUM. CARTRIDGE)	12
HYPER-RTV AUTOMATIC DOSE GASKET MAKER (RED)	M-3327	200 ml. (ALUM. CARTRIDGE)	12
HYPER-RTV AUTOMATIC DOSE GASKET MAKER (GREY)	M-3328	200 ml. (ALUM. CARTRIDGE)	12

HYPER-RTV GASKET MAKER

* Disassembly when necessary

Heat Resistance : [-60 °C / +300 °C]

* Strong grip

Color

It is a new generation neutral gasket maker which is used as a direct, or other gasket assistant in engines and pumps.

* Permanent elasticity at different temperature grades

: Black/Red/Grey

- * Resistant to vibrations
- * Pratical, fast and reliable



Product Name:	Product Code:	Packing:	Parcel:
HYPER-RTV GASKET MAKER (RED)	M-3303	90 g. (BLISTER)	12
HYPER-RTV GASKET MAKER (BLACK)	M-3304	90 g. (BLISTER)	12
HYPER-RTV GASKET MAKER (GREY)	M-3308	90 g. (BLISTER)	12

HYPER-RTV GASKET MAKER



It is a new generation neutral gasket maker which is used as a direct, or other gasket assistant in engines and pumps.

- * Permanent elasticity at different temperature grades
- * Resistant to vibrations
- * Pratical, fast and reliable

* Disassembly when necessary Color : Black/Red

* Strong grip

Heat Resistance : [-60 °C / +300 °C]

Product Name:	Product Code:	Packing:	Parcel:
HYPER-RTV GASKET MAKER (RED)	M-3302	50 ml. (TUBE)	20
HYPER-RTV GASKET MAKER (BLACK)	M-3315	50 ml. (TUBE)	20

HYPER-RTV GASKET MAKER



It is a new generation neutral gasket maker which is used as a direct, or other gasket assistant in engines and pumps.

* Permanent elasticity at different temperature grades

: Black/Red/Grey

- * Resistant to vibrations
 - * Pratical, fast and reliable

Product Name:	Product Code:	Packing:	Parcel:
HYPER-RTV GASKET MAKER (BLACK)	M-3341	85g. (TUBE)	12
HYPER-RTV GASKET MAKER (RED)	M-3342	85g. (TUBE)	12
HYPER-RTV GASKET MAKER (GREY)	M-3343	85g. (TUBE)	12

TRANSPARENT SILICONE



This is high quality, ready to use polysiloxane based, elastic, filling silicone. Features:

- * Ideal for minimize insulation needs
- * Permanent elasticity at different temperature grades
- * Strong adhesion to glass, ceramic, porcelain and all glossy surfaces
- * Antibacterial

* Strong grip

Color

* Disassembly when necessary

Heat Resistance : [-60 °C / +300 °C]

* Economical, practical.

Color : Transparent

Heat Resistance : [-50 °C / +200 °C]

Product Name:	Product Code:	Packing:	Parcel:
TRANSPARENT SILICONE	M-5505	40 ml. (BLISTER)	24
TRANSPARENT SILICONE	M-5506	40 ml. (tube)	60

JELLOCK ORANGE GASKET MAKER



This product is used especially; automative, ship, aircraft industry, all metal flanges and the other requirements. Fills the capillary cracks on the gasket surfaces, deformations and voids. Creates a smooth surface. It is a superior engineering seal with thermal tolerance to -55 °C / +200 °C in narrow gasket areas up to 0.25 mm.

Product Nan	ne:	Product Code:	Packing:	Parcel:
JELLOCK ORAN	GE GASKET MAKER	M-3330	50 ml. (TUBE)	12



PU 2621 Mastics Silicone Cartridges



PU 2621 POLYURETHANE MASTIC

This product cures quickly. Resists to vibration, internal and external weather conditions. It's permanent elastic. It does not lose volume. Good adhesion to raw and painted floors. It can be painted with auto and industrial paints.

Application Areas:

- * Isolation and bonding in sea vehicles,
- * Bonding in sheet metal joints of motor vehicles or joint filling,
- * In construction and in roof joints,
- * On the buildings, concrete, brick, wood, metal, PVC materials, windows and edges,
- * In the construction and repair of containers, caravans,
- * Isolation of any kind of water, gas, air and dust permeate.

Product Name:	Product Code:	Packing:	Parcel:
PU 2621 POLYURETHANE MASTIC (BLACK)	M-5514	300 ml. (CARTRIDGE)	25
PU 2621 POLYURETHANE MASTIC (GREY)	M-5515	300 ml. (cartridge)	25
PU 2621 POLYURETHANE MASTIC (WHITE)	M-5525	300 ml. (cartridge)	25

PU FOAM FIX

Polyurethane foam is used for mounting, insulating, filling, sealing windows, doors, pipes, cracks, holes. After drying, this product ensures excellent thermal and accoustic insulation. Resistant to -50 °C and +90 °C temperatures. Also, resistant to moisture and ageing. Ensures good adhesion to concrete, brick, plaster, foamed polystyrene, PVC, metal, wood and building materials.

Application:

Mounting of doors or windows cannot be performed without the use of mechanical connectors. Clean, degrease and dampen the surface with water. Naturally bring the can up to room temperature. Shake the can several times and screw the straw on. Keep the can upside down during application. Fill the gaps in about 30% (the foam volume increases.)

Cutting time: ca 60 mins. After full cure, protect the foam against UV radiation with silicone, plaster or paint (not sooner than 24h after application.)

Application temperature: $+5 \degree$ C to $+30 \degree$ C. Can temp.: $+15 \degree$ C to $+30 \degree$ C. Fire rating: B3 (DIN 4102). Store upright in a cool and dry place at temperature: $+20 \degree$ C to $+30 \degree$ C.

Product Name:	Product Code:	Packing:	Parcel:
PU FOAM FIX	M-5526	600 g.	16
PU FOAM FIX	M-5531	750 ml.	12
PU FOAM FIX (WITH GUN)	M-5546	750 ml.	12

PRO POWER MASTIC

Features:

* It adheres strongly to many surfaces such as concrete, brick, wood, metal, natural stone, ceramic.

- * It is elastic and strong, absorbs vibrations.
- * It dries fast.
- * Can be overpainted (with water-based paints)
- * It is resistant to weather conditions and UV rays.
- * It dries without air bubbles.
- * It does not contain silicone and isocyanate.
- * It does not lose volume.

Product Name:	Product Code:	Packing:	Parcel:
PRO POWER MASTIC (WHITE)	M-5543	290 ml.	24
PRO POWER MASTIC (BLACK)	M-5544	290 ml.	24
PRO POWER MASTIC (GREY)	M-5545	290 ml.	24





ALCON

SEALANT

FOAM FIX

PROFESSIONA

PU FOAM

RTV ACETOXY RED SILICONE +300 °C

Features:

- * Room temperature curing (RTV) feature
- * Strong adhesion, precise sealing and superior protection
- * Resistant to oil, steam, gas and fuel
- * Vibration absorbing capability in vibrating environments
- * It does not shrink, always remains elastic
- * Resistant to ultraviolet rays.

Color : Red Heat Resistance : [-60 °C / +300 °C]

Product Name:	Product Code:	Packing:	Parcel:
RTV ACETOXY RED SILICONE + 300 °C	M-5508	290 ml. (CARTRIDGE)	24

UNIVERSAL ACETOXY RED SILICONE

Features:

- * It is based on polysiloxane.
- * It is long lasting.

* It is produced from high quality, general purpose and solvent-free real silicone with antibacterial properties and permanently elastic.

* It provides permanent elasticity at different temperatures.

* It provides strong adhesion to glass, ceramic, porcelain, enamel, various metals and painted surfaces.

Heat Resistance : [-50 °C / +250 °C]

Product Name:	Product Code:	Packing:	Parcel:
UNIVERSAL ACETOXY RED SILICONE	M-5504	280 g.	24

UNIVERSAL ACETOXY SILICONE

This is produced polysiloxane-based, anti-bacterial, permanent elastic, high quality, general purpose, solvent-free true silicone.

Features:

- * Continuous elasticity at different temperature grades
- * Long lasting
- * Strong adhesion to glass, ceramic, porcelain, enamel, various metals and painted surfaces * Antibacterial
- Color : Transparent-Black-White-Grey Heat Resistance : [-50 °C / +200°C]

Product Name:	Product Code:	Packing:	Parcel:
UNIVERSAL ACETOXY SILICONE (TRANSPARENT)	M-5511	280 g.	24
UNIVERSAL ACETOXY SILICONE (BLACK)	M-5512	280 g.	24
UNIVERSAL ACETOXY SILICONE (WHITE)	M-5513	280 g.	24
UNIVERSAL ACETOXY SILICONE (GREY)	M-5516	280 g.	24



ALCON

SEALAN1



EXTRA SILICONIZED MASTIC

It is a one-component water-based acrylic sealant. It is used in the assembly of PVC, aluminum, wood, iron joinery, in the filling and expansion points of the buildings, in the repair of joints and small cracks, in the parts where gutters and streams are connected to the roof, in the skirting gaps, in the heating pipe and water installation wall transition connections.

* Paintable and odorless.

- * Permanently flexible,
- * Waterproof after curing.

Application Temperature: [+5 °C / +40 °C]

Product Name:	Product Code:	Packing:	Parcel:
EXTRA SILICONIZED MASTIC (WHITE)	M-5539	280 ml.	24
EXTRA SILICONIZED MASTIC (BLACK)	M-5540	280 ml.	24
EXTRA SILICONIZED MASTIC (GREY)	M-5541	280 ml.	24
EXTRA SILICONIZED MASTIC (GREY BEIGE)	M-5541-01	280 ml.	24

CHEMICAL ANCHOR

It is a general purpose, polyester-based, two-component, high quality product specially formulated for anchoring of construction applications. Concrete, marble, stone etc. It is used in bonding and anchoring of materials to perforated brick and briquette walls.

- * Compressive strength: R2 Class 82N/mm2
- * Thanks to its special foil package, it does not leak from the bottom of the cartridge.
- * It is compatible with all kinds of silicone guns.
- * It saves time and labor. It is economical.
- * Cures and dries fast.
- * It can be applied even at low temperatures.
- * High mechanical strength,
- * Compatible with a variety of building materials, including perforated brick.
- * It is in the form of a non-drip paste.
- Service temperature : [-40 °C / +80 °C]

Maximum long-term temperature +50 °C

Product Name:	Product Code:	Packing:	Parcel:
CHEMICAL ANCHOR	M-5530	300 ml.	20







Technical Sprays



V DRIVING BELT SPRAY



It is especially suitable for fan belts, agricultural machines, industrial belts, power belts, alternators and water pump belts. It cuts squeaks and scratches, silences the strap. It is used in all flat and round V type belts including conveyors.

- * Increases power.
- * Increase and improve the concept.
- * Prevents slippage and putting on the belt.
- * Prevents cracks on the belt.
- * Extends the life of the belt.

Product Name:	Product Code:	Packing:	Parcel:
V DRIVING BELT SPRAY	M-9003	400 ml.	24



CONTACT CLEANER SPRAY (OIL-FREE)

It is a reliable product used for the protection and cleaning of electrical and electronic circuits against oxidation, moisture. It quickly cleans the application surface. It is a multipurpose product and is therefore used safely in plugs, voltage regulators, remote control devices, telephone accessories and all electrical circuits and panels.


* Provides excellent cleaning of electrical circuits and parts.

* Cleans all oils and dirt.

* Prevents corrosion and oxidation.

* Extends the life of electrical circuits.

Product Name:	Product Code:	Packing:	Parcel:
CONTACT CLEANER SPRAY (OIL-FREE)	M-9004	400 ml.	24
CONTACT CLEANER SPRAY (OIL-FREE)	M-9020	200 ml.	24



BRAKE CLEANER SPRAY



Highly effective brake and metal parts cleaner. Cleans the brake linings and the other powders in the brakes. Helps to cutting sizzle and squeak. Cleans the rust, industrial dirt, fluids and oils. Removes the lubricants in the metal parts without any sediment. Also, it uses mechanical and hydraulic discs and cylinders.

Product Name:	Product Code:	Packing:	Parcel:
BRAKE CLEANER SPRAY	M-7701	500 ml.	24



ENGINE CLEANER SPRAY

Highly effective cleaner spray that uses; cleaning of all vehicle engines (automobile, bus, truck, work machine, marine vessel, motorcycle, generator) and removes the oil, dirt and carbon residues from transmission, differantial gear and the other parts. It does not damage rubber and plastic sections because of the product does not contain solvent. ALCON Engine Cleaner Spray is easy to use and effective for both professional and individual users.

Product Name:	Product Code:	Packing:	Parcel:
ENGINE CLEANER SPRAY	M-7709	500 ml.	24

LIQUID GREASE SPRAY



A lubricator, abrasion-resistant, water-resistant, transparent, adhesive, non-fluid lubricant spray. It uses in heavy duty machines and forklifts, gears and chain systems, lubricating all moving parts for a long time. Highly efficient lubricant and corrosion inhibitor. Extends the life of parts, ensures quiet and efficient operation.

Product Name:	Product Code:	Packing:	Parcel:
LIQUID GREASE SPRAY	M-9002	400 ml.	24
LIQUID GREASE SPRAY	M-9022	200 ml.	24

STOP LEAKS SPRAY



It is an easy-to-use, sealing, insulation and coating sealant that protects and covers surfaces against water and other liquid leaks thanks to its specially developed liquefied rubber formulation. Thanks to the special rubber liquid formulation when sprayed on the surface; It quickly stops all kinds of leaks and cracks in the area by penetrating into cracks, leaks and holes. It does not leak, collapse, crack or peel. After drying, it can be painted to the desired color.

Uses: Pipes, plumbing, roofs, gutters, patios, joints, window and door edges, cars, boats and etc. It is suitable for use in many fields.



Product Name:	Product Code:	Packing:	Parcel:
STOP LEAKS SPRAY (WHITE)	M-9014	400 ml.	12
STOP LEAKS SPRAY (BLACK)	M-9015	400 ml.	12



SILICONE LUBRICANT SPRAY



It is a multipurpose lubricant for maintenance workshops, car service centers and individual uses. It is also a very good mold release agent used in mold industry. Used to lubricate parts, reduce friction and noise, clean, not generate static electricity and protect paste. And used to ensure; prevention of cracking of door tires, prevention of freezing and adhering of doors in cold weather, protection of vehicle hood tires, radiator pipes, seat belt mechanism, seat rail railing, lubrication of seat rails, maintenance and dust holding of parts such as vehicle front louvers, bumpers, door tubes.

ATTENTION !!! The car windows, pedals and steering wheel should not be squeezed because makes it lubricated. It should not be used where painting is done. Silicone particles cause undesirable conditions during painting when the paint is applied to the surfaces.

Product Name:	Product Code:	Packing:	Parcel:
SILICONE LUBRICANT SPRAY	M-9005	400 ml.	24



ANTI SPATTER SPRAY (SILICONE-FREE & NON-COMBUSTIBLE)

Due to contains non-combustible raw materials and non-combustible propellant (CO₂), it is used safely in welding process. It prevents the burrs and slags that form during the welding process from adhering to the torch tip, prevents sticking to the nozzle and welding surface, facilitates the welding process. Thanks to the silicone-free formulation, it is also used on surfaces to be painted after welding and used to without any problem in all welding process in wide temperature range. Thus, prevents the surface discoloration as well as burr and slag. Forms a durable film layer. It has a colorless and clean formula. It can be used successfully on chrome plated, galvanized and painted surfaces.

Product Name:	Product Code:	Packing:	Parcel:
ANTI SPATTER SPRAY (SILICONE-FREE & NON-COMBUSTIBLE)	M-9007	400 ml.	24

SMOKE DETECTOR SPRAY



ALCON Smoke Detector Spray; is developed for usage in professional business along with special are as. It is an easy-to-use and reliable testing device used to determine the operability of the systems (fire extinguishing and fire alarms). As it vaporizes with out leaving any residual materials, it does not stain the detector.

Product Name:	Product Code:	Packing:	Parcel:
SMOKE DETECTOR SPRAY	M-9008	200 ml.	24

ZINC SPRAY



It is used on all metal surfaces such as galvanized, stainless steel, inox and provides corrosion protection. The micro-fine zinc particles form a strong protective layer of fast drying and adhesion. It can be used as a high-value rust protection primer and can be used for coating and painting of welds and surfaces.

Product Name:	Product Code:	Packing:	Parcel:
ZINC SPRAY	M-9009	400 ml.	24



STAINLESS STEEL CARE SPRAY

Cleans and polish all stainless steel, inox, chrome, aluminium, brass, laminated plastic, enamel and seramic surfaces & materials. Suitable for ovens, refrigerators, embedded fixed equipments, aspirators, inox parts of yatch and ships, inox elevators, parapets, simply for all stainless steel surfaces. Cleans the soil and polish the surface. Leaves a transparent protective film layer on the surfaces applied. Hides the scratches, reduces the dust on the surface and reduce the finger print formation on the surfaces.

Product Name:	Product Code:	Packing:	Parcel:
STAINLESS STEEL CARE SPRAY	M-9010	400 ml.	24



INSULATING SPRAY

ALCON Insulating Spray; covers the surfaces it is applied to and increases the insulation resistance of the electrical and electronic devices. It forms a water proof and impermeable film layer provides protection against corrosion and oxidization. May be applied in various including coils, cables, traffic lights, all types of electrical motors, billboards, parking barrier systems, exterior lighting devices, underwater illumination systems, military vehicles, weapon maintenance and repair, maritime transportation etc.

Product Name:	Product Code:	Packing:	Parcel:
INSULATING SPRAY (RED)	M-9011	400 ml.	24
INSULATING SPRAY (TRANSPARENT)	M-9012	400 ml.	24

AL-690 SURFACE CLEANER SPRAY



With its spacial formulation, AL-690 Surface Cleaning Spray cleans the surface, for which an inspection for cracks will be carried out, from all dirt on metal like oil, grease, adhesive residues, tar, etc. As it is a transparent liquid, it vaporizes rapidly without leaving any residues on the surface. It further removes the residues of AL-680 and AL-700 that are used with this product.

Product Name:	Product Code:	Packing:	Parcel:
AL-690 SURFACE CLEANER SPRAY	M-7727	500 ml.	24



AL-680 RED PENETRANT SPRAY

With its special formulation, AL-680 Red Penetrant Spray serves to inspect the pores and cracks that occur before or during welding. It penetrates even into the most difficult parts and brings the cracks to daylight.

Product Name:	Product Code:	Packing:	Parcel:
AL-680 RED PENETRANT SPRAY	M-7726	500 ml.	24

AL-700 CRACK IDENTIFIER SPRAY



With its special formulation, AL-700 Crack Identifier Spray is a white colored identifying spray that serves to manifest the pores and cracks that occur before or during welding.

Product Name:	Product Code:	Packing:	Parcel:
AL-700 CRACK IDENTIFIER SPRAY	M-7728	500 ml.	24

RUST REMOVER - MoS₂SPRAY



Due to corrosion caused by water and moisture, stuck bolts, nuts, hand tools, ground and fishing tackle, vehicles, boats, ships, shipyards, bicycle, motorcycle, cabinet and doors hinges, locks and all metal parts like this, penetrates to the surfaces and into the narrow gaps and dissolves rust. Loosens all stuck metal parts. After you fix rust, forming a thin layer on the surface for a long time retard rust. It does not damage the plastic surface, has been developed specifically formulated for multipurpose use.

Product Name:	Product Code:	Packing:	Parcel:
RUST REMOVER - MoS2 SPRAY	M-7714	200 ml.	24
RUST REMOVER - MoS2 SPRAY	M-7715	400 ml.	24

AL-94 REMOVES MOISTURE PENETRATES LUBRICATES CLEANS

CLEANS AND PROTECTS: It is an excellent rust inhibitor and dehumidifier. Lubricates parts. It penetrates into every kind of material, cleans and protects its parts. Silicone-free and can be used on all materials. It has special formula developed for multipurpose use. LUBRICATES: It is used safely several areas for lubrication, protection and cleaning like; door hinges, drawer rails, curtain rails, locks, rusty stuck bolts and nuts, automobiles, boats, bicycle chains, motorcycles, hand tools, lawn mowers, vans, vices, sewing machines. PENETRATES: Quickly loosens rusted and corroded areas.

CORRECTS HUMIDITY: Removes the humidity in the ignition system of vehicles. The rust remover ensures that vehicle runs quietly and regularly if the spray is applied externally to distribution cables. It is suitable for electronic ignition systems.

Product Name:	Product Code:	Packing:	Parcel:
AL-94 REMOVES MOISTURE PENETRATES LUBRICATES CLEANS	M-7705	400 ml.	24
AL-94 REMOVES MOISTURE PENETRATES LUBRICATES CLEANS	M-7706	200 ml.	24
AL-94 REMOVES MOISTURE PENETRATES LUBRICATES CLEANS	M-7705-01	400 ml. (COBRA HOOD)	24
AL-94 REMOVES MOISTURE PENETRATES LUBRICATES CLEANS	M-7706-01	200 ml. (COBRA HOOD)	24

COPPER GREASE MONTAGE PASTE +1100 °C SPRAY



Non-fluid spray which has speciality grease, high temperature and pressure resistance. It uses all bolt and lead terminal, brake unit, flanges, fuel nozzles, assembly and disassembly of dynamica pieces. It is proper to working between -40 °C and +1100 °C temperature and prevent fusing and locking of pieces each other under high temperature. It endures to water and acid. Prevents corrosion.

Product Name:	Product Code:	Packing:	Parcel:
COPPER GREASE MONTAGE PASTE + 1100 °C SPRAY	M-9013	400 ml.	24

PTFE DIESEL PARTICULATE FILTER CLEANER SPRAY



It is compliant with all diesel injector engine types (with or without turbo charger). Without the need for removing the filter, it cleans the carbon and ash deposits that accumulate inside the diesel particle filter over time.

Product Name:	Product Code:	Packing:	Parcel:
PTFE DIESEL PARTICULATE FILTER CLEANER SPRAY	M-9600	500 ml.	24

AIR-CONDITIONER RE-FRESHER SPRAY



With its special formulation, it removes bad and irritating smells odors resulting from bacteria, fungus and microbes that accumulate in the vehicle and associated channels of the air-conditioning system over time. Ensures that there is a pleasant odor within the vehicle.

Product Name:	Product Code:	Packing:	Parcel:
AIR-CONDITIONER RE-FRESHER SPRAY	M-7725	150 ml.	12



TIRE REPAIR SPRAY

ALCON Tire Repair and Inflating Spray, can be utilized on all kinds of passenger cars, motorcycles, bicycles, light commercial vehicles and caravans. It has been produced with the property of repairing the flat tires in urgent situations. Generally, the tires of the vehicles go flat at the most unexpected times. You can resolve the cumbersome and tiring tire changing problem in a practical way with this spray. The Tire Repair Spray containing a special formula that becomes vulcanized upon the contact with the air, mends your flat tire and can inflate it up to 20 psi. Mends the tires without removing them from the vehicle. It is a practicle, fast and reliable product and does not cause any harm to the tire. It ends the problem of to be detained on the road by a flat tire. This product to be absolutely available on every vehicle when considering the difficult road conditions. It does not eliminate the major distortions on the tire rims and does not repair the large cuts on the tires. It helps you to reach the nearest service station. It is recommended that this product be utilized only in emergency cases, not to drive at high speeds after the use of the product and to have the tire to be repaired as soon as possible.

Product Name:	Product Code:	Packing:	Parcel:
TIRE REPAIR SPRAY	M-7722	300 ml.	24
TIRE REPAIR SPRAY	M-9016	400 ml.	24

ALCON UNIVERSAL ACRYLIC PAINT





ALCON UNIVERSAL ACRYLIC PAINT SPRAYS

It is used in vehicles, work machines, white goods, all kinds of metal and wooden surfaces and for hobby purposes.

- * Black (M-7111-BLACK) * Blue (M-7711-BLUE)
- * Brown (M-7711-BRÓWN)
- * Burgundy (M-7711-BURGUNDY) * Green (M-7711-GREEN)
- * Matte Black (M-7711-MATTE BLACK) * Red (M-7711-RED) * Silvery Grey (M-7711-SILVERY GREY)

- * White (M-7711-WHITE)
- * Yellow (M-7711-YELLÓW)

Product Name:	Product Code:	Packing:	Parcel:
ALCON UNIVERSAL ACRYLIC PAINT SPRAYS	M-7711	400 ml.	24



Epoxy Adhesives







EPOXY METALLIC BOND

INSTANT MIX









In All Metals •

- Wood, Plywood
 - Glass, Ceramics
 - Fiberglass
 - Leather •
 - Most Plastics
 - All Purpose •

JAL-ALCON-S SYRINGE 5 MINUTES EPOXY



Fast-drying, general purpose, epoxy-based, metallic bonding and sealant material. Freeze in 5 minutes, bond in 20 minutes, ready to use after 1 hour. Features:

* Fast, gray plastic steel adhesive gel

* Provides very strong and practical bonding.

* It does not lose volume after dryness.

* It is resistant to water, moisture and weak acids after dryness.

Color : Grey when mixed

Heat Resistance : High temperature resistance +120 °C (temporarily +160 °C)

Product Name:	Product Code:	Packing:	Parcel:
JAL-ALCON-S 5 MINUTES EPOXY (SYRINGE)	M-2310	30 g.	12



JAL-ALCON-S 5 MINUTES EPOXY

Fast-drying, general purpose, epoxy-based, metallic bonding and sealant material. Freeze in 5 minutes, bond in 20 minutes, ready to use after 1 hour. Features:

* Fast, gray plastic steel adhesive gel

- * Provides very strong and practical bonding.
- * It does not lose volume after dryness.

* It is resistant to water, moisture and weak acids after dryness.

: Grey when mixed Color

Heat Resistance : High temperature resistance +120 °C (temporarily +160 °C)

Product Name:	Product Code:	Packing:	Parcel:
JAL-ALCON-S 5 MINUTES EPOXY (BLISTER)	M-2110	20 g.	24

JAL-ALCON-S 5 MINUTES EPOXY



Fast-drying, general purpose, epoxy-based, metallic bonding and sealant material. Freeze in 5 minutes, bond in 20 minutes, ready to use after 1 hour.

- Features:
 - * Fast, gray plastic steel adhesive gel
 - * Provides very strong and practical bonding.
 - * It does not lose volume after dryness.

* It is resistant to water, moisture and weak acids after dryness.

Color : Grey when mixed

Heat Resistance : High temperature resistance +120 °C (temporarily +160 °C)

Product Name:	Product Code:	Packing:	Parcel:
JAL-ALCON-S 5 MINUTES EPOXY (BOX)	M-2210	20 g.	288
JAL-ALCON-S 5 MINUTES EPOXY	M-2315	30 gr.	288

RAPID PLASTIC STEEL 5 MINUTES EPOXY TRANSPARENT



Fast-drying, general purpose, epoxy-based, metallic bonding and sealant material. Freeze in 5 minutes, bond in 20 minutes, ready to use after 1 hour.

- Features: * Quick paste
- * Very strong bonding and padding

* Atmospheric exchanges are resistant to weak acids and fuels.

Color : Transparent

Heat Resistance : +120 °C (temporarily +150 °C)

Product Name:	Product Code:	Packing:	Parcel:
RAPID PLASTIC STEEL 5 MINUTES EPOXY TRANSPARENT (Syringe)	M-2204	30 g.	12

RAPID PLASTIC STEEL 5 MINUTES EPOXY TRANSPARENT



Fast-drying, general purpose, epoxy-based, metallic bonding and sealant material. Freeze in 5 minutes, bond in 20 minutes, ready to use after 1 hour. Features:

- * Outole m
- * Quick paste
- * Very strong bonding and padding
- * Atmospheric exchanges are resistant to weak acids and fuels.
- Color : Transparent
- Heat Resistance : +120 °C (temporarily +150 °C)

Product Name:	Product Code:	Packing:	Parcel:
RAPID PLASTIC STEEL 5 MINUTES EPOXY TRANSPARENT (BLISTER)	M-2205	16 g.	12

SPECIAL PLASTIC STEEL EPOXY



It is a very strong industrial adhesive with two component.

Features:

It is very resistant to time and various atmospheric conditions, has a strong and wide application area. Hardens for 9-11 hours at room temperature (+23 °C). If the parts adhered in an urgent are subjected to flameless heating at 60 °C - 90 °C, adhesion occurs in 1-2 hours.

Heat Resistance : +120 °C (temporarily +150 °C)

Product Name:	Product Code:	Packing:	Parcel:
SPECIAL PLASTIC STEEL EPOXY (RESIN)	M-8801	4,5 kg. (TIN)	1
SPECIAL PLASTIC STEEL EPOXY (CATALYST)	M-8803	3 kg. (TIN)	1

EPOXY METALLIC BOND SYRINGE MIX



Through its special formulation which cures very quickly (at room temperature at 25-30 °C for 5-6 minutes) It is mainly used for fixing and repairing especially iron, steel and other metal alloys glass, porcelain, tiles, wood, hard plastics, ebonite, bakelite and similar materials. It is also used successfully in repairing auto flare, stop window, radiator, fuel tank holes, cable insulation and motor cracks. The electrical isolation value is very high. EPOXY METALLIC BOND is resistant to fuel oil, alkalis, light acids, oils and water after hardening. The hardened EPOXY METALLIC BOND can be sanded, milled and punched. Can be painted.

Heat Resistance : [-40 °C / +120 °C]

Product Name:	Product Code:	Packing:	Parcel:
EPOXY METALLIC BOND SYRINGE MIX	M-2312	30 g.	12



EPOXY TRANSPARENT SUPER BOND SYRINGE MIX

Through its special formulation which cures very quickly (at room temperature at 25-30 °C for 5-6 minutes) It is mainly used for fixing and repairing especially iron, steel and other metal alloys glass, porcelain, tiles, wood, hard plastics, ebonite, bakelite and similar materials. It is also used successfully in repairing auto flare, stop window, radiator, fuel tank holes, cable insulation and motor cracks. The electrical isolation value is very high. EPOXY TRANSPARENT SUPER BOND is resistant to fuel oil, alkalis, light acids, oils and water after hardening. The hardened EPOXY TRANSPARENT SUPER BOND can be sanded, milled and punched. Can be painted.

Color : Transparent Heat Resistance : [-40 °C / +120 °C]

Product Name:	Product Code:	Packing:	Parcel:
EPOXY TRANSPARENT SUPER BOND SYRINGE MIX	M-2313	30 g.	12

METALLISED PLASTIC STEEL EPOXY

It reaches to the cold welding strength by connecting to the iron with great power. It is an epoxy based, very strong industrial adhesive containing steel powders. Features:

- * Especially for iron and iron alloys.
- * Cold welding strength
- * Curing occurs after 8 12 hours at room temperature.
- * After the material has hardened, it can be edited, pierced, processed.
- Color : Metallic Grey

Heat Resistance :+120 °C (temporarily +160 °C)

Product Name:	Product Code:	Packing:	Parcel:
METALLISED PLASTIC STEEL EPOXY	M-2220	100 g. (BOX)	20
METALLISED PLASTIC STEEL EPOXY	M-2221	500 g. (BOX)	8



PRO-MIX EPOXY PUTTY



It is used successfully in the repair of gasoline, engine deposits and all kinds of radiator holes of motor vehicles, repair of cowl decays, repair of engine cracks, repair of water pipes, heating ponds, repair of all kinds of water and fuel tanks drilled.

Caution !!! The Mini PRO-MIX does not stick rubber or similar elastic materials.

Product Name:	Product Code:	Packing:	Parcel:
PRO-MIX EPOXY PUTTY	M-2217	40 g. (BOX)	36
PRO-MIX EPOXY PUTTY	M-2207	80 g. (BOX)	36

AQUA MIX BOND EPOXY PUTTY (UNDER WATER)



AQUA MIX practically fixes everything. All metals, ceramics, wood, glass, cement, plastics and so on. (not suitable for soft or flexible surfaces such as rubber, sponge). AQUA MIX adheres to wet surfaces even under water. AQUA MIX hardens in 15 minutes. AQUA MIX application is easy and your fingers do not stick. AQUA MIX can be drilled with a drill, cut with saw, guided, sandblasted, can be processed with sandpaper or file, polished and painted. **Technical Information**: Running time after kneading : 3 minutes at 20 °C Standard hardening time : 15 minutes at 20 °C Under water : 20 minutes at 20 °C **Product Code:** Packing: Parcel: **Product Name:** AQUA MIX BOND EPOXY PUTTY (UNDER WATER) M-2239 57 g. (BLISTER) 12

SPECIAL PLASTIC STEEL EPOXY ARMATURE VARNISH



It is the biggest contributor to the winding of enduvines produced for heat, high revolutions and severe conditions.

Features:

It is used for heat resistant, strong insulation in the endurance of automobile motors, power drill, hilti etc. tools and submersible pumps. It penetrates into the windings and forms a solid body. Wide application area. Rapid drying can be achieved in 30 minutes by the special application method indicated on the product.

Color : Amber

Heat Resistance : +120 °C (temporarily +150 °C)

Product Name:	Product Code:	Packing:	Parcel:
SPECIAL PLASTIC STEEL EPOXY ARMATURE VARNISH	M-8814	1000 g. (BOX)	6

BUMPER & DASHBOARD REPAIR KIT EPOXY



It can be used as a quick repair, repair, pre-painting filler and finish sealer for all plastic parts such as bumper, torpedo, mudguard, stop and head lamps, plastic radiator boilers, fan frames, mirrors and can be sanded and painted. It is not influenced by external factors and vibrations. It lives with the material without cracking or breaking.

Product Name:	Product Code:	Packing:	Parcel:
BUMPER & DASHBOARD REPAIR KIT EPOXY	M-2211	1000 g. (BOX)	6



JAL-ALCON-S 5 MINUTES EPOXY

VERY STRONG AND PRACTICAL ADHESIVE!





Wood, Plywood, Glass, Ceramics, Fiberglass, leather, Most Plastics, In All Metals, **All Purpose**

2 CONPONENT ADHESNES MINU DALALCONTO

JALALCON

2 COMPONENT ADHES



Industrial Metal - Filled Epoxies



ALCON (A) PLASTIC METAL BOND EPOXY & STEEL PUTTY



With a mixture of epoxy resins and steel powders; very strong adhesions to many metals such as steel, pig, casting, concrete and some hard plastics. It is used safely in the adhesion of broken machine parts, filling of casting faults and cavities, gluing of drilled tanks, storage tanks and pipes and coating and protection of worn matel surfaces due to repair, breakage or rubbing.

Features:

ALCON (A) after being hardened, it is resistant to fuel oil, water, oil, vibration and certain heat. Color : Grey-Black after mixing

Heat Resistance : [-35 °C / +120 °C]

Product Name:	Product Code:	Packing:	Parcel:
ALCON (A) PLASTIC METAL BOND EPOXY & STEEL PUTTY	M-2222	500 g. (BOX)	10



ALCON (B) PLASTIC METAL BOND EPOXY & STEEL (LIQUID)

It is a mixture of epoxy resins and steel powders. In works such as model, mold making, re-casting of machine parts; cracks and gaps that are difficult to fill pastes in the form of adhesives are ideal for easy filling of casting cavities, filling and corrosion of wear and corrosion parts of old molds.

Features :

ALCON (B) after being hardened, it is resistant to fuel oil, water, oil, vibration and certain heat.

Color : Grey - Black after mixing Heat Resistance : [-35 °C / +120 °C]

Product Name:	Product Code:	Packing:	Parcel:
ALCON (B) PLASTIC METAL BOND EPOXY & STEEL (LIQUID)	M-2226	500 g. (BOX)	10



ALCON (BR) PLASTIC METAL BOND EPOXY & BRONZE PUTTY

It is a mixture of epoxy resins and bronze dust; It is ideal for the repair of all kinds of metals such as bronze, yellow and brass, the filing of corroded, worn out ship propellers and other bronze and brass castings or the filling of parts such as bearings and bearings worn parts of shafts. After the material has hardened, it can be sanded, turned and leveled. Features :

ALCON (BR) after being hardened, it is resistant to fuel oil, water, oil, vibration and certain heat.

Color : Bronze after mixing Heat Resistance : $[-35 \degree C / +120 \degree C]$

Product Name:	Product Code:	Packing:	Parcel:
ALCON (BR) PLASTIC METAL BOND EPOXY & BRONZE PUTTY	M-2223	500 g. (BOX)	10

ALCON (F) PLASTIC METAL BOND EPOXY & ALUMINIUM PUTTY



It is a highly compatible repair material for the repair of cracks and cracks of aluminum engine blocks, machine bodies, part finishing work, filling of shaft bearings and casting cavities. Features :

ALCON (F) after being hardened, it is resistant to fuel oil, water, oil, vibration and certain heat. Color : Aluminum after mixing

Heat Resistance : [-35 $^\circ\text{C}$ / +120 $^\circ\text{C}]$

Product Name:	Product Code:	Packing:	Parcel:
ALCON (F) PLASTIC METAL BOND EPOXY & ALUMINIUM PUTTY	M-2224	500 g. (BOX)	10

ALCON (F-2) PLASTIC METAL BOND EPOXY & ALUMINIUM (LIQUID)



This product with epoxy and dense aluminum filling makes it possible to make model, mold and prototype, lightweight aluminum casting. The most sensitive details can be obtained when taking the model. In repair works, it penetrates into the thinnest spaces of materials and fills them. It integrates with applied materials without pulling or shrinking. Cracks, casting cavities, corroded areas can be fully filled, leveled. After the material is hardened, it can be turned, leveled. Suitable for practical use.

Features :

ALCON (F-2) after being hardened, it is resistant to fuel oil, water, oil, vibration and certain heat. Color : Aluminum after mixing

Heat Resistance : [-35 °C / +120 °C]

Product Name:	Product Code:	Packing:	Parcel:
ALCON (F-2) PLASTIC METAL BOND EPOXY & ALUMINIUM (LIQUID)	M-2225	500 g. (BOX)	10

ALCON (SF) PLASTIC METAL BOND EPOXY & STEEL 5 MINUTE PUTTY



It is a steel filled machine that hardens for 5 minutes for general purpose emergency repairs. It is a suitable material for filling, bonding, covering and finishing parts on all metal surfaces. Available hardening time is 1 hour. In emergency situations where rapid repair is required, filling of casting cavities and corrosion cavities, repair of broken metal materials is possible in a short time. This product should be applied within 1-2 minutes after mixing. For this reason, it is advisable to mix enough to be used in one place. Features :

ALCON (SF) after being hardened, it is resistant to fuel oil, water, oil, vibration and certain heat. Color : Grey - Black after mixing

Heat Resistance : [-35 $^{\circ}\text{C}$ / +120 $^{\circ}\text{C}]$

Product Name:	Product Code:	Packing:	Parcel:
ALCON (SF) PLASTIC METAL BOND EPOXY & STEEL 5 MIN. PUTTY	M-2228	500 g. (BOX)	10

ALCON (ST) PLASTIC METAL BOND EPOXY & STAINLESS STEEL PUTTY



It is a mixture of epoxy resins and stainless steel powders; repair of stainless steel materials, as needed for part finishing and gluing, filling of worn parts, repair of connection pipes, assembly and repair of fitting connections. Protect the materials used against rust. Features :

ALCON (ST) after being hardened, it is resistant to fuel oil, water, oil, vibration and certain heat. Color : Grey after mixing

Heat Resistance : [-35 °C / +120 °C]

Product Name:	Product Code:	Packing:	Parcel:
ALCON (ST) PLASTIC METAL BOND EPOXY & STAINLESS STEEL PUTTY	M-2227	500 g. (BOX)	10



ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM PUTTY

Titanium filled paste used to fill and repair shafts of worn miller, bushes, valves and pipes exposed to high pressure and corrosion, covering mill and closed mixer walls which are exposed to continuous wear. It is used for especially in salt water and many chemical exposures, metal covers and protecting tanks. Epoxy, titanium and 9.5 mohs hard ceramic special reinforcements resistant to all tough conditions.

Features :

ALCON (TI) after being hardened, it is resistant to fuel oil, water, oil, vibration and certain heat.

Color : Grey after mixing Heat Resistance : [-32 °C / +180 °C]

Product Name:	Product Code:	Packing:	Parcel:
ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM PUTTY	M-2234	500 g. (BOX)	10

ALCON (WR-2) PLASTIC METAL BOND EPOXY & WEAR RESISTAND PUTTY



Wear and abrasion resistance is very high mineral filler repair paste. It is reinforced with a durable epoxy that is resistant to all demanding conditions and a special ceramic filler with a hardness of 9.5 mohs. Does not flow on vertical surfaces. Repair of flange surfaces, repair of valve bodies and housing, repair of bearings, salty sea water and various chemicals, mechanical abrasion; It is ideal for repairing metal covers, vessel storage tanks, casting faults, shaft and shafts.

Product Name:	Product Code:	Packing:	Parcel:
ALCON (WR-2) PLASTIC METAL BOND EPOXY & WEAR RESISTAND PUTTY	M-2235	500 g. (BOX)	10

ALSONA 7111 PLASTIC EPOXY & METAL PUTTY



It is a reinforced polymer system material for two component, repair, filling, new part and mold production. This product provides quality and fast solutions for a wide range of applications for general engineering requirements.

Features : After hardening ALSONA 7111, it is resistant to fuel oil, water, oil, vibration and certain heat.

Color : Grey- Black after mixing Heat Resistance : [-40 °C / +200 °C max]

Product Name:	Product Code:	Packing:	Parcel:
ALSONA 7111 PLASTIC EPOXY & METAL PUTTY	M-7111	1000 g. (BOX)	10

ALCOBOND EPOXY PATCH

It is high performance epoxy patch and repair kit. Especially used in ship maintenance, factories, manufacturing companies; pipes, flanges, gasket locations, stock tanks, machines and warehouses. Used in condersens showing temperature difference and other similar applications that can be repaired with practical and very robust fixtures using the appropriate glass fabric bands, kevlar fabrics, carbon fabrics and glass fabrics, which are usually repaired areas.

Features :

After ALCOBOND being hardened, it is resistant to fuel oil, water, oil, vibration and certain heat. Color : After mixing, ice white

Heat Resistance : [-35 °C / +120 °C]

Product Name:	Product Code:	Packing:	Parcel:
ALCOBOND EPOXY PATCH	M-2229	455 g. (BOX)	10

ALCOBOND GLASS BAND



Especially used in ship maintenance, factories, manufacturing companies; pipes, flanges, gasket locations, stock tanks, machines and warehouses. The application is done by wetting with M-2229 ALCON ALCOBOND Epoxy Patch Adhesive to prevent leakage in all applications such as heaters and condensers showing temperature difference. For the application method, please apply the usage instructions contained in our products packaging. It is a very solid and practical repair material.



Product Name:	Product Code:	Packing:	Parcel:
ALCOBOND GLASS BAND	M-2232	35mm x 100m	10
ALCOBOND GLASS BAND	M-2233	50mm x 100m	4





Industrial Technical Products



AL-94 CUTTINGTAP CUTTING FLUID



CUTTINGTAP is a high performance metal cutting fluid. Provides superior support when working on difficult metal surfaces. Reduce friction. Extends the life of used instruments. Features;

*Provides excellent results in all matals that are difficult to process (except aluminum). *Extend the life of used instruments.

*Reduce friction.

*Prevents buring and sticking of metal surfaces and metal chips formed during operation. *Increases the mass production volume.

*Reduce labor costs.

Product Name:	Product Code:	Packing:	Parcel:
AL-94 CUTTINGTAP CUTTING FLUID	M-9809	250 ml. (BOTTLE)	24
AL-94 CUTTINGTAP CUTTING FLUID	M-9803	500 ml. (BOTTLE)	12
AL-94 CUTTINGTAP CUTTING FLUID	M-9805	4 It. (DRUM)	6

VALVE GRINDING PASTE


It gives the best results in the operation of the intake and exhaust valves of the engines, blasting, polishing and polishing works for the highest performance, eliminating and correcting the metal deformations caused by heavy usage conditions on the metal floor.

Thanks to its special formula, it provides reliable, high performance abrasion, correction, leveling, honing, cleaning and polishing. For the best results, it is important to choose the appropriate thickness of sand and it is recommended to first adjust the abrasion-level with thick putty and then smooth-finish-polish with fine putty.

Features:

*High resistant metal surface abrasive.

- *It provides metal correcting, leveling, honing, cleaning and polishing.
- *It is an ideal material for accustoming suction and exhaust valves.



PRUSSIAN BLUE TECHNICAL TEST PASTE



The Prussian Blue is a perfect technical test putty, which dries on the CNC and lathe looms dries for a long time in the room heat, allowing the level and leveling errors on sensitive metal surfaces to appear instantly and practically. In addition, mold parts that need to be matched to each other in mold manufacturing can be easily applied to their surfaces, particularly in which positions they are contacted in hard to reach areas. Minimizes the probability of error.

Product Name:	Product Code:	Packing:	Parcel:
PRUSSIAN BLUE TECHNICAL TEST PASTE	M-9804	40 g. (BOX)	24



Valve Grinding Pasi

iahest F

WATER LEVEL INDICATOR



It is used to measure the amount of water remaining at the bottom of vessels, tanks, factories and buildings, fuel and water reservoirs. Application :

* Cover the measuring stick with a paste of ALCON Gasoline Level Indicator paste in the film layer.

* Dip the measuring bar until you touch the bottom of the tank.

- * Putty in contact with water changes color and gets red color.
- * After use, close the cover of the box and cut off the contact paste with air.

* The paste in the package can be crystallized in cold weather. Crystallization can be removed simply by waiting for a while in a heating source like a radiator. This does not harm the product feature.

Product Name:	Product Code:	Packing:	Parcel:
WATER LEVEL INDICATOR	M-9802	75 ml. (BOX)	48
WATER LEVEL INDICATOR	M-9811	85 g. (TUBE)	48



GASOLINE LEVEL INDICATOR

It is used for the leveling of fuel in fuel tanks of ships, factories and buildings. Application;

* Cover the measuring stick with a paste of ALCON Gasoline Level Indicator paste in the film layer.

* Dip the measuring bar until you touch the bottom of the tank.

⁶ Putty that comes in contact with fuel is changed color and level is detected.

Product Name:	Product Code:	Packing:	Parcel:
GASOLINE LEVEL INDICATOR	M-9812	75 ml. (BOX)	48
GASOLINE LEVEL INDICATOR	M-9830	85 g. (TUBE)	48

MULTI LUBE WR 2 ROLLER GREASE

ALCON MULTI LUBE WR 2, EP is added and lubrication is reinforced with solid lubricant. It is a high performance grease resistant to high pressure and temperature. Features:

- * Resistant to work under load
- * Good protection against corrosion and wear
- * High resistance to washing, water and damp
- * Long-term protection against corrosion and oxidation
- * Long-term lubrication

Color : Grey-Black

Product Name:	Product Code:	Packing:	Parcel:
MULTI LUBE WR 2 ROLLER GREASE	M-9810	1000 g. (BOX)	12





COPPERSOLID MONTAGE PASTE +1100 °C



It contains copper, bentone, ceramic and various special materials; It is an assembly paste that can be used in environments exposed to high temperatures. Easy installation, protection of materials such as bolts, studs, nuts, flanges, molds working under heat and heavy environmental conditions; and most importantly this type of parts can be easily removed later.ALCON COPPERSOLID Copper Mounting Paste can be used safely under all harsh conditions and protects the materials.

Working Heat Range: [-40 °C / +1100 °C]

Product Name:	Product Code:	Packing:	Parcel:
COPPERSOLID MONTAGE PASTE	M-9800	500 g. (BOX)	24
COPPERSOLID MONTAGE PASTE	M-9801	90 ml. (TUBE)	6
AUTOMATIC DOSE COPPERSOLID MONTAGE PASTE	M-9815	200 ml. (alum. cartridge)	12

METAL POLISH CREAM



It is a multi-purpose, very effective, practical use polishing paste. In automobiles; provides a sparkling effect in cleaning the dirty paint of steel and aluminum wheels, metal roller shutters, headlight frames, polished nickel plated bars. At home; gold, silver, platinum, jewelery, brass, chandeliers, picture frames, brass vase, umbrella holder, trinket etc. other metal objects, steel pots, teapots, plexiglas, tiles and thick painted surfaces are cleaned and polished with METAL POLISH, the oxides formed are removed and protection is provided.

Product Name:	Product Code:	Packing:	Parcel:
METAL POLISH CREAM	M-9935	80 g. (TUBE)	18

MARKER BALL



Indelible paint. Industrial use only.

- It is suitable for all kinds of surfaces.
- Works on wet, oily, greasy and rusty surfaces.
- Resistant to UV rays.
- Excellent water resistance.
- Functional over a wide temperature range.
- Steel construction.
- Ship repair.
- Building and civil engineering.
- Topographic surveys.

Product Name:	Product Code:	Packing:	Parcel:
MARKER BALL (WHITE)	M-3340	50 ml. (TUBE)	20
MARKER BALL (YELLOW)	M-3344	50 ml. (TUBE)	20
MARKER BALL (RED)	M-3345	50 ml. (TUBE)	20

INDUSTRIAL NANOLIN HAND CLEANER CREAM

It is a fast, effective, cleaning agent for heavy industry oils and other dirt for ships, shipyards, paints, auto industry, printing industries. Features:

* Deeply cleans all industrial dirt in hands.

* It cleans all kinds of stubborn and sticky pollution such as fats and oils, paints, tar, varnish, polyurethane without damaging the skin.

- * Keeps the skin soft, provides care.
- * Pleasant odor, removes unwanted odors.

* Contains no acid, phosphate, caustic or free alcohol. It does not risk human health.

* Environment friendly, biodegradable in nature.

Product Name:	Product Code:	Packing:	Parcel:
INDUSTRIAL NANOLIN HAND CLEANER CREAM	M-4302	1000 ml.	12
INDUSTRIAL NANOLIN HAND CLEANER CREAM	M-4303	3000 ml.	4
INDUSTRIAL NANOLIN HAND CLEANER CREAM	M-4304	5000 ml.	1
INDUSTRIAL NANOLIN HAND CLEANER CREAM	M-4305	18000 ml.	1

SHELLAC UNIVERSAL GASKET BOND

cork, paper, rubber, metal, repa, cardboard etc.



Features:

Product Name:	Product Code:	Packing:	Parcel:
SHELLAC UNIVERSAL GASKET BOND	M-9904	50 ml. (BOTTLE)	36

Universal Gasket Bond SHELLAC-based is used for sealing; leather, fiber, cylinder head,





ANAEROBIC LOW STRENGTH THREADLOCKER D.K.S STEEL LOCK

It is easy to disassemble anaerobic adhesive which is used for soft metal and gears that smaller than 1/4 "(6 mm) in components and where setting is required. Color : Green

Product Name:	Product Code:	Packing:	Parcel:
ANAEROBIC LOW STRENGTH THREADLOCKER D.K.S STEEL LOCK	M-5222	15 ml.	12
ANAEROBIC LOW STRENGTH THREADLOCKER D.K.S STEEL LOCK	M-7222	50 ml.	12
ANAEROBIC LOW STRENGTH THREADLOCKER D.K.S STEEL LOCK	M-8222	250 ml.	6

ANAEROBIC MEDIUM STRENGTH THREADLOCKER O.K.S STEEL LOCK

Medium-strength, detachable, general-purpose anaerobic product. It can be used in all bolts and nuts. It does not drip and flow after it is pasted. It is easy to apply and has a sealing feature. It is used in machine setting bolts, hydraulic system bolts, roller bearing bolts, conveyor belt bolts.

Color : Blue

Product Name:	Product Code:	Packing:	Parcel:
ANAEROBIC MEDIUM STRENGTH THREADLOCKER O.K.S STEEL LOCK	M-5242	15 ml.	12
ANAEROBIC MEDIUM STRENGTH THREADLOCKER O.K.S STEEL LOCK	M-7242	50 ml.	12
ANAEROBIC MEDIUM STRENGTH THREADLOCKER O.K.S STEEL LOCK	M-8242	250 ml.	6



ANAEROBIC HIGH STRENGTH THREADLOCKER Y.K.S STEEL LOCK

It is used where studs and nuts are not to be removed up to 1 "(25 mm). It is generally used in engine stubs, cylinder block anchors, water pump coupling connections and white goods industry.

Color : Red

Product Name:	Product Code:	Packing:	Parcel:
ANAEROBIC HIGH STRENGTH THREADLOCKER Y.K.S STEEL LOCK	M-5271	15 ml.	12
ANAEROBIC HIGH STRENGTH THREADLOCKER Y.K.S STEEL LOCK	M-7271	50 ml.	12
ANAEROBIC HIGH STRENGTH THREADLOCKER Y.K.S STEEL LOCK	M-8271	250 ml.	6

ANAEROBIC ROLLER RETAINER



Alcon Anaerobic Roller Retainer which have strong strength, high viscosity and used for fixing in bearings, shafts and shrink-fits and can be applied to the hard surfaces.

Color : Green

Product Name:	Product Code:	Packing:	Parcel:
ANAEROBIC ROLLER RETAINER	M-5638	15 ml.	12
ANAEROBIC ROLLER RETAINER	M-7638	50 ml.	12
ANAEROBIC ROLLER RETAINER	M-8638	250 ml.	6





Cylinder Block & Radiator Care





SILVERY SEALERLEAK RADIATOR SEALER POWDER

With its metallic super micro fibers, Sealer Leak repairs the leak very quickly and permanently seals the cracks it carries. Sealer Leak Stop Seal is used for a water cooling system for automobiles, trucks, work machines etc. and radiators, blocks, hoses etc. and all plastic, brass, copper radiators can be used as they have been repaired against leaks without having to dismantle their parts. Besides, to repairing cracks and leaks in the system or steel engine blocks, block or rust in the system; inhibits oxidation and prevents corrosion that may resurface.

Product Name:	Product Code:	Packing:	Parcel:
SILVERY SEALERLEAK RADIATOR SEALER POWDER	M-9906	3/4 OZ. (BOX)	288



CONSTAR STOP SEAL RADIATOR SEALER POWDER

CONSTAR Powder Stop Seal is used as anti-leakage for cylinder block and all-water cooling cracking systems. Depending on the time and the corrosion, cracks can occur in the cylinder block of the vehicle and all water-based cooling systems. Especially when antifreeze is put into the cooling water, due to the antifreeze is thinner than water, it causes the water in the system to leak out of these cracks, causing the increase heat in the engine. In this case the vehicle is put risk. In such cases, using the CONSTAR Powder Stop Seal, you can repair the leak very quickly, with its microfibers it contains. It saves time and money because the problem can be solved without disassembling the radiator and engine block. It can be used with antifreeze in the system due to it is compatible with all known antifreeze.

Product Name:	Product Code:	Packing:	Parcel:
CONSTAR STOP SEAL RADIATOR SEALER POWDER	M-9914	20 gr. (BAG)	288

Block Leaks with One Box!



COOLING SYSTEM LIQUID STOP LEAK (ANTIFREEZE COMPATIBLE)



It is an anti-leakage crack repair seal which may be used in all automobiles, trucks, tractors and engineering vehicles with cooling systems. It successfully prevents visible or invisible crack leaking and liquid losses in water cooling systems of vehicles. It restrains the leakage in gaskets and hoses. It does not make a negative effect on connections and flanges. It has neutral property against copper and light metals, does not affect them. Even if there is antifreeze in the cooling system of the vehicle, this product is used without making a trouble and complies with all known antifreeze.

Product Name:	Product Code:	Packing:	Parcel:
COOLING SYSTEM LIQUID STOP LEAK	M-9913	300 ml. (TIN BOX)	12



HOTSEALANT CYLINDER BLOCK SEALER LIQUID

It is the practical repair material of the cracks in the engine block, especially in water-borne cooling systems of vehicles, the leaks in the rotting sand taps, the holes in the radiator and the leaks. It provides a practical and effective solution without disassembling or distributing the system.

ATTENTION !!!

Application must be carried out after the antifreeze in the cooling system, has been emptied. Otherwise, it reacts with the antifreeze and leads to unwanted consequences. A few days after this procedure, the water in the system is drained, the system can be cleaned well and antifreeze can be placed again.

Product Name:	Product Code:	Packing:	Parcel:
HOTSEALANT CYLINDER BLOCK SEALER LIQUID	M-9901	350 g. (BOTTLE)	12

COPPPER SUPER LEAK COOLING SYSTEM

ATTENTION !!!

1- Do not use with antifreeze. Do not add when Copper Super Leak is available in system. Read the usage instructions.

2- Do not use on the vehicles with turbo oil radiator on cooling system and construction machines. Usage Method: Discharge the water with antifreeze in the system completely. Shake the bottle well and evacuate into the radiator, if possible after removing the thermostat. After this operation, fixate the thermostat and fill the cooling system with water. Start the engine and provide the temperature reach to 80-90 °C normal thermostat level. In this case stop the engine and let rest for 2 hours, set to work for 10-15 mins. The process is complete. Add the antifreeze after 3-4 days.

Product Name:	Product Code:	Packing:	Parcel:
COPPER SUPER LEAK COOLING SYSTEM	M-9905	240 ml.	12



RICON LUBES Fuel Additives Engine & Radiator Care Products

LUBES

ALCON EDG

DIESEL INJECTION CLEANER



Thanks to its special formulation, it provides cleaning and protection from tank to combustion chamber by removing charred residues in engine and injection system. It protects fuel system from corrosion. It provides maximum saving and performance. In cold weathers, it makes the engine run more easily by preventing the fuel from cooling. It is suitable for all diesel-engine passenger cars, commercial and engineering vehicles with or without turbocharger.

Product Name:	Product Code:	Packing:	Parcel:
DIESEL INJECTION CLEANER	M-9603	300 ml. (TIN BOX)	12



DIESEL FUEL SYSTEM CLEANING ADDITIVE

It is compliant with all diesel injector engine types (with or without turbo charger). It provides complete combustion inside the system and destroys the deposits in the pump and injectors and protects the system. It prevents contamination of the fuel filter. Protect against rust and corrosion. By keeping injectors clean, it improves combustion efficiency, reduces fuel consumption and improves engine performance.

Product Name:	Product Code:	Packing:	Parcel:
DIESEL FUEL SYSTEM CLEANING ADDITIVE	M-9611	300 ml. (TIN BOX)	12

DIESEL CETANE BOOSTER DIEL SETAN ARTTIRICI

DIESEL CETANE BOOSTER ADDITIVE

Thanks to its special formulation; increases the cetane number of the fuel. Injectors help reduce fuel consumption by keeping the combustion chamber and fuel system clean. Increase the draw. Reduce the formation of soot in the combustion system. Allows the engine to operate without knocking. It makes it easier to fire.

Product Name:	Product Code:	Packing:	Parcel:
DIESEL CETANE BOOSTER ADDITIVE	M-9613	300 ml. (TIN BOX)	12

DIESEL FUEL ANTI-FREEZE



With its special formulation, this product profects fluency of diesel fuel in a cold weather by under control to occurence of paraffin crystal on fuel and also avoid congesting of filters. Protects core spray system corrosion and rust. Facilitates the starting of the engine.

Product Name:	Product Code:	Packing:	Parcel:
DIESEL FUEL ANTI-FREEZE	M-9607	300 ml. (TIN BOX)	12

DIESEL PARTICULATE FILTER CLEANING ADDITIVE



LUBES

NANO BOR

ENGINE

OIL ADDITIVE

NANO BOR MOTOR YAĞ KATKISI It is an effective fuel additive product that prolongs the life of the filter by minimizing the accumulation of residue in the particulate filters due to the stop-overs in vehicles used especially in the city. Used to protect and clean particulate filters of diesel vehicles.

Product Name:	Product Code:	Packing:	Parcel:
DIESEL PARTICULATE FILTER CLEANING ADDITIVE	M-9610	300 ml. (TIN BOX)	12

NANO BOR ENGINE OIL ADDITIVE

Owing to the micro film layer created by its Nano-dimensional bor particle content on the mobile surfaces, it reduces friction in all four-cycle engines significantly reduces the corrosion & abrasion in mobile surfaces.

Benefits of Use

- * Reduces engine noise.
- * Prolongs engine and oil life.
- * Prevents heat and overheating.
- * Increases the adherence coefficient of oil.
- * Enables fuel savings.
- * Increases horsepower.
- * Prevents oil consumption.

Product Name:	Product Code:	Packing:	Parcel:
NANO BOR ENGINE OIL ADDITIVE	M-9606	300 ml. (TIN BOX)	12

GASOLINE INJECTION CLEANER



Thanks to its special formulation, high performance cleaning and protection contributions, it ensures that the valves run sensitively by removing charred residues occuring in injectors and injector valves. It decreases fuel consumption. It reduces exhaust fumes and contamination. It makes traction productive. It protects against corrosion. It is suitable for all gasoline-powered carburetor and injector engines which have catalytic converters or not.

Product Name:	Product Code:	Packing:	Parcel:
GASOLINE INJECTION CLEANER	M-9602	300 ml. (TIN BOX)	12



GASOLINE FUEL SYSTEM CLEANING ADDITIVE

This cleaning product specially designed for petrol engines; cleans fuel injectors, valves, combustion chambers and fuel system and prevents formation of deposits. Provides protection against rust and corrosion. It makes working cold easier.

Product Name:	Product Code:	Packing:	Parcel:
GASOLINE FUEL SYSTEM CLEANING ADDITIVE	M-9612	300 ml. (TIN BOX)	12



GASOLINE OCTANE BOOSTER ADDITIVE

Thanks to its special formulation; the condensate distributes the water formed in the gasoline tank. As a result, rust and corrosion in the fuel storage will be prevented. Increase the octane value of leaded or unleaded fuels by 2 or 3 units. Reduce fuel consumption. Reduce motor noise. Reduces emissions. Increases first take-off performance.

Product Name:	Product Code:	Packing:	Parcel:
GASOLINE OCTANE BOOSTER ADDITIVE	M-9614	300 ml. (TIN BOX)	12

OIL SMOKE STOP



ALCON

LUBES

ENGINE FLUSH &

CLEANER

MOTOR IC TEMIZLEVIC With its special formulation, it increases the oil viscosity and prevents it from getting thick. It helps to prevent the oil from becoming oxidized and decayed under high temperatures. It increases the oil viscosity and helps easy operation. It decreases the noise and knocking coming from the engine. It is appropriate for use in engines that consume oil or that emit blue/gray smoke from the exhaust.

Product Name:	Product Code:	Packing:	Parcel:
OIL SMOKE STOP	M-9605	300 ml. (TIN BOX)	12

ENGINE FLUSH & CLEANER

With its special formulation, cleans the oil-carbon deposits inside the engine and provides that the oil newly added to the engine fully performs its duty.

* As it neutral additive, it does not damage the engine parts or the engine bolts.


* It cleans all dirt and deposits that can dissolve in oil.

* Melts the deposits that result from cleaning and ensures their disposal.

* It reduces corrosion.

Product Name:	Product Code:	Packing:	Parcel:
ENGINE FLUSH & CLEANER	M-9601	300 ml. (TIN BOX)	12







ALCON

LUBE

RADIATOR IL-SLUDGE-RUST CLEANER RADYATÖR YAĞ+CAMUR+PA

 Product Name:
 Product Code:
 Packing:
 Parcel:

 RADIATOR OIL - SLUDGE - RUST CLEANER
 M-9604
 300 ml. (TIN BOX)
 12

DOT-3 HYDRAULIC BRAKE OIL



ALCON Hydraulic Brake Oils are a special synthetic based fluid and are used in the hydraulic brake and clutch systems of motor vehicles. It prolongs the life of the system by protecting the systems in which it is used against wear, rust and corrosion. It provides excellent performance and increased braking safety at different temperatures.

Product Name:	Product Code:	Packing:	Parc
DOT-3 HYDRAULIC BRAKE OIL	M-9618	500 gr.	24



DOT-4 HYDRAULIC BRAKE OIL

ALCON Hydraulic Brake Oils are a special synthetic based fluid and are used in the hydraulic brake and clutch systems of motor vehicles. It prolongs the life of the system by protecting the systems in which it is used against wear, rust and corrosion. It provides excellent performance and increased braking safety at different temperatures.

Product Name:	Product Code:	Packing:	Parc
DOT-4 HYDRAULIC BRAKE OIL	M-9619	500 gr.	24

NEW GENERATION BRAKING PERFORMANCE







HEAVY DUTY CLEANER & DEGREASER



It's a general purpose and strong cleaning product. Thanks to it's special water based formulation, it used for cleaning heavy dusts and oil from industrial areas industrial machines, lathes, machine tools, painted-unpainted metals, hand tools, vehicles (automobile, truck, motorcycle, construction equipment, vessel, ship) engine outer surfaces, floors and walls of workshops and factories easily.

Product Name:	Product Code:	Packing:	Parcel:
HEAVY DUTY CLEANER & DEGREASER	M-9816	500 ml.	12
HEAVY DUTY CLEANER & DEGREASER	M-9817	1 kg.	6
HEAVY DUTY CLEANER & DEGREASER	M-9818	5 kg.	4
HEAVY DUTY CLEANER & DEGREASER	M-9819	25 kg.	1

ALCON

AUTO DASHBOARD CLEANER

It's a strong, emulsified liquid silicone formula. It cleans and makes a semi-matt renovation on leather and vinyl parts, torpedo and door panels of vehicles. Prevents cracking on the surfaces. Provides care of your vehicle by keeping surfaces soft. Protects the surfaces from harmfull sun rays and effect of extreme heat, prevents dulling. Helps torpedo and pannels of your vehicle to look like first day. Prevents dusting for a long time due to its antistatic properties. Provides a nice smell in your vehicle.

Product Name:	Product Code:	Packing:	Parcel:
AUTO DASHBOARD CLEANER	M-9939	500 ml.	12
AUTO DASHBOARD CLEANER	M-9940	1 kg.	6
AUTO DASHBOARD CLEANER	M-9956	5 kg.	4
AUTO DASHBOARD CLEANER	M-9957	25 kg.	1

AUTO INTERIOR CLEANER

Alcon Auto Interior Cleaner is suitable for auto, home and office uses. (except for leather parts). It's an effective cleaner for fabrics, floors, carpets and plastic surfaces. Can be used on vehicle seats, door inner areas, torpedo, safety belt, ceiling and base carpets, baggage. Provides to clean dirts from smoking and external factors, dirt and stain easily. Doesn't contain phosphate. Provides effective cleansing on the application area, has a nice odor.

Product Name:	Product Code:	Packing:	Parcel:
AUTO INTERIOR CLEANER	M-9986	500 ml.	12
AUTO INTERIOR CLEANER	M-9979	1 kg.	6
AUTO INTERIOR CLEANER	M-9980	5 kg.	4
AUTO INTERIOR CLEANER	M-9930	25 kg.	1

LEATHER & VINYL CLEANER



Cleans the dirt and oils on leather seatings and furnitures in automobiles etc. vehicles, homes and offices. Doesn't cause cracks on leather. Through its special formula, provides cleaning stains and yellowings due to daily using on leather seating and parts of your vehicle easily. Has a nice odor. Doesn't contain phosphate.

Product Name:	Product Code:	Packing:	Parcel:
LEATHER & VINYL CLEANER	M-9894	500 ml.	12
LEATHER & VINYL CLEANER	M-9895	1 kg.	6
LEATHER & VINYL CLEANER	M-9896	5 kg.	4
LEATHER & VINYL CLEANER	M-9897	25 kg.	1

LEATHER & VINYL CARE LOTION

Alcon Leather & Vinyl Care Lotion, provides close to natural look without causing oily feeling on leather, vinyl and plastic surfaces. Through its unique formulation, avoids cracks and fadings caused sun effect. Delays staining and wearing caused daily using.

Product Name:	Product Code:	Packing:	Parcel:
LEATHER & VINYL CARE LOTION	M-9880	500 ml.	12
LEATHER & VINYL CARE LOTION	M-9881	1 kg.	6
LEATHER & VINYL CARE LOTION	M-9882	5 kg.	4
LEATHER & VINYL CARE LOTION	M-9883	25 kg.	1

AUTO ENGINE WASHING AGENT

Alcon Auto Engine Washing Agent, is a very powerfull, water-based, alcali product that developed for cleaning all kinds of engine oils, grease and dirt on engine and metal parts of vehicle. Doesn't damage cables and plastic parts thought it's caustic-free formulation. Has a nice odor.

Product Name:	Product Code:	Packing:	Parcel:
AUTO ENGINE WASHING AGENT	M-9994	500 ml.	12
AUTO ENGINE WASHING AGENT	M-9958	1 kg.	6
AUTO ENGINE WASHING AGENT	M-9959	5 kg.	4
AUTO ENGINE WASHING AGENT	M-9938	25 kg.	1





AUTO ENGINE RENEWER & CARE



Alcon Auto Engine Renewer & Care, provides new look to all parts under the cowling, through its powerfull formula that includes emulsifying polymers. It forms a protective film layer without oily feeling through its special solvent-free formulation. This uniqe formula, avoids cracking, fading and hardening by renewing plastic parts and hoses and provides a long lasting new look. Avoids gathering dust for a long time through its anti-static property.

Product Name:	Product Code:	Packing:	Parcel:
AUTO ENGINE RENEWER & CARE	M-9884	500 ml.	12
AUTO ENGINE RENEWER & CARE	M-9885	1 kg.	6
AUTO ENGINE RENEWER & CARE	M-9886	5 kg.	4
AUTO ENGINE RENEWER & CARE	M-9887	25 kg.	1

AUTO RIM CLEANER

Alcon Auto Rim Cleaner, cleans steel and aluminium rim surfaces and each surfaces steel and aluminium coated. It's an ideal and powerfull, water based and alcali product which used for cleansing this surfaces from solidified heavy dirt and stain, iron, shoe and rubber powders, heavy burned oil and another matters, rust etc, all stubborn dirt and stains. Alcon Auto Rim Cleaner is suitable for all soft plastic and painted surfaces through its acid and caustic free formulation. Solves and drains the dirt on vertical surface by holding the surface very well with its special foamy and alcali formulation. Transforms rims to their first look and provides protection against contamination.

Product Name:	Product Code:	Packing:	Parcel:
AUTO RIM CLEANER	M-9985	500 ml.	12
AUTO RIM CLEANER	M-9971	1 kg.	6
AUTO RIM CLEANER	M-9972	5 kg.	4
AUTO RIM CLEANER	M-9999	25 kg.	1

AUTO RIM SHINER

Alcon Auto Rim Shiner, forms a deep, rich and long lasting shine on vehicle rim through its special acidic formulation. Provides staying clean by protecting rim from external factors for a while. Transforms rims original shiny look.

Product Name:	Product Code:	Packing:	Parcel:
AUTO RIM SHINER	M-9890	500 ml.	12
AUTO RIM SHINER	M-9891	1 kg.	6
AUTO RIM SHINER	M-9892	5 kg.	4
AUTO RIM SHINER	M-9893	25 kg.	1


AUTO BODYWORK AND RIM IRON & RUST CLEANER



That developed with a special formulation, provides a deep cleansing by reacting with hidden iron particles on the bodywork and rim without damaging your vehicle throught color-changing technology. This technological product is suitable for painted surfaces, intense traffic dirts on the rims, bird droppings, tree resins, pitch, waves on the bodywork, metal fallouts formed in industrial zones and iron particles on rims.

Product Name:	Product Code:	Packing:	Parcel:
AUTO BODYWORK AND RIM IRON & RUST CLEANER	M-9988	500 ml.	12
AUTO BODYWORK AND RIM IRON & RUST CLEANER	M-9989	1 kg.	6
AUTO BODYWORK AND RIM IRON & RUST CLEANER	M-9998	5 kg.	4
AUTO BODYWORK AND RIM IRON & RUST CLEANER	M-9898	25 kg.	1

AUTO TIRE & RUBBER CLEANER



Product Name:	Product Code:	Packing:	Parcel:
AUTO TIRE & RUBBER CLEANER	M-9926	500 ml.	12
AUTO TIRE & RUBBER CLEANER	M-9927	1 kg.	6
AUTO TIRE & RUBBER CLEANER	M-9928	5 kg.	4
AUTO TIRE & RUBBER CLEANER	M-9929	25 kg.	1

AUTO TIRE SHINER

Alcon Auto Tire Shiner, provides a black and natural look to tires of your vehicle. It goes on 3-8 days in asphalt conditions. Does not contain damaging, hardening, causes cracks raw-metarials. Provides a shiny and new look on tires of your vehicle. Helps protection from external factors througt film layer that it form. Shines, renews by providing a polished new look to tires, black rubber panels, bumper, plastic radiator, air filter, black plastic and rubber engine parts, rubber hoses, window side rubbers, door and luggage rubbers of your vehicle. It has a concentrated formulation.

Product Name:	Product Code:	Packing:	Parcel:
AUTO TIRE SHINER	M-9945	500 ml.	12
AUTO TIRE SHINER	M-9946	1 kg.	6
AUTO TIRE SHINER	M-9949	5 kg.	4
AUTO TIRE SHINER	M-9995	25 kg.	1



Oto Lastik Parlate

AUTO RAIN REPELLENT



Through its special formulation, forms a compeletely invisible layer by covering the surface of the auto windows. Provides a safe driving and vision by repellenting rain, snow, mud etc. stains easily. It doesn't cause changes on the texture, appearance or color of the auto glass surface. Provides a clean vision by repellenting the rain drops especially on windshields and rear glass which complicates vision. Helps to auto glass staying as shiny as new by delaying powders to stick to auto glass and facilitate cleaning. When your speed up to 50 km/h you can see the rain repellenting effect on windshields easily.

Product Name:	Product Code:	Packing:	Parcel:
AUTO RAIN REPELLENT	M-9824	500 ml.	12
AUTO RAIN REPELLENT	M-9825	1 kg.	6
AUTO RAIN REPELLENT	M-9826	5 kg.	4
AUTO RAIN REPELLENT	M-9827	25 kg.	1

AUTO QUICK WET POLISH

Alcon Auto Quick Wet Polish, forms a shiny and smooth film layer on vehicle surface through water-activated polymers. Instead of drying wet vehicle first then polishing, it provides to do both at the same time. Throught its developed special formulation makes the surface water repellent, so provides drying in a short while and easily. Therewithal helps to avoid accumulation of dirt, dust, particles on the surface. It is resistant to detergents and cleaning agents. Transforms your vehicles paint as smooth as beginning.

Product Name:	Product Code:	Packing:	Parcel:
AUTO QUICK WET POLISH	M-9993	500 ml.	12
AUTO QUICK WET POLISH	M-9952	1 kg.	6
AUTO QUICK WET POLISH	M-9953	5 kg.	4
AUTO QUICK WET POLISH	M-9899	25 kg.	1



BRUSHLESS CAR WASH SHAMPOO

Cleans without damaging the exterior surfaces, plastic parts, nickel plating and alloy wheels of the vehicles. Through its special foam formula, it is compatible with professional or amateur dosing and hopper foam production washing machines without the use of brush, sponge. Does not contain raw metarials damaging for painted surfaces, rubber and plastic parts of vehicles. (caustic, salt etc.) It's an economic and concentrated product. Active foam effectively and easily removes bird droppings, fly, insect residues, traffic pollution and dried mud stains on the surface.

Product Name:	Product Code:	Packing:	Parcel:
BRUSHLESS CAR WASH SHAMPOO	M-9975	1 kg.	6
BRUSHLESS CAR WASH SHAMPOO	M-9976	5 kg.	4
BRUSHLESS CAR WASH SHAMPOO	M-9977	25 kg.	1


POLISH CAR WASH SHAMPOO



It is a product for washing with a brush or sponge, without damaging the exterior surfaces, plastic parts, nickel wheels and alloy wheels of vehides. Through its special formula, while washing your car at the same time creates a thin film and provides brightness. Does not contain raw metarials damaging for painted surfaces, rubber and plastic parts of vehicles. (caustic, salt etc.) It can be rinsed easily and reduce drying time with cloth.

Product Name:	Product Code:	Packing:	Parcel:
POLISH CAR WASH SHAMPOO	M-9962	1 kg.	6
POLISH CAR WASH SHAMPOO	M-9963	5 kg.	4
POLISH CAR WASH SHAMPOO	M-9964	25 kg.	1

POWER CLEAN MULTI PURPOSE CLEANER



Product Name:	Product Code:	Packing:	Parcel:
POWER CLEAN MULTI PURPOSE CLEANER	M-9828	500 ml.	12

CLEANER CLAY BAR MAGIC CLEANER



It quickly and safely cleans your vehicle from settled things on the paint surface and which do not come out with the wash process such as; resin, paint residues, heavy traffic dirt, brake lining dust, cement dust, sludge by acid rain, bird droppings, spills and pitch residue in the industry and shipyard area. It creates a smooth and brillant surface before pasting and polishing.

Product Name:	Product Code:	Packing:	Parcel:
CLEANER CLAY BAR MAGIC CLEANER	M-2000	200 g. (BOX)	12

CLEANER CLAY BAR MAGIC CLEANER



Cleaner Clay Composition of the second of th

Auto Wiper Water Additives

ANTI-FREEZE WIPER WATER ADDITIVE



This product ensures that safer sight in all kinds of road conditions. Prevents freezing of water in the glass water tank and protects water spray system in winter. Allows wiper to slip perfectly. Destroys dust, bugs, oil and traffic stains. Plastic and metal parts are not damaged.

Product Name:	Product Code:	Packing:	Parcel:
ANTI-FREEZE WIPER WATER ADDITIVE (-20 °C)	M-9822	1000 ml.	12
ANTI-FREEZE WIPER WATER ADDITIVE (-20 °C)	M-9829	500 ml.	24
ANTI-FREEZE WIPER WATER ADDITIVE (-20 °C)	M-9941	250 ml.	36
ANTI-FREEZE WIPER WATER ADDITIVE (-80 °C)	M-9821	250 ml.	36

AUTO GLASS CLEAN VISION CONCENTRATE



Whether or not your vehicle has wiper water antifreeze; this product is added to the wiper water tank to create a slippery surface for the wiper blades. Allows wiper blades to run for a long time without tracing. Dissolve oily residues such as exhaust fumes, dirt, fly, insects and provides safe driving with a gleaming glass. Pleasant odor refreshes the passengers in the car.

Product Name:	Product Code:	Packing:	Parcel:
AUTO GLASS CLEAN VISION CONCENTRATE	M-9921	75 ml.	42





ALCON ENDÜSTRİYEL ÜRÜNLER SAN. ve TİC. LTD. ŞTİ

 Soğanlık Yeni Mh. Aliağa Sk. BUMERANG KARTAL REZIDANS No:8/37 Kartal/İSTANBUL/TÜRKİYE

© Tel: +90 216 661 00 90 Fax: +90 216 661 01 57

www.alcon.com.tr/en/ alcon@alcon.com.tr