

PRODUCT INFORMATION





MANUAL PUMPS

DP-14 Siphon Hand Pump





DP-15 Siphon Hand Pump (High Speed)



12LPM

4LPM



DP-16-1N Siphon Hand Pump (Fixable & High Speed)

Features & Applications

- Mechanism: Manual up and down piston
 Applicable supply tank height:
- 300mm ~ 390mm
- Applicable liquids: Kerosene, diesel, gasoline, non-potable water, deodorants, antifreeze, windshield washer fluid, thinner, toluene, chemical insecticides, agricultural chemicals, motor oil(ex.5W30), hydraulic oil(ex.AW46), lubricants
- Non-corrosive, non-toxic plastic material construction

Specifications

- Total length: 650mm
- Suction tube length: 425mm
- Suction tube outer diameter: 25mm
- Discharge tube length: 660mm
- Discharge tube outer diameter: 19mm
- Head outer diameter: 60mm
- Delivery volume: 12LPM
- Main material: P.E
- Net weight/pc: 150g

DP-50 Siphon Hand Pump (with Long Hose)



Features & Applications

- Mechanism: Manual squeezing
- Applicable liquids: Kerosene, diesel, gasoline, non-potable water, Deodorants, antifreeze, windshield washer fluid, thinner, toluene, chemical insecticides, agricultural chemicals
- Non-corrosive, non-toxic plastic material construction

- Total length: 1,788mm
- Suction tube outer diameter: 13mm
- Head outer diameter: 46mm
- Delivery volume: 4LPM
- Main material: P.E
- Net weight/pc: 70g



MANUAL DRUM PUMPS

DP-20 Siphon Hand Pump for Drum Can



18.5LPN

211 PM



Features & Applications

- Mechanism: Manual up and down piston
 Applicable liquids: Kerosene, diesel, gasoline, non-potable water, deodorants, antifreeze, windshield washer fluid, thinner, toluene, chemical insecticides, agricultural chemicals, motor oil(ex.5W30), hydraulic oil(ex.AW46),
- Non-corrosive, non-toxic plastic material construction, light-weight
- 30mm long adapter for standard 2" NPS

Specifications

- Total length: 1,125mm
- Suction tube length: 875mm
- Suction tube outer diameter: 22mm
- Discharge tube length: 1,200mm
- Discharge tube outer diameter: 22mm
- Head outer diameter: 71mm
- Delivery volume: 17.5LPM
- Main material: P.E
- Net weight/pc: 300g

DP-25 Siphon Hand Pump for Drum Can (Heavy Duty)



TI-901 Siphon Hand Pump for Drum Can (Heavy Duty / High Speed)

Features & Applications

- Mechanism: Manual up and down piston
- Applicable liquids: Kerosene, diesel, gasoline, non-potable water, deodorants, antifreeze, windshield washer fluid, thinner, toluene, chemical insecticides, agricultural chemicals, motor oil(ex.5W30), hydraulic oil(ex.AW46), lubricants
- Non-corrosive, non-toxic plastic material construction, light-weight
- 30mm long adapter for standard 2" NPS
- 30mm long adapter for standard 2" NPS drum bung
 DO NOT use this pump for transferring the following liquids: ACETONE, BENZENE, CREOSOL, NITRIC ACID, METHYL ETHYL, ETHYL, PHENOL, HYDROCHLORIC ACID, Concentrated CAUSTIC SODA LIQUID, SULFURIC ACID, etc.

Specifications

- Total length: 1,150mm
- Suction tube length: 850mm
- Suction tube outer diameter: 25.5mm
- Discharge tube length: 1,200mm
- Discharge tube outer diameter: 22.5mm
- Head outer diameter: 83.5mm
- Delivery volume: 21LPM
- Main material: P.E
- Net weight/pc: 365g

TI-901N Siphon Hand Pump for Drum Can (Segmented Suction Pipe)

2" NPS to Trisure adapte



Features & Applications Mechanism: Manual up and down piston Applicable liquids: Kerosene, diesel, gasoline, non-potable water, deodorants, antifreeze, windshield washer fluid, thinner, toluene, chemical insecticides, agricultural chemicals, motor oil(ex.5W30), hydraulic oil(ex.AW46), lubricants Segmented suction pipe for height adjustment and storage • 30mm long adapter for standard 2" NPS drum bung DO NOT use this pump for transferring the following liquids: ACETONE, BENZENE, CREOSOL, NITRIC ACID, METHYL ETHYL, ETHYL, PHENOL, HYDROCHLORIC ACID, Concentrated CAUSTIC SODA LIQUID, SULFURIC ACID, etc. Optional parts 2" NPS to 2" NPS to 2" NPS Buttress adapter Trisure adapter Mauser ad

- Total length: 1,150mm
- Suction tube length: 850mm
- Suction tube outer diameter: 25mm Discharge tube length: 1,200mm
- Discharge tube outer diameter: 22.5mm Head outer diameter: 83.5mm
- Delivery volume: 21LPM
- Main material: P.E.
- Net weight/pc: 413g



MANUAL DRUM PUMPS

DLP-2105S Manual Lever Pump (Spout Type)





Features & Applications

- Mechanism: Manual up and down lever • Applicable liquids: motor oil, hydraulic oil,
- lubricants, DEF(AdBlue), antifreeze, windshield washer fluid, non-potable water, agricultural chemicals
- Non-corrosive, non-toxic plastic material construction, light-weight
- 30mm long adapter for standard 2" NPS drum bung

Specifications

- Total length: 665 ~ 1,300mm
- Suction tube length: 350 ~ 985mm
- Suction tube outer diameter: 20mm
- Spout outer diameter: 20.8mm
- Head outer diameter: 255mm
- Delivery volume: 320ml per stroke • Main material: P.P. P.E. Acetal
- Net weight/pc: 1,080g

DLP-2105H Manual Lever Pump (Hose Type)





DLP-2105N Manual Lever Pump (Nozzle Type)

Optional parts

2" NPS to 2" NP ter Trisure adapter Mauser



- Mechanism: Manual up and down lever
- Applicable liquids: DEF(AdBlue), non-potable water, windshield washer fluid, antifreeze, agricultural chemicals, lubricants
- Multi-purpose hose - ISO 22241-2 certified for DEF compatibility
- Comes with a trigger nozzle
- Non-corrosive, non-toxic plastic material construction, light-weight
- 30mm long adapter for standard 2" NPS drum bung

Specifications

- Total length: 665 ~ 1,300mm
 Suction tube length: 350 ~ 985mm
- Suction tube outer diameter: 20mm
- Discharge tube length: 2,000mm
- Head outer diameter: 255mm
- Delivery volume: 320ml per stroke
- Main material: P.P, P.E, Acetal
- Net weight/pc: 2,580g





Features & Applications

- Mechanism: Manual up and down lever
- Applicable liquids: Kerosene, diesel
- A unique toggle mechanism is incorporated in the handle linkage to correct piston shaft geometry to creat smooth operation and also prevent premature piston shaft seal failure.
- 2" NPS drum bung adapter with Lock nut
- DO NOT use this pump for transferring the following liquids: ACETONE, BENZENE, CREOSOL, NITRIC ACID, METHYL ETHYL, ETHYL, PHENOL, HYDROCHLORIC ACID, Concentrated CAUSTIC SODA LIQUID, SULFURIC ACID, TOLUENE, etc.

- Total length: 665 ~ 1,300mm
- Suction tube length: 350 ~ 980mm
- Suction tube outer diameter: 20mm
- Discharge tube length: 2,000mm
- Discharge tube outer diameter: 20mm Delivery volume: 530ml per stroke
- Main material: P.P, P.E, Acetal
- Net weight/pc: 980g





DP-14S Chemical Siphon Hand Pump

7LPN



TI-901S Chemical Siphon Hand Pump for Drum Can



Features & Applications

- Mechanism: Manual up and down piston
- Applicable liquids: Thinner, toluene, hydrochloric acid 35%, nitric acid 35%, sulfuric acid 35%, acetic acid 35%, water, gasoline, diesel, kerosene, brake cleaner, windshield washer fluid, chemical insecticides,
- agricultural chemicals, motor oil(ex.5W31), hydraulic oil(ex.AW46), lubricants • Non-corrosive, non-toxic plastic material
- construction, light-weight
- 30mm long adapter for standard 2" NPS drum bung

Specifications

Main material: P.E.

Net weight/pc: 68g

Specifications

• Total length: 530mm • Suction tube length: 385mm

• Suction tube outer diameter: 15mm

• Discharge tube outer diameter: 12mm

Discharge tube length: 540mm

 Head outer diameter: 51mm Delivery volume: 7LPM

- Total length: 1,150mm
- Suction tube length: 850mm
- Suction tube outer diameter: 25.5mm
- Discharge tube length: 1,200mm
- Discharge tube outer diameter: 22.5mm
- Head outer diameter: 83.5mm
- Delivery volume: 21LPM
- Main material: P.E
- Net weight/pc: 390g



* PATENTED US D755,925 D777,007

ELECTRIC PUMPS

DEP-1504-12V Electric Pump (with Nozzle)



Features & Applications Delivery volume: 12LPM Mechanism: Centrifugal motor • Main material: P.P, P.E, Acetal Applicable liquids: Gasoline, kerosene, diesel, non-potable water, DEF(AdBlue), Power: DC12V Total length: 670mm antifreeze, windshield washer fluid, agricultural chemicals

- Comes with a trigger nozzle
- Use DC 12V car battery or AC power
- Comes with different nozzle heads - Ideal for garden and outdoor use with sprayer head
- Useful for refilling gas to fuel tanks Available with suction end filter
- Ideal for aquarium
 - For boat, plumbing, excess water, etc.

Specifications

DEP-1504RB Rechargeable Battery Pump (with Nozzle)



Features & Applications

- Mechanism: Centrifugal motor
- Applicable liquids: Gasoline, kerosene, diesel, non-potable water, DEF(AdBlue), antifreeze, windshield washer fluid, agricultural chemicals
- Comes with a trigger nozzle
- USB 2.0 micro type B connector
- · Comes with different nozzle heads - Ideal for garden and outdoor use with sprayer head - Useful for refilling gas to fuel tanks

- For boat, plumbing, excess water, etc.

Specifications

- Delivery volume: 11.8LPM
- Main material: P.P, P.E, Acetal
- Power: Rechargeable li-ion battery
- Total length: 602 ~ 742mm
- Suction tube length: 380 ~ 520mm
- Suction tube outer diameter: 32mm
- Discharge tube length: 1,500mm
- Net weight/pc: 483g



4

11.8LPM

- Suction tube outer diameter: 32mm
- Suction tube length: 467mm

- Discharge tube length: 2,500mm
- Net weight/pc: 693g

- Available with suction end filter
- Ideal for aquarium

21LPN



ELECTRIC PUMPS

DEP-1403S Electric Drum Pump (Heavy Duty)



Delivery volume(Power source: DC 12V)

Main material: PP, P.E, POM, NBR

• Suction tube length: 850 ~ 865mm

Suction end outer diameter: 55mm

• Discharge tube length: 2,000mm

Head outer diameter: 110mm

Features & Applications Mechanism: Centrifugal motor Applicable liquids: Diesel, DEF(AdBlue), non-potable water, kerosene, antifreeze, windshield washer fluid, agricultural chemicals Handy nozzle holster built in • Two types of nozzle - Plastic spout: 24.7mm - Stainless steel spout:18mm Comes with 2" NPS bung adapter - Optional parts: 2" NPS to Buttress adapter 2" NPS to Mauser adapter Filter-equipped intake end protects the motor from damage due to alien matters

DEP-1403T Electric Drum Pump (Telescopic Intake)



- Mechanism: Centrifugal motor Applicable liquids: Diesel, DEF(AdBlue), non-potable water, kerosene, antifreeze, windshield washer fluid, agricultural chemicals
- Handy nozzle holster built in
- Two types of nozzle - Plastic spout: 24.7mm
- Stainless steel spout:18mm • Comes with 2" NPS bung adapter
- Optional parts: 2" NPS to Buttress adapter 2" NPS to Mauser adapter
- Filter-equipped intake end protects the motor from damage due to alien matters

DEP-1403-20V Electric Pump (Heavy Duty / High Speed)

Crimping with metal sleeve

ers with oil & flame

Flow Me

Hose

2" NPS to Buttrace adapt

Crimping

1245n

Optional parts



- Mechanism: Centrifugal motor Applicable liquids: Motor oil(ex.5W30), hydraulic oil(ex.AW46), lubricants, diesel, DEF(AdBlue), non-potable water, kerosene, antifreeze, windshield washer fluid, agricultural chemicals
- · Handy nozzle holster built in Two types of nozzle
- Plastic spout: 24.7mm
- Stainless steel spout. 24./100
 Stainless steel spout.18mm
 Comes with 2" NPS bung adapter
 Optional parts: 2" NPS to Buttress adapter 2" NPS to Mauser adapter
- Filter-equipped intake end protects the motor from damage due to alien matters

I9LPN Specifications

- Delivery volume(Power source: DC 12V) - Water: 19LPM
- Main material: PP, P.E, POM, NBR
- Power: DC 12V ~ 20V

Specifications

Water: 19I PM

Power: DC 12V ~ 20V

Total length: 1,110mm

Net weight/pc: 2,000g

- Total length: 1,110 ~ 1500mm
- Suction tube length: 850 ~ 1,245mm
- Suction end outer diameter: 55mm
- Head outer diameter: 110mm
- Net weight/pc: 2,000g



22LPI

Specifications

- Delivery volume(Power source: DC 20V) - Motor oil: 16LPM(20°C, 5W30) - Water: 27LPM
- Main material: PP, P.E, POM, NBR
- Power: DC 20V
- Total length: 1,110mm
- Suction tube length: 850mm ~ 865mm
- Suction end outer diameter: 55mm
- Discharge tube length: 2,000mm
- Head outer diameter: 110mm
- Net weight/pc: 3,000g

DEP-1403RB **Rechargeable Battery Drum Pump**



Features & Applications

- Mechanism: Centrifugal motor Applicable liquids: Motor oil(ex.5W30)
- hydraulic oil(ex.AW46), lubricants, diesel, DEF(AdBlue), non-potable water, kerosene, antifreeze, windshield washer fluid, agricultural chemicals
- Handy nozzle holster built in
- Two types of nozzle Plastic spout: 24.7mm
- Stainless steel spout:18mm Comes with 2" NPS bung adapter Optional parts: 2" NPS to Buttress adapter 2" NPS to Mauser adapter
- · Filter-equipped intake end protects the motor

Specifications

 Delivery volume(14.8V Li-ion battery) - Water: 22LPM

20v D.C

- Main material: PP, P.E, POM, NBR
- Power: Rechargeable li-ion battery
- Total length: 1,110mm
- Suction tube length: 850mm ~ 865mm
- Suction end outer diameter: 55mm
- Discharge tube length: 2,000mm
- Head outer diameter: 110mm
- Net weight/pc: 2,900g





ELECTRIC PUMPS

DEP-1603-12V Electric Submersible Pump (with Nozzle)





Filter-equipped intake end protects the motor

from damage due to alien matters

DEP-1702P Electric Pail Pump



Features & Applications

- Mechanism: Centrifugal motor
- Applicable liquids: Motor oil(Ex.5W30) hydraulic oil(ex.AW46), lubricants, diesel, DEF(AdBlue), non-potable water, kerosene, antifreeze, windshield washer fluid,
- agricultural chemicals • Comes with a trigger nozzle
- Filter-equipped intake end protects the motor from damage due to alien matters

Specifications

• Delivery volume(Power source: DC 16V) - Motor oil: 5.3LPM(20°C, 5W30) - Water: 17LPM

17LPN

- Main material: P.P, P.E, Acetal
- Power: DC16V
- Total length: 678 ~ 833mm
- Suction tube length: 420 ~ 575mm
- Suction end outer diameter: 38mm
 - Discharge tube length: 1,800mm



DEP-1908A Dx2 Battery Operated Pump





DEP-1908N Dx2 Battery Operated Pump (with Nozzle)



* PATENTED US D755,925 EU 002681833-0002 JP 1538043 Features & Applications Specifications Mechanism: Battery operated submersible Delivery volume: 9LPM(2.4GPM) Main material: P.P, P.E, Acetal motor • Power: DC 3V("D" size battery X 2) · Applicable liquids: Gasoline, diesel, kerosene, DEF(AdBlue), non-potable water, antifreeze, Total length: 580 ~ 720mm windshield washer fluid, agricultural chemicals • Suction tube length: 380 ~ 520mm • Comes with a trigger nozzle • Suction tube outer diameter: 32mm Comes with different nozzle heads Discharge tube length: 1,000mm - Ideal for garden and outdoor use with sprayer head • Discharge spout outer diameter: 15.9mm - Useful for refilling gas to fuel tanks Net weight/pc: 765g Telescopic suction tub

DEW-1904-14 AAx4 Battery Operated Watering Pump (with Nozzle)





Features & Applications

- Mechanism: Battery operated submersible
- Applicable liquids: Non-potable water
- Various nozzle heads: Shower mode and normal spout nozzle heads are available

Specifications

- Delivery volume: 5LPM
- Main material: P.P, P.E, Acetal
 Power: DC 3V("AA" size battery X 4)
- Total length: 482mm
- Suction tube length: 400mm
- Suction tube outer diameter: 32mm
- Discharge tube length: 750mm
- Net weight/pc: 1,310g

DEW-1904RB Rechargeable Battery Watering Pump (with Nozzle)





Features & Applications

- Mechanism: Battery operated submersible motor
- Applicable liquids: Non-potable water
- USB C type connector
- · Various nozzle heads: Shower mode and normal spout nozzle heads are available
- Nozzle holder: Safe and convenient way to stow the nozzle after use
- Water tank: Slim design is easy to store

- Delivery volume: 8.5LPM
- Main material: P.P, P.E, PC, Acetal
- Power: Rechargeable li-ion battery
- Total length: 509mm
- Suction tube length: 400mm
- Suction tube outer diameter: 32mm
- Discharge tube length: 2,150mm
- Net weight/pc: 1,780g



DP-03 AAx2 Battery Operated Pump

CAAx4 10LPM



DP-03-1 AAx2 Battery Operated Pump (Auto Stop)





DP-03-2 AAx2 Battery Operated Pump (Auto Stop & Buzzer)

AAx4	Auto Stop	I()) Buzzer	9LPM
------	--------------	----------------	------

Dx2

3.5LPN

•	Features & Applications	Specifications
	 Mechanism: Battery operated submersible motor Applicable liquids: Gasoline, kerosene, diesel, non-potable water User-friendly automatic liquid supply Auto stop before overflowing by sensor Acoustic signal when auto stop 	 Delivery volume: 9LPM Main material: P.P, P.E, Acetal, ABS Power: DC 3V("D" size battery X 2) Total length: 592mm Suction tube length: 385mm Suction tube outer diameter: 32mm Discharge tube length: 560mm Discharge tube outer diameter: 19.5mm Net weight/pc: 223g

DPC-06 DX2 Battery Operated Cooking Oil Pump

	 Features & Applications Mechanism: Battery operated motor Applicable liquids: Cooking oil User-friendly automatic liquid supply Effortlessly transfers oil from container to receptacle. Filter will ensure no food or other particles will be transferred into receptacle. 	Specifications • Delivery volume: 3.5LPM • Main material: P.P. P.E, Acetal • Power: DC 3V("D" size battery X 2) • Total length: 660mm • Suction tube length: 404mm • Suction tube outer diameter: 62.5mm • Discharge tube length: 1,000mm • Discharge tube outer diameter: 14.5mm • Net weight/pc: 280g
--	--	--



DP-06CH Dx2 Battery Operated Chemical Pump





DP-07EA Dx2 Battery Operated Pump (High Speed)





Features & Applications

- · Mechanism: Battery operated submersible motor
- Applicable liquids: Gasoline, kerosene, diesel, non-potable water, DEF(AdBlue), antifreeze, windshield washer fluid, agricultural chemicals
- User-friendly automatic liquid supply

Specifications

Specifications

Delivery volume: 7LPM

Total length: 630mm

Net weight/pc: 245g

• Suction tube length: 375mm Suction tube outer diameter: 29mm • Discharge tube length: 605mm • Discharge tube outer diameter: 14.5mm

• Main material: P.P, P.E, ABS, Acetal

• Power: DC 3V("D" size battery X 2)

- Delivery volume: 10LPM
- Main material: P.P, P.E, Acetal
- Power: DC 3V("D" size battery X 2)
- Total length: 592mm
- Suction tube length: 385mm
- Suction tube outer diameter: 32mm
- Discharge tube length: 605mm
- Discharge tube outer diameter: 14.5mm
- Net weight/pc: 195g

DP-08EA Dx2 Battery Operated Pump (Auto Stop)



Features & Applications

- Mechanism: Battery operated submersible motor
- · Applicable liquids: Gasoline, kerosene, diesel, non-potable water
- User-friendly automatic liquid supply
- · Auto stop before overflowing by sensor

Specifications

- Delivery volume: 9LPM
- Main material: P.P, P.E, ABS, Acetal
 Power: DC 3V("D" size battery X 2)
- Total length: 592mm
- Suction tube length: 385mm
- Suction tube outer diameter: 32mm
- Discharge tube length: 560mm
- Discharge tube outer diameter: 19.5mm
- Net weight/pc: 223g

DP-08-1EA DX2 Battery Operated Pump (Auto Stop & Buzzer)





Features & Applications

- Mechanism: Battery operated submersible motor
- Applicable liquids: Gasoline, kerosene, diesel, non-potable water
- User-friendly automatic liquid supply
- Auto stop before overflowing by sensor
- Acoustic signal when auto stop

- Delivery volume: 9LPM
- Main material: P.P, P.E, ABS, Acetal
- Power: DC 3V("D" size battery X 2)
- Total length: 592mm
- Suction tube length: 385mm Suction tube outer diameter: 32mm
- Discharge tube length: 560mm
- Discharge tube outer diameter: 19.5mm
- Net weight/pc: 223g





DPN-07EA DX2 Battery Operated Pump (with Nozzle)





DP-101N AAx4 Battery Operated Pump (with Nozzle & Fixable)



Features & Applications Specifications Mechanism: Battery operated submersible Delivery volume: 9LPM • Main material: P.P, P.E, Acetal motor Applicable liquids: Gasoline, kerosene, diesel, Power: DC 3V("AA" size battery X 4) non-potable water, DEF(AdBlue), antifreeze, Total length: 535mm windshield washer fluid, agricultural chemicals

Trigger nozzle

Use DC 3V with 4xAA Alkaline batteries

- More safe: controls the flow at the

discharge end with no spill

S/W in on position

- - Suction tube length: 460mm Suction tube outer diameter: 32mm

 - Discharge tube length: 1,000mm
 - Discharge spout outer diameter: 15.9mm
- Net weight/pc: 467g - More convenient: flow control by flow switch Nozzle prevents spill while electric





SUBMERSIBLE PUMPS

DP-55 Submersible DC 12V Pump





DBP-09N Submersible Water Pump (with Switch)



12LPM

18LPM

Features & Applications	Specifications	
 Mechanism: Submersible motor Applicable liquids: Non-potable water, DEF(AdBlue), Antifreeze, Kerosene, Diesel, Windshield washer fluid, Agricultural chemicals Membrane Switch Rain proof membrane switch protects against dust and easy to use LED is on while pump is running 	 Delivery volume: 13LPM at 0 meter high 11LPM at 1 meter high Max lift height: Approx. 4M Pump body length: 140mm Pump body diameter: 70mm Net weight/pc: 387g 	
 Not to be used with petrol or volatile liquids Efficient and Easy to clean filter 		

DBP-09A Submersible Water Pump



DBP-15A Submersible Water Pump (High Speed)





AQUARIUM CLEANER PUMPS

DP-40 Aquarium Cleaner Pump (Big Type)





DP-45 Aquarium Cleaner Pump (Small Type)







ACCESSORIES

DS-01 Plastic Pipette

Features & Specifications

- Convenient to remove waste liquid in bottom of container
- Total length: 265mm
- Main material: P.E
- Suction capacity: 50cc
- Net weight/pc: 13.5g

DS-03 LED Lamp



- Convenient to use in dark places
- Applicable model: DP-03-1, DP-08EA, DP-101A
- Main materials: PD ARS
- Main materials: PP, ABS

DSC-01 Storage Case for Hand Pump (Big Type)



Features & Specifications Storage case for pump Main material : P.E, P.P Net weight/pc: 130g

DSC-03 Storage Case for Hand Pump (Small Type)





ACCESSORIES

Buttress Adapter

2" NPS to Buttress

2" NPS

Flow Meter for Water-based Fluid

Trisure Adapter



Mauser Adapter



Flow Meter for Oil



Features & Specifications

- Flow rates: 1 ~ 35LPM
 Accuracy: ± 0.5%
 - Accuracy: ± 0.5%
- Operating pressure(Max.): 50bar
- Operating temp.: +5°C~40°C
 Net weight/pc: 400g
- Inlet connection: 1/2"
- BSP female thread

DN-1403 Trigger Nozzle



Features & Specifications

Features & Specifications

• Operating pressure(Max.): 10bar

• Operating temp.: +5°C~40°C

• Flow rates: 5 ~ 120LPM

• Accuracy: ± 1%

• Net weight/pc: 214g

Inlet connection: 1"

BSP male thread

- Two types of spout
 Plastic spout: 24.7mm
- Stainless steel spout:18mm
- Applicable hose inner diameter: 19mm

DN-1504 Trigger Nozzle



Features & Specifications

- Nozzle lever designed to operate in two different ways according to the application
- Flow adjustable
- Applicable hose inner diameter: 16mm
 Discharge spout outer diameter: 15.9mm

DN-1706 Trigger Nozzle



Features & Specifications

- Nozzle lever designed to operate in two different ways according to the application
- Applicable hose inner diameter: 16mm
 Discharge spout outer diameter:
- 15.9mm

DMH Multi-purpose Hose



RB-2500 Rechargeable Li-ion Battery



Features & Specifications

- Capacity: 14.8V 2.5Ah (37Wh)
- Recharge with designated charger
- Charging time: About 3 hours
- Battery level indication with LED
- Automatically idle after 30 minutes
- Applicable model: DEP-1403RB, DEP-1702RB

RB-2109 Rechargeable Li-ion Battery



Features & Specifications

- Capacity: 3.7V --- 2.5Ah (9.25Wh)
- Recharge with USB-C cable
- Charging time: About 3 hours
- Battery level indication with LED
- Automatically idle after 30 minutes
- Applicable model: DEW-1904RB

JP 1538043

NOTE

Professional Pumping Systems

Dukshin Corp., Ltd.

110, Seunggicheon-ro Namdong-gu, Incheon, Korea Tel : 82 . 32 . 812 . 6257 Fax : 82 . 32 . 232 . 3131 www.dukshin.com info@dukshin.com