

AC300

Automatic Dispenser



➡ High Accuracy: 0.015ml(1/2000Y)

➡ Purge Free

➡ Flexible Modular Design

➡ Dispense Formula Simultaneously

SANTINT • CHINA

Add: Feilong Road, Xingyang,
Zhengzhou, China
Email: info@santint.com

SANTINT • HOLLAND

Add: Gieterij 28, 2211 XK
Noordwijkerhout, The Netherlands
Email: sales@santint-europe.com

SANTINT • POLAND

Add: 43 Szyszkowa Street,
02-285 Warsaw, Poland
Email: albert@santintpoland.com

SANTINT • U.S.A

Add: 2000 Bloomingdale Road,
Suite 205, Glendale Heights,
IL 60139, U.S.A
Email: info@santintusa.com

SANTINT • BRAZIL

Add: Av. Rosa Kasinski,
1109, G29 Capuava, Mauá,
SP - Brasil CEP 09380-128
Email: marcos@santint.com

SANTINT • INDIA

Add: H.No.692, Gala No.04, Print
World Industrial Complex,
Bhatale, Vhele Village, Opposite
Balaji Compound, Bhiwandi,
Maharashtra - 421302
Email: nick@santint.com

AC300 Main Features >>>

SANTINT
WHERE INNOVATION MEETS PRECISION



High-precision pump & valve technology



Intelligent and Fast Conveyor System



Digital LCD Display



Spot Repair (15mm open) Dispensing



Optional high-accuracy electronic scale(0.01g readability)

- Pump Type: Piston Pump
- Single Pump Efficiency: 200ml/min *It depends on the product property
- Minimum Shot: 1/2000Y(0.015ml) *It depends on the product property

- Modular Design: 32 canisters each module, 4x4.3L + 28x1.25L
- Three Modules: 12x4.3L+84x1.25L
- Three Modules Size: 2820x1480x1020mm
- Single Module Size(WxHxD): 940x1500x1035mm
- Total Weight of Three Modules: 780kg
- Single Module Weight: 260kg

- Operation Height: 1250mm
- Dispensing Modes: Volumetric or Gravimetric
- Others: Compatible for Small Vials (15mm open)
- Power Supply: 220V/110V 50/60HZ
- Refilling Height: 1300mm
- Conveyor Speed: 6m/min
- Rated Power: 800W

AC300

<<< Technical Parameters

