

AC100 Automatic Dispenser			
Dispensing Mode	Automatic Dispensing	Max Can Size (D x H)	200x180mm (with scale)
Efficiency (single toner)	200ml/min		200x280mm (without scale)
Minimum Shot	1/2000Y(0.015ml) *It depends on the product property	Machine Dimension (WxDxH)	1770x1215x1400mm(96 toners)
Pump Capacity	60ml/90ml (Optional)	Heating Module	Optional
Stirring Speed	20-25rpm	Net Weight	650kg
Canister Size	12x4.3L+84x1.25L	Rated Power	Standard: 520W Heating: 2.2kW
No. of Canisters	Up to 96	Power Supply	220V/110V 50Hz/60Hz

SANTINT • CHINA

Add: Feilong Road, Xingyang, Zhengzhou, China
Email: info@santint.com

SANTINT • HOLLAND

Add: Gieterij 28, 2211 XK Noordwijkerhout, The Netherlands
Email: sales@santint-europe.com

SANTINT • POLAND

Add:43 Szyszkowa Street, 02-285 Warsaw, Poland
Email:albert@santintpoland.com

SANTINT • U.S.A

Add: 2000 Bloomingdale Road, Suite 205, Glendale Heights,IL 60139, U.S.A
Email: info@santintusa.com

SANTINT • INDIA

Add: H.No.692, Gala No.04, Print World Industrial Complex, Bhatale, Vehele Village, Opposite Balaji Compound, Bhiwandi, Maharashtra – 421302
Email: nick@santint.com

SANTINT• BRASIL

Add: Av.Rosa Kasinski, 1109, G29 Capuava,Mauá, SP - Brasil CEP 09380-128
Email: marcos@santint.com

WELCOME TO AUTOMATIC CAR-REFINISH TINTING ERA



High Return · Simple Maintenance · High Efficiency

Automatic Dispenser AC100


HOW TO TINT




1. Spectrophotometer Reading



2. Formula Creating or Selecting



3. Automatic Dispensing




4. Color Comparing

OTHER FEATURES



Heating (Optional)
Keep toners in an environment of 8-15 °C.

Low Maintenance Nozzle
100% recirculation technology. Timed recirculation makes the colorant noncondensing and prevents the nozzle from dryness and blockage & colorant from deterioration.



Repeatable Accuracy
Minimum Shot : 1/2000Y(0.015ml) with one-time calibration.



Clean Tinting Area
No more paint spillage.



Automatic Stirring
To prevent sedimentation of the toners.



Toners Last Long
Single direction valve + sealing ring effectively prevent toners from volatilizing.

ROAMING INTO THE NEW ERA TO

Save labor cost
Increase efficiency
Eliminate mistints

