



Magical Angle Impact Wrench

1/2" Square Drive YU-RA4002T



Freely Workable In Any Tough Space!!

Work Torque: 332 ft.lb (450 Nm) / Max. Torque: 369 ft.lb (500 Nm)

Bolt Breakaway Torque: 966 ft.lb (1310 Nm)


Twin Hammer Mechanism

Durable, less vibration, excellent balance and no reaction force. Ultra short length **85mm** only.



120° Nano Flex Impact Head

The head can 60 degree flex forward & backward respectively. Freely reach to the target bolt even in confined, restrained space.



"Double-Air-Intake" Motor

By increased air flow can largely deliver powerful output.



Innovative Mechanism

Tubeless Dual Air Channel

Air flows smoothly and sufficiently even though rotating the handle and motor housing.




360° Free Swivel Handle

For optimal handling, the Handle or Trigger is adjustable allowing operation in any position.




Patented Technology „Double Air Intake“

Redesign air motor construction to Double-Air-Intake and Double-Air-Exhaust, in tiny motor space significantly generate huge power by largely and rapidly increasing air intake and air exhaust.



Air-Intake Normal Type



Double Air Intake

Variable Speed Trigger

Ensure the Anvil working steadily, prevent bolts from damage.

Aluminum Housing

Aluminum housing gives the Hammer & Motor a very rugged & robust protection.

Cold Insulated 360° Swivel Handle

Plastic & ergonomic design for lightweight, anti-slip, better grip and no sweat on handle operation. 360° swivel can reach to the trigger easily.

Application

Mainly aim for working in confined space with obstacles, like gearbox, engine, transmission, farming cultivator and so on. **Freely workable in any tough space!!**



Low Sound Level

Hidden muffler can greatly decrease working noise.

Anti-loose Angle Regulator

With the anti-loose bolt, the impact head can adjust the angle but wouldn't flex casually in working.



Specification

| | |
|------------------|------------------------------|
| Model No. | YU-RA4002T |
| Hammer Mechanism | Twin Hammer |
| Square Drive | 1/2" |
| Bolt Capacity | 1/2" (13 mm) |
| Working Torque | 332 FT-LB (450 N-m) |
| Max. Torque | 369 FT-LB (500 N-m) |
| Breakaway Torque | 966 FT-LB (1310 N-m) |
| Free Speed | 8,000 R.P.M. |
| Air Consumption | 4 CFM (28scfm, 113.3 L/min.) |
| Air Inlet | 1/4" |
| Air Pressure | 90 PSI |
| Air Hose | 3/8" (10 mm) |
| Overall Length | 85 mm |
| Net Weight | 1.336 kg (2.94 lb) |
| Sound Pressure | 90.1 dB(A) (Load) |

Patent No. & Country

| | |
|--------|---|
| China | ZL 2017 1 0547151.2 ZL 2017 3 0029100.1 ZL 2019 3 0631791.1 |
| Europe | 3351723 |
| Taiwan | M541520, D185042 I711511, D204376 |
| USA | US 10,677,060 B2 |



Yueh-Chi Enterprise Co., Ltd.

www.scorpiotool.com.tw

sales@scorpiotool.com.tw