

AHD/ TVI



Specification	CER48M	CER55M	CEC51M	CEC57M
Image Sensor	1/3" CMOS	1/3" CMOS	1/3" CMOS	1/4" CMOS
Resolution	1920x1080	1280x720	1280x960	1280x720
FOV	H133°/V72°/D150°	H135°/V85°/D160°	H180°/V138°/D220°	H180°/V110°/D200°
Min. Illumination	≥ 0.5 Lux @ 3M	0 Lux with IR @ 8M	≥ 0.5 Lux @ 3M	≥ 0.5 Lux @ 3M
IP Level	IP 69K	IP 69K	IP 69K	IP 69K
Working Temp.	- 30°C ~ +75°C	- 30°C ~ +80°C	- 30°C ~ +85°C	- 40°C ~ +80°C
MIC	—	V	—	—
WDR	V	—	V	V
Dimension (W/H/D)	37/27/30mm	34/38/38mm	23/23/36mm	23/23/34.2mm

CVBS



Specification	CER44M	CEC39M	CER32M	CES12M
Image Sensor	1/3" CMOS	1/4" CMOS	1/4" CMOS	1/4" CMOS
Resolution	720x480	720x480	720x480	720x480
FOV	H135°/V80°/D155°	H155°/V115°/D190°	H123°/V95°/D154°	H123°/V95°/D154°
Min. Illumination	≥ 0.5 Lux @ 3M	≥ 0.5 Lux @ 3M	0Lux with IR	0.5 Lux at F2.0
IP Level	IP 69K	IP 67	IP 68	IP 68
Working Temp.	- 30°C ~ +75°C	- 20°C ~ +70°C	- 30°C ~ +70°C	- 30°C ~ +70°C
MIC	—	—	V	—
Dimension (W/H/D)	37/27/33mm	23.5/23.2/23.5mm	27/27/35mm	27/27/28mm