



SMF BATTERY



»Higher Cold Cranking Start Up »Maximum Reserve Capacity
»Extreme Durability »Absolute Safety & Convenience

SILVER X-TREME

TOUGH, HIGH VOLTAGE



JIS PRODUCT SPECIFICATION

Sealed Maintenance Free Automotive Battery						BATTERY DIMENSION (mm)				Weight		10 pallets packing		
Model name (JIS)	Capacity (c-20)	Number of plate	CCA (IEC)	RC	Base hold down	L	W	H	TH	NW. KGS.	GW. KGS.	Q'ty per Level (pcs.)	Level /Pallet	Q'ty (pcs.) /Pallet
40B19R (L)	30	8	240	45	no	187	127	199.5	222	8.90	9.10	40	5	200
44B19R (L)	35	10	330	52	no	187	127	199.5	222	10.00	10.20	40	5	200
48B19R (L)	40	11	370	56	no	187	127	199.5	222	10.35	10.68	40	5	200
46B24R (L)	38	10	330	52	no	236	129	199.5	222	11.40	11.70	32	5	160
60B24R (L)	45	12	400	75	no	236	129	199.5	222	12.20	12.50	32	5	160
64B24R (L)	48	13	460	80	no	236	129	199.5	222	12.70	13.00	32	5	160
75D23R (L)	60	11	500	99	B7	231	173	202.5	222	15.37	15.67	24	5	120
85D23R (L)	65	12	580	118	B7	231	173	202.5	222	16.10	16.40	24	5	120
55D26R (L)	50	10	400	85	B7	257	173	202.5	222	15.70	16.00	24	5	120
75D26R (L)	65	12	550	100	B7	257	173	202.5	222	16.90	17.20	24	5	120
80D26R (L)	70	13	580	120	B7	257	173	202.5	222	17.60	17.90	24	5	120
90D26R (L)	75	14	600	125	B7	257	173	202.5	222	18.10	18.40	24	5	120
75D31R (L)	75	14	600	130	B7	303	173	202.5	222	19.90	20.20	18	6	108
95D31R (L)	80	15	660	140	B7	303	173	202.5	222	20.50	20.90	18	6	108
105D31R (L)	85	16	670	140	B7	303	173	202.5	222	20.80	21.20	18	6	108
115D31R (L)	90	18	750	155	B7	303	173	202.5	222	22.00	22.50	18	6	108

DIN PRODUCT SPECIFICATION

Sealed Maintenance Free Automotive Battery						BATTERY DIMENSION (mm)				Weight		10 pallets packing		
Model name (DIN)	Capacity (c-20)	Number of plate	CCA (IEC)	RC	Base hold down	L	W	H	TH	NW. KGS.	GW. KGS.	Q'ty per Level (pcs.)	Level /Pallet	Q'ty (pcs.) /Pallet
LN1-54459	44	9	400	80	B13	207	175	190	190	13.2	13.5	24	6	144
LN2-55559	55	12	480	90	B13	242	175	190	190	14.4	14.7	24	6	144
LN2-55565	55	12	480	90	B13	242	175	190	190	14.4	14.7	24	6	144
LN2-56219	62	13	540	100	B13	242	175	190	190	15.0	15.3	24	6	144
LN2-56220	62	13	540	100	B13	242	175	190	190	15.0	15.3	24	6	144
LN3-56633	66	14	540	113	B13	278	175	190	190	16.9	17.2	18	7	126
LN3-56638	66	14	540	113	B13	278	175	190	190	16.9	17.2	18	7	126
LN3-57219	72	15	610	130	B13	278	175	190	190	17.2	17.5	18	7	126
LN3-57220	72	15	610	130	B13	278	175	190	190	17.2	17.5	18	7	126
LN3-57412	74	16	680	140	B13	278	175	190	190	17.9	18.2	18	7	126
LN3-57413	74	16	680	140	B13	278	175	190	190	17.9	18.2	18	7	126
LN5-58821	88	18	680	155	B13	353	175	190	190	22.1	22.5	18	5	90
LN5-58827	88	18	680	155	B13	353	175	190	190	22.1	22.5	18	5	90
LN5-59218	92	19	720	155	B13	353	175	190	190	22.9	23.3	18	5	90
LN5-60038	100	21	850	170	B13	353	175	190	190	23.5	23.9	18	5	90

