

AW050JTH (Anvil Changeable Version)


1/2" Composite Air Impact Wrench

- ### Features

 - Mechanism: Twin Hammer
 - Highest durable Japanese steel anvil
 - M l c f _ l b m n c p _ r g m l d m p D m p u _ p b \$ P c t c p q c
 - Forward & Reverse : 1 n m q g r g m l d m p c _ a f q g b c
 - J g e f r u c i g h t w i t h c o m p o s i t e h o u s i n g
 - Handle exhaust
 - Powerful torque with Low noise (muffler option)

Patent

Anvil Changeable 1/2" and 3/8"



Other APACH Made Accessories Changeable



Applications

Automotive

Industry Assembling Line

Agriculture Machine

Motorcycle

Tool Specifications

	Square Drive	Bolt Capacity	Avg/Air Con.	Air Inlet	Air Pressures	Hose Size I.D.	Working Torque	Max Torque 10 Sec.	Free Speed	Vibration	Sound Pressure Level	Overall Length	Net Weight
AW050ITH	1/2"		5 CFM	1/4"	6.2 Bar	3/8"	500 FT-LB	650 FT-LB	8000 RPM	----	----	127 mm	1.43 KG
			142 L/Min		90 psi		770 N.m.	881 N.m.				5"	3.37 LB

APACH INDUSTRIAL CO., LTD.
 176 Industrial 9th Rd., Tali Dist., Taichung City, Taiwan 41208
 Tel +886 4 2271 2835 Fax +886 4 2271 4840
 www.apach-tools.com info@apach.com.tw



AW070ETH(Anvil Changeable Version)

1/2" Composite Air Impact Wrench



Features

- Mechanism: Twin Hammer
- Highest durable Japanese steel anvil
- M l c f _ l b m n c p _ r g m l d m p D m p u _ p b \$ P c t c p q c
- Forward & Reverse : 1 n m q g r g m l d m p c _ a f q q b c
- J g e f r u c i g h t w i t h c o m p o s i t e h o u s i n g
- Handle exhaust
- Powerful torque with Low noise (muffler option)
- 2 Patents introduced on the right side →

Patent 1

Experience Easy One-Handed Operation




Use Your Forefinger to Push back



Use Your Thumb to Push up

Patent 2

Anvil Changeable 1/2" and 3/8" & Other APACH Made Accessories



Short Bits



Short Sockets



1/2" Anvil



3/8" Anvil



Bit Holder



Extension Bar

Tool Specifications

	Square Drive	Bolt Capacity	Avg/Air Con.	Air Inlet	Air Pressures	Hose Size I.D.	Working Torque	Max Torque 10 Sec.	Breakaway Torque 15Sec.	Free Speed	Overall Length	Net Weight
AW070DTH	1/2"		5.48 CFM	1/4"	6.2 Bar	3/8"	650 FT-LB	800 FT-LB	1500 FT-LB	8500 RPM	159 mm	2.2 KG
			155 L/Min		90 psi		881 N.m.	1085 N.m.	2033 N.m.		6.26"	4.50 LB

APACH INDUSTRIAL CO., LTD.
 176 Industrial 9th Rd., Tali Dist., Taichung City, Taiwan 41208
 Tel +886 4 2271 2835 Fax +886 4 2271 4840
www.apach-tools.com info@apach.com.tw



AWARDED PRODUCT

AW050H

14mm 超短嵌入式小鋼炮

14mm Super Stubby Air Impact Wrench

Jumbo Hammer



Anvil Changeable: 3/8" Dr. & 1/2" Dr.
傳動軸轉接頭: 3/8"Dr. & 1/2"Dr.



**Super Short
Special Impact Socket Design**
超短特殊套筒 13, 17, 19, 21mm



Magnetic Design: Super Short Bit Attachable
內附磁鐵可直接吸附bit使用



**Extension Bar Attached to
Increase Length Easily**
延長桿增加兩倍用途



8 & 10 Bit Holder Attachable
8 & 10mm套筒內附磁鐵可裝bit



Side Exhaust

傳動尺寸	Square Drive	: 1/2"
螺栓規格	Bolt Capacity	: 5/8" (M16)
耗氣量	Avg/ Air Con.	: 4.0 CFM (113 L/min)
進氣接頭	Air Inlet	: 1/4"
進氣壓力	Air Pressure	: 90 PSI (6.2 Bar)
風管內徑	Hose Size I.D.	: 3/8"
工作扭力	Working Torque	: 400 FT-LB / 542 N.m. (5 Sec.)
最大扭力	Max. Torque	: 600 FT-LB / 813 N.m.
空轉轉速	Free Speed	: 9000 RPM
震動值	Vibration	: 11.6 m/s ²
噪音值	Sound Pressure	: 96.5 DbA
工具長度	Overall Length	: 86 mm (3.38")
工具重量	Net Weight	: 1.35 Kg (2.98 LB)
包裝	Packing	: 6 Sets/15.55Kg/16.60kg/1.3'

- 單錘結構
- 耐磨耗傳動軸
- 握把下排氣
- 單手操控正反轉與變速(各三速)。專利嵌入式裝置
- 專利創新型內凹六邊形傳動軸, 以求多功能運用:
 - 可裝上特殊短套筒 (17, 19, 21mm) 以利達到最短距離
 - 可裝上 1/2" 或 3/8" 傳動軸, 配合傳統套筒作使用
 - 8 & 10mm 套筒內附磁鐵可吸附bit
 - 內附磁鐵。可裝上 14mm bit, torx, 使用範圍廣泛同時達到短距離效果
- 機構縮短至 3.38", 小巧輕量符合人體工學, 可降低施工空間的限制
- 高扭力, 低噪音(可加裝消音器)

Patent



- Mechanism: Jumbo Hammer
- Highest durable Japanese steel anvil
- Handle exhaust
- One hand operation for Forward & Reverse : 3 positions for each side
- Replaceable anvil design for multiple functions:
 - Impact socket (17, 19, 21mm) & Extension bar: 14mm
 - Adapter anvil of 3/8" Dr. & 1/2" Dr.
 - Bit holder : 8 & 10mm
 - H14 & T60 (magnetic design)
- Short Length: only 3.38" allows to easily access in cramped spaces
- Powerful torque with low noise (muffler option)