

AW120CTT/ AW120DTH

3/4" Composite Air Impact Wrench



Features

- Mechanism: Twin Hammer
- Highest durable Japanese steel anvil
- Forward & Reverse : 2 baef[a` XadV&LZ e[VW
- >[YZfi Vight with composite housing
- Upon exhaust-AW120CTT/ Handle exhaust-AW120DTH
- Hose fitting can swirl
- Left / Right handle available
- Inside or outside trigger available

Applications



Automotive



Industry
Assembling Line



Agriculture
Machine

Tool Specifications

	Square Drive	Bolt Capacity	Avg/Air Con.	Air Inlet	Air Pressures	Hose Size I.D.	Working Torque	Max Torque 10 Sec.	Free Speed	Vibration	Sound Pressure Level	Overall Length	Net Weight
AW120CTT	3/4"		7.7 CFM 218 L/Min	3/8"	6.2 Bar 90 psi	1/2"	1200 FT-LB 1627 N.m.	1500 FT-LB 2034 N.m.	7500 RPM	---	---	313 mm 12.33"	3.39 KG 7.47 LB
AW120DTH			7.7 CFM 218 L/Min				1200 FT-LB 1627 N.m.	1500 FT-LB 2034 N.m.	7500 RPM	---	---	217 mm 8.55"	3.28 KG 7.23 LB

APACH INDUSTRIAL CO., LTD.

176 Industrial 9th Rd., Tali Dist., Taichung City, Taiwan 41208

Tel +886 4 2271 2835 Fax +886 4 2271 4840

www.apach-tools.com info@apach.com.tw



AW050ITH/ AW070ITH

1/2" Composite Air Impact Wrench



Features

- Mechanism: Twin Hammer / pin-less optional
- Highest durable Japanese steel anvil
- A` VZS` V abVsf[a` XadBad ScV` DMVdW
- Forward & Reverse : %baef[a` XadVUZ e[VW
- >[YZfi Vght with composite housing
- Handle exhaust
- Powerful torque with Low noise (muffler option)

Applications



Automotive



Industry
Assembling Line



Agriculture
Machine



Motorcycle

Tool Specifications

	Square Drive	Bolt Capacity	Avg/Air Con.	Air Inlet	Air Pressures	Hose Size I.D.	Working Torque	Max Torque 10 Sec.	Free Speed	Vibration	Sound Pressure Level	Overall Length	Net Weight
AW050ITH	1/2"		5 CFM	1/4"	6.2 Bar	3/8"	500 FT-LB	550 FT-LB	9000 RPM	----	----	127 mm	1.53 KG
			142 L/Min		90 psi		679 N.m.	750 N.m.				5"	3.37 LB
AW070ITH			5.48 CFM				650 FT-LB	730 FT-LB	8500 RPM	----	----	159 mm	2.04 KG
			155 L/Min				870 N.m.	985 N.m.				6.26"	4.50 LB

APACH INDUSTRIAL CO., LTD.

176 Industrial 9th Rd., Tali Dist., Taichung City, Taiwan 41208

Tel +886 4 2271 2835 Fax +886 4 2271 4840

www.apach-tools.com info@apach.com.tw



Schonhammer

Five Types of Rubber / Metal Heads Replaceable
Patented Locking Design Ensure User's Safety



Features

- Hammer Heads Replaceable (Two Sides) – Five Types of Hammer Heads
- Get One Hammer Instead of Buying Several Traditional Hammers
- Traditional Hammers like Mallet Rubber, Mallet Soft Faced, Dead Blow, Mallet Copper & Rawhide Could be Replaced
- Patented Special Design: Locking System – Make Working Environment Safer!
- Well Balanced Handle
- Weather Resistant and Easy to Clean
- Total weight: 650g and overall length: 30cm
- Applicable to Various Environment According to Different Heads



Hardness Comparison for Each Hammer Heads



Soft-Metal
Brass



Very Hard
SuperPlastic



Very Hard
Nylon



Medium
Hard Plastic



Medium
Soft TPE

More Heaving Duty Working

More Careful Extra Careful Working

Comparing to Other Similar Hammers

- ☑ Heads will not get loosening and come off while using
 - ◆ Locking system ensure user's safety
- ☑ Screw thread will not get damaged Easily
 - ◆ Hammer and thread are one-piece design
- ☑ Rubber heads may not be twisted under pressure
- ☑ Easy to change heads



APACH INDUSTRIAL CO., LTD.

176 Industrial 9th Rd., Tali Dist., Taichung City, Taiwan

41208 Tel +886 4 2271 2835 Fax +886 4 2271 4840

www.apach-tools.com info@apach.com.tw

