

****Please note that this series are not covered with warranty****

■ Heavy Duty Air Hammer Kit

AH-003-KIT
1 PCS ...AIR HAMMER (AH-003)
1 PCS...STANDARD SPRING RETAINER
5 PCS...CHISEL SET 5" (ROUND OR HEX. SHANK)
1 PCS...MINI OILER
1 PCS...OIL POT
1 PCS...NIPPLE
1 PCS...BLOW CASE

HEAVY DUTY AIR HAMMER					
INFORMATION	AIR PRESSURE	AIR CONSUMPTION	BLOWS PER MINUTE	HOSE SIZE	AIR INLET(NPT)
AH-003	90 psi	4 cfm	3200	3/8"	1/4"

■ Mini Die Grinder Kit

DG-110-KIT
1 PCS ...MINI DIE GRINDER (DG-110)
2 PCS... COLLECT (1/4", 1/8") OR (6mm, 3mm)
2 PCS...SPANNER
5 PCS...MOUNTED STONE WITH 1/8" SHANK OR 3mm SHANK
5 PCS...MOUNTED STONE WITH 1/4" SHANK OR 6mm SHANK
1 PCS...PLASTIC CARRYING CASE

INFORMATION	SPEED	CAPACITY	AIR PRESSURE	AIR CONSUMPTION	AIR INLET(NPT)	HOSE SIZE	OVERALL LENGTH	WEIGHT	COLLET SIZE
DG-110	20000 rpm	1/4"	90 psi	17 cfm	1/4"	3/8"	6-5/8"	0.57 KG	1/4", 1/8", 6mm, 3mm

■ Air Hose Reel

MODEL	DESCRIPTION
PUR-1012M-PA	AIR HOSE 6.5mm*10mm*12M
PUR-1210M-PA	AIR HOSE 8mm*12mm*10M
PUR-1212M-PA	AIR HOSE 8mm*12mm*12M
PUR-1215M-PA	AIR HOSE 8mm*12mm*15M
PUR-1410M-PA	AIR HOSE 10mm*14mm*10M
PUR-1415M-PA	AIR HOSE 10mm*14mm*15M

MODEL	DESCRIPTION
HRSC-25PU15M-JP	AIR HOSE REEL IN STEEL CASE 5/16**50ft PU BRAIDED HOSE (Japan Type)
HRSC-25PU15M-US	AIR HOSE REEL IN STEEL CASE 5/16**50ft PU BRAIDED HOSE (US Type)
HRSC-25PU15M-EU	AIR HOSE REEL IN STEEL CASE 5/16**50ft PU BRAIDED HOSE (EU Type)
HCHR-0812PU30M-JP	HAND CRANK HOSE REEL, PU BRAIDED HOSE 8*12mm*30M (Japan Type)
HCHR-0812PU30M-US	HAND CRANK HOSE REEL, PU BRAIDED HOSE 8*12mm*30M (US Type)
HCHR-0812PU30M-EU	HAND CRANK HOSE REEL, PU BRAIDED HOSE 8*12mm*30M (EU Type)
HCHR-0812FZ30M-JP	±40°CHAND CRANK HOSE REEL, PU BRAIDED HOSE 8*12mm*30M (Japan Type)
HCHR-0812FZ30M-EU	±40°CHAND CRANK HOSE REEL, PU BRAIDED HOSE 8*12mm*30M (EU Type)

■ Tundra Soft Hose

MODEL	DESCRIPTION
FZR-081210-EU	8*12MM*10M WITH S31-25STD/PTD& BLUE COVERS
FZR-081215-EU	8*12MM*15M WITH S31-25STD/PTD& BLUE COVERS
FZR-081208-EU	8*12MM*8M WITH S31-25STD/PTD&BLUE COVERS
FZR-081212-EU	8*12MM*12M WITH S31-25STD/PTD&BLUE COVERS
FZR-061010-JP	6.5*10.7MM*10M WITH 20STD/PTD&BLUE COVERS
FZR-061015-JP	6.5*10.7MM*15M WITH 20STD/PTD&BLUE COVERS
FZR-061008-JP	6.5*10.7MM*8M WITH 20STD/PTD&BLUE COVERS
FZR-061012-JP	6.5*10.7MM*12M WITH 20STD/PTD&BLUE COVERS

■ Quick Connector

MODEL	DESCRIPTION
0990125-US	3/8" Hose Male Quick Connector
0990127-US	1/4" NPT Female Quick Connector
0990128-US	3/8" NPT Female Quick Connector
0990130-US	1/4" Hose Male Quick Connector
0990132-US	3/8" Hose Male Quick Connector
0990132-S	3/8" Male Quick Connector (One Touch)
0990133-S	1/2" Male Quick Connector (One Touch)
0990172-S	1/4" Female Quick Connector (One Touch)
0990128-S	3/8" Female Quick Connector (One Touch)
0990127	1/4" PT Female Quick Connector
0990128	3/8" PT Female Quick Connector
0990129	1/2" PT Female Quick Connector



DG-110-KIT

AH-003-KIT

DG-110



HRSC-25PU15M-EU



HCHR-0812PU30M-US



FZR-081210-EU



FZR-061015-JP



EU Type

US Type

JP Type

■ ACCESSORIES - Socket Set/ Sockets



1/2" Sockets (CR-MO)	
Model	Description
SK041-27M	1/2" 27MM 43L CR-MO IMPACT SOCKET
SK041-30M	1/2" 30MM 48L CR-MO IMPACT SOCKET
SK041-32M	1/2" 32MM 48L CR-MO IMPACT SOCKET
SK043-30M	1/2"DR.30MM 78L CR-MO DEEP IMPACT SOCKET
SK043-32M	1/2"DR.32MM 78L CR-MO DEEP IMPACT SOCKET
SK043-36M	1/2"DR.36MM 78L CR-MO DEEP IMPACT SOCKET

1" Sockets (CR-MO)	
Model	Description
SK081-27M	1"DR.27MM 58L CR-MO IMP.SKT
SK081-30M	1"DR.30MM 60L CR-MO IMP.SKT
SK081-32M	1"DR.32MM 61L CR-MO IMP.SKT
SK081-33M	1"DR.33MM 61L CR-MO IMP.SKT
SK081-36M	1"DR.36MM 65L CR-MO IMP.SKT
SK083-33M	1"DR.33MM 90L CR-MO DEEP IMP.SKT

1/2" Double Hexagon Sockets	
Model	Description
SK04F-17M063	1/2" Double Hexagon DR. 17*19mm 28D1 30D2 63L CR-MO
SK04F-19M063	1/2" Double Hexagon DR. 19*21mm 28D1 30D2 63L CR-MO
SK04F-12S07613	1/2" Double Hexagon DR. 3/4*13/16 28D1 28D2 76L CR-MO
SK04F-19M07613	1/2" Double Hexagon DR. 19*21mm 28D1 28D2 76L CR-MO

■ We provide socket size from 1/4" ~2" (Standard and deep socket are all available)

AIRBOSS AIR TOOLS CO., LTD.

📍 No.1688,Zhongke Rd., Xitun Dist., Taichung City,Taiwan

☎ +886-4-2451-1800

☎ +886-4-2451-2388

✉ airboss@twairboss.com

🌐 www.twairboss.com

📘 www.facebook.com/twairboss

🐦 twitter.com/twairboss



PROFESSIONAL AUTO REPAIR TOOL

BASIC NEEDS FOR YOUR RIDE



www.twairboss.com

■ AIR IMPACT WRENCH



INFORMATION

Information		Bolt Capacity	Clutch Type	Free Speed	Suitable Torque		Max Torque		Overall Length	Net Weight		Air Consumption	Air Inlet	Air Hose	Air Pressure
Model	Size	mm	Mechanism	r.p.m.	ft-lb	N.M.	ft-lb	N.M.	mm	lbs	kg	m³/min	PT(in.)	mm	kg/cm²
AB-162	1/2"	16	Twin Hammer	8000	25-324	34-440	450	610	171	5.7	2.6	0.3	1/4"	6.4	6.3
AB-162L	1/2"	16	Twin Hammer	8000	25-324	34-440	450	610	200	6.1	2.8	0.3	1/4"	6.4	6.3
AB-170P	1/2"	15	Twin Hammer	7600	25-225	34-306	375	510	122	3.1	1.4	0.3	1/4"	6.4	6.3
	3/8"								122	3.1	1.4				
AB-190P	1/2"	19	Twin Hammer	7400	27-387	36-525	627	850	145	4.9	2.2	0.3	1/4"	6.4	6.3
AB-190PL	1/2"	19	Twin Hammer	7400	27-387	36-525	627	850	175	5.1	2.3	0.3	1/4"	6.4	6.3
AB-200P	1/2"	19	Twin Hammer	6800	50-596	68-808	1372	1860	165	5.8	2.65	0.3	1/4"	6.4	6.3
AB-200PL	1/2"	19	Twin Hammer	6800	50-596	68-808	1372	1860	198	6.4	2.75	0.3	1/4"	6.4	6.3
AB-200P	3/4"	19	Twin Hammer	6800	50-596	68-808	1372	1860	170	5.9	2.7	0.3	1/4"	6.4	6.3
AB-230P	3/4"	23	Twin Hammer	6500	295-649	400-800	812	1100	192	8.2	3.7	0.4	3/8"	9.5	6.3
AB-230PL	3/4"	23	Twin Hammer	6500	265-584	360-720	738	1000	317	9.3	4.2	0.4	3/8"	9.5	6.3
AB-300P	3/4"	30	Twin Hammer	4800	332-885	450-1200	1253	1700	212	12.1	5.5	0.5	3/8"	9.5	6.3
	1"								218	12.3	5.6				
AB-300PL	3/4"	30	Twin Hammer	4800	299-796	405-1080	1127	1530	335	13.7	6.2	0.5	3/8"	9.5	6.3

■ The above data is for reference only, please refer to the actual measurement.

■ AIR IMPACT WRENCH



■ Inner Trigger for Safety Purpose

INFORMATION


Information		Bolt Capacity	Clutch Type	Free Speed	Suitable Torque		Max Torque		Overall Length	Net Weight		Air Consumption	Air Inlet	Air Hose	Air Pressure
Model	Size	mm	Mechanism	r.p.m.	ft-lb	N.M.	ft-lb	N.M.	mm	lbs	kg	m³/min	PT(in.)	mm	kg/cm²
AB-412P	1"	41	Swing Hammer	4200	649-1416	880-1920	1771	2400	284	21.4	9.7	0.6	1/2"	12.7	6.3
AB-412PL	1"	41	Swing Hammer	4200	649-1416	880-1920	1771	2400	427	24.2	11.0	0.6	1/2"	12.7	6.3
AB-562P	1"	56	Swing Hammer	3000	1328-1948	1800-2640	2508	3400	319	30.4	14.0	0.6	1/2"	12.7	6.3
AB-562PL	1"	56	Swing Hammer	3000	1328-1948	1800-2640	2508	3400	520	32.3	14.7	0.6	1/2"	12.7	6.3
AB-412GS	1"	41	Swing Hammer	4200	649-1416	880-1920	1771	2400	392	21.3	9.7	0.6	1/2"	12.7	6.3
AB-412GL	1"	41	Swing Hammer	4200	649-1416	880-1920	1771	2400	525	24.5	11.1	0.6	1/2"	12.7	6.3
AB-562GS	1"	56	Swing Hammer	3000	1328-1948	1800-2640	2508	3400	434	30.5	13.9	0.6	1/2"	12.7	6.3
AB-562GL	1"	56	Swing Hammer	3000	1328-1948	1800-2640	2508	3400	614	34.2	15.5	0.6	1/2"	12.7	6.3

■ The above data is for reference only, please refer to the actual measurement.

■ Roller Cabinet

Model	Number Of Drawers	Overall W x D x H	Overall Of Caster W x D x H	Drawers Size W x D x H	Caster	Net Weight
		mm	mm	mm		
DRW26-6XL	6	670 x 460 x 812	670 x 460 x 960	576 x 380 x 75 x 3 unit 576 x 380 x 154 x 3 unit	5" x 1-1/4" (2 fixed +2 swivel)	62.7KG

Option	Description
DRW-EA-04	Workpanel for W26 series
DRW-EA-05	Side panel for W26 & ET series
DRW-EA-07	Top tray for W26 series
DRW-AC-MAT01	Cabinet top liner for W26 series
DRW-AC-2SH	2" Single hook
DRW-AC-2DH	2" Double hook
DRW-AC-4SH	4" Single hook
DRW-AC-4DH	4" Double hook



DRW-EA-04



DRW-EA-05



DRW-EA-07



DRW-AC-MAT01



DRW-AC-2SH



DRW-AC-2DH



DRW-AC-4SH



DRW-AC-4DH

DRW26-6XL

■ Air Sander - SA Series



SA-101-5



SA-101-6



SA-122

Information	Pad Size		Orbital Diameter		Free Speed	Overall Length	Net Weight		Air Consumption	Air Inlet	Air Hose	Air Pressure
Model	mm	in	mm	in	r.p.m	mm	lbs	kg	m³/min	PT(in.)	mm	kg/cm²
SA-101-5	127	5"	5	3/16"	10000	180	1.7	0.8	0.3	1/4"	9.5	6.3
SA-101-6	152	6"	5	3/16"	10000	180	1.7	0.8	0.3	1/4"	9.5	6.3
SA-122	152	6"	---	---	10000	240	4.3	1.9	0.6	1/4"	9.5	6.3

■ Air Belt Sander



BS-113



BS-102



SE-101



TB-101



SH-105



RW-113



RW-114

Model	Belt Size	Belt speed	Wheel size		Sheet Capacity	Free Speed	Overall Length	Net Weight		Air Consumption	Air Inlet	Air Hose	Air Pressure
	mm	r.p.m	mm	in.	mm	r.p.m	mm	lbs	kg	m³/min	PT(in.)	mm	kg/cm²
BS-113	60 x 260	800	---	---	---	7000	170	2.4	1.1	0.3	1/4"	10	6.3
BS-102	10 x 330	1350	---	---	---	18000	280	1.8	0.8	0.2	1/4"	6.4	6.3
BS-103	20 x 520	2200	---	---	---	18000	350	2.2	1	0.3	1/4"	6.4	6.3
SE-101	---	---	102	4"	---	4000	200	2.1	1	0.2	1/4"	6.4	6.3
TB-101	---	---	12	½"	---	2500	210	2	0.9	0.3	1/4"	6.4	6.3
SH-105	---	---	---	---	1.2	2500	215	2.8	1.3	0.5	1/4"	10	6.3

Model	Driver Size		Bolt Capacity		Suitable Torque		Free Speed	Overall Length	Net Weight		Air Consumption	Air Inlet	Air Hose	Air Pressure
	mm	in.	mm	in.	ft-lb	N.m	r.p.m	mm	lbs	kg	m³/min	PT(in.)	mm	kg/cm²
RW-113	6	1/4"	6	1/4"	35	47.5	300	134	0.99	0.45	0.07	1/4"	10	6.3
RW-114	9	3/8"	9	3/8"	35	47.5	300	134	0.99	0.45	0.07	1/4"	10	6.3

■ The above data is for reference only, please refer to the actual measurement.