

DHC[®]

DHC SPECIALTY CORP.

Copyright[®] DHC Specialty Corporation. All rights reserved. **DHC[®]**, **MioPro[®]** & **EVERSMART[®]** are trademarks of DHC Specialty Corporation registered in Taiwan, China, Japan, Europe, U.S.A. and other countries. We continually work to improve the quality of our products. Therefore, product specifications, designs & packaging may change without notice.



*Taiwan Xizhi Factory
(Testers & Chargers)*



*China Shanghai Factory
(Cables, Wires &
Battery Accessories)*

Globally Superior Battery and Energy Management Solutions



Taiwan, Head Office
7Fl., No. 83, Chou Tzu St., Nei Hu District,
Taipei 11493, Taiwan

Taiwan, R&D and Manufacturing
8Fl., No. 308, Sec. 1, Datong Rd., Xizhi District,
New Taipei City 22146, Taiwan
Tel: +886-2-2641-7399
Fax: +886-2-2641-6218

China, Manufacturing
No. 8, Standard Building, Lane 669, Mintu Rd.,
Songjiang Area, Shanghai, China 201617
Tel: +86-21-5784-7403
Fax: +86-21-5784-7398

United States, Office
Johnson City, TN 37604
Tel: 423-646-6697
Fax: 423-283-7039

www.dhc.com.tw

EV Car Charger Cable

Specification

MODEL 3 CHARGER CABLE 240161

PHASE	CURRENT	PLUG STANDARD	POWER	LENGTH
1-Phase	16A	TYPE 2-TYPE 2	3.7KW	5M

MODEL 3 CHARGER CABLE 240321

PHASE	CURRENT	PLUG STANDARD	POWER	LENGTH
1-Phase	32A	TYPE 2-TYPE 2	7.4KW	5M



Specification

MODEL 3 CHARGER CABLE 240163

PHASE	CURRENT	PLUG STANDARD	POWER	LENGTH
3-Phase	16A	TYPE 2-TYPE 2	11KW	5M

MODEL 3 CHARGER CABLE 240323

PHASE	CURRENT	PLUG STANDARD	POWER	LENGTH
3-Phase	32A	TYPE 2-TYPE 2	22KW	5M

■ REQUIRE A 400V GRID AND ACOMPATIBLE CHARGER



FEATURES OF PRODUCT:

- Minimalist Design
- Dependable Material & Durability
- Broad Compatibility
- Outstanding Protective Features
- Portability



Choose a charger cable that suits your electric vehicle model and charging needs to ensure a safe and convenient charging experience.

“Charge Ahead, you EV, your way”



Battery Cables

Top Post Battery Cables

Part No.	Length	Wire Range Gauge / mm ²	Leads
TP4100	10"	4GA	0
TP4150	15"	4GA	0
TP4250L	25"	4GA	1
TP4320L	32"	4GA	1
TP4510L	51"	4GA	1
TP4720L	72"	4GA	1
TP35030	30cm	35mm ²	0
TP35041	41cm	35mm ²	0
TP35051	51cm	35mm ²	0
TP35061	61cm	35mm ²	0
TP35076	76cm	35mm ²	0
TP35081	81cm	35mm ²	0
TP35107	107cm	35mm ²	0
TP35127	127cm	35mm ²	0

Lead Free Top Post Battery Cables

Part No.	Length	Wire Range Gauge / mm ²	Leads
LFTP4100	10"	4GA	0
LFTP4150	15"	4GA	0
LFTP4250L	25"	4GA	1
LFTP4320L	32"	4GA	1
LFTP4510L	51"	4GA	1
LFTP4720L	72"	4GA	1

Side Terminal Battery Cables

Part No.	Length	Wire Range Gauge / mm ²	Leads
SP4350L	35"	4GA	1
SP4450L	45"	4GA	1

Lead Free Side Terminal Battery Cables

Part No.	Length	Wire Range Gauge / mm ²	Leads
LFSP4350L	35"	4GA	1
LFSP4450L	45"	4GA	1

Lead Free Lawn & Garden Battery Cables Lead Free Switch to Starter Battery Cables

Part No.	Length	Wire Range Gauge / mm ²	Leads
SS6190	19"	6GA	0
SS6490	49"	6GA	0
SS4240	24"	4GA	0
SS2510	51"	2GA	0

Angle Double Top Battery Cable

Part No.	Length	Wire Range Gauge / mm ²	Leads
ATP3525	25cm	35mm ²	0

Engine and Ground Strap

Part No.	Length	Wire Range Gauge / mm ²
GS413	13"	4GA
GS409	9"	4GA
EG408	8"	4GA
GS2530	30cm	25mm ²
GS2541	41cm	25mm ²
EG2525	25cm	25mm ²
EG2536	36cm	25mm ²

Battery Lug, Solid Copper Lug

Item No	GA.	Stud Hole
LS0838	8	3/8"
LS0814	8	1/4"
LS0810	8	#10
LS0614	6	1/4"
LS0638	6	3/8"
LS6516	6	5/16"
LS0412	4	1/2"
LS0414	4	1/4"
LS0438	4	3/8"
LS4516	4	5/16"
LS0212	2	1/2"
LS0238	2	3/8"
LS0112	1	1/2"
LS0138	1	3/8"
LS1516	1	5/16"
LS1012	1/0	1/2"
LS1038	1/0	3/8"
LS2012	2/0	1/2"
LS2058	2/0	5/8"
LS2516	2/0	5/16"
LS3012	3/0	1/2"
LS3038	3/0	3/8"
LS4012	4/0	1/2"
LS4038	4/0	3/8"

ITEM NO	GA.	Stud Hole
LSH1012	1/0	1/2"
LSH1038	1/0	3/8"
LSH2012	2/0	1/2"
LSH2038	2/0	3/8"
LSH3012	3/0	1/2"
LSH3038	3/0	3/8"
LSH4012	4/0	1/2"
LSH4038	4/0	3/8"

Heavy Duty Butt Splice Connector

ITEM NO	GA.
BUH10	1/0
BUH20	2/0
BUH30	3/0
BUH40	4/0

Primary wire

Spool



Blister Pack

Primary Wire				
Wire Range Gauge / mm ²	Card Length Blister Pack	Card Part No.	Spool Length	Spool Part No.
10 Gauge	7FT	PW100-7	100FT	PW100-100
12 Gauge	11FT	PW120-11	100FT	PW120-100
14 Gauge	17FT	PW140-17	100FT	PW140-100
16 Gauge	24FT	PW160-24	100FT	PW160-100
18 Gauge	33FT	PW180-33	100FT	PW180-100
0.75 mm ²	10M	PW0750-10	30M	PW0750-30
1.50 mm ²	10M	PW1500-10	30M	PW1500-30
2.50 mm ²	10M	PW2500-10	30M	PW2500-30
4.00 mm ²	4M	PW4000-4	30M	PW4000-30

Wire color: 0 Black, 1 Red, 2 White, 3 Brown, 4 Yellow, 5 Blue, 6 Green

Clamp



A1 A7 A11 A18 A20 A23



A31 A32 A34 A35 A36 A38

Booster Cables

Specification

Model No.	Specification
BC163032	16MM ² X 3.0M
BC253532	25MM ² X 3.5M
BC354532	35MM ² X 4.5M



Specification

Model No.	Specification
BC354534	35MM ² X 4.5M
BC505034	50MM ² X 5.0M
BC705034	70MM ² X 5.0M



Specification

Model No.	Specification
BC101001C	10Ga/10Feet (For Power sports Batteries)



EZ812 (8Ga / 12 Feet)

EVERSMART® Electronic Booster Cable

- No more worry which clamp goes where. Simply attach one end of cable clamps to one battery post and the other end of cable clamps to the other battery post. The polarity will be adjusted automatically and green indicator lights will be on to confirm proper hook-up and connection.
- No sparking
- For 12 Volt system only
US Patent : 6,262,492 B1
China Patent : ZL03200141. X



BC0425 (4Ga / 25 Feet)

BC0425 (4Ga / 25 Feet)

- Overall length 25ft. Including:
1pc : 20ft cables with heavy duty clamps and quick connector
1pc : 5ft cables with quick connector, includes protective cap
- Perfect for tow trucks or fork lifts



Battery Terminals



B101 (Lead)
B101A (Lead Free Alloy)



B102 (Lead)
B102A (Lead Free Alloy)



B104 (Lead)
B104A (Lead Free Alloy)



B106 (Lead)
B106A (Lead Free Alloy)



B107 (Lead)
B107A (Lead Free Alloy)



B1000 (Brass)



B4900 (Lead)



B5300 (Lead)



B5400 (Lead)



B5000 (Zinc Alloy)



B4000 (Brass)



B4600 (Brass)



B1012 (Lead)
B1012A (Lead Free Alloy)



B0422 (Lead)
B0422A (Lead Free Alloy)



B5100 (Brass)



B4400 (Brass)



B4500 (Brass)



B113 (Lead, Post Shims)



B105 (Lead)
B105A (Lead Free Alloy)



B4200 (Brass, Top post)



B4700 (Brass)



B4800 (Brass)



B1142 (Lead Free)



B1152 (Lead Free)



B4300 (Brass, Side post)



B4100 (Brass)



B0809 (Zinc Alloy)
B0809A (Lead Free Alloy)
B0809B (Brass): 16-35mm²



BT1011 (Zinc Alloy)



B108 (OEM Bolt)



202306 (Top post)
202307 (Side post)
2023067 (Universal)

Battery Accessories



Memory Saver



MS-7

7AH BATTERY
PROFESSIONAL AUTO COMPUTER
MEMORY SAVER

Battery capacity	7Ah
Dimension	L245 X W245 X H180 (mm)
Included Accessories	• 1 OBDII connector cable (build-in) • 1 cigarette plug cable • 1 AC charger
Features	• OBDII connector plugs directly into vehicles OBDII port. • Easy to read battery status LEDs indicate the internal battery power & charging status. • Accessory outlet supplies power for 2V DC accessories outfitted with an accessory plug. • 7Ah high capacity, rechargeable sealed lead acid battery. • Power on-off switch.

Battery Isolator



Model No.	Rating	Application
IS70	70Amp	For 1 Alternator, 2 Batteries
IS95	95Amp	
IS120	120Amp	
IS95C	95Amp	For 1 Alternator, 2 Batteries For Delco CS Series Alternators
IS120C	120Amp	

Features:

1. Let you run accessories in vehicle **without draining battery**.
2. Automatically charges auxiliary battery as you drive, never overcharge.
3. Self-contained electrical system converts alternator or generator to safe, efficient charger.
4. For all multi-battery systems.
5. Designed for negative alternator systems and batteries of the same nominal voltage.
6. Easy to follow step-by-step installation instruction.

Load Tester



500A2

500-Amp Carbon Pile Battery Load Tester

KEY SPEC

Battery Tests	12V Batteries
System Tests	12V Cranking/Charging System
Operating Range	Up To 1,000 CCA/SAE
Ture Load Capacity	500 Amps
Display	Analog Voltmeter and Ammeter
Additional Features	Temperature Compensated Pass/Fail Result Bands, Built-In Buzzer, UL Compliant



50113

100-Amp Battery Load Tester



50888

100-Amp Digital Controlled Battery Load and Charging System Tester



60113

125-Amp Battery Load Tester



60888

125-Amp Digital Controlled Battery Load and Charging System Tester

KEY SPEC

Model Feature	50113	60113	50888	60888
Battery Tests	6V, 12V Batteries		12V Batteries	
System Tests	12V Cranking/Charging System			
Operating Range	Up To 1,000 CCA/SAE			
Ture Load Capacity	100 Amps	125 Amps	100 Amps	125 Amps
Clamp-Cable Set	0.5m (approx. 1.6ft)	0.6m (approx. 2ft)	0.5m (approx. 1.6ft)	0.6m (approx. 2ft)
Display	Analog		3-Digit LED	
Additional Features	Asbestos Free		Auto Load Timer (10 sec), Polarity Check	

Battery Charger

www.dhc.com.tw

DHC

AEA/AEE1500

15-Amp Selectable Amperage Digital Battery Charger



KEY SPEC

Battery Types	12V Flooded, AGM Flat/Spiral, EFB, VRLA, GEL, Lithium (LFP)
Charge Capacity	7Ah - 200Ah
Maximum Sustained Output	Battery Charging Mode 15 Amps Power Supply Mode 15 Amps
Clamp-Cable Length	2m (approx. 6.5ft) Detachable
AC Cord/Input	1.9m (approx. 6.2ft) 110 - 240V 50/60Hz
Dimensions (LxWxH)	280 x 108 x 230 mm (approx. 11" x 4.3" x 9.1")

AEA/AEE400

4-Amp Digital Battery Charger/Maintainer



KEY SPEC

Battery Types	6V, 12V Flooded, AGM Flat/Spiral, EFB, VRLA, GEL 12V Lithium (LFP)
Charge Capacity	15Ah - 50Ah
Maximum Current	4 Amps
Clamp-Cable Length	1.9m (approx. 6.2ft) Detachable
AC Cord/Input	1.8m (approx. 6ft) 100 - 240V 50/60Hz
Dimensions (LxWxH)	173 x 90 x 46mm (approx. 6.8" x 3.5" x 1.8")

AEA/AEE1.2

1.2-Amp Digital Battery Charger/Maintainer



KEY SPEC

Battery Types	12V Flooded, AGM Flat/Spiral, EFB, VRLA, GEL
Charge Capacity	2Ah - 15Ah
Maximum Current	1.2 Amps
Clamp-Cable Length	1.9m (approx. 6.2ft) Detachable
AC Cord/Input	1.8m (approx. 6ft) 100 - 240V 50/60Hz
Dimensions (LxWxH)	132 x 74 x 48mm (approx. 5.2" x 3" x 1.9")