

奥泰新材优质喷涂、EDM 及灯用钼钽丝

Top Quality World Lowest Price Molybdenum Lanthania MoLa Wire for Thermal Spraying, Filament & EDM



1. 奥泰新材优质喷涂、EDM 及灯用钼钽丝化学成分

Top Quality World Lowest Price Molybdenum Lanthania MoLa Wires for Thermal Spraying, Filament & EDM Chemical Composition (wt%, max. for Impurities)

型号 Type	Fe	Ni	Al	Si	Ca	C	N	La ₂ O ₃	Mo
AMMo1	0.010	0.005	0.002	0.010	0.002	0.010	0.002	-	≥99.95
AMMoLa	0.010	0.005	0.002	0.010	0.002	0.010	0.002	0.2-0.6	余量 Balance

2. 奥泰新材优质喷涂、EDM 及灯用钼钽丝再结晶温度

Top Quality World Lowest Price Molybdenum Lanthania MoLa Wires for Thermal Spraying, Filament & EDM Molybdenum Wire Recrystallization Temperature

型号 Type	AMMo1	AMMoLa
再结晶温度 Molybdenum Wire Recrystallization Temperature	>1100°C	>1500°C

3. 奥泰新材优质喷涂、EDM 及灯用钼钽丝包装

Top Quality World Lowest Price Molybdenum Lanthania MoLa Wires for Thermal Spraying, Filament & EDM Packaging

AMTmetalTech finest diameter of Molybdenum or Lanthania MoLa Wire can be 0.02mm, black or white. Wire d0.8-1.6mm Packaging 12.5kg/Plastic Spool in Carton. 10kg, 15kg, 20kg/coil in Paper Drum at Coil D400-600mm for Wire d0.8-2.0mm or Coil D600-800mm for Wire d2.0-3.2mm. Specified Control Wire Tensile Strength, Elongation, Diameter Tolerance, Length are available.

4. 奥泰新材优质喷涂、EDM 及灯用钼钽丝应用

Top Quality World Lowest Price Molybdenum Lanthania MoLa Wires for Thermal Spraying, Filament & EDM Application

热喷涂马达、涡轮、齿轮、轴等高性能零件用钼丝，车灯用钼丝，线切割钼丝。

Molybdenum Lanthania MoLa Wire for Filament / EDM / Thermal Spraying quality parts in the Motor, Turbine, Gear, Shaft etc. of good wear resistance.

其他规格可以根据客户要求定制。

Other specifications can be available as per customers' requirements.