



EPIC[®] PRO

CERAMIC COATING

**MALCO[®] AUTOMOTIVE'S
NEXT-GENERATION CERAMIC COATING,
DESIGNED TO PROTECT AND PRODUCE
THE ULTIMATE VEHICLE FINISH**



EPIC[®] PRO CERAMIC COATING



The new EPIC[®] PRO Ceramic Coating is specially formulated to provide 3 years (or 36,000 miles) of protection, along with the industry's highest gloss finish. It bonds with clear coat to create a durable, hydrophobic surface that prevents dirt, water spots and other contaminants from adhering to paint. Apply EPIC PRO Ceramic Coating to your vehicle for the ultimate "wet" look. If you cannot achieve a professional level of cleaning and paint correction on your own, please seek professional help to apply EPIC PRO Ceramic Coating.

Additional Features & Benefits

- Easy-to-apply coating
- Bonds with clear coat for outstanding depth of gloss
- Designed to complement the EPIC[®] Paint Correction System
- Produces the ultimate "wet" look
- Optimum viscosity simplifies application for experts and novices alike
- Excellent hydrophobic properties allow water and dirt to slide right off

The NEW EPIC[®] PRO Ceramic Coating Single Use Kit (#109330)

Package Contents

- 30ml EPIC PRO Ceramic Coating
- 1 Technical Data Sheet
- 1 Applicator Pad
- 10 Suede Cloths



EPIC[®] Paint Correction System and EPIC[®] Ceramic Coating System

When applying EPIC PRO Ceramic Coating, we recommend that you pair it with the complete EPIC Paint Correction System and EPIC Ceramic Coating System to ensure your vehicle surface is prepared correctly. Additionally, applying EPIC CR2 Hyrdo Protect Ceramic Spray every six months will help boost the life of the ceramic coating.



EPIC Paint Correction System (#800213)

This kit is ideal for surface correction before installing the EPIC Ceramic Coating System.

EPIC[®] Ceramic Prep Wash Concentrate (#109632)

A powerful detergent for removal of automotive exterior dirt, road film, brake dust and other soils.

EPIC[®] Ceramic Final Prep Wipe (#109716)

Cleans and preps vehicle surface for successful application of ceramic coating.

EPIC[®] CR2 Hydro Protect Ceramic Spray (#109416)

An SiO₂ spray-on ceramic formula, designed to be used standalone or as a booster for existing ceramic coating.

Edgeless Microfiber Towels (#800137)

Plush, absorbent 16-in x 16-in microfiber towels that will not cause micro scratches on paint surfaces.



Application Instructions

1. Put on a pair of rubber gloves, for protection. Shake product well, prior to use.
2. Clean and prep your surface with EPIC Ceramic Final Prep Wipe, using a lint-free cloth.
3. Wrap a Suede Cloth around the Applicator Pad. Apply 3-4 drops of EPIC PRO Ceramic Coating to the cloth, and immediately reseal product.
4. Apply coating to surface in a crosshatch pattern, using even pressure. We recommend working in a defined area of 20-in x 20-in, until product is worked into the clear coat.
5. Expect the coated area to rainbow, or flash, within 30-90 seconds of application. At this point, begin removing the product with a clean microfiber towel. Be sure to remove any remaining residue.
6. Repeat steps for coating of the entire vehicle, using an overlapping technique on each section to ensure full coverage.
7. Keep the vehicle in a controlled environment for at least 12 hours, while keeping dry for a minimum of 24 hours. Full bonding with the paint can take up to seven days, so it is vital to have garage access.

PRODUCT FAQs

Question: How long will EPIC PRO Ceramic Coating last?

Answer: Malco Automotive warrants this ceramic coating for 3 years, or 36,000 miles.



Question: What does EPIC PRO Ceramic Coating protect my vehicle from?

Answer: This coating repels water and dirt from sticking, as well as preventing hard water, acid rain, environmental contaminants, and bird droppings from etching the clear coat.

Question: How is EPIC PRO Ceramic Coating better than wax?

Answer: The EPIC PRO Ceramic Coating System bonds with the clear coat, providing years of protection. Additionally, the ceramic cures to create up to a 9H hardness.

Question: What should I use to apply EPIC PRO Ceramic Coating?

Answer: The suede cloth should always be used for application. These cloths are designed for one use only and should be disposed after application.

Question: How long does it take to apply EPIC PRO Ceramic Coating?

Answer: It depends on the level of paint correction required prior to application, as well as the experience level of the installer. It is important to not rush application. A few hours can be typical.

Question: How do I know when the coating is completely worked into the clear coat?

Answer: Work the product into the vehicle surface in a crosshatch pattern, until you can no longer see any remaining product. You will feel a slight resistance building, as the coating is fully worked in.

Question: Is one layer of coating enough to provide protection?

Answer: Yes, one layer is enough. However, multiple layers of ceramic coating will not harm your vehicle and will only provide extended durability.

Question: How do I care for my EPIC PRO Ceramic Coated vehicle?

Answer: To ensure the coating cures properly, the installer should keep the freshly treated car indoors for at least 12 hours after installation. It is ideal to avoid washing the vehicle for the first 7 days, after application. Hand wash or use touchless car washes to prevent premature wear of the coating.

To maintain the best protection and longevity, we recommend applying EPIC CR2 Hydro Protect Ceramic Spray at least every 6 months.



© 2022 Malco Products, Inc. All Rights Reserved
The Malco Automotive and EPIC PRO Ceramic Coating Logo, EPIC Ceramic Coating System, EPIC Paint Correction System, EPIC Ceramic Prep Wash Concentrate, EPIC Ceramic Final Prep Wipe, and EPIC CR2 Hydro Protect Ceramic Spray are registered trademarks of Malco Products, Inc.

800608R

