



Sauleda

TECHNICAL

DRAFT

DRAFTEX

DRAFT



Producción respetuosa
Production that respects
the environment



Anti-UVI
Anti-UVI



Climático
Climatic



Fácil mantenimiento
Easy to maintain



Máxima resistencia
Maximum resistance



Anti-manchas
Non-stain



Estabilidad dimensional
Dimensional stability



Tratamiento antimoho
Mold treatment



Doble cara, tejido protegido
Double sided, protected fabric



Impermeable
Waterproof



Rápido secado
Quick drying




Ignífugo
Fire retardant



Blanco
60128 250 cm



Hueso Ral 9010
60135 250 cm



Marfil Ral 1013
60132 250 cm



Arena
60131 250 cm



Champagne Ral 1015
60129 250 cm



Beige Ral 1001
60136 250 cm



Avena
60130 250 cm



Maíz
60137 250 cm



Burdeos Ral 3004
60140 250 cm



Aloe Ral 6011
60138 250 cm



Mar Ral 5015
60139 250 cm



Marino Ral 5013
60141 250 cm



Perla Ral 7035
60133 250 cm



Gris claro Ral 7038
60134 250 cm



Antracita Ral 7016
60142 250 cm



Negro Ral 9005
60143 250 cm

Características técnicas

Aplicaciones



RESISTENCIA TRACCIÓN TENSILE STRENGTH Urdimbre Warp Trama Weft		RESISTENCIA DESGARRE TEAR STRENGTH Urdimbre Warp Trama Weft		ANCHO WIDTH	COMPOSICIÓN COMPOSITION	RECUBRIMIENTO COATING	PESO WEIGHT
180 daN/5 cm	150 daN/5 cm	15 daN	10 daN	250 cm	Poliéster AT 550 dtex Polyester high tenacity 550 dtex	2 caras Coating 2 faces	490 gr / m ² EN ISO 2286.2
UNE EN ISO 1421		EN ISO 13937.2					

Sujeto a cambios en relación con las mejoras técnicas. Los valores indicados sin niveles de tolerancia son valores nominales con un rango de tolerancia de $\pm 5\%$. Todos los datos presentados aquí se ofrecen, según nuestro leal saber y entender, con fines orientativos y no son legalmente vinculantes. V0923

Subject to change with respect to technical improvements. The values stated without tolerance levels are nominal values with a tolerance range of $\pm 5\%$. All data presented here are to the best of our knowledge and belief for guidance purposes and are not legally binding. V0923

DRAFTEX



Sauleda da un salto de calidad sacando al mercado el tejido Sauleda Draft. Un tejido técnico de altas prestaciones ideal para la demanda solicitada del mercado actual.


Sauleda Draft es un tejido que cumple con la normativa T2 de resistencia al fuego, que tiene un tratamiento antimoho y lacado a dos caras. Disponible en ancho de 250 cm y una gama de 16 colores lisos consigue adaptarse a todo tipo de entornos.

Además, sale al mercado Sauleda Draft Tex, una gama de 4 colores que cumple con las mismas características técnicas que el Draft pero con un acabado Tex para adaptarse a peticiones de mercado.


Sauleda takes a leap in quality by putting the Sauleda Draft fabric on the market. An ideal high-performance technical fabric for the current market's demands.

Sauleda Draft is a fabric that complies with the T2 fire resistance regulations, which has an anti-mold treatment and is lacquered on both sides. Available in a width of 250 cm and a range of 16 solid colors, it manages to adapt to all kinds of environments.

In addition, Sauleda Draft Tex has reached the market, with a range of 4 colors that meets the same technical characteristics as the Draft but with a Tex finish to suit market demand.




Marfil | Muestra de calidad Quality sample



Draftex Blanco
60198 250 cm



Draftex Arena
60199 250 cm



Draftex Perla Ral 7035
60200 250 cm



Draftex Antracita Ral 7016
60201 250 cm



Applications

Technical Characteristics

ACABADO FINISH	ADHERENCIA ADHESION	LONGITUD DE LAS PIEZAS ROLL LENGTH	SOLIDEZ A LA LUZ LIGHT FASTENESS	RESISTENCIA TEMPERATURA TEMPERATURE RESISTENCE	IGNÍFUGO FIRE RETARDANT
Lacado 2 caras Lacquered 2 faces	6 daN/5 cm UNE EN ISO 2411	50 ml	6-8 UNE EN ISO 105 B02	-30° + 70°	T2 UNE EN 15619





Sauleda

1897

@sauledatextiles
www.sauleda.com
sauleda@sauleda.com
+34 933 397 150

