

MH56021-1500

Items 项目	Value 数值	Unit 单位	Ref. test method 参考测试标准
Base fabric 基布	Polyester 高强聚酯	Dtex	
Yarn 纱线粗细	1500D×1500D	D	
Weight 克重	1500	g/sq. m	
Breaking Strength (Warp/Weft) 拉伸强度（经向/纬向）	7000/6500	N/5cm	DIN53354
Tear Strength (Warp/Weft) 撕裂强度（经向/纬向）	1000/900	N	DIN53363
Adhesion 粘接强度	120	N/5cm	DIN53357（IVK）
Temperature resistance 适用温度	-30~+70	℃	DIN53361
Flame Retardncy 防火性能	B1		GB8624-1997
Surface Treatment 表面处理	Double sides Non weldable PVDF		
Quality management according to 质量保证体系	ISO9001: 2000		

技术说明
Technology Statement

本产品作为建筑膜结构材料使用，按照欧洲 DIN 标准设计

Used as the membrane structural material use, according to European DIN standard

请客户按照相关规定和行业标准正确选择使用本公司产品。本公司仅就产品是否符合本页注明的技术数据和性能负责，除此之外不对产品承担其他任何法律责任

Customers might choose our product properly accord to the related stipulation and standard .

We take liability of technical date and performance of this page. And except of this we don' t undertake any other legal duty.

本页技术数据为算术平均值，允许误差 5%

This technical date of this page are all arithmetical average and the error permitted is 5percent above or below.