


Technical Datasheet 技术规格表

Article Number 产品号码: L2120-xxxx-W

Application 应用领域: Architecture Membrane 建筑膜结构



Base fabric (DIN ISO 2076)

基布

100% Polyester



Total weight (DIN EN ISO 2286-2)

克重

ca. 1200 g/m² | 35.4 oz/yd²



Coating material

涂层


PVC



Surface finish: Double-side weldable

PVDF

双面可焊 PVDF



Tensile strength W/F

拉伸强度

DIN EN ISO 1421-1

6000/4800 N/5 cm

717/567 lbs/inch



Tear resistance W/F

撕裂强度

DIN 53363

950/950 N

214/214 lbs



Welding adhesion

高频焊接强度

IVK 3.13

130 N/5 cm

14.7 lbs/inch



Temperature resistance

耐温性

DIN EN 1876-1

-30 °C to +70 °C

-22 °F to +158 °F



Flex resistance

抗弯性

DIN 53359 A

at least 100,000 bends

至少弯曲 10 万次



Flame retardancy

阻燃性

DIN 4102-1

B1/B2 optional

B1/B2 根据客户要求选择

*kindly be noted, anti-wick is optional in all series of LIVITE products requested by customers

备注: 利威德所有系列的产品均可按照客户要求做抗芯析