


Technical Datasheet 技术规格表

Article Number 产品号码: L1650-xxxx-P

Application 应用领域: Tarpaulin



Base fabric (DIN ISO 2076)

基布

100% Polyester



Total weight (DIN EN ISO 2286-2)

克重

ca. 650 g/m² | 19.2 oz/yd²



Coating material


涂层

PVC



Surface finish:

表处类型:



Tensile strength W/F

拉伸强度

DIN EN ISO 1421-1

3200/2800 N/5 cm

365/319 lbs/inch



Tear resistance W/F

撕裂强度

DIN 53363

450/350 N

101/79 lbs



Welding adhesion

高频焊接强度

IVK 3.13

150 N/5 cm

17.0 lbs/inch



Temperature resistance

耐温性

DIN EN 1876-1

-30 °C to +70 °C

-22 °F to +158 °F



Flex resistance

抗弯性

DIN 53359 A

at least 100,000 bends

至少弯曲 10 万次



Flame retardancy

阻燃性

DIN 4102-1

B1

B1

Warranty 10 years 质保 10 年

公司: 利威德(无锡)高分子材料有限公司 地址: 江苏省江阴市周庄镇砂山大道 287 号

Company: Livite(wuxi) High polymer materials co.,Lt Address: No. 287, shashan Ave. Zhouzhuang Town, Jiangyin City, Jiangsu PR, China

电话: +86 (510) 8663 9888 传真: +86 (510) 8663 9888 网址: www.livite.cn

Tel: +86 (510) 86639888 Fax: +86(510) 8663 9888