




800G/3300N



VT8-38091AA




VT8-38093AA



VT8-38095AA

Single side Lychee embossing



- All weather
- Strong sense of pattern design
- High temperature resistance
- Strong tensile and tear strength

Yuma Vantex Superior Sunshading Membrane covers a variety of categories, a wide range of application scenarios:

- Architecture indoor shading
- Architecture outdoor shading
- Outdoor recreation space shading
- Public commercial space shading

• Technical properties

Width	300cm	DIN EN ISO 2286-1
Thickness	0.63mm	DIN EN ISO 2286-3
Total Weight	800g/m²	DIN EN ISO 2286-2
Roll length	50/100 m/roll	-

• Physical properties

Tensile strength	Warp 3300N/5CM Weft 3000N/5CM	EN ISO 1421
Tear strength	Warp 350N/5CM Weft 280N/5CM	DIN 53363
Temperature resistance	-30~70°C	DIN EN 1876-1

• Flame retardancy

Flame retardancy	B1	DIN 4102
------------------	----	----------

• Surface treatment

Surface treatment	Acrylic	-
Embossing technology	Single side lychee embossing technology	-

• Solar optical values

Color fastness	8	EN ISO 105-B02
Shading effect	Blackout	-

• Eco friendly

Heavy metal test (Cd/Pb/Hg)	None	GB/T 26125-2011
Odor test	None	GB 18401-2010.6.7
PH test	Pass	GB/T 7573-2009
Formaldehyde content test	None	GB/T 2912.1-2009
Mouldproof test	0 (Highest)	ASTM G 21-15 (2021)

• Certifications, labels, guarantees

China Environmental Labelling	Pass	-
BSCI	Pass	-
System certification	ISO 9001 / ISO 14001 / ISO 45001	DIN EN

The technical data here above are average values with +/- 5% tolerance.



Functionality
waterproof, fire resistance,
mould-proof, sunscreen,
formaldehyde resistance,
sun shading and heat insulation



All-weather
Aging resistance and extreme
temperature resistance,
corrosion resistance,
Anti-fouling and self-cleaning



Strong sense design
Using lychee grain fine flower pattern,
sun shading heat insulation and
good decorative effect.



**High temperature resistance
and tear resistance**
After the special process surface treatment, it can
be suitable for the high frequency and high
temperature welding machine. Strong welding
strength, high tensile resistance and tear resistance.