

TORO

— TECHNICAL COATED FABRICS —

DIGITAL PRINT MEDIA

FRONTLIT

BLACKBACK

POLYCANVAS

PC CANVAS

















TS 140 FRONTLIT

Coating Type: Acrylate/PU Dispersion with IRC

top coat (Ink Receptive Coating)

Thickness: 140 microns

Weight: 140 GSM

Finish: White

Fabric Blend :100% Woven Polyester

Tensile: Warp: 1050 N/5cm

Weft: **1150 N/5cm**

Tear: Warp: **50 N/5cm**

Weft: **50 N/5cm**

Availability: **Upto 3.2 m**

Ink Compatibility:

Coated Side: Latex, UV, Eco-Solvent, Solvent

Vertical Flammability: IS 11871 Method A

No top/edge flaming No molten debris No after flame No after glow



Available up to 3.2m seamless / standard 50m roll length

The specification and information mentioned are for information purposes and in no way contractually binding. This information is subjected to revision as additional technology is developed. MRT Ltd and it reserves the right to change/modify the data without prior notice.



Fax: +91-79-40008030









TS 165 BLACK BACK

Coating Type: Acrylate/PU Dispersion with IRC

top coat (Ink Receptive Coating)

Thickness: 165 microns

Weight: 165 GSM

Finish: White / Black

Fabric Blend :100% Woven Polyester

Tensile: Warp: 1050 N/5cm

Weft: **1150 N/5cm**

Tear: Warp: **50 N/5cm**

Weft: **50 N/5cm**

Availability: Upto 3.2 m

Ink Compatibility:

Coated Side: Latex, UV, Eco-Solvent, Solvent

Vertical Flammability: IS 11871 Method A

No top/edge flaming No molten debris No after flame No after glow



Available up to 3.2m seamless / standard 50m roll length

The specification and information mentioned are for information purposes and in no way contractually binding. This information is subjected to revision as additional technology is developed. MRT Ltd and it reserves the right to change/modify the data without prior notice.



YSL Avenue, Opp.Ketav Petrol Pump, Polytechnic Road Ambawadi Ahmedabad 380015 India

Fax: +91-79-40008030

Contact: +91-79-40008000 www.mrtglobal.com









TS 250 POLY CANVAS

Coating Type: Acrylate/PU Dispersion with IRC

top coat (Ink Receptive Coating)

Thickness: 255 microns

Weight: 250 GSM

Finish: White Matte

Fabric Blend :100% Woven Polyester

Tensile: Warp: 1850 N/5cm

Weft: **1350 N/5cm**

Tear: Warp: **100 N/5cm**

Weft: **100 N/5cm**

Availability: Upto 3.2 m

Ink Compatibility:

Coated Side: Latex, UV, Eco-Solvent, Solvent

Vertical Flammability: IS 11871 Method A

No top/edge flaming No molten debris No after flame No after glow



Available up to ${\bf 3.2m}$ seamless / ${\bf standard}$ ${\bf 50m}$ ${\bf roll}$ ${\bf length}$

The specification and information mentioned are for information purposes and in no way contractually binding. This information is subjected to revision as additional technology is developed. MRT Ltd and it reserves the right to change/modify the data without prior notice.



YSL Avenue, Opp.Ketav Petrol Pump, Polytechnic Road Ambawadi Ahmedabad 380015 India









TS 330 PC CANVAS

Coating Type: Acrylate/PU Dispersion with IRC

top coat (Ink Receptive Coating)

Thickness: 440 microns

Weight: 330 GSM

Finish: White Matte

Fabric Blend: 65% Polyester 35% Cotton Woven Fabric

Tensile: Warp: 1900 N/5cm

Weft: **1600 N/5cm**

Tear: Warp: **100 N/5cm**

Weft: **100 N/5cm**

Availability: Upto 3.2 m

Ink Compatibility:

Coated Side: Latex, UV, Eco-Solvent, Solvent

Vertical Flammability: IS 11871 Method A

No top/edge flaming No molten debris No after flame No after glow



Available up to **3.2m** seamless / **standard 50m roll length**

The specification and information mentioned are for information purposes and in no way contractually binding. This information is subjected to revision as additional technology is developed. MRT Ltd and it reserves the right to change/modify the data without prior notice.



Corporate Head Office

YSL Avenue , Opp.Ketav Petrol Pump , Polytechnic Road Ambawadi Ahmedabad 380015 India

Contact : **+91-79-40008000**

Fax: +91-79-40008030

Manufacturing Unit

Mahalaxmi Rubtech Limited. Uma Industrial Estate, Near Hotel Bhagyoday, Sanand Viramgam Highway, Village: Vasna-Iyava, Sanand, Ahmedabad: 382 170

Tel No: +91-79-29919650

Contact: +02717-284309 / 284310

Fax: **+02717-284152**



www.mrtglobal.com