

TECHNICAL DATA SHEET

FUSION

CHEMICAL CONTENT

Polyurethane	%	7
PVC	%	74
Polyester	%	19

PHYSICAL PROPERTIES

Criteria	Standard	Unit	Test Standard
Weight	600 ± %5	g/m2	ISO 3801
Thickness	1,00 ± 0,10	mm	ISO 2589
Tear Strength - Width	22	N	ISO 4674-1
Tear Strength - Length	28	N	ISO 4674-1
Abrasion Resistance	≥ 100.00	cycle	ISO 12947-4
Abrasion Resistance After 3 weeks of hydrolysis(70°C / %95 RH)	≥ 100.00	cycle	ISO 12947-4
Color Fastness to Rubbing Dry	≥ 4,5	GS	ISO 105x12
Color Fastness to Rubbing Wet	≥ 4,5	GS	ISO 105x12
Width	140	cm	-

KEY FEATURES

- Has a higher scratch resistance compared to other Pull-up products from the market
- Offers a high variety of colour and design options
- Long lasting, UV resistant, enviromental-friendly product
- Compatible with Reach, harmful chemicals are not accepted in our factory

** Physical property values are just an indicator, higher standards can be achieved and showed when requested*

** Any additional features(flame retardancy, anti-bacterial etc.) can be added when requested.*

