

CHENILLE/CHAIN STITCH EMBROIDERY MACHINE SERIES



MAIN PERFORMANCE CHARACTERISTICS

- Flat Head can choose Double Cam Double receptor, Double crank head structure.
- High Precision Integrated structure machine body processing by large Milling machine.
- High proforma industrial grade electric control system.
- High Precision suspension embroidery frame and C type Frame Structure option.
- All-Round oil lubrication system .
- All servo motor driver, with High strength import belt.
- High precision customization gear type driver box .
- High performance upper thread holding system .
- Sequin,cording,beads, laser cutting , boring device enable you to choose flexibly according head distance .
- Flexible selection of inner cam and external cam of towel heads according to application scenarios .
- Automatic change of 12 colors of chenille head.
- Equipped with a temperature-controlled air-cooling system and automatic cleaning structure.

A mixed machine can use a variety of traditional techniques in one piece of embroidery with additional effect of towel stitch, chain stitch and taping embroidery and the mix of designs and materials.

APPLICATIONS

The looping/chain stitch embroidery had broad prospects of development in fields of children 's wear, home decoration,ladies shoes with advantages of strong 3D effect,rich gradation and brilliant colors,it widely applied in embroideries of table cloth,napkin,bed over,pillowcase, children 's wear, knitted over pull, badge, blanket, lady 's shirt, cap,furs, silk,and linen etc.

GENERAL MACHINE SPECIFICATIONS

Model	Needles No. (Flat)	Needles No. (chenille)	Heads No. (Flat)	Head No. (Chenille)	Head interval (mm)	Emb.Area (mm)	Inner Frame Size (mm)	Machine Size (mm)
SINSIM-MT(9+6)(4+4)	9	6	4	4	550	1100*900	3240*940	5720*2357
SINSIM-T612	0	6	0	12	500	550*900	6130*940	7650*2357
SINSIM-MT(9+6)(12+12)	9	6	12	12	600	1200*1500	7880*1660	10160*3797
SINSIM-T614	0	6	0	14	840	840*1750	11840*1790	13460*4057
SINSIM-T615	0	6	0	15	500	550*1650	7630*1690	9150*3857
SINSIM-MT(6+6)(15+15)	6	6	15	15	500	1100*1300	8410*1340	10840*3157
SINSIM-MT(12+9)(20+20)	12	9	20	20	500	600*900	10410*940	12780*2377
SINSIM-T624	0	6	0	24	450	600*1350	11030*1390	12580*3257
SINSIM-MT(9+9)(24+24)	9	9	24	24	500	1000*900	12810*940	15280*2357
SINSIM-MT(9+6)(26+26)	9	6	26	26	450	750*850	12090*900	14160*2277
SINSIM-T628	0	6	0	28	330	750*1330	9740*1370	11690*3217
SINSIM-T632	0	6	0	32	300	650*1500	10030*1540	11780*3557
SINSIM-MT(6+4)(32+32)	6	4	32	32	330	700*1600	11260*1640	13380*3777
SINSIM-T639	0	6	0	39	240	750*1750	9950*1790	11800*4027

▼ SINSIM-MT(12+6)(12+12)/600

