

Margia-Crete Topping

The perfect combination for your renovation



Understanding the needs of the client very well, Ruys Vloeren understands that floor renovation is becoming more and more important. And with renovation the aspect "time is money" is all important. In production rooms renovations frequently have to be carried out during wet conditions, with limited available time and limited allowable thicknesses. But with all these restraints, the quality still has to be good and durable. With this in mind, and after years of testing, Ruys presents the MARGIA-CRETE floor.

The floor combines the strength and anti-slip qualities of the famous Margia granite floor and the moisture insensitive, minimal thicknesses and short curing time (maximum 24 hours) of a polyurethane-cement floor. This give the additional advantages of thermal and chemical resistance.

Characteristics of the Margia Crete

- · very wear resistant and able to withstand heavy traffic
- High anti-slip qualities (R13)
- Fluid and moisture tight
- Seamless
- almost complete chemical resistance
- Thermal resistance up to 130 °C can be achieved
- Possible in thin toppings (4-6 mm)
- Fast curing time (24 hours)
- Easy to clean

Do it right, do it once!

Appearance

The Margia-Crete floor also has the pleasing look of the Margia granite floor which is most popular in the meat processing facilities. However, now a finer gradation of the granite chips are use and not a 40 – 50 mm cement based floor, but a approximately 4-6 mm thick polyurethane-cement floor is used. The Margia-Crete floor can be installed in short installation times and can quickly put to use.



Sloping

oere



In case new drainage and slope is needed, the Margia-Crete can be combined with a new steel fiber reinforced special concrete sub layer. This sloped layer is installed by our people under a 1% slope by which Ruys can guarantee you a puddle free floor. In combination with for instance our stainless steel bump curbs, where Ruys finishes the top of the curb with the same floor material, the total gives you a perfect solution which meets and exceeds all HACCP, USDA, EC and BCE requirements.



Curaçao 30, 7332 BM Apeldoorn Postbus 558, 7300 AN Apeldoorn Tel. 0031 (55) 533 53 63 Fax 0031 (55) 533 79 59 Email: info@ruysvloeren.nl Website: www.ruysvloeren.nl



