



Optimus *SE/SEL*

EN Version

OPTIMUS *SE/SEL*

The perfect entry model with outstanding performance for automatic packaging

The **VARIOVAC Optimus SE** has a 3 m frame length; whereas the **VARIOVAC Optimus SEL** has a 3.5 m frame length. Both models are ideally suited as entry-

level models for fully automatic packaging. The **VARIOVAC Optimus SE/SEL** impress with a short delivery time. Their pre-configured, standard equipment

has been developed to suit the market needs. Its extensive standard equipment as well as optimised additional options enables the **VARIOVAC Optimus SE/**

SEL to be used for a wide range of products. VARIOVAC's RapidAirSystem is standard in every **VARIOVAC Optimus SE/SEL** to ensure high performance and

the beste packaging results all with low energy requirements.

simpler faster better



OPTIMUS *SE/SEL*


Equipment features

Basic equipment

- » Basic machine OL 30 or 35 with 420 mm film width
- » Basic die 240, 260, 280, 300 or 320 mm with side pins
- » Pack size 2.1
- » Flat sealing plate
- » Unwinding system with storage roll
- » Vacuuming system
- » Trim removal system
- » Max. package depth 60 or 110 mm
- » Safety cover VA (hinged) in the cutting area
- » Vacuum pump 100 cbm/h
- » Automatic chain greasing
- » Activated carbon filter
- » One guillotine
- » Long cut with rotating blades
- » Discharge conveyor

Options

- » Pack size 1.1, 3.1, 4.1, 2.2, 3.2
- » Frame sealing plate 1.1, 2.1, 3.1, 4.1, 2.2, 3.2
- » Gas flushing
- » O2-safety kit
- » Gas buffer tank
- » Die cooling system
- » Second guillotine
- » Print mark control
- » Control cabinet heating
- » End of film recognition



Example: Optimus SE

OPTIMUS *SE/SEL*

VARIOVAC
simpler faster better

MORE VARIOVAC. MORE INFORMATION.

VARIOVAC PS SystemPack GmbH
Ernst-Litfaß-Str. 3 and 5
19246 Zarrentin am Schaalsee

Telefon +49 38851-823 0
Telefax +49 38851-823 220

info@variovac.de



VARIOVAC.DE