

YOUR PARTNER IN INDUSTRIAL WEIGHING




**EQUIPMENT
FOR THE MOST
DEMANDING
FOOD
INDUSTRY**

COMMERCIAL AND TECHNICAL OFFICE
C/Thomas Alva Edison, 67
Pol. Ind. Plans d'arau
08787 La Pobla de Claramunt
(Barcelona)
+34 931 160 874

ADMINISTRATIVE OFFICE
Pol. Ind. Pagatza, 9
20690 Elgeta
(Gipuzkoa)
+34 943 761 236

info@grupoosg.com
www.grupoosg.com

www.grupoosg.com



PHOTOCELLS

- Product volume detection in the auger feeder.



TOUCH SCREEN

- Size 10,4"
- Memory for 10 programs.
- One single screen controls up to 6 modules.



AUGER FEEDER

- Adjustable speed, independent stepper motors on each line.
- Easy dismantling and cleaning.
- Stainless steel.



ELECTRIC CABINET


- Made in stainless steel.
- Top with more than 30° inclination.
- Double locking system.



UP-DOWN FILLING STATION


- Designed for each tray.
- To guide and canalise the product into the tray.

TECHNICAL DATA



MODULE AND BELTS

- Standard interchangeable components between modules.
- Easy dismantling, tool-free, for cleaning.



REJECTION DEVICE

- Product rejection due to nominal overweight.
- Recoverable rejected product.
- To prevent overweight inside the trays.

Tray volume according to product.

Precision + / - 1 piece

Production 6 - 40 dpm (according to product)

Number of heads 1 - 6

Number of levels 3

Compact design

Hygienic design for easy cleaning

Easy mobility for adaptation to other production lines.

Multiproduct option available.

