

DARIBO

MEAT PROCESSING MACHINE PROGRAM

PASSION FOR MEAT PROCESSING



SHANGHAI DARIBO FOOD MACHINERY CO. , LTD.


Tel: +86 (021) 33311110

Website: en.daruibao.com

INTEGRITY AS THE ROOT, QUALITY AS THE BASE.

Cutter

DRB-QR160



Model	DRB-QR160
Inlet's Size(MM/Inch)	600 × 160 × 100 MM/23.6" × 6.3" × 3.9"
Power(KW/HP)	1.25 KW/1.6 HP
Voltage (V)	380 V(Customization is available)
Net Weight(KGS/Pound)	370 KGS/816 LBS
Dimension(MM/Inch)	2450 × 700 × 1525 MM/96.5" × 27.5" × 60"
Capacity	60-260 RPM(Adjusted)

Chop Cutter

DRB-17K



Model	DRB-17K
Inlet's Size(MM/Inch)	600*170*155 MM/23.6" × 6.7" × 5.9"
Power(KW/HP)	3.4 KW/4.5 HP
Voltage (V)	380 V(Customization is available)
Net Weight(KGS/Pound)	355 KGS/783 LBS
Dimension(MM/Inch)	1740 × 770 × 1220 MM/68.5" × 30.3" × 48"
Capacity	190/220/280 RPM (Optional)

Chop Cutter

DRB-21K



Model	DRB-21K
Inlet's Size(MM/Inch)	650*210*165 MM/25.6" × 8.3" × 6.5"
Power(KW/HP)	3.4 KW/4.5 HP
Voltage (V)	380 V(Customization is available)
Net Weight(KGS/Pound)	375 KGS/827 LBS
Dimension(MM/Inch)	1775 × 800 × 1220 MM/69.9" × 31.5" × 48"
Capacity	190/220/280 RPM (Optional)

Chop Cutter

DRB-21KC



Model	DRB-21KC
Inlet's Size(MM/Inch)	650*210*165 MM/25.6" × 8.3" × 6.5"
Power(KW/HP)	3.48 KW/4.6 HP
Voltage (V)	380 V(Customization is available)
Net Weight(KGS/Pound)	415 KGS/915 LBS
Dimension(MM/Inch)	2015 × 800 × 1220 MM/79.3" × 31.5" × 48"
Capacity	190/220/280 RPM (Optional)

Chop Cutter

DRB-25K



Model	DRB-25K
Inlet's Size(MM/Inch)	650 × 250 × 165 MM/25.6" × 9.8" × 6.5"
Power(KW/HP)	4.75 KW/6.3 HP
Voltage (V)	380 V(Customization is available)
Net Weight(KGS/Pound)	465 KGS/1025 LBS
Dimension(MM/Inch)	1950 × 940 × 1320 MM/77.2" × 37" × 52"
Capacity	190/220/280 RPM (Optional)

Chop Cutter

DRB-25KC



Model	DRB-25KC
Inlet's Size(MM/Inch)	650 × 250 × 165 MM/25.6" × 9.8" × 6.5"
Power(KW/HP)	4.84 KW/6.4 HP
Voltage (V)	380 V(Customization is available)
Net Weight(KGS/Pound)	490 KGS/1080 LBS
Dimension(MM/Inch)	2600 × 940 × 1320 MM/102.4" × 37" × 52"
Capacity	190/220/280 RPM (Optional)

Chop Cutter

DRB-36K



Model	DRB-36K
Inlet's Size(MM/Inch)	650 × 350 × 210 MM/25.6" × 13.8" × 8.3"
Power(KW/HP)	5 KW/6.6 HP
Voltage (V)	380 V(Customization is available)
Net Weight(KGS/Pound)	970 KGS/2138 LBS
Dimension(MM/Inch)	1920 × 1180 × 1500 MM/75.6" × 46.5" × 59.1"
Capacity	160-220-280-320 RPM(Adjusted)

Chop Cutter

DRB-36KC



Model	DRB-36KC
Inlet's Size(MM/Inch)	650 × 350 × 210 MM/25.6" × 13.8" × 8.3"
Power(KW/HP)	5 KW/6.6 HP
Voltage (V)	380 V(Customization is available)
Net Weight(KGS/Pound)	998 KGS/2200 LBS
Dimension(MM/Inch)	2700 × 1180 × 1500 MM/106.3" × 46.5" × 59.1"
Capacity	160-220-280-320 RPM(Adjusted)

Meat Slicer

DRB-430



Model	DRB-430
Inlet's Width(MM/Inch)	430 MM/16.93"
Power(KW/HP)	9.12 KW/12.1 HP
Voltage (V)	380 V(Customization is available)
Net Weight(KGS/Pound)	1240 KGS/2734 LBS
Dimension(MM/Inch)	2530 × 1120 × 1680 MM/99.21" × 44.09" × 66.14"
Temperature(°C/°F)	-10°C-0°C/14°F-32°F

Meat Slicer


DRB-455



Model	DRB-455
Inlet's Width(MM/Inch)	430 MM/16.93"
Power(KW/HP)	9.12 KW/12.1 HP
Voltage (V)	380 V(Customization is available)
Net Weight(KGS/Pound)	970 KGS/2138 LBS
Dimension(MM/Inch)	2050 × 1100 × 1740 MM/80.71" × 43.31" × 68.5"
Temperature(°C/°F)	-10°C-0°C/14°F-32°F

Meat Dicer

DRB-EW455



Model	DRB-EW455
Inlet's Width(MM/Inch)	430 MM/16.93"
Power(KW/HP)	12 KW/16 HP
Voltage (V)	380 V(Customization is available)
Net Weight(KGS/Pound)	1485 KGS/3274 LBS
Dimension(MM/Inch)	2580 × 1185 × 1625 MM/101.57" × 46.65" × 63.98"
Temperature(°C/°F)	-10°C-0°C/14°F-32°F

Meat Dicer

DRB-PSD300



Model	DRB-PSD300
Inlet's Width(MM/Inch)	292 MM/11.5"
Power(KW/HP)	2.25 KW/3 HP
Voltage (V)	380 V(Customization is available)
Net Weight(KGS/Pound)	605 KGS/1336 LBS
Dimension(MM/Inch)	2065 × 1045 × 1445 MM/81.3" × 41.14" × 56.9"
Capacity(KGS/LBS)	300-1000 KGS/661-2205 LBS

Meat Dicer

DRB-QK300



Model	DRB-QK300
Inlet's Width(MM/Inch)	300 MM/11.8"
Power(KW/HP)	3 KW/4 HP
Voltage (V)	380 V(Customization is available)
Net Weight(KGS/Pound)	284 KGS/626 LBS
Dimension(MM/Inch)	680 × 1000 × 1200 MM/26.8" × 39.4" × 47.2"
Capacity(KGS/LBS)	300-500 KGS/661-1102 LBS

Meat Dicer

DRB-QK300L



Model	DRB-QK300L
Inlet's Width(MM/Inch)	300 MM/11.8"
Power(KW/HP)	3.75 KW/4 HP
Voltage (V)	380 V(Customization is available)
Net Weight(KGS/Pound)	306 KGS/675 LBS
Dimension(MM/Inch)	1450 × 700 × 1180 MM/57.5" × 27.6" × 46.5"
Capacity(KGS/LBS)	300-500 KGS/661-1102 LBS

Meat Dicer

DRB-R350H



Model	DRB-R350H
Inlet's Size(MM/Inch)	84 × 84 × 390 MM/3.3" × 3.3" × 15.4"
Power(KW/HP)	3.2 KW/4.2 HP
Voltage (V)	380 V(Customization is available)
Net Weight(KGS/Pound)	332 KGS/732 LBS
Dimension(MM/Inch)	1415 × 775 × 985 MM/55.7" × 30.5" × 38.8"
Capacity(KGS/LBS)	500-600 KGS/1102-1323 LBS

Meat Dicer

DRB-500



Model	DRB-500
Inlet's Size(MM/Inch)	120 × 120 × 490 MM/4.7" × 4.7" × 19.3"
Power(KW/HP)	7 KW/9.3 HP
Voltage (V)	380 V(Customization is available)
Net Weight(KGS/Pound)	712 KGS/1570 LBS
Dimension(MM/Inch)	1940 × 1325 × 1600 MM/76.5" × 52.1" × 62.9"
Capacity(KGS/LBS)	600-800 KGS/1323-1764 LBS

INTEGRITY AS THE ROOT, QUALITY AS THE BASE.

Dicer

DRB-QD330



Model	DRB-QD330
Inlet's Size(MM/Inch)	D<120 MM/4.7"
Power(KW/HP)	4 KW/5.3 HP
Voltage (V)	380 V(Customization is available)
Net Weight(KGS/Pound)	500 KGS/1102 LBS
Dimension(MM/Inch)	1200 × 800 × 1700 MM/49.6" × 35.4" × 66.9"
Capacity(KGS/LBS)	Meat:1000-3000 KGS/2205-6614 LBS Cheese:500-700KGS/1102-1543 LBS
Cutting Thickness(MM/Inch)	Slice/Shredded/Cube:3-20 MM/0.12"-0.79"

Dicer

DRB-D450



Model	DRB-D450
Inlet's Size(MM/Inch)	D<120 MM/4.7"
Power(KW/HP)	11 KW/14.6 HP
Voltage (V)	380 V(Customization is available)
Net Weight(KGS/Pound)	748 KGS/1649 LBS
Dimension(MM/Inch)	1950 × 1150 × 1600 MM/77.2" × 45.3" × 63"
Capacity(KGS/LBS)	1200-3000 KGS/2646-6614 LBS
Cutting Thickness(MM/Inch)	Slice:2-20 MM/0.08"-0.79" Shredded:5-12 MM/0.2"-0.47" Cube:5-20 MM/0.2"-0.79"

Fish Processing Machine

DRB-YM450



Model	DRB-YM450
Cutting Speed	3200 RPM
Power(KW/HP)	1.5 KW/2 HP
Voltage (V)	380 V(Customization is available)
Net Weight(KGS/Pound)	173 KGS/381 LBS
Dimension(MM/Inch)	340 × 600 × 1200 MM/55.1" × 23.6" × 47.2"
Inlet's Width(MM/Inch)	450 MM/17.7"

EU-Standard Saw

DRB-JG440



Model	DRB-JG440
Max Processable Height(MM/Inch)	440 MM/17.3"
Table Size(MM/Inch)	940 × 920MM/37" × 36.2"
Power(KW/HP)	2.2 KW/2.9 HP
Voltage (V)	380 V(Customization is available)
Net Weight(KGS/Pound)	210 KGS/463 LBS
Dimension(MM/Inch)	895 × 940 × 1930 MM/35.2" × 37" × 76"
Blade Size(MM/Inch)	3340 MM/131.5"

EU-Standard Saw

DRB-JG550



Model	DRB-JG550
Max Processable Height(MM/Inch)	550 MM/21.7"
Table Size(MM/Inch)	940 × 920MM/37" × 36.2"
Power(KW/HP)	2.2 KW/2.9 HP
Voltage (V)	380 V(Customization is available)
Net Weight(KGS/Pound)	230 KGS/503 LBS
Dimension(MM/Inch)	920 × 950 × 2040 MM/36.2" × 37.4" × 80.3"
Blade Size(MM/Inch)	3550 MM/139.8"

Full-Automatic Saw

DRB-ATJG150B



Model	DRB-ATJG150B
Max Processable Height(MM/Inch)	150 MM/5.9"
Table Size(MM/Inch)	650 × 800MM/25.6" × 31.5"
Power(KW/HP)	8.5 KW/11.3 HP
Voltage (V)	380 V(Customization is available)
Net Weight(KGS/Pound)	895 KGS/1973 LBS
Dimension(MM/Inch)	1460 × 2200 × 1900 MM/57.5" × 86.6" × 74.8"
Blade Size(MM/Inch)	3430 MM/135"

Trotter Splitting Machine

DRB-ZT100



Model	DRB-ZT100
Max Processable Height(MM/Inch)	115 MM/4.5"
Max Processable Width(MM/Inch)	2-100 MM/0.2-3.9"
Power(KW/HP)	2.25 KW/3 HP
Voltage (V)	380 V(Customization is available)
Net Weight(KGS/Pound)	280 KG/613 LBS
Dimension(MM/Inch)	1400 × 800 × 1740 MM/55.1" × 31.5" × 68.5"
Blade Size(MM/Inch)	2495 MM/98.2"

Trotter Cutting Machine

DRB-ZT5



Model	DRB-ZT5
Max Processable Height(MM/Inch)	160 MM/6.3"
Max Processable Width(MM/Inch)	380 MM/14.96"
Power(KW/HP)	9.2KW/ 12.2 HP
Voltage (V)	380 V(Customization is available)
Net Weight(KGS/Pound)	514 KG/1133 LBS
Dimension(MM/Inch)	1600 × 995 × 1950 MM/63" × 39.2" × 76.8"
Blade Size(MM/Inch)	2000 MM/2 Pcs&3550 MM/2 Pcs/78.7" × 2&139.8" × 2

Cutter DRB-120



Model	DRB-120
Inlet's Size(MM/Inch)	120 MM/4.7"
Power(KW/HP)	0.75 KW/1 HP
Voltage (V)	220/380V(Customization is available)
Net Weight(KGS/Pound)	115 KGS/254 LBS
Dimension(MM/Inch)	1350 × 600 × 1250 MM/53.1" × 23.6" × 49.2"
Capacity(KGS/LBS)	150~800 KGS/331~1764 LBS
Cutting Thickness(MM/Inch)	1~32 MM/0.04"~1.26"(adjustable)

Cutter DRB-180



Model	DRB-180
Inlet's Size(MM/Inch)	180 MM/7.1"
Power(KW/HP)	1.3 KW/1.73 HP
Voltage (V)	380V(Customization is available)
Net Weight(KGS/Pound)	230 KGS/507 LBS
Dimension(MM/Inch)	2600 × 900 × 1100 MM/102.4" × 35.4" × 43.3"
Capacity(KGS/LBS)	200~1000 KGS/441~2205 LBS
Cutting Thickness(MM/Inch)	1~40 MM/0.04"~2"

Cutter DRB-SPK4



Model	DRB-SPK4
Inlet's Size(MM/Inch)	430 × 600 × 180 MM/16.9" × 23.6" × 7.1"
Power(KW/HP)	1.5 KW/2 HP
Voltage (V)	380V(Customization is available)
Net Weight(KGS/Pound)	528 KGS/1164 LBS
Dimension(MM/Inch)Host	1205 × 755 × 1380 MM/47.4" × 29.9" × 54.3"
Dimension(MM/Inch)Discharge Belt	1230 × 650 × 760 MM/48.4" × 35.6" × 29.9"
Capacity(KGS/LBS)	100~800 KGS/220~1764 LBS
Cutting Thickness(MM/Inch)	1~100 MM/0.04"~3.9"

Cutter DRB-KP160



Model	DRB-KP160
Inlet's Size(MM/Inch)	160 MM/6.3"
Power(KW/HP)	1.1 KW/1.4 HP
Voltage (V)	380V(Customization is available)
Net Weight(KGS/Pound)	266 KGS/584 LBS
Dimension(MM/Inch)	2100 × 600 × 1350 MM/82.7" × 26.8" × 53.1"
Capacity(KGS/LBS)	100~600 KGS/200~1323 LBS
Cutting Thickness(MM/Inch)	2~3~2.5MM/0.09"~0.10"

Cutter DRB-QR200



Model	DRB-QR200
Inlet's Size(MM/Inch)	200 × 100 MM/7.9" × 3.9"
Power(KW/HP)	1.5 KW/2 HP
Voltage (V)	380V(Customization is available)
Net Weight(KGS/Pound)	90 KGS/198 LBS
Dimension(MM/Inch)	570 × 500 × 1030 MM/22.4" × 19.7" × 40.6"
Capacity(KGS/LBS)	600~1000 KGS/1323~2205 LBS
Cutting Thickness(MM/Inch)	2~25 MM/0.08"~0.1"

Shredder DRB-RS180



Model	DRB-RS180
Inlet's Size(MM/Inch)	100 × 175 MM/3.9" × 6.8"
Power(KW/HP)	1.1 KW × 2p/1.4 HP × 2p
Voltage (V)	380V(Customization is available)
Net Weight(KGS/Pound)	125 KGS/276 LBS
Dimension(MM/Inch)	600 × 620 × 1030 MM/23.6" × 24.4" × 40.6"
Capacity(KGS/LBS)	600~1000 KGS/1323~2205 LBS
Cutting Thickness(MM/Inch)	2~25 MM/0.08"~0.1"

Strips Cutter/Dicer DRB-FT330



Model	DRB-FT330
Inlet's Width(MM/Inch)	330 MM/13"
Power(KW/HP)	0.75 KW/1 HP
Voltage (V)	220/380V(Customization is available)
Net Weight(KGS/Pound)	164 KGS/362 LBS
Dimension(MM/Inch)	2000 × 850 × 1200 MM/78.7" × 25.98" × 47.24"
Capacity(KGS/LBS)	300~1000 KG/661~2205 LBS
Temperature(°C/°F)	-2°C~0°C/28.4°F~32°F

Strips Cutter/Dicer DRB-FT500



Model	DRB-FT500
Inlet's Width(MM/Inch)	500 MM/19.7"
Power(KW/HP)	1.1 KW/1.4 HP
Voltage (V)	220/380V(Customization is available)
Net Weight(KGS/Pound)	180 KGS/397 LBS
Dimension(MM/Inch)	2000 × 820 × 1200 MM/78.7" × 32.28" × 47.24"
Capacity(KGS/LBS)	500~3000 KG/1102~6614 LBS
Temperature(°C/°F)	-2°C~0°C/28.4°F~32°F

INTEGRITY AS THE ROOT, QUALITY AS THE BASE.

Grinder

DRB-JR32V



Model	DRB-JR32V
Inlet's Size(MM/Inch)	80 × 80 MM/3.1" × 3.1"
Power(KW/HP)	1.5 KW/2 HP
Voltage (V)	380V(Customization is available)
Net Weight(KGS/Pound)	70 KGS/154 LBS
Dimension(MM/Inch)	560 × 520 × 930 MM/22" × 20.8" × 36.6"
Capacity(KGS/LBS)	150~400 KGS/331~1764 LBS
Temperature(°C/°F)	-5°C -0°C/23°F -32°F
Plate Diameter(MM/Inch)	95 MM/3.7"

Flaker

DRB-PR3000



Model	DRB-PR3000
Inlet's Size(MM/Inch)	430 × 525 × 170 MM/16.9" × 20.7" × 6.7"
Power(KW/HP)	11 KW/14.8 HP
Voltage (V)	380V(Customization is available)
Net Weight(KGS/Pound)	865 KGS/1907 LBS
Dimension(MM/Inch)	2130 × 1175 × 1290 MM/83.9" × 46.3" × 50.8"
Capacity(KGS/LBS)	2000~4000 KGS/4409~8818 LBS
Cutting Speed	500 RPM

Frozen Meat Grinder

DRB-JR120X



Model	DRB-JR120X
Hopper Volume (L)	70 L
Power(KW/HP)	7.5 KW/10 HP
Voltage (V)	380V(Customization is available)
Net Weight(KGS/Pound)	302 KGS/666 LBS
Dimension(MM/Inch)	660 × 560 × 1150 MM/25.9" × 37.8" × 45.2"
Capacity(KGS/LBS)	800~2000 KGS/1764~4409 LBS
Temperature(°C/°F)	-5°C -0°C/23°F -32°F
Plate Diameter(MM/Inch)	120 MM/4.7"

Frozen Meat Grinder

DRB-JR160



Model	DRB-JR160
Hopper Volume (L)	170 L
Power(KW/HP)	18.5 KW/24.6 HP
Voltage (V)	380V(Customization is available)
Net Weight(KGS/Pound)	580 KGS/1279 LBS
Dimension(MM/Inch)	905 × 1180 × 1330 MM/35.6" × 46.4" × 52.3"
Capacity(KGS/LBS)	1000~2000 KGS/2205~4409 LBS
Temperature(°C/°F)	-10°C -0°C/14°F -32°F
Plate Diameter(MM/Inch)	160 MM/6.3"

Fresh&Frozen Meat Grinder (Double Shaft)

DRB-JR200



Model	DRB-JR200
Hopper Volume (L)	360L
Power(KW/HP)	42K W/56 HP
Voltage (V)	380V(Customization is available)
Net Weight(KGS/Pound)	1700 KGS/3748 LBS
Dimension(MM/Inch)	1855 × 1700 × 1730 MM/73" × 66.9" × 68.1"
Capacity(KGS/LBS)	3000~7000 KGS/6614~15432"
Temperature(°C/°F)	-10°C -5°C/14°F -41°F
Plate Diameter(MM/Inch)	200 MM/7.87"

Fresh&Frozen Meat Grinder

DRB-JR250DX



Model	DRB-JR250DX
Hopper Volume (L)	200 L
Power(KW/HP)	37 KW/49.3 HP
Voltage (V)	380V(Customization is available)
Net Weight(KGS/Pound)	1500 KGS/3307 LBS
Dimension(MM/Inch)	2200 × 1400 × 1650 MM/86.6" × 55.1" × 64.9"
Capacity(KGS/LBS)	3000~12000 KGS/6614~26455 LBS
Temperature(°C/°F)	-10°C -5°C/14°F -41°F
Plate Diameter(MM/Inch)	250 MM/9.8"

Vacuum Filler

DRB-ZG6600



Model	DRB-ZG6600
Hopper Volume (L)	245 L Single-piece
Power(KW/HP)	7.5 KW/10 HP
Voltage (V)	380V(Customization is available)
Net Weight(KGS/Pound)	730 KG/1609 LBS
Dimension(MM/Inch)	2050 × 1220 × 1780 MM/80.7" × 48" × 70"
Filling Capacity(KGS/LBS)	3600 KG/7937 LBS
Filling Pressure	0.1 Mpa

Twisting Machine

DRB-GN1200



Model	DRB-GN1200
Folding Diameter(MM/Inch)	Nylon Casings: 25~45 MM/0.98"~1.77"
	Nature Casings: 16~26 MM/0.63"~1.02"
Power(KW/HP)	3 KW/4 HP
Voltage (V)	380V(Customization is available)
Net Weight(KGS/Pound)	350 KG/772 LBS
Dimension(MM/Inch)	1310 × 550 × 1080 MM/51.5" × 21.6" × 42.5"
Twisting Capacity	1500 Twistings/Min
Casings	Nylon Casings/Nature Casings

Mixer(Double Shaft)

DRB-JB400L



Model	DRB-JB400L
Volume(L)	400 L
Power(KW/HP)	3 KW/4 HP
Voltage (V)	380V(Customization is available)
Net Weight(KGS/Pound)	450 KGS/992 LBS
Dimension(MM/Inch)	1700 × 924 × 1450 MM/66.9" × 36.3" × 57"
Capacity(KGS/LBS)	120-280 KGS/265-617 LBS

Mixer(Double Shaft)

DRB-ZJB1500L



Model	DRB-ZJB1500L
Volume(L)	1500 L
Power(KW/HP)	15 KW/20 HP
Voltage (V)	380V(Customization is available)
Net Weight(KGS/Pound)	1450 KGS/3197 LBS
Dimension(MM/Inch)	2580 × 1455 × 1785 MM/101.5" × 57.2" × 70.2"
Capacity(KGS/LBS)	500-1200 KGS/1102-2646 LBS

Mixer(Single Shaft)

DRB-DH130



Model	DRB-DH130
Volume(L)	130 L
Power(KW/HP)	0.75 KW/1 HP
Voltage (V)	380V(Customization is available)
Net Weight(KGS/Pound)	196 KGS/432 LBS
Dimension(MM/Inch)	1255 × 815 × 1070 MM/49.4" × 32" × 42.1"
Capacity(KGS/LBS)	40-60 KGS/88-132 LBS

Patty Former

DRB-RBJ100



Model	DRB-RBJ100
Hopper Volume (L)	50 L
Power(KW/HP)	0.55 KW/0.73 HP
Voltage (V)	380V(Customization is available)
Net Weight(KGS/Pound)	105 KGS/231 LBS
Dimension(MM/Inch)	970 × 820 × 1580 MM/38.1" × 24.4" × 62.2"
Capacity(KGS/LBS)	1800 ~ 2200 Pcs/H
Temperature(°C/°F)	-4~-0°C/24.8°F~32°F

Bowl Cutter

DRB-ZB80



Model	DRB-ZB80
Volume(L)	82 L
Power(KW)	22.23 KW/29.6 HP
Voltage (V)	380V(Customization is available)
Net Weight(KGS/POUND)	920 KGS/2028 LBS
Dimension(MM/Inch)	2000 × 1165 × 1210 MM/78.7" × 45.9" × 47.6"
Capacity(KGS/LBS)	40-50 KGS/88-110 LBS

Bowl Cutter

DRB-ZB200



Model	DRB-ZB200
Volume(L)	200 L
Power(KW)	58.5 KW/78 HP
Voltage (V)	380V(Customization is available)
Net Weight(KGS/POUND)	3600 KGS/7937 LBS
Dimension(MM/Inch)	2560 × 2450 × 2220 MM/100.7" × 96.4" × 87.4"
Capacity(KGS/LBS)	100-140 KGS/220-309 LBS

Stuffing Machine

DRB-TC600



Model	DRB-TC600
Air Pressure	0.4-0.6 Mpa
Casing Diameter(MM/Inch)	70-140 MM/2.7" × 5.5"
Net Weight(KG/Pound)	165 KGS/364 LBS
Dimension(MM/Inch)	1860 × 580 × 1430 MM/73.2" × 22.8" × 56.3"
Capacity	10-12 Times/Min

Clipping Machine

DRB-DK810



Model	DRB-DK810
Air Pressure	0.4-0.6 Mpa
Casing Diameter(MM/Inch)	70-140 MM/2.7" × 5.5"
Net Weight(KG/Pound)	28 KGS/62 LBS
Dimension(MM/Inch)	900 × 420 × 830 MM/35.4" × 16.5" × 32.6"
Capacity	10-12 Times/Min

Vacuum Tumbler DRB-GR300L



Model	DRB-GR300L
Volume(L)	300 L
Power(KW/HP)	1.5 KW/2 HP
Voltage (V)	220V(Customization is available)
Net Weight(KGS/Pound)	270 KGS/595 LBS
Dimension(MM/Inch)	1230 × 800 × 1380 MM/48.4" × 31.5" × 54.3"
Capacity(KGS/LBS)	150 KGS/331 LBS
Vacuum Degrees(Mpa)	0.6~0.8 Mpa

Vacuum Tumbler DRB-GR1000L



Model	DRB-GR1000L
Volume(L)	1000 L
Power(KW/HP)	3 KW/4 HP
Voltage (V)	220/380V(Customization is available)
Net Weight(KGS/Pound)	480 KGS/1058 LBS
Dimension(MM/Inch)	1760 × 1020 × 1573 MM/69.2" × 40.1" × 61.9"
Capacity(KGS/LBS)	100~300 KGS/220~661 LBS
Vacuum Degrees(Mpa)	0.6~0.8 Mpa

Vacuum Tumbler DRB-GRY1200L



Model	DRB-GRY1200L
Volume(L)	1200 L
Power(KW/HP)	4.8 KW/6.4 HP
Voltage (V)	380V(Customization is available)
Net Weight(KGS/Pound)	900 KGS/1984 LBS
Dimension(MM/Inch)	1350 × 2450 × 1730 MM/53.1" × 96.4" × 68.1"
Capacity(KGS/LBS)	720 KGS/1587 LBS
Vacuum Degrees(Mpa)	0.6~0.8 Mpa

Vacuum&Cooling Tumbler DRB-ZG300L



Model	DRB-ZG300L
Volume(L)	300 L
Power(KW/HP)	4.2 KW/5.6 HP
Voltage (V)	380V(Customization is available)
Net Weight(KGS/Pound)	580 KGS/1279 LBS
Dimension(MM/Inch)	1760 × 1220 × 1750 MM/69.2" × 48.0" × 68.9"
Capacity(KGS/LBS)	30~220 KGS/66~485 LBS
Vacuum Degrees(Mpa)	0.6~0.8 Mpa

Presser DRB-R1



Model	DRB-R1
Max Inlet's Height(MM/Inch)	40 MM/1.5"
Power(KW/HP)	1.5 KW/2 HP
Voltage (V)	220/380V(Customization is available)
Net Weight(KGS/Pound)	105 KGS/231 LBS
Dimension(MM/Inch)	450 × 700 × 560 MM/17.7" × 27.5" × 22"
Capacity	2~8 S/Time
Hydraulic Pressure(Mpa/Cm ²)	10 Mpa/Cm ²

Meat Tenderizer DRB-200



Model	DRB-200
Inlet's Size(MM/Inch)	200 MM/7.8"
Power(KW/HP)	0.75 KW/1 HP
Voltage (V)	380V(Customization is available)
Net Weight(KGS/Pound)	82 KGS/181 LBS
Dimension(MM/Inch)	520 × 410 × 940 MM/20.4" × 16.1" × 37"
Capacity(KGS/LBS)	300 KGS/661 LBS
Suitable Meat Thickness(MM/Inch)	8~25 MM/0.31"~0.98" (Adjusted)

Meat Injector DRB-ZS84



Model	DRB-ZS84
Number's of Needles	84 Pcs
Power(KW/HP)	4 KW/5.3 HP
Voltage (V)	380V(Customization is available)
Net Weight(KGS/Pound)	587 KGS/1294 LBS
Dimension(MM/Inch)	2170 × 1030 × 1740 MM/85.4" × 39.3" × 68.5"
Capacity	10~56 Times/Min
Inlet's Size(MM/Inch)	585 × 147 MM/23" × 5.7" (W × H)

Membrane Skinner DRB-JM520



Model	DRB-JM520
Blade Length(MM/Inch)	520 MM/20.4"
Power(KW/HP)	1.1 KW/1.4 HP
Voltage (V)	380V(Customization is available)
Net Weight(KGS/Pound)	166 KGS/366 LBS
Dimension(MM/Inch)	850 × 620 × 980 MM/33.4" × 24.4" × 38"
Capacity	38 MM/Min
Membrane Thickness(MM/Inch)	0.1~2 MM/0"~0.08"(Adjusted)