LEDriving® HL POWER BOOST

OSRAM's most powerful LED off-road[1] retrofit lamp ever!

With the power of 200 W[2] and integrated CANbus (for avoiding error messages on the dashboard)[3] the OSRAM LEDriving® HL POWER BOOST provides a compact LED replacement for conventional high and low beam lamps. These LED retrofit lamps are 12 V compatible, come with an optimized beam pattern, color temperature of 6500 K, and up to 400% more brightness.[4] The improved OSRAM thermal management technology with integrated active cooling – a high speed fan – ensures maximized heat dissipation for more powerful performance. Premium OSRAM quality and LED technology grant up to 5 times more lifetime.[5] The pair of lamps comes with a 3-year OSRAM guarantee.[6]

[1] These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information. [2] Initial value per pair. [3] Applicable to plenty of car models. [4] Compared to minimum ECE R112. [5] Compared to traditional halogen bulbs. [6] For precise guarantee conditions please refer to osram.com/am-guarantee.

Be road ready

100 YEARS
OSRAM
AUTOMOTIVE

LEDriving® HL POWER BOOST

Features

- Power up to 200 W[1]
- Up to 400% more brightness[2]
- Integrated CANbus[3]
- Top OSRAM technology provides optimized beam pattern
- Improved thermal management technology with integrated active cooling
- Premium OSRAM quality

Benefits

- More light allows to recognize obstacles and hazards sooner
- Easy installation with a wide range of suitable OSRAM accessories
- Reduced glaring thanks to an optimized light distribution
- A high-speed fan ensures maximized heat dissipation for more powerful performance
- 3-year guarantee[4]

≙H4/H19



≙H7



≙H9/H11



≙HB3/HB4



LEDriving® HL POWER BOOST

Product number	EAN10		ECE	W	V	K	COLOR	lm		i
64193DWPB-2HB	4062172**421362**	P43t/PU43t-3	≙H4/H19	up to 200/200	12	6500	Cool White	5000/3500[5]	2	NEW
64210DWPB-2HB	4062172**421348**	PX26d	≙H7	up to 200	12	6500	Cool White	5000[5]	2	NEW
64211DWPB-2HB	4062172**421386**	PGJ19-5/PGJ19-2	≙H9/H11	up to 200	12	6500	Cool White	5000[5]	2	NEW
9005/6DWPB-2HB	4062172**421409**	P20d/P22d	≙HB3/HB4	up to 200	12	6500	Cool White	5000[5]	2	NEW

[1] Initial value per pair. [2] Compared to minimum ECE R112 – please check for concrete types. [3] On almost all car models. [4] For precise conditions please refer to osram.com/am-guarantee. [5] ±20%.

Please note: These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.