POWER UP
MUSCLE TECH
PERFORMANCE ENGINE OIL CLEAN AND PROTECT
FULLY SYNTHETIC
ENGINE OIL
5W-40
MAS Formula
API SP/GF-6
FORMULA AND TECHNOLOGY FROM USA
HIGH WEAR PROTECTION
FOR HIGH MILEAGE & INADEQUATE OIL CHANGES
ACEA, A3/B3-04, ACEA, A3/B4-04
Mercedes Benz 229.5/226.5
BMW LONGLIFE-01
VOLKSWAGEN 502.00/505.00
PERFORMANCE ENGINE OIL
CLEAN AND PROTECT
4 LITRE
POWER UP
MUSCLE TECH
FULLY SYNTHETIC
5W-40
API SP/GF-6
Description:
EN
POWER UP MUSCLE TECH FULLY SYNTHETIC 5W-40 API SP/GF-6 MAS is the premium Fully Synthetic engine oil with MAS Formula. The Metal Treatment in MAS Formulation penetrates into micro pores of the metal surface & forms a tough low friction shield that is able to withstand friction 4 to 5 times more than premium engine oil in the market.
Manufactured to meet requirements of almost all modern multi valves with or without turbo chargers. It provides smoother, cooler and quieter engines. Its balanced additive system ensure excellent control over wear due to friction, wear induced heat, control temperature, deposits, corrosion, wear, high oxidation stability. This engine oil is manufactured with high safety measures and quality control according to ISO 9001:2015 standard. Recommended shelf life is 3 to 3½ years.
Features:
• Reduces wear more effectively as compared to normal engine oil.
• Metal Treatment in MAS Formulation penetrates into micro pores & forms a tough low friction shield & withstand friction 4 to 5 times more as compared to most of the premium engine oil in the market.
• Reduces premium engine performance & power.
• Reduces oxidation during engine operation.
• Recommended Min. 10,000km per oil change. (This is subjected to engine in good condition, for more than 10,000km per oil change, but not worn out engine shorter mileage per oil change).
• Reduces carbon, acid and sludge formations.
• Protection against cooler and quieter engine.
• Protection against engine internal corrosion.
• Keeps engine running cleaner and efficient.
In meeting the demanding quality test equipment standards.
Meet ACEA A3/B3 & A5/B5
Performance:
• API SP/GF-6 SAE 5W-40
• ACEA A3/B3 & A5/B5
• BMW LL-01
• MB-Approval 229.5
• Mercedes Benz 229.5/226.5
• LSAC GF-6 & SP
• Passes Friction Lubricity Test
• Complies with CF-4, CI-4 & CJ-4
Caution: Long term contact with skin may cause skin irritation or dermatitis. Wash off immediately with soap and water. Repeat as often as needed. Prolonged or repeated contact may cause dryness or cracking of the skin. Keep away from open flame, sparks, hot surface and heat. Keep away from children. Avoid contact with eyes. Rinse with water immediately. If ingested, do not induce vomiting. Seek medical treatment immediately!
Protect the Environment - Dispose of used oil responsibly. Do not discharge into drains, soil or water.
Manufactured in Malaysia.
Distributed by: POWER UP (M) SDN BHD (525590-W)
No. 2, Jalan Cekal 1/KS6, Taman Industri Cemerlang, 81800 Ulu Tiram, Johor Darul Ta'zim, Malaysia.
Email: info@powerup.com.my
www.powerup.com.my